

BS 11:2015



BSI Standards Publication

Specification for dimensional properties and associated tolerances of railway rails

bsi.
British Standards Institution

...making excellence a habit.™

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2015

Published by BSI Standards Limited 2015

ISBN 978 0 580 87771 1

ICS 45.080

The following BSI references relate to the work on this document:

Committee reference RAE/2

Draft for comment 14/30311697 DC

Publication history

First published, February 1905

Second edition, January 1921

Third edition, June 1922

Fourth edition, March 1926

Fifth edition, January 1936

Sixth edition, January 1955

Seventh edition, February 1959

Eighth edition, January 1978

Ninth edition, February 1985

Tenth (present), edition May 2015

Amendments issued since publication

Date	Text affected
------	---------------

Contents

Foreword *ii*

- 1 Scope 1
- 2 Normative references 1
- 3 Dimensions of rail sections 1
- 4 Tolerances 16

Annexes

Annex A (normative) Referee gauge for hole height for 95 RBH rails 18

List of figures

- Figure 1 – BS rail no. 50 “O” 2
- Figure 2 – BS rail section no. 60 R 3
- Figure 3 – BS rail section no. 70 A 4
- Figure 4 – BS rail section no. 75 A 5
- Figure 5 – BS rail section no. 75 R 6
- Figure 6 – BS rail section no. 80 R 7
- Figure 7 – BS rail section no. 80 “O” 8
- Figure 8 – BS rail section no. 90 R 9
- Figure 9 – BS rail section no. 95 A 10
- Figure 10 – BS rail section no. 95 R 11
- Figure 11 – BS rail section no. 95 RBH 12
- Figure 12 – BS rail section no. 95 N 13
- Figure 13 – BS rail section no. 100 A 14
- Figure 14 – BS rail section no. 100 R 15
- Figure 15 – Key to position of fishbolt holes 16
- Figure A.1 – Vertical drilling gauge for 95 RBH rails 18

List of tables

- Table 1 – Tolerances on rail section profiles 16
- Table 2 – Position of fishbolt holes 17
- Table 3 – Tolerances on fishbolt hole dimensions and positions 17
- Table 4 – Rail straightness measured over 1.5 m 17

Summary of pages

This document comprises a front cover, an inside front cover, pages i to ii, pages 1 to 18, an inside back cover and a back cover.

Foreword

Publishing information

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 May 2015. It was prepared by Technical Committee RAE/2, *Railway Applications - Infrastructure*. A list of organizations represented on this committee can be obtained on request to its secretary.

Supersession

This British Standard supersedes BS 11:1985, which is withdrawn.

Information about this document

The revision has been prepared because most of the content concerning rail manufacture, steel grades and some of the rail profiles has been superseded by the new editions of BS EN 13674-1:2011 and BS EN 13674-4:2006. This revision of BS 11 therefore deals only with those aspects not covered by BS EN 13674-1:2011 and BS EN 13674-4:2006 and may therefore be used as a supplement to them.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its requirements are expressed in sentences in which the principal auxiliary verb is "shall".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Where words have alternative spellings, the preferred spelling of the Shorter Oxford English Dictionary is used (e.g. "organization" rather than "organisation").

Requirements in this standard are drafted in accordance with *Rules for the structure and drafting of UK standards*, subclause J.1.1, which states, "Requirements should be expressed using wording such as: 'When tested as described in Annex A, the product shall ...'". This means that only those products capable of passing the specified test will be deemed to conform to this standard.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

1 Scope

This British Standard specifies requirements for the dimensional properties and associated tolerances of railway rails of 24.8 kg/m (50 lb/yd) and greater linear mass which are not specified in BS EN 13674-1 or BS EN 13674-4.

For chemical and mechanical properties, grade designation, marking and certification requirements see BS EN 13674-1.

2 Normative references

The following document, in whole or in part, is normatively referenced in this document and is indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS EN 13674-1:2011, *Railway applications – Track – Rail – Part 1: Vignole railway rails 46 kg/m and above*

3 Dimensions of rail sections

Rail section dimensional properties and mass per unit length shall conform to the appropriate values given in Figure 1 to Figure 14.

NOTE The rail sections in this British Standard were designed before the change to SI units was planned. The original imperial dimensions used have been converted to SI dimensions with an accuracy necessary for the retention of the previous imperial profiles and properties of the rails.

Figure 1 BS rail no. 50 "O"




Figure 2 BS rail section no. 60 R




Figure 3 BS rail section no. 70 A




Figure 4 BS rail section no. 75 A




Figure 5 BS rail section no. 75 R




Figure 6 BS rail section no. 80 R






Figure 7 BS rail section no. 80 "O"



The diagram shows a cross-section of a channel section. The total height of the section is indicated as 142.9. The thickness of the web is indicated as 20.6. The section consists of a vertical web and two horizontal flanges (head and foot) connected by rounded corners.



Cross-sectional area:		
Whole section	5 669.6	mm ²
Head	2 432.7	mm ² (42.91%)
Web	1 212.6	mm ² (21.39%)
Foot	2 024.3	mm ² (35.70%)
Calculated mass	44.506	kg/m
Moment of inertia	1 584.3	cm ⁴
Section modulus	211.9	cm ³
Distance from top of rail to neutral axis	74.78	mm

Figure 9 BS rail section no. 95 A






Figure 10 BS rail section no. 95 R




Technical drawing of a cross-section of a 100 lb/yd rail. The drawing shows the profile of the rail with various dimensions and radii. The top flange has a width of 69.9 mm and a height of 49.2 mm. The web has a thickness of 19.1 mm. The bottom flange has a width of 69.9 mm and a height of 33.3 mm. The total height of the rail is 145.3 mm. The drawing includes radii for the top flange (R12.7, R304.8), the web (R6.4), and the bottom flange (R1.6, R304.8). The cross-sectional area is divided into four parts: Whole section (5 996.1 mm²), Head (2 890.8 mm², 48.21%), Web (1 275.0 mm², 21.26%), and Foot (1 830.4 mm², 30.53%). The calculated mass is 47.069 kg/m, the moment of inertia is 1 458.0 cm⁴, the section modulus is 188.5 cm³, and the distance from the top of the rail to the neutral axis is 67.89 mm.

Cross-sectional area:		
Whole section	5 996.1	mm ²
Head	2 890.8	mm ² (48.21%)
Web	1 275.0	mm ² (21.26%)
Foot	1 830.4	mm ² (30.53%)
Calculated mass	47.069	kg/m
Moment of inertia	1 458.0	cm ⁴
Section modulus	188.5	cm ³
Distance from top of rail to neutral axis	67.89	mm

Figure 12 BS rail section no. 95 N



[illegible]



4 Tolerances

4.1 Rail section profile

The dimensional tolerances shall conform to Table 1. Profile conformity gauges shall conform to BS EN 13674-1:2011, Annex E.

Table 1 Tolerances on rail section profiles

Characteristic	1	2
	Flat bottom sections	Bull head sections
	mm	mm
Overall height of rail measured at the rail end	±0.50	+0.80 −0.40
Width of head	±0.50	±0.40
Width of foot	±1.00	±0.40
Thickness of web	+1.00 −0.50	±0.40
Verticality: maximum deviation at rail head	0.50	0.40
Foot base: flat to maximum concavity deviation from nominal profile	0.50 —	— ±0.50
Fishing surfaces: maximum stand off of fishing template (see BS EN 13674-1:2011, Figure E.8): from web	1.20	1.20
maximum clearance from fishing surface	0.15	0.13
Asymmetry of rail section	0.50	0.40
Asymmetry of rail section as checked by means of combined verticality and asymmetry gauge: flat bottom rails only	1.25	(see Note)

NOTE The gauge shown in BS EN 13674-1:2011 is not applicable to bull head rails. This British Standard does not specify a symmetry gauge for 95 RBH.

4.2 Fishbolt hole sizes and positions

The sizes and positions of fishbolt holes shall conform to Figure 15 and Table 2 with tolerances as given in Table 3. In case of dispute, the fishbolt holes in the rail shall be checked with templates and gauges of the type given in Annex A and BS EN 13674-1:2011, Figure E.12 and Figure E.13.

Figure 15 Key to position of fishbolt holes




Table 2 Position of fishbolt holes

BS rail section number	Dimensions			
	A	B	C	D
	Height of centreline of hole from foot of rail	Distance of centreline of 1 st hole from end of rail	Pitch of hole centres	Diameter of holes ^{A)}
	mm	mm	mm	mm
50 "O"	41.5	47.6	101.6	23.8
60 R	47.6	47.6	101.6	25.4
70 A	50.8	47.6	101.6	27.0
75 A	52.4	47.6	101.6	28.6
75 R	54.0	47.6	101.6	28.6
80 R	56.0	47.6	101.6	28.6
80 "O"	54.0	60.3	127.0	28.6
90 R	59.9	54.0	114.3	30.2
95 A	58.7	54.0	114.3	31.8
95 R	61.9	54.0	114.3	31.8
95 RBH	64.7	60.3	114.3	28.6
95 N	64.3	54.0	114.3	31.8
100 A	60.3	54.0	114.3	31.8
100 R	63.5	54.0	114.3	31.8

^{A)} Where circumstances call for different size holes, these may be ordered.

Table 3 Tolerances on fishbolt hole dimensions and positions

Fishbolt holes	Tolerances	
	Diameter ≤30 mm	Diameter >30 mm
Diameter of fishbolt holes	±0.5 mm	±0.7 mm
Centre position of fishbolt holes vertically and horizontally	±0.5 mm	±0.7 mm

4.3 Straightness

After cold straightening a finished rail shall, when standing on its base or lying on its side, be capable of being pulled into a straight line and of retaining that position.

When checked using a 1 500 mm straight edge, the straightness of the rail shall conform to Table 4, measured as the maximum gap between the rail and the straight edge.

Table 4 Rail straightness measured over 1.5 m


Dimensional property	Rail position	Maximum gap
Horizontal and vertical straightness	Body	0.8 mm
Horizontal straightness	End	0.8 mm
Vertical straightness	End	0.8 mm upturned 0.2 mm downturned

Annex A
(normative)

Referee gauge for hole height for 95 RBH rails

The vertical drilling gauge for 95 RBH rails is shown in Figure A.1.

Figure A.1 Vertical drilling gauge for 95 RBH rails



British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com