



BSI Standards Publication

Rubber and rubber products — Determination of 2-mercaptobenzothiazole content by high performance liquid chromatography (HPLC)

National foreword

This British Standard is the UK implementation of [ISO 21490:2022](#).

The UK participation in its preparation was entrusted to Technical Committee PRI/22, Testing and analysis of rubber.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2022
Published by BSI Standards Limited 2022

ISBN 978 0 580 99418 0

ICS 83.060

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 28 February 2022.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL
STANDARD

ISO
21490

First edition
2022-01-21

Rubber and rubber
products — Determination of
2-mercaptobenzothiazole content
by high performance liquid
chromatography (HPLC)

*Caoutchouc et produits à base de caoutchouc — Détermination de la
teneur en 2-mercaptobenzothiazole par chromatographie en phase
liquide haute performance*



Reference number
ISO 21490:2022(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO’s member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	1
5	Reagents and materials	1
6	Apparatus	2
7	Sampling	2
8	Procedure	2
8.1	Sample preparation	2
8.2	Chromatographic conditions	3
8.3	Preparation of standard working solutions and the calibration curve	3
8.4	HPLC-DAD testing	3
9	Test results	3
9.1	Calibration curve	3
9.2	Calculation	4
10	Precision	4
11	Test report	4
Annex A (informative) Schematic chemical reactions during curing of rubber with sulfenamide that gives 2-MBT		5
Annex B (informative) A gradient programme of HPLC		6
Annex C (informative) Calibration		7
Annex D (informative) Spectrum and chromatogram of 2-MBT		9
Annex E (informative) Precision		11
Bibliography		12

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 2, *Testing and analysis*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

2-Mercaptobenzothiazole (sometimes also referred to as: MBT; 2-MBT; 2-benzothiazolethione, or BTSH) is used in the rubber industry as a curing agent. MBT is in the group of thiazoles and is considered as scorch fast when used as a primary accelerator.

2-Mercaptobenzothiazole as the acidic sulfur accelerator is widely used in rubber materials because of its good characteristics: stable sulfides, good vulcanization, and a low critical temperature to accelerate vulcanization so that the rubber product can reach higher tensile strength and hardness levels.

Measuring 2-mercaptobenzothiazole concentration in rubber compounds at different stages of curing the rubber product is an excellent means to define the optimal curing conditions of temperature and time in order to obtain the right properties for the products at the best cost.

During the curing of rubber compounds sulfenamides are used as accelerators, which chemically react at an early stage of the curing to produce 2-mercaptobenzothiazole and other species. 2-Mercaptobenzothiazole then contributes to the initiation of the mechanism which creates the sulfur crosslinks between the rubber macromolecules at the end (an example is given in [Figure A.1](#)). To ensure continuous progress, it is important to know the chemical mechanisms involved at each stage. Thus, it is necessary to quantify the content of 2-mercaptobenzothiazole during the decomposition of the sulfenamide and to know whether 2-mercaptobenzothiazole has disappeared in any further chemical reactions.

This page deliberately left blank

Rubber and rubber products — Determination of 2-mercaptobenzothiazole content by high performance liquid chromatography (HPLC)

1 Scope

This document specifies a quantitative test method to determine the 2-mercaptobenzothiazole content in rubber and rubber products by high performance liquid chromatography (HPLC).

This document delivers a method for quantifying 2-mercaptobenzothiazole in rubber products for a better selection of curing conditions.

This document provides a method to follow the curing of rubber with sulfur- and benzothiazole-based accelerators using a chemical measurement which is complementary to the classical rheometric technique.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 3696](#), *Water for analytical laboratory use — Specification and test methods*

[ISO 4661-2](#), *Rubber, vulcanized — Preparation of samples and test pieces — Part 2: Chemical tests*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 Principle

The 2-mercaptobenzothiazole in rubber is ultrasonically extracted with a chloroform-methanol solution determined and confirmed with HPLC-DAD (high performance liquid chromatography equipped with a diode-array detector).

NOTE There is a risk of neo-formed MBT from MBTs if a thiazole accelerator is used in the formulation of the sample.

5 Reagents and materials

Unless otherwise specified, analytical grade chemicals should be used. Water shall be distilled or deionized to fulfil grade 3 in accordance with [ISO 3696](#).

5.1 Methanol, of analytical grade.

8.2 Chromatographic conditions

Since the test results depend on the equipment that is used, there are no universal parameters for chromatographic analysis (see example in [Annex B](#)). The following parameters have been proven to be suitable for testing as reference:

- column: C18, 5 µm, 4,6 mm × 250 mm or chromatographic column with the similar performance;
- temperature of column: 35 °C;
- wavelength range: 200 nm to 400 nm;
- test wavelength: 320 nm;
- mobile phase A (water containing 1 % acetonitrile) and mobile phase B (acetonitrile);
- flow rate: 1,0 ml/min;
- injection volume: 10 µl.

8.3 Preparation of standard working solutions and the calibration curve

Weigh 100 mg of a 2-mercaptobenzothiazole standard material and put it into a 100 ml volumetric flask. Fill the flask with methanol to obtain a 1 mg/ml standard stock solution. The standard stock solution is diluted with methanol stepwise into 0,005 mg/ml, 0,010 mg/ml, 0,020 mg/ml, 0,030 mg/ml and 0,050 mg/ml standard working solutions (see example in [Annex C](#)).

Inject those solutions using the analytical conditions described in [8.2](#), and the calibration curve is obtained by plotting the peak area of each standard against their concentration. Because of the instability of MBT, standard working solutions shall be analysed without delay to avoid systematic errors in the calibration.

8.4 HPLC-DAD testing

Filter the solution through the filtration membrane for HPLC detection.

Analyse the sample solutions (10 µl) and standard working solutions (10 µl) by HPLC-DAD separately. To ensure that the peak of response in the extracts is indeed 2-mercaptobenzothiazole, it is necessary to verify that the retention time and the UV-visible spectrum of the peak are identical for the extracts and standard solutions (see example in [Annex D](#)).

A blank test shall be carried out in parallel with the determination. The blank test is performed according to [8.1](#) but omitting the test sample.

To avoid column damages, appropriate measures should be taken such as washing the column after testing.

9 Test results

9.1 Calibration curve

The linear calibration equation is determined by plotting the standard working solution concentration (ordinate) against the peak area (abscissa). An example of a calibration curve is given in [Annex C](#). Through the least square fitting, the linear determination coefficient R^2 should be greater than 0,995.

The 2-mercaptobenzothiazole content in standard solution can be calculated by [Formula \(1\)](#).

$$c = K \times A + b \tag{1}$$

where

- c is the 2-mercaptobenzothiazole content in the standard solution, in mg/ml;
- K is the slope of the calibration curve;
- A is the chromatography area of 2-mercaptobenzothiazole in the standard solution;
- b is the intercept of the calibration curve.

9.2 Calculation

The 2-mercaptobenzothiazole content in sample is calculated according to [Formula \(2\)](#).

$$W = \frac{(c - c_0) \cdot V}{m} \tag{2}$$

where

- W is the 2-mercaptobenzothiazole concentration in the sample, in g/kg;
- c is the 2-mercaptobenzothiazole concentration in the extracted solution, in mg/ml;
- c_0 is the 2-mercaptobenzothiazole concentration in the blank, in mg/ml;
- V is the final constant volume of the extracted solution, in ml;
- m is the sample mass, in g.

10 Precision

See [Annex E](#).

11 Test report

The test report shall include the following information:

- a) reference to this document, i.e. [ISO 21490:2022](#);
- b) detailed description of the test sample;
- c) content of the 2-mercaptobenzothiazole in the test sample for each curing temperature and time condition, g/kg;
- d) the difference between the test procedure and the specified steps;
- e) any deviations during the analytical procedure;
- f) date of the test.

Annex A
(informative)

Schematic chemical reactions during curing of rubber with
sulfenamide that gives 2-MBT

Figure A.1 provides a schematic representation of the reaction of sulfenamides during the curing of a rubber compound. The level of the curing process can be followed chemically by the concentration of 2-MBT, the reaction of crosslinking with 2-MBT ends on a plateau.





Figure A.1 — Reaction of sulfenamides during the curing of a rubber compound

Annex B
(informative)

A gradient programme of HPLC

[Table B.1](#) shows a gradient programme of HPLC as an example.

Table B.1 — A gradient programme of HPLC

Time min	Eluent A %	EluentB %
0 to 2	70	30
2 to 17 linearly to	10	90
17 to 22	10	90
22 to 25 linearly to	70	30
25 to 28	70	30

Annex C
(informative)

Calibration

An example is given for preparation of 2-MBT standard solutions from 0,005 mg/ml to 0,050 mg/ml.


The solutions are prepared by successive dilutions of a 2-MBT solution of 1 mg/ml obtained by dissolving 100 mg of 2-MBT (of purity $\geq 99,1\%$) in 100 ml of methanol.

NOTE The order of injection of the standard solutions generally is from the less concentrated to the more concentrated.

[Table C.1](#) provides information for preparation of the 2-MBT standard solutions. [Figure C.1](#) provides an example of a calibration curve for 2-MBT.

Table C.1 — Steps for preparation of the 2-MBT standard solutions for the calibration range

Solutions	2-MBT concentration mg/ml
2,5 ml of 1 mg/ml solution, then complete up to 50 ml of methanol	0,050
6 ml of 0,05 mg/ml solution, then complete up to 10 ml of methanol	0,030
4 ml of 0,05 mg/ml solution, then complete up to 10 ml of methanol	0,020
2 ml of 0,05 mg/ml solution, then complete up to 10 ml of methanol	0,010
1 ml of 0,05 mg/ml solution, then complete up to 10 ml of methanol	0,005



Key
X amount (mg/ml)
Y area (mV.min)

Figure C.1 — Example of a calibration curve for 2-MBT

Annex D
(informative)

Spectrum and chromatogram of 2-MBT

[Figure D.1](#) shows an example of the chromatogram of 2-MBT in a real sample extract at the concentration of 0,015 mg/ml.




Figure D.1 — Example of a chromatogram of 2-MBT

[Figure D.2](#) shows an example of the spectrum of 2-MBT in a real sample extract at the same concentration of 0,015 mg/ml.




Figure D.2 — Example of a spectrum of 2-MBT

Annex E

(informative)

Precision

E.1

General

An interlaboratory test programme (ITP) was organized in October 2020. The precision evaluated was a type 1 precision in accordance with method B of [ISO 19983:2017](#).

Eight laboratories participated in the ITP and two different materials were used. Two tests were carried out on two different days of two weeks, at intervals of one week. Two measurements were repeated each day. The data from one laboratory were discarded as outliers.

E.2

Precision results

The precision results for this document are given in [Table E.1](#). These results were obtained using outlier deletion procedures as described in [ISO 19983](#).

Repeatability: The difference between the two-days test (value) averages, found on nominally identical material samples under correct application of this test method, does not exceed the tabulated day-to-day repeatability in more than one in 20 cases on average.

Reproducibility: The difference between two independently measured test averages (values), found in two laboratories using the correct application of this test method on nominally identical material samples, does not exceed the tabulated reproducibility in more than one in 20 cases.

Table E.1 — Precision data

Sample	Mean content	Within laboratories			Between laboratories			Number of laboratories
		S_{rD}	r_D	(r_D)	S_R	R	(R)	
A	2,41	0,15	0,43	17,97	0,38	1,08	44,81	7
B	4,72	0,26	0,74	15,74	0,58	1,64	34,66	7
<div>The symbols used in this table are defined as follows:</div> <div>S_{rD} is the day-to-day repeatability standard deviation;</div> <div>r_D is the day-to-day repeatability, in measurement units;</div> <div>(r_D) is the relative day-to-day repeatability, in percent;</div> <div>S_R is the reproducibility standard deviation;</div> <div>R is the reproducibility, in measurement units;</div> <div>(R) is the relative reproducibility, in percent.</div>								

Bibliography

[1] [ISO 19983:2017](#), *Rubber — Determination of precision of test methods*

This page deliberately left blank

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email cservices@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email: cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

