



BSI Standards Publication

# **Adhesives for load bearing timber structures other than phenolic and aminoplastic — Test methods**

Part 1: Long-term tension load test perpendicular to the bond line at varying climate conditions with specimens perpendicular to the glue line  
(Glass house test)

**National foreword**

This British Standard is the UK implementation of EN 15416-1:2017.

The UK participation in its preparation was entrusted to Technical Committee PRI/52, Adhesives.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017.  
Published by BSI Standards Limited 2017

ISBN 978 0 580 85714 0

ICS 83.180

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 January 2017.

**Amendments/corrigenda issued since publication**

Date	Text affected
------	---------------

---

EUROPEAN STANDARD

**EN 15416-1**

NORME EUROPÉENNE

EUROPÄISCHE NORM

January 2017

ICS 83.180

English Version

**Adhesives for load bearing timber structures other than phenolic and aminoplastic - Test methods - Part 1: Long-term tension load test perpendicular to the bond line at varying climate conditions with specimens perpendicular to the glue line (Glass house test)**

Adhésifs pour structures portantes en bois de type autre que phénolique et aminoplaste - Méthodes d'essais - Partie 1 : Essai de charge soutenue à long terme dans des conditions climatiques cycliques avec des éprouvettes chargées perpendiculairement au joint de colle (essai de la serre)

Klebstoffe für tragende Holzbauteile ausgenommen Phenolharzklebstoffe und Aminoplaste - Prüfverfahren - Teil 1: Langzeit-Zugprüfung senkrecht zur Klebfuge bei verschiedenen Klimabedingungen mit Prüfkörpern senkrecht zur Klebstofffuge (Glashaus-Prüfung)

This European Standard was approved by CEN on 30 October 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels**

<b>Contents</b>		Page
<b>European foreword.....</b>		<b>3</b>
<b>Introduction .....</b>		<b>5</b>
<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Principle .....</b>	<b>6</b>
<b>4</b>	<b>Apparatus.....</b>	<b>6</b>
<b>4.1</b>	<b>House for weather exposure.....</b>	<b>6</b>
<b>4.2</b>	<b>Test jig.....</b>	<b>6</b>
<b>4.3</b>	<b>Testing machine .....</b>	<b>8</b>
<b>5</b>	<b>Method .....</b>	<b>9</b>
<b>5.1</b>	<b>General.....</b>	<b>9</b>
<b>5.2</b>	<b>Selection of timber.....</b>	<b>9</b>
<b>5.3</b>	<b>Production of the test sticks.....</b>	<b>9</b>
<b>5.4</b>	<b>Cutting of the test pieces and build-up of the test batches.....</b>	<b>11</b>
<b>5.5</b>	<b>Test procedures.....</b>	<b>11</b>
<b>5.5.1</b>	<b>General.....</b>	<b>11</b>
<b>5.5.2</b>	<b>Climate for duration of load tests.....</b>	<b>12</b>
<b>5.5.3</b>	<b>Tensile test procedure .....</b>	<b>12</b>
<b>6</b>	<b>Expression of results.....</b>	<b>12</b>
<b>7</b>	<b>Requirements .....</b>	<b>12</b>
<b>8</b>	<b>Test report.....</b>	<b>13</b>
<b>Bibliography.....</b>		<b>14</b>

## European foreword

This document (EN 15416-1:2017) has been prepared by Technical Committee CEN/TC 193 “Adhesives”, the secretariat of which is held by AENOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by July 2017, and conflicting national standards shall be withdrawn at the latest by July 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document is intended to harmonize the provisions in EN 14080:2013, B.2, EN 15497:2014 and EN 16254:2013+A1:2016, Annex B and EN 16351. It differs with respect to the following:

- a) consistent specification of the test method for the determination of the long-term performance at varying climate conditions in one standard;
- b) reference to EN 16254 for EPI adhesives added in the scope;
- c) Figure 1 and Figure 2 for connection device added;
- d) alternative cutting scheme of the components of the test sticks presented in Figure 4.

This document is one of a series dealing with adhesives for use with timber structures, and is published in support of product standards for bonded load-bearing timber structures.

The series consists of three classification and performance requirements for adhesives for load-bearing timber structures, phenolic and aminoplastic adhesives (EN 301), one component polyurethane adhesives (EN 15425) and emulsion polymerized isocyanate adhesives (EN 16254), together with 12 test methods (EN 302 Parts 1 to 8 and EN 15416 Parts 1 and 3 to 5).

These European Standards have the following titles:

EN 301, *Adhesives, phenolic and aminoplastic, for load-bearing timber structures — Classification and performance requirements*

EN 15425, *Adhesives — One component polyurethane (PUR) for load-bearing timber structures - Classification and performance requirements*

EN 16254, *Adhesives — Emulsion polymerized isocyanate (EPI) for load-bearing timber structures — Classification and performance requirements*

EN 302-1, *Adhesives for load-bearing timber structures — Test methods — Part 1: Determination of longitudinal tensile shear strength*

EN 302-2, *Adhesives for load-bearing timber structures — Test methods — Part 2: Determination of resistance to delamination*

EN 302-3, *Adhesives for load-bearing timber structures — Test methods — Part 3: Determination of the effect of acid damage to wood fibres by temperature and humidity cycling on the transverse tensile strength*

EN 302-4, *Adhesives for load-bearing timber structures — Test methods — Part 4: Determination of the effects of wood shrinkage on the shear strength*

EN 302-5, *Adhesives for load-bearing timber structures — Test methods — Part 5: Determination of maximum assembly time under referenced conditions*

EN 302-6, *Adhesives for load-bearing timber structures — Test methods — Part 6: Determination of the minimum pressing time under referenced conditions*

EN 302-7, *Adhesives for load-bearing timber structures — Test methods — Part 7: Determination of the working life under referenced conditions*

EN 302-8, *Adhesives for load-bearing timber structures — Test methods — Part 8: Static load test of multiple bond line specimens in compression shear*

EN 15416-1, *Adhesives for load bearing timber structures other than phenolic and aminoplastic — Test methods — Part 1: Long-term tension load test perpendicular to the bond line at varying climate conditions with specimens perpendicular to the glue line (Glass house test)*

EN 15416-3, *Adhesives for load bearing timber structures other than phenolic and aminoplastic — Test methods — Part 3: Creep deformation test at cyclic climate conditions with specimens loaded in bending shear*

EN 15416-4, *Adhesives for load bearing timber structures other than phenolic and aminoplastic — Test methods — Part 4: Determination of open assembly time under referenced conditions*

EN 15416-5, *Adhesives for load bearing timber structures other than phenolic and aminoplastic — Test methods — Part 5: Determination of minimum pressing time under referenced conditions*

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

## **Introduction**

### **Safety statement**

Persons using this European Standard should be familiar with the normal laboratory practice, if applicable. This European Standard cannot address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices and to ensure compliance with any regulatory conditions.

### **Environmental statement**

It is understood that some of the material permitted in this European Standard may have negative environmental impact. As technological advantages lead to better alternatives for these materials, they will be eliminated from this European Standard to the extent possible.

At the end of the test, it is recommended that the user of this European Standard take care to carry out an appropriate disposal of the wastes, according to local regulation.

## 1 Scope

This European Standard specifies a method of determining the ability of adhesive bonds to resist long-term sustained load applied vertical to the glue lines. It is applicable to adhesives used in load-bearing timber structures.

It is suitable for the following applications:

- a) for assessing the compliance of adhesives according to EN 15425 and EN 16254;
- b) for assessing the suitability and quality of adhesives for load-bearing timber structures;
- c) for assessing the effect on the bond strength resulting from long-term sustained load at cyclic climate conditions.

This method is intended primarily to obtain performance data for the classification of adhesives for load bearing timber structures according to their suitability for use in defined climatic environments.

This method is not intended to provide data for structural design, and does not necessarily represent the performance of the bonded member in service.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 302-3:2013, *Adhesives for load-bearing timber structures — Test methods — Part 3: Determination of the effect of acid damage to wood fibres by temperature and humidity cycling on the transverse tensile strength*

## 3 Principle

Bonded test pieces are subjected to long-term sustained load applied vertical to the glue lines at cyclic climate conditions. The test climate is at natural outdoor conditions in Europe between latitude 45° and 60°. The loaded samples are protected with light penetrable covering ("Glass house").

## 4 Apparatus

### 4.1 House for weather exposure


The weather exposure shall take place in a natural ventilated house covered with a light penetrating material where the air can circulate through openings along the floor and the roof.

### 4.2 Test jig

The 10 samples, making a test set for each of the 3 duration of load times, shall be placed in a suitable test jig and loaded with a transverse tensile load according to 5.5.1. The test jigs shall enable a smooth loading of the test pieces. The individual samples shall be free to rotate to secure that the load will be applied 90° to the glue lines.

NOTE Test jigs with a hanging dead load for the load application in combination with a vertical loading of the individual specimens using a principle as visualized in Figure 1 and Figure 2, has shown to be a suitable method.


Dimensions in millimetres



**Key**

- 1 screw M12x30
- 2 spherical washers, conical seats (DIN 6319)
- 3 connection device 70 mm × 40 mm; length 50 mm

**Figure 1 — Example of connection device between two specimens**



**Key**

- 1 connection device
- 2 loaded test piece
- $F$  load

**Figure 2 — Specimen mounted in the connection device**

### 4.3 Testing machine

The test machine shall be identical with the equipment described in EN 302-3.

## 5 Method

### 5.1 General

The specimens shall be produced following EN 302-3, but with specimens made from untreated beech wood (*Fagus sylvatica* L.) with close contact and 0,5 mm thick glue line for application areas “Special purpose” and “General purpose”, and a close contact glue line for application area “Finger joints”.

### 5.2 Selection of timber

The beech wood boards from which the specimens are cut shall be free from knots, straight grained and shall have a density of  $(700 \pm 50) \text{ kg/m}^3$  at 12 % moisture content. The timber prior to specimen manufacture shall be conditioned in a climate chamber at storage conditions of  $(20 \pm 2) ^\circ\text{C}$  and  $(65 \pm 5) \%$  relative humidity (hereafter climate [20/65]). The moisture content shall be  $(12 \pm 1) \%$ .

Each beech wood board shall have a width of at least 150 mm, a length of at least 750 mm and a thickness of at least 35 mm, and shall be used to manufacture one test stick as shown in Figure 3, a) and b). The annual ring orientation of both components glued together shall be roughly co-linear and with an angle of the growth rings in the range of  $30^\circ$  and  $60^\circ$ .

### 5.3 Production of the test sticks

In total, 5 sticks with a cross section of 50 mm × 60 mm (after bonding and final preparation) and a length of at least 700 mm, enabling the cutting of 8 test specimens and 2 spare specimens from each stick of the specimen type described in EN 302-3, shall be manufactured for each glue line thickness.

Alternatively, longer sticks can be pre-assembled into sub-sections of at least 300 mm prior to bonding, providing sufficient matched samples for cutting the required number of specimens.

Not more than 8 h before the bonding, the boards are planed to their final thickness. For test pieces

## 5 Method

### 5.1 General

The specimens shall be produced following EN 302-3, but with specimens made from untreated beech wood (*Fagus sylvatica* L.) with close contact and 0,5 mm thick glue line for application areas “Special purpose” and “General purpose”, and a close contact glue line for application area “Finger joints”.

### 5.2 Selection of timber

The beech wood boards from which the specimens are cut shall be free from knots, straight grained and shall have a density of  $(700 \pm 50) \text{ kg/m}^3$  at 12 % moisture content. The timber prior to specimen manufacture shall be conditioned in a climate chamber at storage conditions of  $(20 \pm 2) ^\circ\text{C}$  and  $(65 \pm 5) \%$  relative humidity (hereafter climate [20/65]). The moisture content shall be  $(12 \pm 1) \%$ .

Each beech wood board shall have a width of at least 150 mm, a length of at least 750 mm and a thickness of at least 35 mm, and shall be used to manufacture one test stick as shown in Figure 3, a) and b). The annual ring orientation of both components glued together shall be roughly co-linear and with an angle of the growth rings in the range of  $30^\circ$  and  $60^\circ$ .

### 5.3 Production of the test sticks

In total, 5 sticks with a cross section of 50 mm × 60 mm (after bonding and final preparation) and a length of at least 700 mm, enabling the cutting of 8 test specimens and 2 spare specimens from each stick of the specimen type described in EN 302-3, shall be manufactured for each glue line thickness.

Alternatively, longer sticks can be pre-assembled into sub-sections of at least 300 mm prior to bonding, providing sufficient matched samples for cutting the required number of specimens.

Not more than 8 h before the bonding, the boards are planed to their final thickness. For test pieces

## 5 Method

### 5.1 General

The specimens shall be produced following EN 302-3, but with specimens made from untreated beech wood (*Fagus sylvatica* L.) with close contact and 0,5 mm thick glue line for application areas “Special purpose” and “General purpose”, and a close contact glue line for application area “Finger joints”.

### 5.2 Selection of timber

The beech wood boards from which the specimens are cut shall be free from knots, straight grained and shall have a density of  $(700 \pm 50) \text{ kg/m}^3$  at 12 % moisture content. The timber prior to specimen manufacture shall be conditioned in a climate chamber at storage conditions of  $(20 \pm 2) ^\circ\text{C}$  and  $(65 \pm 5) \%$  relative humidity (hereafter climate [20/65]). The moisture content shall be  $(12 \pm 1) \%$ .

Each beech wood board shall have a width of at least 150 mm, a length of at least 750 mm and a thickness of at least 35 mm, and shall be used to manufacture one test stick as shown in Figure 3, a) and b). The annual ring orientation of both components glued together shall be roughly co-linear and with an angle of the growth rings in the range of  $30^\circ$  and  $60^\circ$ .

### 5.3 Production of the test sticks

In total, 5 sticks with a cross section of 50 mm × 60 mm (after bonding and final preparation) and a length of at least 700 mm, enabling the cutting of 8 test specimens and 2 spare specimens from each stick of the specimen type described in EN 302-3, shall be manufactured for each glue line thickness.

Alternatively, longer sticks can be pre-assembled into sub-sections of at least 300 mm prior to bonding, providing sufficient matched samples for cutting the required number of specimens.

Not more than 8 h before the bonding, the boards are planed to their final thickness. For test pieces

## 5 Method

### 5.1 General

The specimens shall be produced following EN 302-3, but with specimens made from untreated beech wood (*Fagus sylvatica* L.) with close contact and 0,5 mm thick glue line for application areas “Special purpose” and “General purpose”, and a close contact glue line for application area “Finger joints”.

### 5.2 Selection of timber

The beech wood boards from which the specimens are cut shall be free from knots, straight grained and shall have a density of  $(700 \pm 50) \text{ kg/m}^3$  at 12 % moisture content. The timber prior to specimen manufacture shall be conditioned in a climate chamber at storage conditions of  $(20 \pm 2) ^\circ\text{C}$  and  $(65 \pm 5) \%$  relative humidity (hereafter climate [20/65]). The moisture content shall be  $(12 \pm 1) \%$ .

Each beech wood board shall have a width of at least 150 mm, a length of at least 750 mm and a thickness of at least 35 mm, and shall be used to manufacture one test stick as shown in Figure 3, a) and b). The annual ring orientation of both components glued together shall be roughly co-linear and with an angle of the growth rings in the range of  $30^\circ$  and  $60^\circ$ .

### 5.3 Production of the test sticks

In total, 5 sticks with a cross section of 50 mm × 60 mm (after bonding and final preparation) and a length of at least 700 mm, enabling the cutting of 8 test specimens and 2 spare specimens from each stick of the specimen type described in EN 302-3, shall be manufactured for each glue line thickness.

Alternatively, longer sticks can be pre-assembled into sub-sections of at least 300 mm prior to bonding, providing sufficient matched samples for cutting the required number of specimens.

Not more than 8 h before the bonding, the boards are planed to their final thickness. For test pieces

## 5 Method

### 5.1 General

The specimens shall be produced following EN 302-3, but with specimens made from untreated beech wood (*Fagus sylvatica* L.) with close contact and 0,5 mm thick glue line for application areas “Special purpose” and “General purpose”, and a close contact glue line for application area “Finger joints”.

### 5.2 Selection of timber

The beech wood boards from which the specimens are cut shall be free from knots, straight grained and shall have a density of  $(700 \pm 50) \text{ kg/m}^3$  at 12 % moisture content. The timber prior to specimen manufacture shall be conditioned in a climate chamber at storage conditions of  $(20 \pm 2) ^\circ\text{C}$  and  $(65 \pm 5) \%$  relative humidity (hereafter climate [20/65]). The moisture content shall be  $(12 \pm 1) \%$ .

Each beech wood board shall have a width of at least 150 mm, a length of at least 750 mm and a thickness of at least 35 mm, and shall be used to manufacture one test stick as shown in Figure 3, a) and b). The annual ring orientation of both components glued together shall be roughly co-linear and with an angle of the growth rings in the range of  $30^\circ$  and  $60^\circ$ .

### 5.3 Production of the test sticks

In total, 5 sticks with a cross section of 50 mm × 60 mm (after bonding and final preparation) and a length of at least 700 mm, enabling the cutting of 8 test specimens and 2 spare specimens from each stick of the specimen type described in EN 302-3, shall be manufactured for each glue line thickness.

Alternatively, longer sticks can be pre-assembled into sub-sections of at least 300 mm prior to bonding, providing sufficient matched samples for cutting the required number of specimens.

Not more than 8 h before the bonding, the boards are planed to their final thickness. For test pieces