



BSI Standards Publication

Adhesives — Determination of the bond strength of engineering-plastic joints

National foreword

This British Standard is the UK implementation of [ISO 15509:2019](#). It supersedes [BS ISO 15509:2001](#), which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee PRI/52, Adhesives.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019
Published by BSI Standards Limited 2019

ISBN 978 0 539 00361 1

ICS 83.180

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 May 2019.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

**INTERNATIONAL
STANDARD**

**ISO
15509**

Second edition
2019-05-27

**Adhesives — Determination of
the bond strength of engineering-
plastic joints**

*Adhésifs — Détermination de la résistance de joints collés des
plastiques industriels*



Reference number
ISO 15509:2019(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	1
5 Specimen	2
5.1 Preparation.....	2
5.1.1 General.....	2
5.1.2 Mould.....	2
5.1.3 Injection-moulding parameters.....	3
5.1.4 Removal of the sprue.....	3
5.1.5 Geometry.....	3
5.2 Surface preparation.....	3
5.3 Assembly of the specimen in the mounting jig.....	4
5.4 Application of the adhesive.....	5
5.5 Conditioning and testing atmosphere.....	5
6 Apparatus	5
7 Procedure	5
8 Expression of results	8
9 Precision	8
10 Test report	8

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 61, *Plastics*, Subcommittee SC 11, *Products*.

This second edition cancels and replaces the first edition ([ISO 15509:2001](http://www.iso.org/iso/15509:2001)), which has been technically revised. The main changes compared to the previous edition are as follows:

- the list of normative references in [Clause 2](#) has been updated;
- the mandatory terms and definitions clause ([Clause 3](#)) has been inserted.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Methods of determining the strength of adhesive joints are well known. Several International Standards describe various methods including the lap-shear test or the butt torsion test. However, these methods are either not suitable for the determination of values which can be used for design purposes, or are restricted to metallic substrates. Because the existing International Standards for the measurement of the strength of bonded plastic materials are derived from test methods for metals and are less suitable for plastic materials due to the bending of substrates and varying modulus of elasticity, a new test method and a new test geometry have been developed and are described in this document.

Adhesives — Determination of the bond strength of engineering-plastic joints

1 Scope

This document describes a test method for measuring the shear and/or tensile strength of an adhesively bonded plastic/plastic specimen of a specific design. This method allows the determination of a combined shear and tensile behaviour of the bond. These shear and tensile values are useful for design purposes.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 291](#), *Plastics — Standard atmospheres for conditioning and testing*

[ISO 10365](#), *Adhesives — Designation of main failure patterns*

ISO 17212, *Structural adhesives — Guidelines for the surface preparation of metals and plastics prior to adhesive bonding*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Principle

A hollow cylindrical test specimen of specific design is used for the determination of the shear and tensile strengths of adhesively bonded plastic/plastic joints. These values can be used in calculation programmes. The rotationally symmetrical specimen allows testing under tensile, torsional or combined tensile/torsional loads if a suitable test machine is used.

NOTE 1 The shear stress is not uniformly distributed as the stress varies by approximately 15 % from the inner radius to the outer radius. Therefore, the calculated shear strength represents an “average” value.

NOTE 2 The origin of the stress distribution curve is the deformation of the bond line, as the deformation increases with increasing diameter. The superimposition of shear and tensile stresses is negligible in the bondline of rotationally symmetrical specimen compared to lap-shear specimen as described in [ISO 4587](#). There are practically no significant peaks in the stress distribution curve compared with the peaks observed in a lap-shear specimen, since the bond is continuous in the direction of the displacement.

5.1.3 Injection-moulding parameters

The parameters shall be agreed upon between the user and the plastic material supplier.

NOTE 1 The injection-moulding parameters will depend on the geometry of the mould and the nature of the plastic material.

Dimensions in millimetres




Figure 2 — Dimensions of adherend

The plastic material shall be pre-dried. The temperature and time shall be as agreed upon between the user and the plastic material supplier.

NOTE 2 Temperatures between 100 °C and 150 °C (depending on the type of plastic) over periods of 4 h to 6 h in a vacuum oven are the preferred conditions.

5.1.4 Removal of the sprue

Remove the central part, or sprue, from each of the adherends. A simple method consists of using a chisel while rotating the adherend in a lathe.

Avoid any contact with the bonding area during this operation.

5.1.5 Geometry

The specimen shall consist of two adherends bonded together.

The dimensions of each adherend shall be as given in [Figure 2](#).


5.2 Surface preparation

Prepare the bonding surfaces of the adherends in accordance with ISO 17212.

Corona discharge at ambient pressure is the preferred method.

5.3 Assembly of the specimen in the mounting jig

Assemble the specimen using the mounting jig shown in [Figure 3](#).



Key

- 1 baseplate
- 2 guide pin
- 3 fixation holding the adherend on the baseplate (three fixation points round the circumference, using springs exceeding a force higher than the weight of the adherend)
- 4 metal sleeve
- 5 screw for fixing spacers on the metal sleeve
- 6 gap for adhesive bond
- 7 adherend
- 8 spacer used to define the bond gap thickness (three pairs of spacers round the circumference, manufactured from the same material as the adherends)
- 9 adjustment screw (for adjusting bond gap)

Figure 3 — Schematic drawing of the specimen during the assembly process

NOTE 1 The mounting jig allows a small amount of movement of the adherends. This compensates for deformations which are caused by the shrinkage or thermal expansion of the adhesive and the adherends during curing.

The spacers shall be made of the same material as the adherends in order to eliminate differences in thermal expansion between the spacers and the adherends.

The spacers shall be linked to the metal sleeves which shall be freely movable along the guide pins.

The alignment of the adherends in the two halves of the mounting jig shall be ensured by a metal centering cone on each baseplate. Each cone shall be freely rotating and have a spring (strong enough to prevent the adherend sliding) which presses the adherend against the centering cone. When contact is established between the adherends and the centering cones, fix the adherends in place at the fixation points.

Assemble both baseplates (with the adherends but without adhesive) by introducing the guide pins into the sleeves and verify the gap between them (for the adhesive bond). The gap can be adjusted by means of the adjustment screws.

NOTE 2 The adjustment is usually made in order to achieve a bond thickness of 0,1 mm.

5.4 Application of the adhesive

Apply the adhesive using the application device as shown in [Figure 4](#), as follows.

Place a baseplate carrying one of the adherends under the dispenser.

Adjust the dispenser so that the nozzle is located exactly above the application area. Apply the adhesive.

NOTE An automated rotating device coupled with the dispenser has been shown to give good results.

Assemble the two halves of the mounting jig and cure the adhesive in accordance with the manufacturer's instructions.

5.5 Conditioning and testing atmosphere

The specimens shall be conditioned and tested in one of the standard laboratory atmospheres specified in [ISO 291](#).

6 Apparatus

5.1 Test machine, equipped with a temperature-controlled enclosure for tests carried out at temperatures other than ambient.

5.2 Clamping jig (see [Figure 5](#)), consisting of an adapter, and two jaws with hinge, screw and locknut.

NOTE This special clamping jig allows easy and quick fixing of the specimen in the test machine.


7 Procedure

Place the adapter and the specimen in the jaws. Secure them with the screws. Draw in the locknut to hold the specimen by its flange.

Insert the clamping jigs in the test machine, ensuring that no load is applied to the bonded joint.

Apply a tensile force at a crosshead speed of 1 mm/min and/or a torsional force at a speed of 5°/min until the joint fails. Record the ultimate force reached during the test.


Examine the surface of the bonded parts after failure, and record the failure pattern in accordance with [ISO 10365](#).



Key

- 1 dispenser
- 2 dispenser nozzle
- 3 adherend
- 4 fixation holding the adherend on the baseplate
- 5 centering cone
- 6 baseplate
- 7 rotating support

Figure 4 — Application of the adhesive



Key

- 1 adapter
- 2 jaws (hinge, screw and locknut not shown)
- 3 spring
- 4 metal centering cone
- 5 test specimen

Figure 5 — Schematic drawing of clamping jig

8 Expression of results

The bonded area corresponds to [Formula \(1\)](#)

$$\frac{\pi}{4}(d_1^2 - d_2^2) \quad (1)$$

where

d_1 is the outer diameter of the bonded area, expressed in millimetres (mm);

d_2 is the inner diameter of the bonded area, expressed in millimetres (mm).

Since $d_1 = 24$ mm and $d_2 = 20$ mm, the area is 138 mm².

The tensile strength, in pascals is given by the force at failure in newtons, divided by the bonded area, in square millimetres.

The shear strength τ_{\max} is given in megapascals by [Formula \(2\)](#)

$$\tau_{\max} = \frac{M_t \times 16 \times d_1}{\pi(d_1^4 - d_2^4)} \quad (2)$$

where M_t is the moment at failure, expressed in megapascals (MPa).

9 Precision

The precision data of this test method are not available at the time of publication.

10 Test report

The test report shall include the following information:

- a) a reference to this document, i.e. [ISO 15509:2019](#);
- b) all details necessary for complete identification of the adhesive tested, including type, source and manufacturer's code number, batch or lot number, etc.;
- c) all details necessary for complete identification of the adherends used, including details of preparation and moulding, the method of preparation of the surface prior to bonding, the conditions used to cure the adhesive and the atmosphere used to condition the specimens;
- d) the test conditions and test mode (tensile or torsional);
- e) the number of specimens tested;
- f) the shear and/or tensile strength of each specimen;
- g) the failure pattern of each specimen, in accordance with [ISO 10365](#);
- h) the date of the testing.

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.
- Standards purchased in hard copy format:
- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email subscriptions@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK