



BSI Standards Publication

Plain bearings — Thermoplastic bushes — Dimensions and tolerances

INTERNATIONAL
STANDARD

ISO
16287

Second edition
2021-03

Plain bearings — Thermoplastic
bushes — Dimensions and tolerances

Paliers lisses — Bagues thermoplastiques — Dimensions et tolérances



Reference number
ISO 16287:2021(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO’s member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org
Published in Switzerland

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols	1
5	Dimensions	2
6	Material	8
7	Design	9
8	Testing	9
	8.1 General	9
	8.2 Outside diameter, D_o	9
	8.3 Inside diameter, D_i	9
9	Assembling	10
10	Designation	12
Bibliography		13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 123, *Plain bearings*, Subcommittee SC 7, *Special types of plain bearings*.

This second edition cancels and replaces the first edition (ISO 16287:2005), which has been technically revised. The main changes compared to the previous edition are as follows:

- [Clause 3](#), “Terms and definitions”, has been added;
- [Figures 2](#) and [3](#) have been revised.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Plain bearings — Thermoplastic bushes — Dimensions and tolerances

1 Scope

This document specifies the dimensions and tolerances for inserted thermoplastic bushes used as plain bearings with or without lubrication grooves in accordance with ISO 12128. These thermoplastic bushes are dimensionally exchangeable to wrapped bushes according to ISO 3547-1.

This document is not applicable to reinforced plastics.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 554, *Standard atmospheres for conditioning and/or testing — Specifications*

ISO 3547-2, *Plain bearings — Wrapped bushes — Part 2: Test data for outside and inside diameters*

ISO 6691, *Thermoplastics polymers for plain bearings — Classification and designation*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Symbols

B	nominal width of bush
B_{fl}	flange thickness
C_i	inside chamfer
C_o	outside chamfer
D_{fl}	flange diameter
D_H	nominal housing bore diameter
D_i	nominal inside diameter of the bush
$D_{i,ch}$	inside diameter of the bush when inserted in a ring gauge middle H7
D_o	nominal outside diameter of the bush
r	radius for flange bushes

5 Dimensions

The dimensions and tolerances of the thermoplastic bushes are shown in [Figures 1](#) and [2](#), according to whether cylindrical (type C) or flanged (type F), and given, in millimetres, in [Tables 1](#), [2](#), [3](#) and [4](#). The surface finishes *x* and *y* represented in [Figures 1](#) and [2](#) are given in [Table 5](#).

For the determination of the IT value (see ISO 286-1) of the coaxiality tolerance, the dimensions of D_o are applicable.

For the determination of the IT value (ISO 286-1) of the axial run-out tolerance, the dimensions of D_{fl} are applicable.




Figure 1 — Cylindrical bush




Figure 2 — Flanged bush

Table 1 — Nominal sizes and limits for thick-walled bushes type C and type F

Dimensions in millimetres

D_i^d nom.	D_o nom.		Limits for tolerance group (see Table 5)		D_{fi}^e d13	B_{fi} h13	B^a h13			C_i^b	r
			A	B						C_o^c maximum	
6	10	12	+0,21	zb11	14	3	6	10	—	0,8	0,5
8	12	14	+0,07		18	3	6	10	15	0,8	0,5
10	14	16	+0,27 +0,09		20	3	6	10	15	0,8	0,5
12	16	18			22	3	10	15	20	0,8	0,8
14	18	20			25	3	10	15	20	0,8	0,8
15	18	21	+0,33 +0,11		27	3	10	15	20	0,8	0,8
16	20	22			28	3	12	15	20	0,8	0,8
18	22	24			30	3	12	20	30	0,8	0,8
20	24	26	+0,45 +0,15		32	3	15	20	30	1,5	0,8
22	26	28			34	3	15	20	30	1,5	0,8
24	28	30			36	3	15	20	30	1,5	0,8
25	30	32			38	4	20	30	40	1,5	0,8
28	34	36	+0,60 +0,20		42	4	20	30	40	2	0,8
30	36	38			44	4	20	30	40	2	0,8
32	38	40			46	4	20	30	40	2	0,8
35	41	45	+0,69 +0,23		50	5	30	40	50	2	0,8
38	45	48			54	5	30	40	50	2	0,8
40	48	50			58	5	30	40	60	2	0,8
42	50	52	+0,90 +0,30		60	5	30	40	60	2	0,8
45	53	55			63	5	30	40	60	2,5	0,8
48	56	58			66	5	40	50	60	2,5	0,8
50	58	60			68	5	40	50	60	2,5	0,8
55	63	65			73	5	40	50	70	2,5	0,8
60	70	75		83	7,5	40	60	80	2,5	0,8	
65	75	80		88	7,5	50	60	80	2,5	2	
70	80	85		95	7,5	50	70	90	2,5	2	
75	85	90	f	100	7,5	50	70	90	2,5	2	
80	90	95		105	7,5	60	80	100	2,5	2	
85	95	100		110	7,5	60	80	100	2,5	2	
90	105	110		120	10	60	80	120	2,5	2	
95	110	115		125	10	60	100	120	2,5	2	
100	115	120		130	10	80	100	120	2,5	2	
105	120	125		135	10	80	100	120	2,5	2	
110	125	130		140	10	80	100	120	2,5	2	
120	135	140	za11	150	10	100	120	150	2,5	2	
130	145	150		160	10	100	120	150	3	2	
140	155	160		170	10	100	150	180	3	2	
^a If it is necessary to use the non-standard width B , then these should be arranged to have a final digit of 0, 2, 5 or 8.											
^b As an alternative to the chamfer C_i , a 45° angle may be used.											
^c As an alternative to the chamfer C_o , a radius may be used.											
^d Depending on the material, the wall thickness shall be rated so that the inside diameter D_i of the fitted bush is within the tolerance classes F10 to D12 respectively.											
^e For D_{fi} , the tolerance class d13 is preferred. Other tolerance class up to h13 are allowable and shall be subject to agreement between the manufacturer and the user.											
^f To be agreed between the manufacturer and the user.											

Table 1 (continued)

D_i^d	D_o Limits for tolerance group (see Table 5)		D_{fl}^e	B_{fl}	B^a			C_i^b C_o^c	r		
nom.	nom.		A	B	d13	h13	h13			maximum	maximum
150	165	170			180	10	120	150	180	3	2
160	180	185			200	12,5	120	150	180	3	2
170	190	195			210	12,5	120	180	200	3	2
180	200	210			220	15	150	180	250	3	2
190	210	220			230	15	150	180	250	3	2
200	220	230			240	15	180	200	250	3	2
<p>^a If it is necessary to use the non-standard width B, then these should be arranged to have a final digit of 0, 2, 5 or 8.</p> <p>^b As an alternative to the chamfer C_i, a 45° angle may be used.</p> <p>^c As an alternative to the chamfer C_o, a radius may be used.</p> <p>^d Depending on the material, the wall thickness shall be rated so that the inside diameter D_i of the fitted bush is within the tolerance classes F10 to D12 respectively.</p> <p>^e For D_{fl}, the tolerance class d13 is preferred. Other tolerance class up to h13 are allowable and shall be subject to agreement between the manufacturer and the user.</p> <p>^f To be agreed between the manufacturer and the user.</p>											

Table 2 — Nominal sizes and limits for thin-walled cylindrical bushes type C

Dimensions in millimetres

D_i^d	D_o		B^a	C_i^b C_o^c							
	Limits for tolerance group (see Table 5)										
nom.	nom.	A	B	h13	maximum						
6	8	+0,21	zb11	4	6	8	10	—	—	0,8	
8	10	+0,07		6	8	10	12	15	—	0,8	
10	12	+0,27		6	8	10	12	15	20	0,8	
12	14			8	10	12	15	20	25	0,8	
14	16	+0,09		10	12	15	20	25	—	0,8	
15	17	+0,33		10	12	15	20	25	—	0,8	
16	18			10	12	15	20	25	—	0,8	
18	20			10	15	20	25	—	—	0,8	
20	23	+0,45		10	15	20	25	30	—	1,5	
22	25			—	15	20	25	30	—	1,5	
24	27			+0,15	—	15	20	25	30	—	1,5
25	28			—	15	20	25	30	50	1,5	
28	32	+0.60		—	15	20	25	30	—	2	
30	34			10	15	20	25	30	40	2	
32	36			+0,20	20	30	40	—	—	—	2
35	39	+0,69		20	30	35	40	50	—	2	
38	42			20	30	40	—	—	—	2	
40	44			+0,23	20	30	40	50	—	—	2
<div><div>^a If it is necessary to use the non-standard width B, then these should be arranged to have a final digit of 0, 2, 5 or 8.</div><div>^b As an alternative to the chamfer C_i, a 45° angle may be used.</div><div>^c As an alternative to the chamfer C_o, a radius may be used.</div><div>^d Depending on the material, the wall thickness shall be rated so that the inside diameter D_i of the fitted bush is within the tolerance classes F10 to D12 respectively.</div><div>^e To be agreed between the manufacturer and the user.</div></div>											

Table 2 (continued)

D_i^d	D_o		B^a							C_i^b C_o^c		
	Limits for tolerance group (see Table 5)											
	nom.	nom.	A	B	h13						maximum	
45	50	+0,90 +0,30			20	30	40	45	50	—	2,5	
50	55				20	30	40	50	60	—	2,5	
55	60				20	30	40	50	60	—	2,5	
60	65	e			za11	20	30	40	50	60	70	2,5
65	70					30	50	70	—	—	—	2,5
70	75					30	40	50	70	—	—	2,5
75	80					—	40	60	80	—	—	2,5
80	85					—	40	60	80	100	—	2,5
85	90					30	40	60	80	100	—	2,5
90	95					40	60	100	—	—	—	2,5
95	100		—	60		100	—	—	—	2,5		
100	105		50	60		100	115	—	—	2,5		
105	110		60	100		105	—	—	—	2,5		
110	115		60	100		115	—	—	—	2,5		
115	120		60	100		—	—	—	—	2,5		
120	125		60	100		—	—	—	—	2,5		
125	130		60	100		—	—	—	—	2,5		
130	135		60	100		—	—	—	—	3		
135	140		60	100		—	—	—	—	3		
140	145		60	100		—	—	—	—	3		
150	155	60	100	—	—	—	—	3				
^a If it is necessary to use the non-standard width B , then these should be arranged to have a final digit of 0, 2, 5 or 8.												
^b As an alternative to the chamfer C_i , a 45° angle may be used.												
^c As an alternative to the chamfer C_o , a radius may be used.												
^d Depending on the material, the wall thickness shall be rated so that the inside diameter D_i of the fitted bush is within the tolerance classes F10 to D12 respectively.												
^e To be agreed between the manufacturer and the user.												

Table 3 — Nominal sizes and limits for thin-walled flanged bushes type F

Dimensions in millimetres

D_i^d nom.	nom.	D_o Limits for tolerance group (see Table 5)		D_{fl}^e d13	B_{fl} h13	B^a h13			C_i^b C_o^c	r
		A	B						maximum	maximum
6	8	+0,21	zb11	12	1	6	10	—	0,8	0,5
8	10	+0,07		15	1	6	10	15	0,8	0,5
10	12	+0,27 +0,09		18	1	6	10	15	0,8	0,5
12	14			20	1	10	15	20	0,8	0,8
14	16			22	1	10	15	20	0,8	0,8
15	17	+0,33 +0,11		23	1	10	15	20	0,8	0,8
16	18			24	1	12	15	20	0,8	0,8
18	20			26	1	12	20	30	0,8	0,8
20	23	+0,45 +0,15		30	1,5	15	20	30	1,5	0,8
22	25			31	1,5	15	20	30	1,5	0,8
24	27			34	1,5	15	20	30	1,5	0,8
25	28			35	1,5	20	30	40	1,5	0,8
28	32	+0,60 +0,20		39	2	20	30	40	2	0,8
30	34			42	2	20	30	40	2	0,8
32	36			44	2	20	30	40	2	0,8
35	39	+0,69 +0,23		47	2	30	40	50	2	0,8
38	42			50	2	30	40	50	2	0,8
40	44			53	2	30	40	60	2	0,8
42	47	+0,90 +0,30		55	2,5	30	40	60	2	0,8
45	50			58	2,5	30	40	60	2,5	0,8
48	53			62	2,5	40	50	60	2,5	0,8
50	55			65	2,5	40	50	60	2,5	0,8
55	60			70	2,5	40	50	70	2,5	0,8
60	65	f		75	2,5	40	60	80	2,5	0,8
65	70			80	2,5	50	60	80	2,5	2
70	75			85	2,5	50	70	90	2,5	2
75	80			90	2,5	50	70	90	2,5	2
80	85			95	2,5	60	80	100	2,5	2
85	90			100	2,5	60	80	100	2,5	2
90	95			110	2,5	60	80	120	2,5	2
95	100			115	2,5	60	100	—	2,5	2
100	105			120	2,5	80	100	120	2,5	2
<p>^a If it is necessary to use the non-standard width B, then these should be arranged to have a final digit of 0, 2, 5 or 8.</p> <p>^b As an alternative to the chamfer C_i, a 45° angle may be used.</p> <p>^c As an alternative to the chamfer C_o, a radius may be used.</p> <p>^d Depending on the material, the wall thickness shall be rated so that the inside diameter D_i of the fitted bush is within the tolerance classes F10 to D12 respectively.</p> <p>^e For D_{fl}, the tolerance class d13 is preferred. Other tolerance class up to h13 are allowable and shall be subject to agreement between manufacturer and user.</p> <p>^f To be agreed between manufacturer and user.</p>										

Table 3 (continued)

D_i^d	D_o		D_{fl}^e	B_{fl}	B^a			C_i^b	r	
	Limits for tolerance group (see Table 5)							C_o^c		
	nom.	nom.						A		B
105	110		za11	125	2,5	80	100	—	2,5	2
110	115			130	2,5	80	100	120	2,5	2
120	125			140	2,5	100	—	—	2,5	2
130	135			150	2,5	100	—	—	3	2
140	145			160	2,5	100	—	—	3	2
150	155			170	2,5	100	—	—	3	2
<p>^a If it is necessary to use the non-standard width B, then these should be arranged to have a final digit of 0, 2, 5 or 8.</p> <p>^b As an alternative to the chamfer C_i, a 45° angle may be used.</p> <p>^c As an alternative to the chamfer C_o, a radius may be used.</p> <p>^d Depending on the material, the wall thickness shall be rated so that the inside diameter D_i of the fitted bush is within the tolerance classes F10 to D12 respectively.</p> <p>^e For D_{fl}, the tolerance class d13 is preferred. Other tolerance class up to h13 are allowable and shall be subject to agreement between manufacturer and user.</p> <p>^f To be agreed between manufacturer and user.</p>										

Table 4 — Nominal sizes and limits for thin-walled flanged bushes type F with widths *B* from ISO 3547-1

Dimensions in millimetres

D_i^c	nom.	D_o Limits for tolerance group (see Table 5)		D_{fl}^d	B_{fl}	B				C_i^a	r
		A	B							C_o^b	
nom.	nom.	A	B	d13	h13	h13				maximum	maximum
6	8	+0,21	zb11	12	1	4	8	—	—	0,8	0,5
8	10	+0,07		15	1	5,5	7,5	9,5	—	0,8	0,5
10	12	+0,27		18	1	7	9	12	17	0,8	0,5
12	14			20	1	7	9	12	17	0,8	0,8
14	16	+0,09		22	1	12	17	—	—	0,8	0,8
15	17	+0,33		23	1	9	12	17	—	0,8	0,8
16	18			24	1	12	17	—	—	0,8	0,8
18	20	+0,11		26	1	12	17	22	—	0,8	0,8
20	23	+0,45		30	1,5	11,5	16,5	21,5	—	1,5	0,8
25	28	+0,15		35	1,5	11,5	16,5	21,5	—	1,5	0,8
30	34	+0,60 +0,20		42	2	16	26	—	—	2	0,8
35	39	+0,69		47	2	16	26	—	—	2	0,8
40	44	+0,23		53	2	16	26	—	—	2	0,8
45	50	+0,90 +0,30		58	2,5	16	26	—	—	2,5	0,8
^a As an alternative to the chamfer C_i , a 45° angle may be used.											
^b As an alternative to the chamfer C_o , a radius may be used.											
^c Depending on the material, the wall thickness shall be rated so that the inside diameter D_i of the fitted bush is within the tolerance classes F10 to D12 respectively.											
^d For D_{fl} , the tolerance class d13 is preferred. Other tolerance class up to h13 are allowable and shall be subject to agreement between manufacturer and user.											

6 Material

Thermoplastics shall be in accordance with ISO 6691, e.g. PA, PET, PE, POM.

For modified or other materials, details shall be subject to agreement between the supplier and the purchaser.

NOTE Thermoplastics have a higher coefficient of linear thermal expansion than metals. PA absorbs more moisture than the other materials given and thus, in addition, will alter in volume.

With the tolerance zones and fits specified in this document, these properties are taken into account under the following conditions:

- a) the bearing clearance is designed for an operating temperature of the bush of −10 °C to +50 °C and a relative ambient humidity of 20 % to 95 %;
- b) interference fit in the housing is achieved by the insertion interference (limit deviation of *D*_o) and is also maintained at operating temperatures of −10 °C to +50 °C;

- c) [Tables 1, 2, 3](#) and [4](#) are based upon shaft and housing having coefficients of linear thermal expansion of $10 \cdot 10^{-6} \cdot \text{K}^{-1}$ to $12 \cdot 10^{-6} \text{K}^{-1}$.

For other operating conditions than those given above, the bearing clearance and the type of fixing shall be reviewed and validated. The tolerances are applicable in the conditioned state of the bushes, i.e. they shall have the temperature (23 °C) and the moisture content (50 %) resulting at a standard atmosphere in accordance with ISO 554 (23/50).

To maintain their dimensions, bushes made of PA shall be stored in the above given standard atmosphere or in a suitable hermetically sealed condition.

7 Design

The surface finish and tolerance classes shall be in accordance with [Table 5](#), for group A or B.

Table 5 — Surface finish and limits

Tolerance group	Method of manufacture	Surface finish of bush				Tolerance class for D_i resulting after insertion into the housing bore	Tolerance class of housing bore diameter D_H	Tolerance class of shaft
		x^a		y^a				
		Rz	Ra	Rz	Ra			
		μm						
A	moulded	16	2,5	100	25	F10 to D12	H7	h7 to h9
B	machined	25	6,3			C11		
^a Rz or Ra on agreement.								

The edges shall be free from flash or burrs.

Due to the large insertion interference, the leading edge of the housing bore shall be suitably chamfered or rounded in order to avoid damage during insertion (see [Figure 3](#) in [Clause 9](#)).

The standard bearings (type C and type F) shall have a minimum of one outside diameter chamfer and one inside diameter chamfer at opposite ends. By agreement, additional chamfers may be provided.

8 Testing

8.1 General

The dimensions of the bush shall be tested in the conditioned state (see also the Note in [Clause 6](#)).

8.2 Outside diameter, D_o

- a) Check the outside bush diameter with two ring gauges.

The GO ring corresponds to the maximum D_o size limit and the NO GO ring to the minimum D_o size limit according to [Tables 1](#) to [4](#) or supplier specification for special thermoplastic compounds.

- b) Measure the outside diameter in free condition, determined as the arithmetic mean of at least two measurements (see ISO 12301).

8.3 Inside diameter, D_i

- a) Check the inside bush diameter with two ring gauges.

Insert the bush successively into two gauging rings, one corresponding to the maximum size limit and the other to the minimum size limit of the housing tolerance class H7.

The inside bush diameter shall not exceed the bottom limit of the specified tolerance class according to [Table 5](#), when inserted into the gauging ring having the minimum housing tolerance limit.

The inside bush diameter shall not exceed the upper limit of the specified tolerance class when inserted into the gauging ring having the maximum housing tolerance limit.

The inside maximum and minimum bush diameter shall be checked with a GO and NO GO plug gauge or measured with a 3-point measuring instrument.

- b) Check the inside bush diameter with one ring gauge, in accordance with ISO 3547-2, test C for wrapped bushes

Press the bush into a ring gauge, the size of which is made up of D_o and the rounded average value of the tolerance class H7.

The inside diameter of the bush when it is pressed into the ring gauge $D_{i,ch}$ shall be checked with a GO and NO GO plug gauge or measured with a 3-point measuring instrument.

The width of the gauging ring shall be greater than the width of the bush.

There are tolerance differences between checking the inside diameter of the bush in two ring gauges corresponding to the H7 limit sizes [see [8.3](#), a)] and checking the inside bush diameter in one ring gauge with the average value of H7 [see [8.3](#), b)]. There are further tolerance differences between gauging and measuring the inside bush diameter. Therefore, checking details shall be subject to agreement between the supplier and the purchaser.

9 Assembling

A cylindrical or flange bush should be assembled into its housing with the aid of a stepped mandrel, preferably made from case-hardened mild steel.

A 45° lead-in chamfer should be machined in the housing to assist assembly. For flanged bushes, the minimum chamfer shall be $r_{max} \times 45^\circ$ (to allow for the radius behind the flange).

The bush, mandrel and housing shall be correctly aligned during assembly.

Mandrel and chamfer dimensions should be as shown in [Figure 3](#).




Figure 3 — Fitting instructions

10 Designation

EXAMPLE A thin-walled flanged bush type F of inside diameter $D_i = 20$ mm, tolerance class F10, outside diameter $D_o = 23$ mm, tolerance group A and with $B = 20$ mm, made of PA 6:

Bush ISO 16287 - F 20 F10 × 23 A 20 - PA 6

Bibliography

- [1] ISO 286-1, *Geometrical product specifications (GPS) — ISO code system for tolerances on linear sizes — Part 1: Basis of tolerances, deviations and fits*
- [2] ISO 3547-1, *Plain bearings — Wrapped bushes — Part 1: Dimensions*
- [3] ISO 12128, *Plain bearings — Lubrication holes, grooves and pockets — Dimensions, types, designation and their application to bearing bushes*
- [4] ISO 12301, *Plain bearings — Quality control techniques and inspection of geometrical and material quality characteristics*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email cservices@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email: cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

