

BS ISO 19670:2017



BSI Standards Publication

**Fertilizers and soil conditioners
— Solid urea aldehyde slow
release fertilizer — General
requirements**

bsi.
British Standards Institution

National foreword

This British Standard is the UK implementation of ISO 19670:2017.

The UK participation in its preparation was entrusted to Technical Committee CII/37, Fertilisers and related chemicals.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017.
Published by BSI Standards Limited 2017

ISBN 978 0 580 86778 1

ICS 65.080

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2017.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL
STANDARD

ISO
19670

First edition
2017-03

**Fertilizers and soil conditioners —
Solid urea aldehyde slow release
fertilizer — General requirements**

*Engrais et amendements — Engrais urée aldéhyde solide à libération
lente — Exigences générales*



Reference number
ISO 19670:2017(E)

INTERNATIONAL
STANDARD

ISO
19670

First edition
2017-03

**Fertilizers and soil conditioners —
Solid urea aldehyde slow release
fertilizer — General requirements**

*Engrais et amendements — Engrais urée aldéhyde solide à libération
lente — Exigences générales*



Reference number
ISO 19670:2017(E)

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements	2
4.1 Visual inspection.....	2
4.2 Requirement of solid urea aldehyde slow release fertilizer.....	2
5 Analytical methods	3
5.1 Determination of the appearance.....	3
5.2 Determination of the mass fraction of total nitrogen.....	3
5.3 Determination of the mass fraction of ureic nitrogen.....	3
5.4 Determination of the mass fraction of CWIN.....	3
5.4.1 Principle.....	3
5.4.2 Reagents.....	3
5.4.3 Apparatus.....	3
5.4.4 Procedure.....	4
5.4.5 Expression of results.....	4
5.5 Determination of the mass fraction of HWIN and AI.....	4
5.5.1 Principle.....	4
5.5.2 Reagents.....	4
5.5.3 Apparatus.....	5
5.5.4 Procedure.....	5
5.5.5 Expression of results.....	5
5.6 Determination of the mass fraction of nitrogen from IBDU and CDU.....	6
6 Sampling and preparation of test sample	6
6.1 Sampling method.....	6
6.1.1 Products in bags.....	6
6.1.2 Products in bulk.....	6
6.2 Reduction of samples.....	6
6.3 Test sample preparation.....	6
7 Marking and labelling	7
8 Packaging, transport and storage	7
Bibliography	8

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 134, *Fertilizers and soil conditioners*.

Introduction

Solid urea aldehyde slow release fertilizer is a non-coated and chemically synthesized nitrogen fertilizer with slow release effect. In 1924, the first slow release fertilizer patent in the world was issued to urea formaldehyde (UF) and in 1955, UF was put into commercial production as the oldest slow release fertilizer. Solid urea aldehyde slow release fertilizer has the longest history of research, use and production among the slow release fertilizers used in practice. At the same time, it is the most widely used of all slow release fertilizers.

For facilitating international fertilizer trade, it is necessary to have an international and general standard for solid urea aldehyde slow release fertilizers.

Fertilizers and soil conditioners — Solid urea aldehyde slow release fertilizer — General requirements

1 Scope

This document specifies general requirements, analytical methods, sampling and preparation of test sample, marking and labelling, packaging, transport and storage for solid urea aldehyde slow release fertilizer.

This document applies to pure solid urea aldehyde slow release fertilizer, i.e. urea formaldehyde (UF), methylene urea (MU), crotonylidene diurea (CDU), isobutylidene diurea (IBDU). This document does not apply to mixtures of nitrogenous fertilizers containing solid urea aldehyde slow release fertilizer.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5315, *Fertilizers — Determination of total nitrogen content — Titrimetric method after distillation*

ISO 7409, *Fertilizers — Marking — Presentation and declarations*

ISO 7410, *Fertilizers and soil conditioners — Final samples — Practical arrangements*

ISO 7742, *Solid fertilizers — Reduction of samples*

ISO 8157, *Fertilizers and soil conditioners — Vocabulary*

ISO 8633, *Solid fertilizers — Simple sampling method for small lots*

ISO 19746:2017, *Determination of urea content in urea-based fertilizers by high performance liquid chromatography (HPLC)*

ISO 25705:2016, *Fertilizers — Determination of urea condensates using high-performance liquid chromatography (HPLC) — Isobutylidenediurea and crotonylidenediurea (method A) and methylen-urea oligomers (method B)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8157 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp/>

3.1

urea aldehyde slow release fertilizer

products of reaction between urea and aldehyde(s) that produce a slow release nitrogenous fertilizer

EXAMPLE Urea formaldehyde (UF), methylene urea (MU), crotonylidene diurea (CDU), isobutylidene diurea (IBDU).

3.2
cold water insoluble nitrogen

CWIN
insoluble nitrogen fractions in urea formaldehyde or methylene urea products that are insoluble in phosphate buffer solution (pH 7,5) or distilled water at 25 °C during a 15 min period

3.3
cold water soluble nitrogen

CWSN
soluble nitrogen fractions in urea formaldehyde or methylene urea products that are soluble in phosphate buffer solution (pH 7,5) or distilled water at 25 °C during a 15 min period

Note 1 to entry: CWSN = Total nitrogen – CWIN

3.4
hot water insoluble nitrogen

HWIN
insoluble nitrogen fractions in urea formaldehyde or methylene urea products that are insoluble in phosphate buffer solution (pH 7,5) at 100 °C during a 30 min period

3.5
hot water soluble nitrogen

HWSN
soluble nitrogen fractions in urea formaldehyde or methylene urea products that are soluble in phosphate buffer solution (pH 7,5) at 100 °C during a 30 min period

Note 1 to entry: HWSN = Total nitrogen – HWIN

3.6
hot water soluble nitrogen only

HWSN only
soluble nitrogen fractions in urea formaldehyde or methylene urea products that are soluble in phosphate buffer solution (pH 7,5) at 100 °C during a 30 min period and insoluble in phosphate buffer solution (pH 7,5) at 25 °C during a 15 min period

Note 1 to entry: HWSN only = HWSN – CWSN = CWIN – HWIN

3.7
activity index

AI
percentage of *CWIN* (3.2) that is solubilised in hot water (*HWSN only*) (3.6)

Note 1 to entry: $AI = \frac{CWIN - HWIN}{CWIN} \times 100$

Note 2 to entry: CWIN and HWIN in Note 1 are expressed in the mass fraction (%).

Note 3 to entry: A higher AI indicates better slow release characteristics of urea formaldehyde fertilizer.

4 Requirements

4.1 Visual inspection

The product shall be in powder, granules, prills, pellets, pastilles, chips or other solid forms. Visually inspect for the presence of contaminant and foreign matter.

4.2 Requirement of solid urea aldehyde slow release fertilizer

Solid urea aldehyde slow release fertilizer shall be tested to demonstrate conformance with all the requirements specified in [Tables 1](#) and [2](#) respectively, and declared values on containers.

Table 1 — Requirements of urea formaldehyde/methylene urea fertilizer

Item		Requirements
Total nitrogen (TN) (mass fraction)	≥	36 %
Ureic nitrogen (mass fraction)	≤	5 %
HWSN (mass fraction)	≥	3/5 of the declared total nitrogen content
AI	≥	40 %
The requirements specified by national/regional legislation shall be followed when urea formaldehyde/methylene ureas are covered by legislation.		

Table 2 — Requirements of IBDU and CDU

Item		Requirements
Total nitrogen (mass fraction)	≥	28 %
Ureic nitrogen (mass fraction)	≤	3 %
Nitrogen from IBDU or CDU (mass fraction)	≥	25 %
The requirements specified by the national/regional legislation shall be followed when IBDU or CDU are covered by legislation.		

5 Analytical methods

5.1 Determination of the appearance

It shall be determined by visual method.

5.2 Determination of the mass fraction of total nitrogen

It shall be determined in accordance with ISO 5315.

5.3 Determination of the mass fraction of ureic nitrogen

It shall be determined in accordance with ISO 19746.

5.4 Determination of the mass fraction of CWIN

5.4.1 Principle

Extraction of the test portion in phosphate buffer solution (pH 7,5) or distilled water at 25 °C. Filtration of insoluble residue, washing and determination of nitrogen content in insoluble residue.

5.4.2 Reagents

5.4.2.1 Phosphate buffer solution (pH 7,5). Dissolve 14,3 g KH_2PO_4 and 91,0 g K_2HPO_4 in water and dilute to 1 l. Dilute 100 ml of this solution to 1 l.

5.4.2.2 Anhydrous ethanol.

5.4.2.3 Reagents listed in ISO 5315.

5.4.3 Apparatus

5.4.3.1 Usual laboratory apparatus.

5.4.3.2 Water bath, capable of being maintained at $(25 \pm 2) ^\circ\text{C}$.

5.4.3.3 Quantitative filter paper (intermediate speed).

5.4.3.4 Apparatus listed in ISO 5315.

5.4.4 Procedure

Two analyses shall be performed simultaneously for the determination.

Place 1 g to 1,4 g test portion (accurate to 0,000 1 g) in 50 ml beaker wet with ethanol ([5.4.2.2](#)). Add 20 ml phosphate buffer solution ([5.4.2.1](#)) or distilled water and let stand 15 min in the water bath maintained at $25 ^\circ\text{C} \pm 2 ^\circ\text{C}$ and stir at 5 min intervals during standing. Transfer the supernate to a piece of filter paper ([5.4.3.3](#)) in a long-stem funnel and wash the residue four or five times by decanting with water of $25 ^\circ\text{C} \pm 2 ^\circ\text{C}$. Finally, transfer all the residue to the filter paper and complete washing until the filtrate measures 250 ml. Determine nitrogen content in the filter paper and the residue in accordance with ISO 5315.

Carry out a blank test at the same time as the determination, using the same procedure, using the same reagents, but omitting the test portion.

5.4.5 Expression of results

The CWIN content, w_1 , expressed as a mass fraction (%), is given by [Formula \(1\)](#):

$$w_1 = \frac{(V_1 - V_2) \times c_1 \times 14,01}{m_1 \times 1\,000} \times 100 \quad (1)$$

where

V_1 is the volume, in millilitres, of sodium hydroxide standard solution used for the blank test;

V_2 is the volume, in millilitres, of sodium hydroxide standard solution used for the determination;

c_1 is the concentration, in mol per litre, of sodium hydroxide standard solution used;

m_1 is the mass, in grams, of the test portion.

The calculation results are accurate to two digits after the decimal point. The determination result is the arithmetic average of the duplicate determination results.

5.5 Determination of the mass fraction of HWIN and AI

5.5.1 Principle

Extraction of the test portion in phosphate buffer solution (pH 7,5) at $100 ^\circ\text{C}$. Filtration of insoluble residue, washing and determination of nitrogen content in insoluble residue.

5.5.2 Reagents

5.5.2.1 Reagents listed in [5.4.2](#).

5.5.2.2 Celite.

5.5.3 Apparatus

5.5.3.1 Usual laboratory apparatus.

5.5.3.2 Water bath, capable of being maintained at (100 ± 2) °C.

5.5.3.3 Apparatus listed in [5.4.3.3](#) and [5.4.3.4](#).

5.5.4 Procedure

Two analyses shall be performed simultaneously for the determination.

Place an accurately weighed test portion containing 0,12 g CWIN (accurate to 0,000 1 g) in a 250 ml tall-form beaker. Add 100 ml 100 °C phosphate buffer solution ([5.4.2.1](#)) from a graduated cylinder to the test portion, stir, cover and immerse promptly in a boiling water bath ([5.5.3.2](#)) so that liquid in the beaker is below the water level in the water bath. Maintain the water bath at 98 °C to 100 °C, check with a thermometer and stir at 10 min intervals. After exactly 30 min, remove the beaker from the water bath and filter promptly through a piece of filter paper ([5.4.3.3](#)). If filtration takes more than 4 min, discard determination. Repeat the determination, adding 1 g celite ([5.5.2.2](#)) as filter-aid just before removing the beaker from the water bath, stir and filter.

Wash the insoluble residue completely onto the filter paper with boiling water and continue washing until the total volume used is 100 ml. Complete washing before the filtrate becomes cloudy or its temperature drops to below 60 °C. Determine total nitrogen in the wet filter paper and residue in accordance with ISO 5315.

Carry out a blank test at the same time as the determination, using the same procedure and reagents, but omitting the test portion.

5.5.5 Expression of results

5.5.5.1 HWIN content of the sample

The HWIN content, w_2 , expressed as a mass fraction (%), is given by [Formula \(2\)](#):

$$w_2 = \frac{(V_3 - V_4) \times c_2 \times 14,01}{m_2 \times 1\,000} \times 100 \quad (2)$$

where

V_3 is the volume, in millilitres, of sodium hydroxide standard solution used for the blank test;

V_4 is the volume, in millilitres, of sodium hydroxide standard solution used for the determination;

c_2 is the concentration, in mol per litres, of sodium hydroxide standard solution used;

m_2 is the mass, in grams, of the test portion.

The calculation results are accurate to two digits after the decimal point. The determination result is the arithmetic average of the duplicate determination results.

5.5.5.2 Calculation of AI

AI, expressed in %, is given by [Formula \(3\)](#):

$$AI = \frac{w_1 - w_2}{w_1} \times 100 \quad (3)$$

5.6 Determination of the mass fraction of nitrogen from IBDU and CDU

It shall be determined in accordance with ISO 25705:2016, method A or ISO 19746.

6 Sampling and preparation of test sample

6.1 Sampling method

6.1.1 Products in bags

Carry out the sampling operation by following the procedure described in ISO 8633.

6.1.2 Products in bulk

Carry out the sampling operation by following the procedure described in ISO 8633.

6.2 Reduction of samples

Mix all the increments (collected as in [6.1](#)) uniformly and promptly to form a single aggregate sample using a device or by hand. The aggregate sample is reduced to about 1 kg according to the procedure in ISO 7742. Next, divide into two parts for final laboratory samples. The two laboratory samples are put into two clean and dry glass or plastic containers or any other inert material of adequate resistance capable of maintaining the sample in its original condition. The containers shall be fitted with airtight closures. Carry out all the operations described above as rapidly as possible to avoid loss or gain of moisture. Each container shall be secured and sealed following the instruction given in ISO 7410. Each laboratory sample shall be labelled following the instructions given in ISO 7410. The label shall, at minimum, carry the following information:

- a) the name of manufacturer;
- b) the name of product;
- c) the manufacturer's reference and batch number or production date (if available);
- d) the lot size;
- e) the date of sampling;
- f) the place of sampling;
- g) the signature of the sampler;
- h) the signature and name of the person or his representative on whose premises the sample was taken.

One of the containers is used for further quality analysis, while the other is kept for additional analysis in 6 mos.

6.3 Test sample preparation

Select one of the laboratory samples from the two containers obtained in [6.2](#). Mix the content of the container according to the procedure in ISO 7742. The test sample used for determining the items

specified in [Tables 1](#) and [2](#) should be reduced to 100 g. Grind this test sample in the grinder without warming the sample, pass the portion of the sample that passed a 0,500 mm sieve through a 0,212 mm sieve; use only the portion of the sample that does not pass the 0,212 mm sieve. The test samples are put into clean and dry bottles to be used for further analysis.

7 Marking and labelling

The marking and labelling should follow the legislation. Further information can be provided if appropriate and when the legislation allows.

Any chemical classifications on the label should conform to the United Nations' "Globally Harmonized System of Classification and Labelling of Chemicals" (GHS) and applicable national or regional adoption thereof.

Anything concerning the labels should refer to the latest version of ISO standards and local/regional legislations.

7.1 The following information should appear on the face of the containers:

- a) the total nitrogen content;
- b) the ureic nitrogen content (where this is at least 1 % by weight);
- c) the nitrogen from IBDU/CDU;
- d) the nitrogen that is soluble in cold water (CWSN) for urea formaldehyde/methylene urea fertilizer;
- e) the nitrogen that is soluble only in hot water (HWSN only) and/or AI for urea formaldehyde/methylene urea fertilizer;
- f) the date of production;
- g) the net mass;
- h) the address and name of the manufacturer.

7.2 A product's use instructions should be printed on the back of containers. The information should include the name of product, nutrient content, method of usage, storage and usage precautions.

7.3 The single mass value of each container shall be declared (e.g. 50 kg).

7.4 All other information required by ISO 7409 should also appear on the face of the containers.

8 Packaging, transport and storage

The applicable national or regional safety guidelines for handling and storage should be followed.

8.1 During transportation, the packaged products should be handled with care to avoid moisture, sunlight and damage of fertilizer and fertilizer packages.

8.2 The products should be stored in a dry, cool place (ambient temperature) away from sunlight and moisture.

Bibliography

- [1] AOAC Official Method 945.01 Nitrogen (Water-Insoluble) in Fertilizers Method I
- [2] AOAC Official Method 955.05 Nitrogen Activity Index (AI) of Urea-Formaldehyde Fertilizers
- [3] AOAC Official Method 955.04 Nitrogen (Total) in Fertilizers - Kjeldahl Method
- [4] AOAC Official Method 983.01 Urea and Methylenureas (Water-Soluble) in Fertilizers Liquid Chromatographic Method
- [5] HG 4137-2010 Urea aldehyde slow release fertilizer
- [6] Regulation EC 2003/2003 of the European Parliament and of the Council of 04 April 2013 Method 2.6.3 Determination of urea condensates using HPLC-Isobutylenediurea and crotonylidenediurea (method A) and methylen-urea oligomers (method B)

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email subscriptions@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK