



BSI Standards Publication

**Fatty acid methyl esters (FAME) — Determination
of sulfur content — Inductively coupled plasma
optical emission spectrometry (ICP-OES) method**

National foreword

This British Standard is the UK implementation of [ISO 20424:2019](#).

The UK participation in its preparation was entrusted to Technical Committee PTI/13, Petroleum Testing and Terminology.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019
Published by BSI Standards Limited 2019

ISBN 978 0 580 89426 8

ICS 75.160.40

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 November 2019.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL
STANDARD

ISO
20424

First edition
2019-11-14

**Fatty acid methyl esters (FAME) —
Determination of sulfur content —
Inductively coupled plasma
optical emission spectrometry
(ICP-OES) method**

*Esters méthyliques d'acides gras — Détermination de la teneur en
soufre — Méthode par spectroscopie d'émission optique par plasma à
couplage inductif (ICP-OES)*



Reference number
ISO 20424:2019(E)

© ISO 2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	1
5 Reagents and materials	2
6 Apparatus	2
7 Sampling	3
8 Preparation of stock solution and calibration solution	3
8.1 Stock solution.....	3
8.2 Preparation of the calibration solutions.....	3
8.2.1 Blank solution for sulfur.....	3
8.2.2 Calibration sample set.....	3
9 Calibration	4
10 Procedure	4
10.1 Sample preparation.....	4
10.2 Instrument optimization.....	4
10.3 Sample measurement.....	4
11 Expression of the results	5
12 Quality control	5
13 Precision	5
13.1 Interlaboratory study.....	5
13.2 Repeatability, <i>r</i>	5
13.3 Reproducibility, <i>R</i>	6
14 Test report	6
Annex A (normative) Calculation of the concentration of low viscosity oil in the blank solution	7
Annex B (informative) Interlaboratory study — Used FAME samples to provide precision data	8
Bibliography	9

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 28, *Petroleum and related products, fuels and lubricants from natural or synthetic sources*, Subcommittee SC 7, *Liquid Biofuels*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document seeks to evaluate the quality of fatty acid methyl esters (FAME) in terms of sulfur.

Though FAME itself does not contain sulfur, sulfur might occur as contaminant either in feedstock, due to the use of fertilizers, or in production processes using sulfuric acid. The presence of sulfur in FAME can be caused by the production process of FAME and/or possible contaminations by diesel fuel. Above certain levels of sulfur concentration, it can be harmful to use FAME as fuel. The test method provided in this document offers a simple and effective way to check and control the sulfur level of FAME, which is used as pure fuel or as blend component.

Fatty acid methyl esters (FAME) — Determination of sulfur content — Inductively coupled plasma optical emission spectrometry (ICP-OES) method

WARNING — The use of this document can involve hazardous materials, operations and equipment. This document does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of users of this document to take appropriate measures to ensure the safety and health of personnel prior to the application of this document, and to determine the applicability of any other restrictions.

1 Scope

This document specifies a test method for inductively coupled plasma optical emission spectrometry (ICP-OES) for the detection of the sulfur content from 2 mg/kg to 21 mg/kg in fatty acid methyl esters (FAME).

NOTE 1 For the purposes of this document, the term “% (m/m)” is used to represent the mass fraction (μ) of the material.

NOTE 2 The method can also be used for the determination of concentrations outside the given limits. The precision statement, however, is only valid for the concentration range given in the scope.

NOTE 3 The method described in the document was tested with FAME derived from soybean oil and beef tallow. FAME derived from other feedstock, in particular aged oils, may behave different due to the different nature of sulfur compounds.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 3170](#), *Petroleum liquids — Manual sampling*

[ISO 3171](#), *Petroleum liquids — Automatic pipeline sampling*

[ISO 12185](#), *Crude petroleum and petroleum products — Determination of density — Oscillating U-tube method*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Principle

An exactly weighed test portion is diluted with kerosene to allow the proper introduction of the aerosol into the plasma. The resulting solution is directly injected into the plasma of the ICP-OES spectrometer.

7 Sampling

Samples shall be taken as described in [ISO 3170](#) or [ISO 3171](#).

8 Preparation of stock solution and calibration solution

8.1 Stock solution

Sulfur solution with a concentration of 50 mg/kg: add to an appropriate conical flask ([6.4](#)) approximately 3,0 g of the standard sulfur solution ([5.3](#)), fill up to 30 g with diluent ([5.1](#)).

Weigh the masses with an accuracy of 0,000 1 g and homogenize the solution. Calculate the exact concentration of this solution, which shall be used to prepare the calibration solutions.

It is also permitted to prepare the dilution on volumetric basis. In this case, use appropriate pipettes ([6.5](#)) to transfer the volumes. In this case the concentration is expressed as mass/volume.

Other concentrations and quantities can be used for the stock solution but the precision data in [Clause 10](#) were obtained from analysis with the given concentration above.

8.2 Preparation of the calibration solutions

The calibration solutions are prepared from an organic sulfur compound which is commercially available. The sulfur compound is diluted in a mixture of diluent ([6.1](#)) and base oil ([6.2](#)). The addition of the base oil has the objective to reduce the differences in viscosity between the samples and the calibration solutions.

8.2.1 Blank solution for sulfur

Prepare an adequate amount of a solution of 10 % (*m/m*) low viscosity oil ([5.2](#)) in the solvent ([5.1](#)).

WARNING — When using other oils (see Note to [5.2](#)) the concentration of low viscosity oil in the blank solution shall be calculated as described in [Annex A](#).

8.2.2 Calibration sample set

[Table 1](#) shows the recommended calibration set for sulfur (0,0 mg/kg, 1,0 mg/kg, 2,5 mg/kg, 5,0 mg/kg and 10 mg/kg).

Weigh the masses with an accuracy of 0,000 1 g into the flask and fill up to the given amount with blank solution ([8.2.1](#)). Stir the samples until the homogenization is complete.

Calculate the exact concentrations of the calibration solutions for given in [Table 1](#).

When the concentrations of the solutions are expressed in mass/volume percentages ([8.1](#)), the calibration solutions shall be expressed in the same way.

For each calibration, freshly prepared calibration samples shall be used.

Table 1 — Calibration solutions

Sulfur content mg/kg	Stock solution g	Total quantity g
0	0	10
1,0	0,2	10
2,5	0,5	10
5,0	1,0	10

Sulfur content mg/kg	Stock solution g	Total quantity g
10,0	2,0	10

NOTE Depending on the instrument larger calibration samples might be necessary in order to have suitable amounts for repeat measurement.

9 Calibration

Run the measurements of the calibration solutions, with at least three readings of each one.

Calculate the arithmetic average of the three measurements, for each solution. From these averages, associate the intensity values to the respective concentration values for the calibration solutions, expressed in milligrams per kilogram, using a linear regression to obtain the calibration curve.

In the case of using a mass/volume relationship, express the concentration values for the calibration solutions in mg/l.

NOTE In the ILS, each calibration sample was measured three times.

10 Procedure

10.1 Sample preparation

The FAME sample shall be clear and bright. In case of a turbid sample, heat to a temperature of 50 °C for 10 min. If after heating and homogenization the sample is still turbid, this sample shall be discarded.

NOTE This procedure is based on [ISO 661](#)^[1]. The drying procedure described in that document cannot be executed.

The sample shall be prepared adding 5,0 g of sample, with a resolution of 0,000 1 g, in adequate flasks. Complete to 25 g with the same solvent used in [8.1](#) and stir until completely homogenized. This procedure shall be executed at least in duplicate.

10.2 Instrument optimization

Since instruments from different manufacturers have distinct configurations and settings, it is difficult to define the optimal instrument parameters in advance. The manufacturer's instructions should be followed, adjusting parameters, such as the flows of auxiliary gas, nebulization, refrigeration, radiofrequency power, sample aspiration rate, among others.

The selection of the experimental parameters shall be executed in order to obtain a better signal-to-noise ratio.

The recommended wavelengths are 180,669 nm and 181,975 nm.

For organic solutions, the operating guidelines should be followed:

- temperature of spray chamber should be optimised, depending on sample matrix;
- radiofrequency power generally 30 % greater than the power used for aqueous solutions;
- aspiration rate generally lower than those used for aqueous solutions.

10.3 Sample measurement

Proceed to the measurements of the solution of the sample as per the procedure adopted in the calibration solutions.

It is recommended to verify the stability of the instrument by checking one of the calibration solutions at regular intervals during the measurement of the samples. If the results of this examination differ by more than the repeatability (13.2) from the results obtained during the calibration experiment, a new calibration curve shall be established.

The intensity of the analytical line corresponds to the value of the maximum intensity subtracted from the background intensity. The selected line shall present the best signal-to-noise ratio.

11 Expression of the results

When the concentrations of the calibration solutions are expressed as mass/mass, obtain the concentration C (in milligrams per kilogram) of sulfur in the sample using the analytical curve and multiplying by the dilution factor.

If the result has been obtained in mass/volume (milligrams per litre), use the calibration curve, multiply by the dilution factor and apply [Formula \(1\)](#):

$$C = \frac{c}{d} \quad (1)$$

where

- C is the sulfur concentration in the sample, expressed in milligrams per kilogram (mg/kg);
- c is the sulfur concentration in the reading sample, expressed in milligrams per litre (mg/l);
- d is the average density of FAME, the attributed value of which is 0,88 g/ml at 20 °C.

The value attributed to the density d is not valid for predominantly lauric acid FAME samples (for example coconut or palm kernel FAME). In this case, one shall measure the density at 20 °C in accordance with [ISO 12185](#).

The average concentration (C_m) of sulfur in the sample is the arithmetic mean of two independent measurements on the same sample. Report the result in milligram per kilogram, rounded to the next 0,1 mg/kg.

12 Quality control

Confirm the accuracy of the test using a reference sample, with a maximum tolerance of 10 % in relation to the reference value.

13 Precision

13.1 Interlaboratory study

The precision, as determined by statistical examination in accordance with the ISO 4259 series^[3] on interlaboratory test, results of a matrix of fuels as given in [Annex B](#). The values derived from these tests might not be applicable to concentration ranges and matrices other than those given.

In the interlaboratory study, only FAME produced from beef tallow and from soybean oil were used. Other FAME might cause accuracy problems due to the potentially different nature of sulfur compounds contained.

13.2 Repeatability, r

The difference between two independent results obtained in the normal and correct operation of the same method, for test material considered to be the same, within a short interval of time, under the

same test conditions, that is expected to be exceeded with a probability of 5 % due to random variation, can be calculated using [Formula \(2\)](#):

$$r = 0,1276(X + 3,5060) \quad (2)$$

where X is the average of the two test results being compared.

13.3 Reproducibility, R

The difference between two independent results obtained in the normal and correct operation of the same method, for test material considered to be the same, under different test conditions, that is expected to be exceeded with a probability of 5 % due to random variation, can be calculated using [Formula \(3\)](#):

$$R = 0,1627(X + 3,5060) \quad (3)$$

where X is the average of the two test results being compared.

14 Test report

The test report shall contain at least the following information:

- a) a reference to this document, i.e. [ISO 20424:2019](#);
- b) the type and complete identification of the product tested;
- c) the result of the test ([Clause 8](#));
- d) any deviation, by agreement or otherwise, from the procedure specified;
- e) the date of the test.

Annex A (normative)

Calculation of the concentration of low viscosity oil in the blank solution

In order to obtain concentration (mass/mass) of low viscosity oil in the blank solution, the desired dilution factor for the samples shall be defined. Once this factor has been set, [Formulae \(A.1\)](#) and [\(A.2\)](#) shall be used for the calculation of the concentration:

$$C_{\text{oil}} = \frac{\log v_{\text{b}} - \log v_{\text{s}}}{\log v_{\text{o}} - \log v_{\text{s}}} \times 100 \quad (\text{A.1})$$

where

- C_{oil} is the concentration in mass/mass percentage of low viscosity oil in the blank solution;
- v_{b} is the viscosity of the diluted sample;
- v_{s} is the viscosity of the solvent used;
- v_{o} is the viscosity of the low viscosity oil.

$$\log v_{\text{b}} = \frac{1}{f} \times \log v_{\text{B}} + \left(1 - \frac{1}{f}\right) \times \log v_{\text{s}} \quad (\text{A.2})$$

where

- v_{B} is the viscosity of FAME;
- f is the dilution factor.

It is considered that the viscosity of FAME is 4,5 mm²/s at 40 °C. All the viscosities considered are in mm²/s at 40 °C.

The viscosity may be obtained alternatively by [ISO 3104](#).

Example

Considering a low viscosity oil of 33,5 mm²/s at 40 °C, a commercial kerosene with about 1,5 mm²/s at 40 °C of viscosity and a sample dilution factor of 5:

$$\log v_{\text{b}} = \frac{1}{5} \times \log 4,5 + \left(1 - \frac{1}{5}\right) \times \log 1,5$$

$$\log v_{\text{b}} = 0,272$$

$$C_{\text{oil}} = \frac{0,272 - \log 1,5}{\log 33,5 - \log 1,5} \times 100$$

$$C_{\text{oil}} = \frac{0,0959}{1,3490} \times 100 \cong 7,1 \%$$

In this case, a blank solution with about 7 % (m/m) of low viscosity oil shall be prepared instead of 10 % (m/m).

Annex B (informative)

Interlaboratory study — Used FAME samples to provide precision data

[Table B.1](#) presents the FAME products used during the interlaboratory study

Table B.1 — Sample matrix

Sample	Feedstock composition	Estimated sulfur content mg/kg
1	Soybean	5
2	Soybean	10
3	Soybean	25
4	Soybean (82 %)/Beef tallow (18 %)	4
5	Soybean (82 %)/Beef tallow (18 %)	12
6	Soybean (82 %)/Beef tallow (18 %)	16
7	Soybean (60 %)/Beef tallow (40%)	4
8	Soybean (60 %)/Beef tallow (40 %)	8
9	Soybean	2,5

Bibliography

- [1] [ISO 661](#), *Animal and vegetable fats and oils — Preparation of test sample*
- [2] [ISO 3104](#), *Petroleum product — Transparent and opaque liquids — Determination of the kinematic viscosity and the calculation of the dynamic viscosity*
- [3] ISO 4259 (all parts), *Petroleum and related products — Precision of measurement methods and results*
- [4] [ISO 20846](#), *Petroleum products — Determination of sulfur content of automotive fuels — Ultraviolet fluorescence method*
- [5] ASTM D5453, *Determination of total sulfur in light hydrocarbons, spark ignition engine fuel, diesel engine fuel, and engine oil by ultraviolet fluorescence*
- [6] ABNT NBR 15867, *Biodiesel — Determinação do teor de enxofre por espectrometria de emissão atômica com plasma indutivamente acoplado (ICP-OES) — ABNT NBR 15867: 2010*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email cservices@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email: cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK