



## National foreword

This British Standard is the UK implementation of ISO 21077:2021. It supersedes [BS ISO 21077:2016](#), which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee ACE/68, Space systems and operations.

A list of organizations represented on this committee can be obtained on request to its committee manager.

### Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2021  
Published by BSI Standards Limited 2021

ISBN 978 0 580 99894 2

ICS 49.140

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 August 2021.

### Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

---

**INTERNATIONAL  
STANDARD**

**ISO  
21077**

Second edition  
2021-06

---

---

**Space data and information transfer  
systems — Digital motion imagery**

*Données spatiales et systèmes de transfert d'information - Imagerie  
du mouvement numérique*



Reference number  
ISO 21077:2021(E)



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by the Consultative Committee for Space Data Systems (CCSDS) (as CCSDS 766.1-B-2, August 2016) and drafted in accordance with its editorial rules. It was assigned to Technical Committee ISO/TC 20, *Space vehicles*, Subcommittee SC 13, *Space data and information transfer systems* and adopted under the "fast-track procedure".

This second edition cancels and replaces the first edition (ISO 21077:2016), which has been technically revised.

The main changes compared to the previous edition are as follows:

- adds support for MPEG4 recording and JPEG2000 transmission.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

**CONTENTS**

<u>Section</u>	<u>Page</u>
<b>1 INTRODUCTION</b> .....	<b>1-1</b>
1.1 PURPOSE AND SCOPE.....	1-1
1.2 APPLICABILITY.....	1-1
1.3 NOMENCLATURE .....	1-1
1.4 REFERENCES .....	1-2
<b>2 OVERVIEW</b> .....	<b>2-1</b>
<b>3 SPECIFICATION</b> .....	<b>3-1</b>
3.1 OVERVIEW .....	3-1
3.2 GENERAL.....	3-1
3.3 INTERFACE STANDARDS .....	3-1
3.4 VIDEO FORMAT AND CHARACTERISTICS .....	3-3
3.5 AUDIO.....	3-11
3.6 REAL-TIME VIDEO ENCAPSULATION AND TRANSMISSION .....	3-11
3.7 RECORDED VIDEO AND AUDIO .....	3-12
3.8 DISTRIBUTION OF VIDEO DATA.....	3-13
<b>ANNEX A PROTOCOL IMPLEMENTATION CONFORMANCE STATEMENT (PICS) PROFORMA (NORMATIVE)</b> .....	<b>A-1</b>
<b>ANNEX B SECURITY, SANA, AND PATENT CONSIDERATIONS (INFORMATIVE)</b> .....	<b>B-1</b>
<b>ANNEX C DTN BUNDLE PROTOCOL FOR VIDEO TRANSMISSION (INFORMATIVE)</b> .....	<b>C-1</b>
<b>ANNEX D INFORMATIVE REFERENCES (INFORMATIVE)</b> .....	<b>D-1</b>
<b>ANNEX E ABBREVIATIONS (INFORMATIVE)</b> .....	<b>E-1</b>

Figure

3-1 Video System Elements—Non-Compressed Video Design.....	3-10
3-2 Video System Elements—Compressed Video Design .....	3-10

# 1 INTRODUCTION

## 1.1 PURPOSE AND SCOPE

The purpose of this document is to provide a common reference and framework of standards for digital motion video and imagery, and to provide recommendations for utilization of international standards for sharing or distributing motion video and imagery between spacecraft elements and ground systems.

The scope of this document includes traditional real-time streaming video and television, including human and robotic spacecraft-to-spacecraft and spacecraft-to-ground systems, as well as video recorded and distributed later, either as a real-time stream or as a file transfer. In this context, real-time streaming includes all modes where video is sent from a spacecraft in a continuous stream and is intended for immediate use when received, regardless of the latency of the transmission path. Other specialized motion imagery applications, such as high-speed scientific motion imagery and multi-spectral motion imagery, are not addressed in this document. However, if a specialized imagery camera system has a requirement to interface to spacecraft systems in a video mode, it would be required to match these interfaces.

Ground-systems-to-ground-systems video distribution is obviously a key component of the entire video system. However, this is not the primary focus of this document. Currently, there are significant differences in the ways mission video products are exchanged between the various space agencies on the ground. This is the result of differences in network topologies between space agencies, and agreements for video sharing. Those differences preclude there being a standard methodology for delivering video imagery between agencies. Prior to the commencement of video transmission between space agencies, system design reviews and performance testing should be done between the ground systems in use to assure operability when video imagery comes from spacecraft.

## 1.2 APPLICABILITY

This document is a CCSDS Recommended Standard. It is intended for all missions that produce, consume, or transcode video imagery from low-bandwidth video such as web streaming through high-bandwidth video such as high-definition television imagery.

## 1.3 NOMENCLATURE

### 1.3.1 NORMATIVE TEXT

The following conventions apply for the normative specifications in this Recommended Standard:

- a) the words 'shall' and 'must' imply a binding and verifiable specification;
- b) the word 'should' implies an optional, but desirable, specification;
- c) the word 'may' implies an optional specification;

d) the words 'is', 'are', and 'will' imply statements of fact.

NOTE – These conventions do not imply constraints on diction in text that is clearly informative in nature.

### 1.3.2 INFORMATIVE TEXT

In the normative sections of this document, informative text is set off from the normative specifications either in notes or under one of the following subsection headings:

- Overview;
- Background;
- Rationale;
- Discussion.

### 1.4 REFERENCES

The following publications contain provisions which, through reference in this text, constitute provisions of this document. At the time of publication, the editions indicated were valid. All publications are subject to revision, and users of this document are encouraged to investigate the possibility of applying the most recent editions of the publications indicated below. The CCSDS Secretariat maintains a register of currently valid CCSDS publications.

- [1] *Studio Encoding Parameters of Digital Television for Standard 4:3 and Wide Screen 16:9 Aspect Ratios*. ITU-R BT.601-7. Geneva: ITU, 2011.
- [2] *Television—SDTV Digital Signal/Data—Serial Digital Interface*. SMPTE ST 259:2008. White Plains, New York: SMPTE, 2008.
- [3] *Digital Interfaces for HDTV Studio Signals*. ITU-R BT.1120-8. Geneva: ITU, 2012.
- [4] *1.5 Gb/s Signal/Data Serial Interface*. SMPTE ST 292-1:2012. White Plains, New York: SMPTE, 2012.
- [5] *High-Definition Multimedia Interface Specification*. Version 1.4. Sunnyvale, California: HDMI Licensing, LLC, 2009.
- [6] *Electrical Characteristics of Low Voltage Differential Signaling (LVDS) Interface Circuits*. Revision A. TIA/EIA-644-A. Arlington, Virginia: TIA, February 2001.
- [7] *Serial Digital Interface-Based Transport Interface for Compressed Television Signals in Networked Television Production Based on Recommendation ITU-R BT.1120*. ITU-R BT.1577. Geneva: ITU, 2002.

CCSDS RECOMMENDED STANDARD FOR DIGITAL MOTION IMAGERY

- [8] *Television—Serial Data Transport Interface (SDTI)*. SMPTE ST 305:2005. White Plains, New York: SMPTE, 2005.
- [9] *Teletext Systems*. ITU-R BT.653-3. Geneva: ITU, 1998.
- [10] *Television—Time and Control Code*. SMPTE ST 12-1:2008. White Plains, New York: SMPTE, 2008.
- [11] *Television—Transmission of Time Code in the Ancillary Data Space*. SMPTE ST 12-2:2008. White Plains, New York: SMPTE, 2008.
- [12] *Ancillary Data Packet and Space Formatting*. SMPTE ST 291:2011. White Plains, New York: SMPTE, 2011.
- [13] *Vertical Ancillary Data Mapping of Caption Data and Other Related Data*. SMPTE ST 334-1:2007. White Plains, New York: SMPTE, 2007.
- [14] *Metadata Element Dictionary Structure*. SMPTE ST 335:2012. White Plains, New York: SMPTE, 2012.
- [15] *Metadata Dictionary Registry of Metadata Element Descriptions*. SMPTE RP 210.10:2007. White Plains, New York: SMPTE, 2007.
- [16] *Ultra High Definition Television—Mapping into Single-link or Multi-link 10 Gb/s Serial Signal/Data Interface*. SMPTE ST 2036-3:2010. White Plains, New York: SMPTE, 2010.
- [17] *1280×720, 16:9 Progressively-Captured Image Format for Production and International Programme Exchange in the 60 Hz Environment*. ITU-R BT.1543. Geneva: ITU, 2001.
- [18] *1280 x 720 Progressive Image 4:2:2 and 4:4:4 Sample Structure—Analog and Digital Representation and Analog Interface*. SMPTE ST 296:2012. White Plains, New York: SMPTE, 2012.
- [19] *Parameter Values for the HDTV Standards for Production and International Programme Exchange*. ITU-R BT.709-5. Geneva: ITU, 2002.
- [20] *Television—1920 x 1080 Image Sample Structure, Digital Representation and Digital Timing Reference Sequences for Multiple Picture Rates*. SMPTE ST 274:2008. White Plains, New York: SMPTE, 2008.
- [21] *Dual Link 1.5 Gb/s Digital Interface for 1920 x 1080 and 2048 x 1080 Picture Frames*. SMPTE ST 372:2011. White Plains, New York: SMPTE, 2011.
- [22] *Television—3 Gb/s Signal/Data Serial Interface*. SMPTE ST 424:2006. White Plains, New York: SMPTE, 2006.

- [23] *Ultra High Definition Television—Image Parameter Values for Program Production*. SMPTE ST 2036-1:2009. White Plains, New York: SMPTE, 2009.
- [24] *Ultra High Definition Television—Audio Characteristics and Audio Channel Mapping for Program Production*. SMPTE ST 2036-2-2008. White Plains, New York: SMPTE, 2008.
- [25] *2048 × 1080 and 4096 × 2160 Digital Cinematography Production Image Formats FS/709*. SMPTE ST 2048-1:2011. White Plains, New York: SMPTE, 2011.
- [26] *2048 × 1080 Digital Cinematography Production Image FS/709 Formatting for Serial Digital Interface*. SMPTE ST 2048-2:2011. White Plains, New York: SMPTE, 2011.
- [27] *Parameter Values for Ultra-High Definition Television Systems for Production and International Programme Exchange*. ITU-R BT.2020-1. Geneva: ITU, 2014.
- [28] *Information Technology—Coding of Audio-Visual Objects—Part 10: Advanced Video Coding*. 8th ed. International Standard, ISO/IEC 14496-10:2014. Geneva: ISO, 2014.
- [29] *Advanced Video Coding for Generic Audiovisual Services*. ITU-T H.264. Geneva: ITU, 2012.
- [30] *Data Services in Digital Television Broadcasting*. ITU-R BT.1301-1. Geneva: ITU, 2011.
- [31] *Interface for Digital Component Video Signals in 525-Line and 625-Line Television Systems Operating at the 4:2:2 Level of Recommendation ITU-R BT.601*. ITU-R BT.656-5. Geneva: ITU, 2007.
- [32] *Information Technology—JPEG 2000 Image Coding System: Motion JPEG 2000*. 2nd ed. International Standard, ISO/IEC 15444-3:2007. Geneva: ISO, 2007.
- [33] *Information Technology—Generic Coding of Moving Pictures and Associated Audio Information—Part 7: Advanced Audio Coding (AAC)*. 4th ed. International Standard, ISO/IEC 13818-7:2006. Geneva: ISO, 2006.
- [34] *Digital Audio Interface—Part 3: Consumer Applications*. Edition 3.1 (2009-12-10). IEC 60958-3:2006+AMD1:2009 CSV. Geneva: IEC, 2009.
- [35] *IP over CCSDS Space Links*. Issue 1. Recommendation for Space Data System Standards (Blue Book), CCSDS 702.1-B-1. Washington, D.C.: CCSDS, September 2012.
- [36] J. Postel. *User Datagram Protocol*. STD 6. Reston, Virginia: ISOC, August 1980.
- [37] *CCSDS File Delivery Protocol (CFDP)*. Issue 4. Recommendation for Space Data System Standards (Blue Book), CCSDS 727.0-B-4. Washington, D.C.: CCSDS, January 2007.
- [38] *Transport of JPEG 2000 Broadcast Profile Video in MPEG-2 TS over IP*. VSF TR-01 2013-04-15. New Jersey: Video Services Forum, April 15, 2013.

## 2 OVERVIEW

In the early days of human spaceflight, motion imagery was accomplished with motion picture film cameras, set at varying frame rates depending on lighting conditions. Upon safe return the film was processed and eventually shared with the world via documentaries or television. Inevitably live video became operationally desirable for situational awareness and to satisfy the public's interest in high-profile events such as the Moon landings or the Apollo-Soyuz test project. Compromises were made with those first video systems to fit within the constraints of bandwidth, avionics, and transmission systems. Even in the modern era, video systems on spacecraft are a hybrid of analog and digital systems, typically made to work within the existing spacecraft's avionics, telemetry, and command/control systems.

With the advent of digital cameras, encoding algorithms, and modulation techniques, it is desirable to treat video as data and to utilize commercially available technologies to capture and transmit live and recorded motion imagery, possibly in High Definition (HD) or even better. Thus the Recommended Standard addresses:

- Video Interfaces and Characteristics
- Video Formats and Characteristics

Video data has a number of characteristics which need specification such as frame rate, aspect ratio, bandwidth and compression standards, color sampling, the inclusion of audio, etc.

- Encapsulation and Transmission Protocols

Video data needs to be encapsulated, transported, and distributed. Although the choice of mechanisms and protocols may not be specific to video data, certain aspects need addressing because of the high bandwidth typically required for video. Thus this part will address encapsulation schemes (e.g., IP), transport protocols, and use of CCSDS Encapsulation Packets.

- Interoperability of Standards

Future Human Spaceflight endeavors are expected to be collaborations between many agencies, with complex interactions between spacecraft and non-Earth surface systems, with intermediate locations (EVA crew, habitats, etc.) requiring the ability to view video generated by another agency's systems. Therefore interoperability between these systems will be essential to mission success and in some cases crew safety. Such interoperability will only be achieved by use of common references and joint agreement on international standards, either commercial or CCSDS or a combination of the two.

This Recommended Standard does not cover video quality. The intention of this document is to provide a framework of standards to ensure interoperability, not to define a level of quality. What is acceptable video quality varies widely with the application and requirements of users. A science experiment, for example, may have video quality requirements beyond what is available, or practical, within a spacecraft avionics system. The

science team for that experiment might elect to record video on board at high quality and transfer that video as a digital file after the conclusion of the experiment run. They might elect to do that and have a real-time downlink of lesser quality as a confirmation the experiment is working properly. A requirement for real-time video to support a docking event might sacrifice spatial resolution to lower the latency of the real-time video feed. Within the parameters listed in this document and the capabilities of any given spacecraft, users and controllers can determine how equipment should be configured for the best match to requirements.

## 3 SPECIFICATION

### 3.1 OVERVIEW

There are many system configurations that can be implemented in spacecraft video systems. Choices of interface standards, resolutions, and frame rates are based on the application, user requirements, available equipment, and spacecraft capability. There are multiple ways for signals to flow from the image source through to the spacecraft avionics system and on to the ground (see figures 3-1 and 3-2). Application of this Recommended Standard limits the overall number of options by limiting the interfaces to those that are in most common use. It should be noted that, while scientific imaging systems are excluded from this Recommended Standard, should a scientific imaging system need to interface to the spacecraft video system, the same interfaces would apply to them. It would be the responsibility of the user to provide a matching interface from the user's imaging system.

### 3.2 GENERAL

Users shall select from the following interfaces and standards when designing and implementing new video systems for spacecraft.

### 3.3 INTERFACE STANDARDS

#### 3.3.1 NON-COMPRESSED STANDARD DEFINITION TELEVISION SIGNALS

The interface for non-compressed Standard Definition (SD) television signals shall be Serial Digital Interface (SDI), conforming to

- ITU-R BT.601-7 (reference [1]);
- SMPTE ST 259:2008 (reference [2]).

#### 3.3.2 NON-COMPRESSED HIGH DEFINITION TELEVISION SIGNALS

The interface used for non-compressed high definition television signals shall be one of the following:

- High Definition-Serial Digital Interface (HD-SDI), conforming to
  - ITU-R BT.1120-8 (reference [3]);
  - SMPTE ST 292-1:2012 (reference [4]);
- High Definition Multimedia Interface (HDMI) 1.4 or higher, as defined by the HDMI Founders and licensed by HDMI Licensing, LLC (reference [5]);
- Camera Link Low Voltage Differential Signaling (LVDS) Interface Standard, as defined by the Camera Link Participating Companies (reference [6]).

### **3.3.3 COMPRESSED DIGITAL TELEVISION SIGNALS**

The interface used for compressed digital television signals shall be Digital Video Broadcasting-Asynchronous Interface (DVB-ASI), conforming to

- ITU-R BT.1577 (reference [7]);
- SMPTE ST 305:2005 (reference [8]).

NOTE – DVB-ASI would be used with compressed digital video while still in the serial digital domain. For interfacing to spacecraft systems, Internet Protocol (IP) (see 3.6) is the preferred interface.

### **3.3.4 TELEVISION TIME CODE AND METADATA**

**3.3.4.1** Television time code and metadata may be inserted in non-compressed video. If time codes and/or metadata are inserted into non-compressed video, one of the following standards shall be used:

- ITU-R BT.653-3 (reference [9]);
- SMPTE ST 12-1:2008 (reference [10]);
- SMPTE ST 12-2:2008 (reference [11]);
- SMPTE ST 291:2011 (reference [12]);
- SMPTE ST 292-1-2012 (reference [4]);
- SMPTE ST 334-1:2007 (reference [13]);
- SMPTE ST 335:2012 (reference [14]);
- SMPTE RP 210.10:2007 (reference [15]);
- SMPTE ST 2036-3:2012 (reference [16]).

NOTE – The standards listed above are primarily concerned with the serial digital standard-definition and high-definition interfaces listed in 3.3.1 and 3.3.2. Metadata inserted at a camera conforming to HDMI or Camera Link interfaces conform to the serial digital interfaces when those signals are converted.

**3.3.4.2** Compressed video signals in 3.3.3, per the standards listed in 3.3.3, shall carry all television time code and metadata information inserted into a non-compressed video stream.

## 3.4 VIDEO FORMAT AND CHARACTERISTICS

### 3.4.1 VIDEO RESOLUTIONS

#### 3.4.1.1 Overview

Traditionally, video resolution has been categorized as low resolution, standard definition, high definition, or high resolution. Low resolution is generally defined as less than  $640 \times 480$ , standard definition as  $640 \times 480$  and  $768 \times 576$ , high definition as  $1280 \times 720$  and  $1920 \times 1080$ , and high resolution as anything beyond  $1920 \times 1080$  such as 4K and 8K resolutions. Low resolution was used for streamed Internet video. Standard definition was used for broadcast (pre-HD) and security camera systems. High definition was limited to high-end television broadcast. High resolution was practically non-existent unless it was film based. Now, however, the distinctions are less clear. Laptop computer cameras are now often high definition, with options to stream from  $320 \times 240$  up to  $1280 \times 720$ . Standard definition is now in limited use for broadcast television, web streaming, and monitoring applications. High definition has become the norm for broadcast and cable television. High resolution or ultra-high-definition cameras are replacing 35mm motion picture film for imaging requirements beyond HD. Therefore it is more difficult to classify video in terms of resolutions than in terms of application. A given application can have a broad range of resolutions, depending upon the requirements of the user, available equipment, and bandwidth constraints. The specifications below reflect the diversity of choices available for video systems. Higher resolution applications (e.g., 'public affairs', critical operations) can be used to fulfill lower resolution applications (e.g., 'personal video conferencing').

#### 3.4.1.2 Personal Video Conferencing

Personal video conferencing video resolution should be selected from the following range:

- $320 \times 240$  to  $1280 \times 720$ , progressive scan.

NOTE – Selection of resolution is dependent on immediate requirement and available bandwidth.

#### 3.4.1.3 Medical Conferencing

Medical conferencing video resolution should be selected from the following range:

- $320 \times 240$  to  $1280 \times 720$ , bandwidth-dependent progressive or interlace scan:
  - standard definition legacy systems may be 525 or 576 interlace;
  - $640 \times 480$  and  $768 \times 576$  systems shall conform to ITU-R BT.601-7 (reference [1]) or SMPTE ST 259:2008 (reference [2]).

NOTE – Lower resolution personal video conferencing and medical conferencing applications are most likely to be performed using a personal computer or tablet-type device. All video encoding would be handled internally. Connection to the spacecraft avionics system would be through wired or wireless data connections independent of any video systems. Transmission to the ground would also be handled as part of standard data protocols and also independent of dedicated video transmission.

#### **3.4.1.4 Situational Awareness**

Situational awareness video resolution should be selected from the following range:

- 640 × 480 to 1280 × 720, bandwidth dependent:
  - interlace scan for legacy SD systems shall conform to
    - ITU-R BT.601-7 (reference [1]); or
    - SMPTE ST 259:2008 (reference [2]);
  - progressive scan for HD systems shall conform to
    - ITU-R BT.1543 (reference [17]); or
    - SMPTE ST 296:2011 (reference [18]).

NOTE – Situational awareness may be required in situations where only low-bandwidth transmission is available, such as S-Band, which would likely limit resolution to as low as 320 × 240. In cases such as this, best effort is acceptable. The requirement to have visual confirmation of events may be higher than a specific resolution. This should be considered the exception and not the norm.

#### **3.4.1.5 Public Affairs**

**3.4.1.5.1** Public affairs video resolution should be selected from the following range:

- 640 × 480 to 1280 × 720, bandwidth dependent:
  - Interlace scan for legacy SD systems shall conform to
    - ITU-R BT601-7 (reference [1]); or
    - SMPTE ST 259:2008 (reference [2]);
  - Progressive scan for HD systems shall conform to
    - ITU-R BT.1543 1280 (reference [17]); or
    - SMPTE ST 296:2011 (reference [18]).

## CCSDS RECOMMENDED STANDARD FOR DIGITAL MOTION IMAGERY

**3.4.1.5.2** Multiple resolutions may be used to accommodate mission requirements.

NOTE – There are situations where HD formats are not required. It saves considerable bandwidth to use SD systems. Whether these are US or European standard resolutions and frame rates is not an issue. Regardless of the actual video format, the interface standards allow virtually all current equipment to route and encode the video. Once encoded and packetized, it is not an issue for spacecraft avionics as the video is compatible data packets. That part of the system is format agnostic. Regardless of the interface chosen for a particular spacecraft, routing and encoding utilize the same components.

### **3.4.1.6 High Resolution Digital Imaging**

**3.4.1.6.1** High resolution digital imaging video resolution should have a minimum resolution of  $1920 \times 1080$ , progressive scan:

- 1080 HD systems shall conform to
  - ITU-R BT.709-5 (reference [19]); or
  - SMPTE ST 274:2008 (reference [20]);
- Up to 30 FPS systems shall conform to
  - ITU-R BT.1120-8 (reference [3]); or
  - SMPTE ST 292-1:2012 (reference [4]);
- Above 30 FPS shall conform to
  - ITU-R BT.1120-8 (reference [3]); or
  - SMPTE ST 372:2011 (reference [21]); or
  - SMPTE ST 424:2006 (reference [22]).

**3.4.1.6.2** Systems above  $1920 \times 1080$  shall conform to

- SMPTE ST 2036 Standards Suite, ST 2036 1–3:
  - ST 2036-1:2009 Image Parameter Values for Program Production—Ultra High Definition Television (reference [23]);
  - ST 2036-2:2008 Ultra High Definition Television—Audio Characteristics and Audio Channel Mapping for Program Production (reference [24]);
  - ST 2036-3:2010 Mapping into Single-link or Multi-link 10 Gb/s—Ultra High Definition Television Serial Signal/Data Interface (reference [16]);

- SMPTE ST 2048 Standards Suite ST 2048-1–2:
  - ST 2048-1:2011 2048 × 1080 and 4096 × 2160 Digital Cinematography Production Image Formats FS/709 (reference [25]);
  - ST 2048-2:2011 2048 × 1080 Cinematography Production Image FS/709 Formatting for Serial Digital Interface (reference [26]);
- ITU-R BT.2020-1 (06/2014) Parameter Values for Ultra-High Definition Television Systems for Production and International Programme Exchange (reference [27]).

NOTE – 1920 × 1080 and above is to accommodate users with special requirements. Typically, these systems will have on-board recording and downlink video as file transfers. Any real-time requirement will include that the video system provide a compatible signal to spacecraft video systems.

### **3.4.1.7 Spacecraft to Spacecraft**

Spacecraft-to-spacecraft video resolution should follow 3.4.1.2–3.4.1.6.

NOTE – Selection of spacecraft-to-spacecraft video resolution is dependent on mission requirements.

## **3.4.2 FRAME RATE**

**3.4.2.1** Video frame rates shall be selected from the following ranges for the following applications:

- a) personal video conferencing: 10 – 60 Frames Per Second (FPS);
- b) medical video: 10 – 60 FPS;
- c) situational awareness: 25 – 60 FPS;
- d) public affairs: 24, 25, or 60 FPS;
- e) high resolution digital imaging: 24 – 120 FPS.

NOTE – These are considered optimum frame rates for these applications. However, bandwidth constraints may not allow even the lower frame rates to be utilized. In these cases, best effort should be made to accommodate the recommendations based on available bandwidth for imaging applications.

**3.4.2.2** Spacecraft-to-spacecraft frame rates should be selected from 3.4.2.1 a)–e), above, depending on application.

## NOTES

- 1 Spacecraft-to-spacecraft frame rates are dependent on mission requirements.
- 2 The listing of specific video applications above does not necessarily imply discrete equipment sets dedicated for each application. Most cameras, for example, can be used at multiple resolutions and frame rates allowing them to be used for multiple applications.

### 3.4.3 ASPECT RATIO

Aspect ratio of original material shall be maintained from origination through delivery to end user.

NOTE – By definition within industry standards, HDTV resolution video has an aspect ratio of 16:9.

### 3.4.4 VIDEO COMPRESSION

#### 3.4.4.1 Overview

The two compression standards listed below have different applications. MPEG-4 Part 10 is primarily intended for real-time applications where live, or nearly live, video needs to be monitored at a ground location during an event or experiment. MPEG-4 may also be used for recording applications where the quality level is determined to be sufficient. JPEG2000 is intended for requirements for higher quality or where each individual frame needs to be maintained intact. The data rate required for JPEG2000 would normally preclude JPEG2000 from being used for live transmission. The normal operating mode for JPEG2000 is to record the video and downlink it later as a data file. However, if the bandwidth is available, live transmission of JPEG2000 offers very low latency and may be preferable for operations where low video latency is preferable.

#### 3.4.4.2 Compression Standards

The following video compression standards shall be used as indicated:

- MPEG-4 Part 10 (references [28] and [29]) for real-time transmission and recording:
  - 0.5 to 25 Mb/s—application and user requirement-driven data rates;
  - 8-bit sampling;
  - constant bit rate or variable bit rate acceptable—defined by interface to spacecraft system;
  - Group of Pictures (GOP) from 1 – 30—defined by user requirement;

- Constrained Baseline Profile for conferencing type applications (Personal and Medical Video Conferencing);
- Main Profile for SD applications;
- High Profile for HD applications;
- metadata as required by user:
  - shall conform to
    - ITU-R BT.1301-1 (reference [30]); or
    - SMPTE ST 291:2011 (reference [12]); or
    - ITU-R BT.656-4 (reference [31]) for ancillary data; or
    - SMPTE ST 335:2001 (reference [14]); or
    - SMPTE RP 210.10:2007 (reference [15]);
  - shall be read and passed by encode/decode systems;
  - may include system status and control feedback data;
  - may include embedded television time code conforming to
    - ITU-R BT.1301-1 (reference [30]); or
    - SMPTE ST 12-1:2008 (reference [10]); or
    - SMPTE ST 12-2:2008 (reference [11]).

NOTE – Per specification and established practice, embedded television time code is used as the time reference for the MPEG transport stream time code value.

- JPEG2000 (reference [32]) for analysis and high-quality recording requirements for video stored and transferred as files and real-time transmission:
  - 45 to 140+ Mb/s—application and user requirement-driven;
  - 10-bit (or greater) Sampling;
  - metadata as required by user:
    - shall conform to
      - SMPTE ST 291:2011 (reference [12]); or
      - ITU-R BT.653-3 (reference [9]) for ancillary data; or
      - SMPTE ST 335:2001 (reference [14]); or
      - SMPTE RP 210.10:2007 (reference [15]);

CCSDS RECOMMENDED STANDARD FOR DIGITAL MOTION IMAGERY

- shall be read and passed by encode/decode systems;
- may include system status and control feedback data;
- may include embedded television time code.


### **3.4.5 COLOR SAMPLING**

Color sampling should be as follows:


- 4:2:0 for real-time requirements;
- 4:2:2 for high resolution digital imaging:
  - science and engineering;
  - production and digital cinema applications;
- 4:4:4 for special applications.

### **3.4.6 DISCUSSION—VIDEO SYSTEM BLOCK DIAGRAMS**

The diagrams below illustrate typical video system connectivity and what interfaces are associated with each stage in the system for a typical human spaceflight video system. These diagrams assume separate components for each of these functions. While the same functions occur with the use of a laptop- or tablet-based video system used for medical or personal video conferencing, they are internal with an IP connection to the spacecraft avionics system for transmission.



**Figure 3-1: Video System Elements—Non-Compressed Video Design**



**Figure 3-2: Video System Elements—Compressed Video Design**

## 3.5 AUDIO

### 3.5.1 AUDIO AS PART OF VIDEO STREAM

Audio as part of a video stream should conform to the following standards:

- Advanced Audio Codec (AAC) (reference [33]) for compressed audio;
- AES/EBU-3 (reference [34]) for uncompressed audio.

NOTE – Generally, audio as part of a compressed bitstream for live applications (MPEG-4) will be compressed. There are several different audio codecs available. AAC was chosen as the highest quality, most widely used audio codec for this application. Non-compressed AES/EBU-3 is another possibility supported by a number of audio/video codecs. It is less common, but might be a requirement based on user needs.

### 3.5.2 DISCUSSION—AUDIO SEPARATE FROM VIDEO STREAM

For those applications where audio is distributed separately from video, audio/video synchronization (lip sync) is handled on the ground. Time stamps in the audio stream, corresponding to time stamps in the video stream, are recommended to aid in synchronization.<sup>1</sup>

## 3.6 REAL-TIME VIDEO ENCAPSULATION AND TRANSMISSION<sup>2</sup>

### 3.6.1 INTERNET PROTOCOL TRANSPORT STREAM

**3.6.1.1** MPEG-4-encoded video shall be formatted as Transport Stream (TS) with Packet Identification (PID) for transport in IP datagrams.

**3.6.1.2** JPEG2000 for transmission shall adhere to Video Services Forum (VSF) TR-01 Transport of JPEG2000 Broadcast Profile video in MPEG-2 TS over IP (reference [38]).

NOTE – TR-01 maps JPEG2000 encoding to an MPEG2 Transport Stream. This makes JPEG2000 compatible with the same IP connections used for MPEG-4 compression.

**3.6.1.3** IP datagrams shall be encapsulated for transmission over the CCSDS space link as specified in reference [35].

<sup>1</sup> It is anticipated the Voice Working Group standard will address this issue with standard practices to be employed for audio/video synchronization.

<sup>2</sup> Delay Tolerant Networking is being standardized as an internetworking layer for CCSDS missions. Future missions may want to consider transmitting real-time video encoded with MPEG-4 or file-based video encoded with JPEG2000 via DTN Bundle Protocol (reference [D9]) bundles. Annex C presents a narrative of the classes of real-time video transmission still under development by the DTN working group.

### **3.6.2 ELEMENTARY STREAM**

**3.6.2.1** Real-time video and audio elementary streams may be transmitted via User Datagram Protocol (UDP) (reference [36]).

**3.6.2.2** IP datagrams containing User Datagrams with real-time video and audio elementary streams shall be encapsulated for transmission over the CCSDS space link as specified in reference [35].

### **3.6.3 JITTER AND BIT ERROR RATES**

Real-time video delivery jitter and Bit Error Rate (BER) shall be limited as follows:

- jitter (packet delay variation) not to exceed 10 ms (assumes 300 ms decoder buffer);
- BER not to exceed  $1 \times 10^{-6}$ .

### **NOTES**

- 1 Use of elementary streams is possible for lower bandwidth video applications, such as personal video conferencing. However, commercial hardware decoders do not recognize elementary streams, so transport stream should be used exclusively for video systems interfacing directly to spacecraft avionics. Also, audio cannot be embedded with video when using elementary stream for compressed video transport. Audio and video in an elementary stream are not synchronized for transmission.
- 2 Real Time Protocol (RTP) and Hypertext Transfer Protocol (HTTP) are commonly used for video transmission. HTTP is common for computer-based applications, such as family video conferencing. In this application it is not only acceptable, but may be the only methodology available on that type of platform. However, for higher bandwidth video transmission where transport streams are utilized, HTTP is not efficient. RTP is acceptable, but UDP offers better performance over space based networks. The use of TCP for video over space based networks is also not recommended.

## **3.7 RECORDED VIDEO AND AUDIO**

### **3.7.1 ACQUISITION AND STORAGE OF VIDEO DATA**

**3.7.1.1** Recordings shall be file based.

NOTE – This is required to allow for transfer of recorded video data via established file transfer methodologies. This standard does not dictate how an application might create a video file, and specific file formats will vary based on systems being used.

**3.7.1.2** Encoding shall be MPEG-4 or JPEG 2000, dependent upon the application.

**3.7.1.3** Specific file formats will change based on systems being used. Data rates to be used for recording shall be determined by user requirements.

## 3.7.2 FILE TRANSFER OF RECORDED VIDEO

### 3.7.2.1 Recorded File Transmission

Recorded video shall be transmitted as files via the CCSDS File Delivery Protocol (CFDP) Class 1 or Class 2 (reference [37]).

### 3.7.2.2 Discussion—CFDP

CFDP supports four classes that are distinct from the three video classes:

- Class 1—Unreliable CFDP Transfer;
- Class 2—Reliable CFDP Transfer;
- Class 3—Unreliable Transfer Via One Or More Waypoints In Series;
- Class 4—Reliable Transfer Via One Or More Waypoints In Series.

When using CFDP to transfer video, one of the following mechanisms is used:

- Class 1—Unreliable CFDP transfer over a reliable UT layer;
- Class 2—Reliable CFDP.

## 3.8 DISTRIBUTION OF VIDEO DATA

### 3.8.1 REAL-TIME DISTRIBUTION

Real-time video shall be distributed as MPEG-4 program streams with resolution and frame rate dependent on available bandwidth and user requirements.

### 3.8.2 DELAYED DISTRIBUTION

Video files should be distributed on the ground via established file distribution methodologies.

NOTE – For file transfer of video, this will likely be recorded JPEG 2000, as MPEG-4 will be used for real-time distribution.

### 3.8.3 END USER CAPABILITIES

End user capabilities should include:

- decoding capability for real-time video distribution:

format conversion as required to meet local user requirements for display (i.e., conversion from 525i to 625i and vice versa, 50/60 Hz frame rate conversion, up-conversion or down-conversion);

- ability to record data stream from real-time applications;
- ability to participate in and store video files from transfer operations;
- ability to decode and play the stored files.

## ANNEX A

### PROTOCOL IMPLEMENTATION CONFORMANCE STATEMENT (PICS) PROFORMA

#### (NORMATIVE)

## A1 INSTRUCTIONS FOR COMPLETING THE PICS PROFORMA

### A1.1 OVERVIEW

#### A1.1.1 Columns

##### A1.1.1.1 General

In order to reduce the size of tables in the PICS proforma, notations have been introduced that have allowed the use of a multi-column layout, where the columns are headed 'Status' and 'Support'. The definition of each of these follows.

##### A1.1.1.2 Status Column

The 'Status' column indicates the level of support required for conformance to the standard. The values are as follows:

- |                   |   |
|-------------------|---|
| <b>M</b>          | Mandatory support is required.  |
| <b>O</b>          | Optional support is permitted for conformance to the standard. If implemented, it must conform to the specifications and restrictions contained in the standard. These restrictions may affect the optionality of other items.                    |
| <b>O.<i>n</i></b> | The item is optional, but support of at least one of the options labeled with the same number <i>n</i> is mandatory. The definitions for the qualification statements used in this annex are written under the tables in which they first appear. |
| <b>C.<i>n</i></b> | The item is conditional (where <i>n</i> is the number which identifies the applicable condition). The definitions for the conditional statements used in this annex are written under the tables in which they first appear.                      |
| <b>n/a</b>        | The item is not applicable.   |

## ANNEX A

### PROTOCOL IMPLEMENTATION CONFORMANCE STATEMENT (PICS) PROFORMA

#### (NORMATIVE)

## A1 INSTRUCTIONS FOR COMPLETING THE PICS PROFORMA

### A1.1 OVERVIEW

#### A1.1.1 Columns

##### A1.1.1.1 General

In order to reduce the size of tables in the PICS proforma, notations have been introduced that have allowed the use of a multi-column layout, where the columns are headed 'Status' and 'Support'. The definition of each of these follows.

##### A1.1.1.2 Status Column

The 'Status' column indicates the level of support required for conformance to the standard. The values are as follows:

- M** Mandatory support is required.
- O** Optional support is permitted for conformance to the standard. If implemented, it must conform to the specifications and restrictions contained in the standard. These restrictions may affect the optionality of other items.
- O.n** The item is optional, but support of at least one of the options labeled with the same number *n* is mandatory. The definitions for the qualification statements used in this annex are written under the tables in which they first appear.
- C.n** The item is conditional (where *n* is the number which identifies the applicable condition). The definitions for the conditional statements used in this annex are written under the tables in which they first appear.
- n/a** The item is not applicable.

CCSDS RECOMMENDED STANDARD FOR DIGITAL MOTION IMAGERY

**A3 REFERENCED BASE STANDARDS**

Motion Imagery and Applications (MIA, this document) is the only base standard referenced in the PRL. In the tables below, numbers in the Reference column refer to applicable subsections within this document.

**A4 GENERAL INFORMATION**

**A4.1 IDENTIFICATION OF THE PICS**

Date of statement (yyyy-mm-dd)	
PICS version	
System Conformance Statement cross-reference	
Other information	

**A4.2 IDENTIFICATION OF THE SYSTEM SUPPLIER / TEST LABORATORY CLIENT**

Organization name	
Contact name	
Address	
Telephone	
E-mail	
Other information	

**A4.3 IDENTIFICATION OF THE IMPLEMENTATION UNDER TEST**

Implementation name	
Implementation version	
Encoder name	
Decoder name	
Camera	
Software viewer	
Special configuration	
Other information	

**A4.4 EQUIPMENT CONFIGURATION FOR VIDEO FORMAT IN DETAILS  
(ENCODER/DECODER)**

Source Device IP address	
Source Device Netmask	
Source Device Gateway	
Destination IP Addresses	
Network Protocol	
Source /destination UDP ports	
Bandwidth	

**A4.5 GLOBAL STATEMENT OF CONFORMANCE**

Are all mandatory features implemented? (Yes or No)	
---	--

NOTE – If a positive response is not given to this box, then the implementation does not conform to the standard.

**A5 SIGNAL INTERFACES**

Item	Protocol Feature	Reference	Status	Support
1	Non-Compressed Standard Definition Television Signals	3.3.1	O.1	
2	Non-Compressed High Definition Television Signals	3.3.2	O.1	
3	Compressed Digital Television Signals	3.3.3	O	

**A6 SUPPORTED VIDEO RESOLUTIONS**

Item	Protocol Feature	Reference	Status	Support
1	Personal Video Conferencing	3.4.1.2	O.2	
2	Medical Conferencing	3.4.1.3	O.2	
3	Situational Awareness	3.4.1.4	O.2	
4	Public Affairs	3.4.1.5	O.2	
5	High Resolution Digital Imaging	3.4.1.6	O.2	

CCSDS RECOMMENDED STANDARD FOR DIGITAL MOTION IMAGERY

**A7 INTEROPERABILITY**

Item	Protocol Feature	Reference	Status	Support
1	Acquisition and storage of video data	3.7.1	M	
2	Real time distribution	3.8.1	C	
3	Delayed distribution	3.8.2	O	
4	End User Capabilities	3.8.3	M	

**A8 COMPRESSION**

MPEG-4	High Definition 720p			
Item	Protocol Feature	Reference	Status	Support
1	Mpeg 2 /TS stream (7 TS packet /UDP Frame) Transmission Only	3.6.1	O.3	
2	Elementary Stream	3.6.2	O.3	
3	Codec Mpeg-4, part 10	3.4.4	M	
4	Color code 4:2:0/4:2:2	3.4.5	O.4	
5	Video Format (720p)	3.4.1.2-3.4.1.5	O.4	
6	HD H.264 High profile. Level 4.0	3.4.4.2	O	
7	GOP < 31	3.4.4.2	O	
8	Constant Bit Rate (CBR)	3.4.4.2	O	
9	Embedded audio	3.5.1	O	
JPEG2000	High Definition 720p			
Item	Protocol Feature	Reference	Status	Support
1a	Mpeg 2 /TS stream (7 TS packet /UDP Frame) Transmission Only	3.6.1	O.3	
2a	Color code 4:2:0/4:2:2	3.4.5	O.5	
3a	Codec JPEG2000	3.4.4	M	
4a	Video Format (720p)	3.4.1.2-3.4.1.5	O.5	
5a	CBR	3.4.4.2	O	
6a	Embedded Audio	3.5.1	O	

**A9 SUPPORTED OPERATIONS**

Item	Protocol Feature	Reference	Status	Support
1	Personal Video Conferencing	3.4.1.2	O.6	
2	Medical Conferencing	3.4.1.3	O.6	
3	Situational Awareness	3.4.1.4	O.6	
4	Public Affairs	3.4.1.5	O.6	
5	High Resolution Digital Imaging	3.4.1.6	O.6	

## ANNEX B

### SECURITY, SANA, AND PATENT CONSIDERATIONS

#### (INFORMATIVE)

#### B1 SECURITY CONSIDERATIONS

##### B1.1 INTRODUCTION

Aside from the generic security needs of computing systems, security concerns are applicable to motion imagery where there are specific requirements to ensure that transmitted imagery not be disclosed, altered, spoofed, or redistributed without authorization.

Robotic space systems that transmit imagery frequently need the capability to control access to the imagery, whether for proprietary reasons or for national security. Human space applications frequently have the additional requirements to provide private video teleconferencing capabilities for communications with families, physicians, ground operations personnel, and/or news media outlets. Ground systems that receive and/or redistribute motion imagery have additional threats and countermeasures as well.

The focus of this discussion is on the specific protocols and methods recommended earlier in this document. It may be necessary to implement security services at other layers within the protocol stack, to account for distributed processing and cross support, to account for different classes of data or end users, or to account for protection of data during unprotected portions of the complete end-to-end transmission (e.g., across ground networks). The specification of security services at other layers is outside the scope of this document.

##### B1.2 SECURITY CONCERNS WITH RESPECT TO THE CCSDS DOCUMENT

The most common method of applying security to digital video and audio streams is through the use of multimedia *container* formats. Containers provide a file-based mechanism for exchanging, processing, and storing interleaved fragments of video, audio, metadata, and/or other data such as subtitles and still images. Most container files may be read or written by ordinary computer systems in the same manner as other files.

The 'MP4' standard, ISO/IEC 14496-14 (reference [D6]), is a multimedia container format standard specified as a part of MPEG-4. The 'Secure JPEG 2000' standard, ISO/IEC 15444-8 (reference [D7]), is a multimedia container format standard specified as a part of JPEG 2000.

### **B1.3 DATA PRIVACY**

The first major area of security concern is *privacy*, the requirement that the imagery not be disclosed to any other than the intended recipient(s). Limited privacy can be achieved through the use of data *scrambling*, which weakly obfuscates the data stream using a reversible non-cryptographic mechanism, or through employment of protected data transport at lower layers and restricting distribution.

Better privacy can be achieved using cryptographic techniques, which may be applied to all or part of a container format. Since any transcoding or decoding system must be able to read and pass metadata in order to process the stream, imagery metadata must be visible at these points. It is therefore highly desirable to have the capability to perform selective encryption of container file fields (e.g., imagery but not metadata, or imagery and imagery metadata but not cryptographic metadata). ‘Secure JPEG 2000’ includes mechanisms for selective encryption of JPEG 2000 image content and metadata. Various proprietary methods also exist for encrypting MP4 streams.

### **B1.4 DATA INTEGRITY**

The second major area of security concern is *data integrity*, the requirement that the imagery not be altered, whether to introduce false imagery or to interfere with decoding. Integrity verification mechanisms can be used for data validation to prevent security problems due to non-compliant malignant data. Like privacy, data integrity is commonly provided at other layers of the protocol stack or through a container format. ‘Secure JPEG 2000’ includes mechanisms for cryptographic verification of JPEG 2000-compliant data.

### **B1.5 AUTHENTICATION OF COMMUNICATING ENTITIES**

*Source authentication* is the requirement that the imagery be attributable to a known origin. Closely related to data integrity, it can also be used for data validation. Source authentication, if provided, is commonly provided at other layers of the protocol stack or through a container format. ‘Secure JPEG 2000’ includes digital signature mechanisms for authentication of JPEG 2000-compliant data.

### **B1.6 CONTROL OF ACCESS TO RESOURCES**

The third major area of security concern is *access control*, the requirement that the imagery be restricted from unauthorized further use by the recipient(s). Access control is commonly provided at other layers of the protocol stack. Various methods also exist for attempting access control through the inclusion of proprietary metadata in a container format, although it should be noted that many similar techniques in the past have been defeated by determined attackers. As discussed in B1.3 above, some protocols provide for selective encryption of imagery (e.g., high-resolution imagery encrypted while metadata or a low-resolution preview is unencrypted). This method may be used to provide controlled access to imagery.

### **B1.3 DATA PRIVACY**

The first major area of security concern is *privacy*, the requirement that the imagery not be disclosed to any other than the intended recipient(s). Limited privacy can be achieved through the use of data *scrambling*, which weakly obfuscates the data stream using a reversible non-cryptographic mechanism, or through employment of protected data transport at lower layers and restricting distribution.

Better privacy can be achieved using cryptographic techniques, which may be applied to all or part of a container format. Since any transcoding or decoding system must be able to read and pass metadata in order to process the stream, imagery metadata must be visible at these points. It is therefore highly desirable to have the capability to perform selective encryption of container file fields (e.g., imagery but not metadata, or imagery and imagery metadata but not cryptographic metadata). ‘Secure JPEG 2000’ includes mechanisms for selective encryption of JPEG 2000 image content and metadata. Various proprietary methods also exist for encrypting MP4 streams.

### **B1.4 DATA INTEGRITY**

The second major area of security concern is *data integrity*, the requirement that the imagery not be altered, whether to introduce false imagery or to interfere with decoding. Integrity verification mechanisms can be used for data validation to prevent security problems due to non-compliant malignant data. Like privacy, data integrity is commonly provided at other layers of the protocol stack or through a container format. ‘Secure JPEG 2000’ includes mechanisms for cryptographic verification of JPEG 2000-compliant data.

### **B1.5 AUTHENTICATION OF COMMUNICATING ENTITIES**

*Source authentication* is the requirement that the imagery be attributable to a known origin. Closely related to data integrity, it can also be used for data validation. Source authentication, if provided, is commonly provided at other layers of the protocol stack or through a container format. ‘Secure JPEG 2000’ includes digital signature mechanisms for authentication of JPEG 2000-compliant data.

### **B1.6 CONTROL OF ACCESS TO RESOURCES**

The third major area of security concern is *access control*, the requirement that the imagery be restricted from unauthorized further use by the recipient(s). Access control is commonly provided at other layers of the protocol stack. Various methods also exist for attempting access control through the inclusion of proprietary metadata in a container format, although it should be noted that many similar techniques in the past have been defeated by determined attackers. As discussed in B1.3 above, some protocols provide for selective encryption of imagery (e.g., high-resolution imagery encrypted while metadata or a low-resolution preview is unencrypted). This method may be used to provide controlled access to imagery.

### **B3 PATENT CONSIDERATIONS**

It is expected that implementation of this Recommended Standard by space-agency users will occur through the use of commercial off-the-shelf equipment that implements the referenced standards, and that patent-rights issues for such equipment will have been settled between the equipment manufacturer and the patent-right holders. It is not expected that space-agency users will develop new equipment based on the standards referenced herein. Therefore patent rights for the referenced standards are outside the scope of this Recommended Standard.

## ANNEX C

### DTN BUNDLE PROTOCOL FOR VIDEO TRANSMISSION

#### (INFORMATIVE)

##### **C1 MODE 1 REAL TIME DELIVERY, BEST EFFORT**

Mode 1 provides best-effort delivery of data and should be used for unicast or multicast data delivery when the data is to be utilized immediately upon arrival (perhaps for near-real-time decision making). The data will be forwarded using the DTN Bundle Protocol without custody transfer and will be available to the receiving CODEC/application on a best-effort basis. Therefore the data will be ‘played’ in the order it is received. Missing, damaged, or out-of-order packets will be ignored with subsequent CODEC responses being typical. Additional items such as excessive latency or jitter may be deleterious to the CODEC response.

##### **C2 MODE 2 DELAYED DELIVERY, WITH PACKET RESTORATION**

Mode 2 provides delivery of data with the prospect of no packets dropped and should be used for single or multi-transport of data when the data can be utilized after a sufficient latency to allow reassembly of the data. The data will be available to a CODEC/application once the underlying protocol has sufficient time to reassemble the data stream.

Therefore the data will be ‘played’ in its entirety subject to data being wholly lost on a frame basis. Missing and damaged bundles will be forwarded prior to reassembly with out-of-order bundles to be made available to the end CODEC/application. Additional items such as excessive latency or jitter will not affect CODEC/application response.

##### **C3 STORE AND FORWARD ISSUES**

The Delay Tolerant Networking Bundle Protocol (DTN-BP) enables store and forward operation when multiple hops or links are required to send data from source to receiver. There is an additional space link reliability protocol available known as Licklider Transmission Protocol (LTP), which will note loss of DTN bundles (which would contain 1– $n$  video frames depending on system design) and request retransmission of missing bundles.

Use of the LTP reliability mechanism will result in delivery of out-of-order video frames to the application layer (because of the lag in retransmitting missing bundles). This may or may not be acceptable to the end-user application, and consideration of this out-of-order condition must be made.

In current lab experiments, it has been seen that an effective use of DTN to transmit video is to transmit bundles unreliably, accept the consequences of missing data for the real-time viewing of the video stream, and use another mechanism for recovery of missing data. This mechanism could be an application buffer to store retransmitted bundles separately for later reconstruction of the video stream in non-real time, or to record the video on board and later transmit as a video file for playback after the file is completely received without errors. Further experimentation is required to provide definite parameters for the transmission of video using DTN.<sup>3</sup>

---

<sup>3</sup> As this is refined, it will be added to the MIA specifications.

## ANNEX D

### INFORMATIVE REFERENCES

#### (INFORMATIVE)

- [D1] *Motion Imagery and Applications*. Issue 2. Report Concerning Space Data System Standards (Green Book), CCSDS 706.1-G-2. Washington, D.C.: CCSDS, May 2015.
- [D2] J. Postel. *Internet Protocol*. STD 5. Reston, Virginia: ISOC, September 1981.
- [D3] *Hypertext Transfer Protocol -- HTTP/1.1*. RFC 2616. Reston, Virginia: ISOC, June 1999.
- [D4] H. Schulzrinne, et al. *RTP: A Transport Protocol for Real-Time Applications*. STD 64. Reston, Virginia: ISOC, July 2003.
- [D5] J. Postel. *Transmission Control Protocol*. STD 7. Reston, Virginia: ISOC, September 1981.
- [D6] *Information Technology—Coding of Audio-Visual Objects—Part 14: MP4 File Format*. International Standard, ISO/IEC 14496-14:2003. Geneva: ISO, 2003.
- [D7] *Information Technology—JPEG 2000 Image Coding System: Secure JPEG 2000*. International Standard, ISO/IEC 15444-8:2007. Geneva: ISO, 2007.
- [D8] *Licklider Transmission Protocol (LTP) for CCSDS*. Issue 1. Recommendation for Space Data System Standards (Blue Book), CCSDS 734.1-B-1. Washington, D.C.: CCSDS, May 2015.
- [D9] *CCSDS Bundle Protocol Specification*. Issue 1. Recommendation for Space Data System Standards (Blue Book), CCSDS 734.2-B-1. Washington, D.C.: CCSDS, forthcoming.

## **ANNEX E**

### **ABBREVIATIONS**

#### **(INFORMATIVE)**

AAC	Advanced Audio Codec
BER	Bit Error Rate
CBR	Constant Bit Rate
CFDP	CCSDS File Delivery Protocol
DRM	Digital Rights Management
DTN	Delay Tolerant Networking
DTN-BP	Delay Tolerant Networking Bundle Protocol
DVB-ASI	Digital Video Broadcasting-Asynchronous Interface
EVA	Extra-Vehicular Activity
FPS	Frames Per Second
GOP	Group of Pictures
HD	High Definition
HDMI	High Definition Multimedia Interface
HD-SDI	High Definition-Serial Digital Interface
HTTP	Hypertext Transfer Protocol
IP	Internet Protocol
LTP	Licklider Transport Protocol
LVDS	Low Voltage Differential Signaling
PID	Packet Identification
RTP	Real Time Protocol
SD	Standard Definition
SDI	Serial Digital Interface
TS	Transport Stream
UDP	User Datagram Protocol
UT	Unitdata Transfer



# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

## About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

## Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at [bsigroup.com/standards](http://bsigroup.com/standards) or contacting our Customer Services team or Knowledge Centre.

## Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at [bsigroup.com/shop](http://bsigroup.com/shop), where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

## Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

## Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

## Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to [bsigroup.com/subscriptions](http://bsigroup.com/subscriptions).

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit [bsigroup.com/shop](http://bsigroup.com/shop).

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email [cservices@bsigroup.com](mailto:cservices@bsigroup.com).

## Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

## Useful Contacts

### Customer Services

**Tel:** +44 345 086 9001

**Email:** [cservices@bsigroup.com](mailto:cservices@bsigroup.com)

### Subscriptions

**Tel:** +44 345 086 9001

**Email:** [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com)

### Knowledge Centre

**Tel:** +44 20 8996 7004

**Email:** [knowledgecentre@bsigroup.com](mailto:knowledgecentre@bsigroup.com)

### Copyright & Licensing

**Tel:** +44 20 8996 7070

**Email:** [copyright@bsigroup.com](mailto:copyright@bsigroup.com)

## BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK