



BSI Standards Publication

**Fine ceramics (advanced ceramics,
advanced technical ceramics) — Test
method for air-purification performance of
semiconducting photocatalytic materials**

Part 4: Removal of formaldehyde

National foreword

This British Standard is the UK implementation of ISO 22197-4:2021. It supersedes BS ISO 22197-4:2013, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee RPI/13, Advanced technical ceramics.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2021
Published by BSI Standards Limited 2021

ISBN 978 0 539 15210 4

ICS 81.060.30

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2021.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

**Fine ceramics (advanced ceramics,
advanced technical ceramics) —
Test method for air-purification
performance of semiconducting
photocatalytic materials —**

**Part 4:
Removal of formaldehyde**

*Céramiques techniques — Méthodes d'essai relatives à la performance
des matériaux photocatalytiques semi-conducteurs pour la
purification de l'air —*

Partie 4: Élimination du formaldéhyde





COPYRIGHT PROTECTED DOCUMENT

© ISO 2021, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	2
5 Principle	2
6 Apparatus	3
6.1 Test equipment.....	3
6.2 Test gas supply.....	5
6.3 Photoreactor.....	6
6.4 Light source.....	6
6.5 Analytical system.....	6
7 Test piece	6
8 Procedure	6
8.1 General aspects.....	6
8.2 Pretreatment of test piece.....	7
8.3 Preparation for the test.....	7
8.4 Pretest.....	8
8.5 Removal test.....	8
9 Calculation	8
10 Test method for test pieces with lower performance	9
11 Test report	9
Bibliography	11

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 206, *Fine ceramics*.

This second edition cancels and replaces the first edition ([ISO 22197-4:2013](http://www.iso.org/iso/22197-4:2013)), which has been technically revised.

The main changes to the previous edition are as follows:

- references to [ISO 4892-3](http://www.iso.org/iso/4892-3) and [ISO 6145-7](http://www.iso.org/iso/6145-7) deleted from [Clause 2](#);
- gas flow measurement changed from dry-gas basis to wet-gas basis in [6.2](#);
- tolerance on dimensions of test piece changed in [Clause 7](#);
- procedures for removing water-soluble contaminants added to [8.2](#);
- criterion for acceptable adsorption of formaldehyde added to [Clause 9](#).

A list of all parts in the ISO 22197 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Fine ceramics (advanced ceramics, advanced technical ceramics) — Test method for air-purification performance of semiconducting photocatalytic materials —

Part 4: Removal of formaldehyde

1 Scope

This document specifies a test method for the determination of the air-purification performance of materials that contain a photocatalyst or have photocatalytic films on the surface, usually made from semiconducting metal oxides, such as titanium dioxide or other ceramic materials, by continuous exposure of a test piece to the model air pollutant under irradiation with long-wave ultraviolet (UV) light. This document is intended for use with different kinds of materials, such as construction materials in flat sheet, board or plate shape, that are the basic forms of materials for various applications. This document also applies to structured filter materials including honeycomb-form, woven and non-woven fabrics, and to plastic or paper materials if they contain ceramic microcrystals and composites. This document does not apply to powder or granular photocatalytic materials.

This test method is usually applicable to photocatalytic materials produced for air purification. This method is not suitable for the determination of other performance attributes of photocatalytic materials, i.e. decomposition of water contaminants, self-cleaning, antifogging and antibacterial actions. It concerns the removal of formaldehyde.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 10677](#), *Fine ceramics (advanced ceramics, advanced technical ceramics) — Ultraviolet light source for testing semiconducting photocatalytic materials*

[ISO 16000-3](#), *Indoor air — Part 3: Determination of formaldehyde and other carbonyl compounds in indoor air and test chamber air — Active sampling method*

[ISO/IEC 17025](#), *General requirements for the competence of testing and calibration laboratories*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:


- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

of formaldehyde removed by the test piece (μmol). The simple adsorption of HCHO by the test piece (not due to photocatalysis) is evaluated by tests in the dark. However, some test pieces absorb formaldehyde very strongly, and it is not always possible to attain a stable concentration of formaldehyde in the designated time of test. The photocatalytic activity can depend on physical and chemical properties of pollutants mainly due to the adsorption process involved. For a better evaluation of air purification performance of photocatalytic materials, it is recommended that one or more suitable test methods as provided in the other parts of the ISO 22197 series are combined.

6 Apparatus


6.1 Test equipment

The test equipment enables a photocatalytic material to be examined for its pollutant-removal capability by supplying the test gas continuously, while providing photoirradiation to activate the photocatalyst. It is the same as that used in the test method for the removal of nitric oxide (see [ISO 22197-1](#)) and consists of a test gas supply, a photoreactor, a light source and pollutant-measurement equipment. Since low concentrations of pollutants are to be tested, the system shall be constructed with materials of low absorption and resistant to UV radiation, e.g. acrylic resin, stainless steel, glass and fluorocarbon polymers. An example of a test system is shown in [Figure 1](#).




- Key**
- | | | | |
|---|--------------------------|----|--------------------------|
| 1 | test gas supply | 9 | four-way valve |
| 2 | air compressor | 10 | photoreactor |
| 3 | air-purification system | 11 | test piece |
| 4 | standard gas (pollutant) | 12 | air-tight optical window |
| 5 | pressure regulator | 13 | light source |
| 6 | mass-flow controller | 14 | analyser |
| 7 | humidifier | 15 | vent |
| 8 | gas mixer | | |

Figure 1 — Schematic diagram of the test equipment



a) For flat test pieces



b) For filter-type test pieces

test piece length l_1	test piece width l_2	air layer thickness l_g
$99,0 \pm 1,0$ mm	$49,0 \pm 1,0$ mm	$5,0 \pm 0,5$ mm


Key

- | | |
|----------------------------|-----------------------------|
| 1 test gas inlet | 6 auxiliary plate |
| 2 baffle | 7 test piece (flat-type) |
| 3 air-tight optical window | 8 test gas outlet |
| 4 flow channel | 9 test piece holder |
| 5 height-adjusting plate | 10 test piece (filter-type) |

Figure 2 — Cross-sectional views of photoreactor

6.2 Test gas supply

The test gas supply provides air polluted with model contaminant at a predetermined concentration, temperature and humidity, and supplies it continuously to the photoreactor. It consists of flow regulators, a humidifier, gas mixers and so on. The flow rate of each gas should be within 5 % of the designated value, which is easily attained by using thermal mass-flow controllers with knowledge of temperature and gas type at calibration in accordance with [ISO 6145-7](#). The expression of gas flow rate in this document is that converted to the standard state (0 °C and 101,3 kPa). Typical capacities of flow controller for pollutant gas, dry air and wet air are 200 ml/min, 2 000 ml/min and 2 000 ml/min, respectively. The standard formaldehyde gas in a cylinder, normally balanced with nitrogen, shall have a volume fraction of about 20 µl/l.



Key

- X time (min)
- Y concentration of formaldehyde (µl/l)
- 1 irradiation start
- 2 irradiation stop
- O outlet
- I inlet

Figure 3 — Typical trace of formaldehyde concentration during the test operation

8.2 Pretreatment of test piece

8.2.1 The test piece shall normally be pretreated according to [8.2.2](#) and [8.2.3](#), in this order. When it is anticipated that the test piece will have hydrophobic contamination, [8.2.3](#) may be followed by [8.2.2](#). The procedure in [8.2.2](#) may be omitted if it causes damage to the test piece. If the test pieces are not to be tested immediately after this pretreatment, they shall be kept in an airtight container.

8.2.2 Immerse the test piece in deionized water for 2 h or more, remove it and air-dry at room temperature. The test piece may be dried by heating within a temperature range that does not cause physical or chemical changes to the test piece (maximum 120 °C). Dryness is confirmed when a constant mass is reached. The method of drying and any observations, such as the appearance of sediment in the wash water, shall be recorded.

8.2.3 Irradiate the test piece with an UV lamp for at least 12 h (up to 24 h) to decompose residual organic matter on the test piece. The UV irradiance at the sample surface shall be high enough to secure complete decomposition of organic matter (10 W/m² to 20 W/m²).

8.3 Preparation for the test

8.3.1 Adjust the test gas supply beforehand so that it can stably supply the test gas containing 1,0 ± 0,1 (µl/l) of formaldehyde and 1,56 % ± 0,16 % of volume fraction of water vapour at 25,0 °C ± 2,5 °C. This water-vapour volume fraction is equivalent to a relative humidity of 50 % at 25 °C. The relative humidity shall be measured by using a hygrometer (with accuracy of ±3 % RH) that has been calibrated by a method traceable to a certified reference standard. Adjust the flow regulator in order for the flow rate at the inlet of the reactor to be 3,00 l/min ± 0,15 l/min (0 °C and 101,3 kPa). Measure and record the irradiance from the light source at the surface of the test piece. For the light source that requires warming up, turn the

power on well before the measurement of irradiance and irradiation for the formaldehyde removal test. Use the shutter appropriately to avoid unnecessary irradiation to the photoreactor.

8.3.2 Place the test piece in the centre of the photoreactor and attach the glass window after adjusting the air layer between the test piece and window to be $5,0 \text{ mm} \pm 0,5 \text{ mm}$ thick, using height-adjusting plates. If necessary, adjust the air layer thickness before and after the test piece to be within 1,0 mm difference based on the top of the test piece, using auxiliary plates. Check that the reactor is sealed by visual examination of the sealing material, such as an O-ring to tightly contact the glass window.

8.4 Pretest

The concentration of formaldehyde cannot be obtained instantaneously by the DNPH-HPLC method. Therefore, the time of the adsorption of formaldehyde reaching saturation in a dark condition cannot be confirmed during the test. For this reason, the following pretest shall be carried out. If the time for saturation can be confirmed during the test, there is no need for the pretest.

After pretreatment of the test piece in [8.2](#) and preparation for the test in [8.3](#), introduce the test gas into the reactor. Measure the concentration of formaldehyde under the dark condition every 15 min for 90 min. When the concentration of formaldehyde exceeds 90 % of the supply gas concentration for the first time, then that time and the concentration at that time are defined as the time of the dark condition and concentration of the dark condition, respectively. When the concentration of formaldehyde is still less than 90 % of the concentration after 90 min, then this document shall not apply.

8.5 Removal test

8.5.1 Follow the pretreatment procedure as in [8.2](#) and preparation as in [8.3](#).

8.5.2 If the pretest in [8.4](#) has been done, supply the test gas into the photoreactor until the time of dark conditions which was checked beforehand (if the time is less than 30 min, supply for 30 min). If the pretest has not been done, proceed as follows. Supply the test gas to the photoreactor and record the concentration of formaldehyde under the dark conditions. If the concentration of formaldehyde exceeds 90 % of the supply gas concentration, then that time and the concentration at that time are defined as the time of the dark condition and concentration of the dark condition, respectively. If it does not exceed 90 % even after 90 min, stop measurement and report that this test is not applicable to the test piece used.

8.5.3 Maintain the gas flow and commence irradiation of the test piece. For a light source that requires warming up, the same procedure shall be applied as described in [8.3.1](#). Record the concentration under irradiation for 3 h. When the photocatalytic decomposition begins, the concentration decreases as in [Figure 3](#) and eventually becomes constant. The formaldehyde concentration shall be measured at more than one point in one hour. Measurement shall be made at more than three points as in the final hour (120 min to 180 min after the start of irradiation). The concentration of formaldehyde shall be obtained by the average value based on the concentrations measured in the final hour.

8.5.4 Stop the gas supply to the reactor and remove the test piece from the reactor.

9 Calculation

The test results shall be calculated as follows. The calculated values shall be rounded to one decimal place. The flow rate of test gas f is 3,0 l/min at the standard state (0 °C and 101,3 kPa).

If ϕ_F does not satisfy [Formula \(1\)](#), meaning that the difference between formaldehyde concentrations under dark condition and under photoirradiation is less than 5 % of the formaldehyde concentration supplied, this test method shall not be applied. The removal percentage of formaldehyde (R_F) is calculated by [Formula \(2\)](#). When R_F is either below 5 % or more than 95 %, R_F is expressed as “below 5 %” or “more than 95 %”, respectively. Then, the quantity of formaldehyde removed (n_F) is calculated

by [Formula \(3\)](#). When R_F is either below 5 % or more than 95 %, n_F is expressed as “below $(0,134 \phi_{F0} f)$ μmol ” or “more than $(2,545 \phi_{F0} f)$ μmol ”, respectively.

$$\phi_F \leq \phi_{FD} - \phi_{F0} \times 0,05 \quad (1)$$

$$R_F = \frac{\phi_{F0} - \phi_F}{\phi_{F0}} \times 100 \quad (2)$$

$$n_F = R_F \times \frac{\phi_{F0} \times f \times 60}{100 \times 22,4} \quad (3)$$

where

- R_F is the removal percentage, by test piece, of formaldehyde (%);
- n_F is the removal quantity, by test piece, of formaldehyde (μmol);
- ϕ_{F0} is the supply volume fraction of formaldehyde ($\mu\text{l/l}$);
- ϕ_F is the volume fraction of formaldehyde at the reactor exit ($\mu\text{l/l}$);
- ϕ_{FD} is the formaldehyde volume fraction at the reactor exit under dark conditions ($\mu\text{l/l}$);
- f is the flow rate of test gas converted into that at the standard state (0 °C and 101,3 kPa) (l/min).

10 Test method for test pieces with lower performance

In cases where the removal percentage is less than 5 % and a more certain result is demanded, the number of test pieces and the flow rate of test gas may be altered at the same time as shown in [Table 1](#). However, the removal quantity of formaldehyde to appear in the test report shall be half of the values calculated from [Formula \(3\)](#), as well as using the flow rate of 1,5 l/min. When the test conditions are altered, it is necessary to confirm the time of adsorption (dark condition) at the altered test conditions.

Table 1 — Alternative test conditions

Alternative test conditions	Value after change
Test gas flow rate	1,5 l/min \pm 0,075 l/min
Number of test pieces	Two pieces

11 Test report

The test report shall include the reporting provisions of [ISO/IEC 17025](#), and shall include the following information. Items g), h) and i) shall be reported for each test.

- a) The name and address of the testing establishment.
- b) The date of the test, a unique identification of the report and of each page, the customer’s name and address, the signatory of the report.
- c) A reference to this document, i.e. determined in accordance with ISO 22197-4:2021.
- d) Date of the test, atmospheric temperature, relative humidity.
- e) Description of the test piece (e.g. material, size, shape).
- f) Description of the test equipment (specifications).
- g) Test conditions (e.g. kind of pollutant gas, supply concentration, water-vapour concentration, flow rate, detailed description of light source, irradiance, analyser and radiometer used, condition of pretreatment, modification under [Clause 10](#)).

- h) The amount of formaldehyde removed during the final hour, removal percentage of formaldehyde (optional).
- i) Any other matters of special importance, such as a change in the test piece noticed during the test.

Bibliography

- [1] [ISO 6145-7](#), *Gas analysis — Preparation of calibration gas mixtures using dynamic methods — Part 7: Thermal mass-flow controllers*
- [2] [ISO 22197-1](#), *Fine ceramics (advanced ceramics, advanced technical ceramics) — Test method for air-purification performance of semiconducting photocatalytic materials — Part 1: Removal of nitric oxide*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email cservices@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email: cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK