

BSI Standards Publication

Road vehicles — Test method to evaluate the performance of lane-keeping assistance systems

National foreword

This British Standard is the UK implementation of ISO 22735:2021.

The UK participation in its preparation was entrusted to Technical Committee AUE/15, Safety related to vehicles.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2021
Published by BSI Standards Limited 2021

ISBN 978 0 580 51035 9

ICS 43.020

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 May 2021.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL
STANDARD

ISO
22735

First edition
2021-05-21

**Road vehicles — Test method to
evaluate the performance of lane-
keeping assistance systems**

*Véhicules routiers — Méthode d'essai pour évaluer la performance
des systèmes d'aide au maintien de la trajectoire*



Reference number
ISO 22735:2021(E)

© ISO 2021



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Variables	2
4.1 Coordinate systems.....	2
4.2 Lateral deviation from path (Y_{VUT} error).....	2
4.3 Variables to be measured.....	3
5 Measuring equipment	3
5.1 General.....	3
5.2 Transducer installation.....	3
5.3 Calibration.....	3
5.4 Data processing.....	4
6 Test conditions	4
6.1 General.....	4
6.2 Test data.....	4
6.3 Test track.....	4
6.3.1 General.....	4
6.3.2 Lane marking.....	4
6.4 Environmental conditions.....	5
6.5 Test vehicle.....	5
6.5.1 General condition.....	5
6.5.2 LKAS settings.....	5
6.5.3 Tyres.....	5
6.5.4 Wheel alignment measurement.....	6
6.5.5 Loading conditions.....	6
6.6 Vehicle preparation.....	6
7 Test procedure	7
7.1 Pre-test conditioning.....	7
7.1.1 General.....	7
7.1.2 Brakes conditioning.....	7
7.1.3 Tyres conditioning.....	8
7.1.4 System check.....	8
7.2 Test scenarios.....	8
7.3 Test execution.....	10
8 Performance metrics	10
8.1 General.....	10
8.2 Lateral speed of VUT during a test run (V_{latVUT}) and last lateral speed of VUT before line crossing ($V_{latVUT})_{blc}$	10
8.3 Lane departure warning activation time during a test run (T_{LDW}) and last lane departure warning activation time before line crossing ($T_{LDW})_{blc}$	10
8.4 LKAS activation time during a test run (T_{LKAS}) and last LKAS activation time before line crossing ($T_{LKAS})_{blc}$	10
8.5 Time to line crossing during a test run (T_{TLC}) and last T_{TLC} before line crossing ($T_{TLC})_{blc}$	11
8.6 Distance to line crossing during a test run (D_{TLC}) and last D_{TLC} before line crossing ($D_{TLC})_{blc}$	11
8.7 Maximum yaw velocity during a test run ($\dot{\psi}_{VUT})_{max}$ and last ($\dot{\psi}_{VUT})_{max}$ before line crossing ($\dot{\psi}_{VUT})_{max,blc}$	11
8.8 Maximum lateral acceleration during a test run ($A_{latVUT})_{max}$ and last ($A_{latVUT})_{max}$ before line crossing ($A_{latVUT})_{max,blc}$	11

8.9	Maximum steering torque during a test run $(M_{VUT})_{max}$ and last $(M_{VUT})_{max}$ before line crossing $(M_{VUT})_{max,blc}$	11
Annex A	(informative) Road markings	12
Annex B	(informative) Test report	20
Bibliography	22

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 33, *Vehicle dynamics and chassis components*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The main function of a lane keeping assistance system (LKAS) is to support the driver in keeping the vehicle within the current lane. LKAS acquires information on the position of the vehicle within the lane and, when required, sends commands to actuators to influence the lateral movement of the vehicle, and in turn provides status information to the driver.

This document is intended to assess the complete performance of an LKAS fitted in a road vehicle:

- the capacity to keep the vehicle within the current lane during other situations not described in this test method (more complex scenarios, other weather conditions);
- the capacity to avoid undesired lane change.

Road vehicles — Test method to evaluate the performance of lane-keeping assistance systems

1 Scope

This document specifies test methods and performance metrics to evaluate the behaviour of a vehicle equipped with lane keeping assistance system (LKAS, see 3.2).

For this purpose, variables relevant to vehicle dynamics as well as controllability of a vehicle with LKAS and their measurement methods are defined.

A system requiring a driver intervention is excluded from the scope. This document applies to the vehicles of M1 category.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 8855](#), *Road vehicles — Vehicle dynamics and road-holding ability — Vocabulary*

ISO 15037-1:2019, *Road vehicles — Vehicle dynamics test methods — Part 1: General conditions for passenger cars*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in [ISO 8855](#), [ISO 15037-1](#) and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

distance to line crossing

DTLC

remaining lateral distance (perpendicular to the line) between the inner side of the lane marking and most outer edge of the tyre, before the *vehicle under test (VUT)* (3.5) crosses the line, assuming that the VUT would continue to travel with the same lateral velocity towards the lane marking

3.2

lane keeping assistance system

LKAS

heading correction system that is applied automatically by the vehicle in response to the detection of the vehicle that is about to drift beyond a delineated edge line of the current travel lane

Note 1 to entry: There are two kinds of LKAS: lane centring LKAS where steering intervention is constantly occurring to keep the vehicle running along the centreline of lane and lane departure prevention LKAS where steering intervention only occurs when the vehicle is imminent to cross the lane boundary. Different performance metrics can be applied for each system.

3.3
peak braking coefficient
PBC

measure of tyre to road surface friction based on the maximum deceleration of a rolling tyre

Note 1 to entry: Measured by using the American Society for Testing and Materials (ASTM) E1136-10 (2010) standard reference test tyre, in accordance with ASTM Method E 1337-90 (1996), at a speed of 64,4 km/h, without water delivery.

Note 2 to entry: Alternatively, the method as specified in UNECE R13-H.

3.4
time to line crossing
T_{TLC}

remaining time before the *vehicle under test (VUT)* (3.5) crosses the line, assuming that the VUT continues to travel with the same lateral velocity towards the lane marking

3.5
vehicle under test
VUT

vehicle tested according to this document with a lane keeping assistance system

3.6
vehicle width

widest point of the vehicle ignoring the rear-view mirrors, side marker lamps, tyre pressure indicators, direction indicator lamps, position lamps, flexible mudguards and the deflected part of the tyre sidewalls immediately above the point of contact with the ground


4 Variables

4.1 Coordinate systems

The road fixed reference system X_E - Y_E - Z_E , as shown in [Figure 1](#), is fixed to the lane, and the vehicle fixed reference system X - Y - Z is fixed to the centre of gravity (CG) of VUT.

4.2 Lateral deviation from path (Y_{VUT} error)

The lateral deviation from path is determined as the lateral distance between the centre of the front of the VUT when measured in parallel to the intended path as shown in [Figure 1](#). This measure applies during both the straight-line approach and the curve that establishes the lane departure.



Key

- 1 intended path
- 2 actual path
- 3 lateral deviation from path

Figure 1 — Definition of lateral deviation from path

4.3 Variables to be measured

Variables that shall be measured are listed in [Table 1](#) along with notations.

Table 1 — Measured variables

Variable		Symbol
Time	Time when manoeuvre starts with 2 s of straight path	T_0
	Time when LKAS activates	T_{LKAS}
	Time when lane departure warning is issued	T_{LDW}
	Time when VUT crosses the line	$T_{crossing}$
Position	Position of the VUT during the entire test	X_{VUT}, Y_{VUT}
Speed and angular velocity	Longitudinal and lateral speed of the VUT during the entire test	$V_{longVUT}, V_{latVUT}$
	Speed when VUT crosses the line	$V_{crossing}$
	Yaw velocity of the VUT during the entire test	$\dot{\psi}_{VUT}$
Steering wheel motion	Steering wheel velocity of the VUT during the entire test	$\dot{\Omega}_{VUT}$
	Steering wheel torque of the VUT during the entire test ^a	M_{VUT}
Lateral acceleration and jerk	Lateral acceleration of the VUT during the entire test	A_{latVUT}
	Lateral jerk of the VUT during the entire test ^b	\dot{A}_{latVUT}
^a Steering wheel torque characterizes the beginning of the intervention by LKAS and determines driver's overriding capability to LKAS function.		
^b Lateral jerk is the measure of smoothness of lateral movement. Too high jerk prevents driver from correcting path when needed.		

Variables shall be sampled and recorded at a frequency of at least 100 Hz.

5 Measuring equipment

5.1 General

VUT shall be equipped with data measurement and acquisition system to sample and record data with an accuracy of at least:

- longitudinal speed to 0,1 km/h;
- lateral and longitudinal position to 0,03 m;
- heading angle to 0,1°;
- yaw rate to 0,1°/s;
- longitudinal acceleration to 0,1 m/s²;
- steering wheel velocity to 1,0°/s.

5.2 Transducer installation

The requirements of ISO 15037-1:2019, 5.2 shall apply. In addition, it shall be ensured that transient vehicle pitch changes do not adversely affect the measurement of the velocity and position variables for the chosen transducer system.

5.3 Calibration

All transducers shall be calibrated according to the manufacturer instructions. In some cases, calibration may be performed immediately before testing.

If parts of the measuring system used can be adjusted such calibration shall be performed immediately before the beginning of the tests.

5.4 Data processing

Filter the measured data as follows:

- position and speed are not filtered and are used in their raw state;
- acceleration with a 12-pole phaseless Butterworth filter with a cut off frequency of 10 Hz;
- yaw rate with a 12-pole phaseless Butterworth filter with a cut off frequency of 10 Hz;
- force with a 12-pole phaseless Butterworth filter with a cut off frequency of 10 Hz.

6 Test conditions

6.1 General

The test conditions shall be in accordance with ISO 15037-1:2019, Clause 6, unless otherwise specified below.

6.2 Test data

General data on the test vehicle and test conditions shall be recorded as specified in ISO 15037-1:2019, 6.4.1.

6.3 Test track

6.3.1 General

All tests shall be carried out on a smooth, clean, dry and uniform paved road surface.

Conduct tests on a dry (no visible moisture on the surface), uniform, solid-paved surface with a consistent slope between level and 1 %. The test surface shall have a minimal peak braking coefficient (PBC) of 0,9.

The surface shall be paved and should not contain any irregularities (e.g. large dips or cracks, manhole covers or reflective studs) within a lateral distance of 3,0 m to either side of the test line(s) and with a longitudinal distance of 30 m ahead of the VUT from the point after the test is complete.

6.3.2 Lane marking

The tests described in this document shall use two different types of lane markings conforming to the individual lane markings (width, length of segment or void) to mark a lane with a width of 3,5 m to 3,7 m:

- dashed line with a width between 0,10 m and 0,25 m;
- solid line with a width between 0,10 m and 0,25 m.

The lane markings should be sufficiently long to ensure that there is at least 20 m of marking remaining ahead of the vehicle after the test is complete.

Lane markings for different nations are listed in [Annex A](#).

Some proving grounds have different lane markings. In that case, difficulties to recognizing the lane should be equivalent to the lane marking.




Figure 2 — Lane marking

6.4 Environmental conditions

Conduct tests in dry conditions with ambient temperature above 5 °C and below 40 °C.

For some proving ground where the low limit of ambient temperature of 5 °C is difficult to achieve, lower value can be adopted. However, in that case, the lower limit values shall be reported.

No precipitation shall be falling and horizontal visibility at ground level shall be greater than 1 km. Wind speeds shall be below 10 m/s to minimize VUT disturbance.

Natural ambient illumination shall be homogenous in the test area and in excess of 2 000 lx for daylight testing with no strong shadows cast across the test area other than those caused by the VUT. Ensure testing is not performed driving towards, or away from the sun when there is direct sunlight.

Measure and record the following parameters preferably at the commencement of every single test or at least every 30 min:

- ambient temperature in °C;
- wind speed and direction in m/s;
- ambient illumination in lx.

6.5 Test vehicle

6.5.1 General condition

The test vehicle condition shall be in accordance with the vehicle manufacturer specifications, particularly with respect to the wheel alignments, power train (e.g. differentials and locks) configuration and tyre fitment.

6.5.2 LKAS settings

If different settings are available, the chosen setting shall be kept during the complete test procedure. The test procedure can be repeated for different settings if needed.

NOTE The aim of this document is to measure performance of a vehicle equipped with LKAS. It is not intended to compare performance of different vehicles, such as Euro NCAP procedure.

6.5.3 Tyres

Generally, all measurements shall be conducted with original fitment tyres mounted. If several types of tyres are available, the types of tyres shall be reported.

For a general tyre condition, new tyres shall be fitted on the test vehicle according to the manufacturer's specifications. If not specified otherwise by the tyre manufacturer, they shall be run-in according to the

tyre conditioning procedure specified in [7.1.3](#). After running-in maintain the run-in tyres in the same position on the vehicle for the duration of the testing

Tyres shall have a tread depth of at least 90 % of the original value across the whole breadth of the tread and around the whole circumference of the tyre.

Tyres shall be manufactured not more than one year before the test. The date of manufacturing shall be noted in the presentation of test conditions.

Tyres shall be inflated to the pressure as specified by the vehicle manufacturer for the test vehicle configuration. The tolerance for setting the cold inflation pressure is ± 5 kPa for pressures up to 250 kPa and ± 2 % for pressure above 250 kPa.

6.5.4 Wheel alignment measurement

The vehicle should be subject to a vehicle (in-line) geometry check to record the wheel alignment set by the vehicle manufacturer. This should be done with "unladen kerb mass" specified in [6.5.5](#).

6.5.5 Loading conditions

The fuel tank shall be filled up and, in the course of the measurement sequence, the indicated fuel level should not drop below "half-full".

Check the oil level and top up to its maximum level if necessary. Similarly, top up the levels of all other fluids to their maximum levels if necessary.

Measure the front and rear axle masses and determine the total mass of the vehicle. Record this mass in the test details.

Calculate the required ballast mass, by subtracting the mass of the test driver and test equipment so that the test mass is the "unladen kerb mass" as specified by vehicle manufacturer plus 200 kg.

The weight distribution in a ready-for-measurement condition shall be adjusted according to the axle load distribution specified by the vehicle manufacturer for a ready-to-drive (kerb) condition.

If the vehicle is to be tested in any other load condition (for example, GVM) then the additional payload shall be evenly distributed such that cross-axle variations do not exceed 50 kg.

6.6 Vehicle preparation

Fit the on-board test equipment and instrumentation in the vehicle. Also fit any associated cables, cabling boxes and power sources.

Place weights with a mass of the ballast mass. Any items added should be securely attached to the car. With the driver in the vehicle, weigh the front and rear axle loads of the vehicle.


Compare these loads with the "unladen kerb mass".

The total vehicle mass shall be within ± 1 % of the sum of the unladen kerb mass, plus 200 kg. The front/rear axle load distribution needs to be within 5 % of the front/rear axle load distribution of the original unladen kerb mass plus full fuel load. If the vehicle differs from the requirements given in this paragraph, items may be removed or added to the vehicle which has no influence on its performance. Any items added to increase the vehicle mass should be securely attached to the car.

Repeat weighing the front and rear axle load and comparison until the front and rear axle loads and the total vehicle mass are within the limits set in the above paragraph. Care should be taken when adding or removing weight in order to approximate the original vehicle inertial properties as close as possible. Record the final axle loads in the test details. Record the axle weights of the VUT in the "as tested" condition.

Vehicle dimensional measurements shall be taken. For the purposes of this test procedure, vehicle dimensions shall be represented by a two-dimensional polygon defined by the lateral and longitudinal dimensions relative to the centroid of the vehicle. The corners of the polygon are defined by the lateral and longitudinal locations where the plane of the outside edge of each tyre touches the road. This plane is defined by running a perpendicular line from the outer most edge of the tyre to the ground at the wheelbase, as illustrated in [Figure 3](#).

The vehicle's wheelbase and the lateral and longitudinal locations shall be measured and recorded.



Key

- 1 definition of lateral location
- 2 longitudinal locations
- 3 lateral locations

Figure 3 — Vehicle dimensional measurements

7 Test procedure

7.1 Pre-test conditioning

7.1.1 General

A new car is used as delivered to the test laboratory however, a car may have been used for other active safety tests.

Drive a maximum of 100 km on a mixture of urban and rural roads with other traffic and roadside furniture to calibrate the sensor system. Avoid harsh acceleration and braking.

7.1.2 Brakes conditioning

If not performed already for other tests, or when the vehicle manufacturer requests, condition the vehicle's brakes in the following manner:

- perform 10 stops from a speed of 56 km/h with an average deceleration of approximately 0,5 g to 0,6 g;
- immediately following the series of 56 km/h stops, perform three additional stops from a speed of 72 km/h, each time applying enough force to the pedal to operate the vehicle's antilock braking system (ABS) for most of each stop;
- immediately following the series of 72 km/h stops, drive the vehicle at a speed of approximately 72 km/h for five minutes to cool the brakes;
- initiation of the first test shall begin within two hours after completion of the brake conditioning.

7.1.3 Tyres conditioning

Condition tyres in the following manner to remove the mould sheen:

- drive around a circle of 30 m in diameter at a speed enough to generate a lateral acceleration of approximately 0,5 g to 0,6 g for three clockwise laps followed by three anticlockwise laps;
- immediately following the circular driving, drive four passes at 56 km/h, performing 10 cycles of a sinusoidal steering input in each pass at a frequency of 1 Hz and amplitude enough to generate a peak lateral acceleration of approximately 0,5 g to 0,6 g;
- make the steering wheel amplitude of the final cycle of the final pass double that of the previous inputs.

In case of instability in the sinusoidal driving, reduce the amplitude of the steering input to an appropriately safe level and continue the four passes.


7.1.4 System check

Before any testing begins, perform a maximum of 10 runs, to ensure proper functioning of the system.

7.2 Test scenarios

The performance of the LKAS is assessed in different scenarios that are applicable to the system. Examples of scenarios are given in [Figure 4](#), where solid and dotted lane markings are used as lane boundaries. Including these examples, any other test scenarios along with the number of tests can be selected.

NOTE An example scenario can be performing steering according to [Figure 4](#), which requires four tests. Another example scenario can be performing steering to each dashed and solid line in any direction which requires a minimum of two tests.



- Key**
- 1 dashed line
 - 2 solid line

Figure 4 — Test scenarios

For testing purposes, assume an initial straight-line path followed by a fixed radius of 1 200 m followed again by a straight line, hereby known as the test path. Control the VUT with driver inputs or using alternative control systems that can modulate the vehicle controls as necessary to perform the tests.

Tests shall be performed with 0,1 m/s incremental steps within the lateral velocity range of 0,2 m/s to velocity until LKAS fails.

The vehicle manufacturer shall provide information describing the location when the closed loop path and/or speed control shall be ended so as not to interfere with intervention for each test. Otherwise for each lateral velocity, two calibration runs shall be performed in order to determine when the system activates. Compare steering wheel torque, vehicle speed or yaw rate of both runs and determine where there is a notable difference that identifies the location of intervention.

Run 1: complete the required test path with the system turned OFF and measure the control parameter.

Run 2: complete the required test path with the system turned ON and measure the control parameter.


Complete the tests while ending the closed loop control before system activation. In the case of calibration runs, the release of steering control should occur on the test path and no less than 5 m longitudinally before the location of intervention.

The following parameters should be used to create the test paths.

Table 2 — Test path definition

Lateral velocity [m/s]	Radius of turn [m]	Yaw angle [°]	Lateral distance during curve establishing yaw angle d_1 [m]	Lateral distance travelled during V_{lat} steady-state d_2 [m]
0,2	1 200	0,57	0,06	0,70
0,3		0,86	0,14	0,90
0,4		1,15	0,24	0,80
0,5		1,43	0,38	0,75
0,6		1,72	0,54	0,60
0,7		2,01	0,74	0,60
0,8		2,29	0,96	0,60

NOTE Offset from lane marking (d) = $d_1 + d_2 +$ half of the vehicle width (m).
More than 0,6 m/s lateral velocity test can be performed to validate the system behaviour. In that case, the value of d_2 can be adjusted to ensure correct behaviour and this value should be reported.



Key

$R = 1\ 200\ m$

Figure 5 — Test road

Before every test run, drive the VUT around a circle of maximum diameter 30 m at a speed less than 10 km/h for one clockwise lap followed by one anticlockwise lap, and then manoeuvre the VUT

into position on the test path. If requested by the OEM, an initialisation run may be included before every test run.

For vehicles with an automatic transmission, select D. For vehicles with a manual transmission, select the highest gear where the RPM will be at least 1 500 at the test speed.

Between tests, manoeuvre the VUT at a maximum speed of 50 km/h and avoid riding the brake pedal and harsh acceleration, braking or turning unless strictly necessary to maintain a safe testing environment.

7.3 Test execution

Accelerate the VUT to 72 km/h. If needed for activation of LKAS, change the speed appropriately. The test shall start at T_0 and is valid when all boundary conditions are met between T_0 and T_{LKAS} :

- Speed of VUT $72 \pm 1,0$ km/h;
- VUT lateral deviation from test path $0 \pm 0,05$ m;
- Steady-state lane departure lateral velocity $\pm 0,05$ m/s;
- Steering wheel velocity $\pm 15,0$ °/s.

Steer the vehicle as appropriate to achieve the lateral velocity in a smooth controlled manner and with minimal overshoot.

The subsequent lateral velocity for the next test is incremented with 0,1 m/s. If the test ends because the vehicle has failed to intervene sufficiently it is recommended that the VUT is steered away from the impact, either manually or by reactivating the steering control of the driving robot.

8 Performance metrics

8.1 General

The following metrics can evaluate the performance of a LKAS. Record the time history of the variables in 4.3 and obtain the following characteristic values.

Any line crossing should not be interpreted as a kind of pass/fail criteria.

8.2 Lateral speed of VUT during a test run (V_{latVUT}) and last lateral speed of VUT before line crossing ($(V_{latVUT})_{blc}$)

For each value of V_{latVUT} , other metrics in the following subclauses are obtained and recorded as shown in Table 3. $(V_{latVUT})_{blc}$ is the maximum lateral speed of VUT before line crossing.

8.3 Lane departure warning activation time during a test run (T_{LDW}) and last lane departure warning activation time before line crossing ($(T_{LDW})_{blc}$)

For each value of V_{latVUT} , record corresponding T_{LDW} as shown in Table 3, where $(T_{LDW})_{blc}$ is the last T_{LDW} before line crossing.

8.4 LKAS activation time during a test run (T_{LKAS}) and last LKAS activation time before line crossing ($(T_{LKAS})_{blc}$)

For each value of V_{latVUT} , record corresponding T_{LKAS} as shown in Table 3, where $(T_{LKAS})_{blc}$ is the last T_{LKAS} before line crossing.

8.5 Time to line crossing during a test run (T_{TLC}) and last T_{TLC} before line crossing ($T_{TLC})_{blc}$

For each value of V_{latVUT} , record corresponding T_{TLC} as shown in [Table 3](#), where $(T_{TLC})_{blc}$ is the last T_{TLC} before line crossing. $(T_{TLC})_{blc}$, considered with other metrics such as $(T_{LDW})_{blc}$, and $(T_{LKAS})_{blc}$.

8.6 Distance to line crossing during a test run (D_{TLC}) and last D_{TLC} before line crossing ($D_{TLC})_{blc}$

For each value of V_{latVUT} , record corresponding D_{TLC} as shown in [Table 3](#), where $(D_{TLC})_{blc}$ is the last D_{TLC} before line crossing. $(D_{TLC})_{blc}$, considered with other metrics such as $(T_{LDW})_{blc}$, and $(T_{LKAS})_{blc}$.

8.7 Maximum yaw velocity during a test run $(\dot{\Psi}_{VUT})_{max}$ and last $(\dot{\Psi}_{VUT})_{max}$ before line crossing $(\dot{\Psi}_{VUT})_{max,blc}$

For each value of V_{latVUT} , record corresponding $(\dot{\Psi}_{VUT})_{max}$ as shown in [Table 3](#), where $(\dot{\Psi}_{VUT})_{max,blc}$ is the last $(\dot{\Psi}_{VUT})_{max}$ before line crossing.

8.8 Maximum lateral acceleration during a test run $(A_{latVUT})_{max}$ and last $(A_{latVUT})_{max}$ before line crossing $(A_{latVUT})_{max,blc}$

For each value of V_{latVUT} , record corresponding $(A_{latVUT})_{max}$ as shown in [Table 3](#), where $(A_{latVUT})_{max,blc}$ is the last $(A_{latVUT})_{max}$ before line crossing.

8.9 Maximum steering torque during a test run $(M_{VUT})_{max}$ and last $(M_{VUT})_{max}$ before line crossing $(M_{VUT})_{max,blc}$

For each value of V_{latVUT} , record corresponding $(M_{VUT})_{max}$ as shown in [Table 3](#), where $(M_{VUT})_{max,blc}$ is the last $(M_{VUT})_{max}$ before line crossing.

NOTE $(M_{VUT})_{max}$ is crucial for the driver's ability to override the system.

Test results shall be reported along with all performance metrics in [Table 3](#). Examples of test reports are given in [Annex B](#).

Table 3 — Performance evaluation metrics

V_{latVUT} [m/s]	T_{LDW} [s]	T_{LKAS} [s]	T_{TLC} [s]	D_{TLC} [s]	$(\dot{\Psi}_{VUT})_{max}^a$ [rad/sec]	$(A_{latVUT})_{max}^a$ [m/s]	$(M_{VUT})_{max}^a, b$ [Nm]
0,2							
0,3							
0,4							
0,5							
0,6							
•							
•							
$(V_{latVUT})_{blc}$	$(T_{LDW})_{blc}$	$(T_{LKAS})_{blc}$	$(T_{TLC})_{blc}$	$(D_{TLC})_{blc}$	$(\dot{\Psi}_{VUT})_{max,blc}$	$(A_{latVUT})_{max,blc}$	$(M_{VUT})_{max,blc}$
Line crossing	–	–	–	–	–	–	–

^a Maximum value during a test run with a given V_{latVUT} .

^b Since steering torque is not applied by either steering robot or driver during the "Lateral distance travelled during V_{lat} steady state d_2 " defined in [Table 1](#), for some LKAS where steering intervention occurs imminent to line crossing, steering torque may not be measurable.

Annex A (informative)

Road markings






A.1 General



National road markings are specified in [ISO 11270](#). [Table A.1](#) states road markings and patterns of selected countries.

Table A.1 — Road markings and patterns of selected countries

Country	Pattern (m)	Width (cm)		
		Left lane marking	Centre line	Right lane marking
Spain		20	10	20
Sweden		20	10	20
France		22	15	22

Country	Pattern (m)		Width (cm)			
			Left lane marking	Centre line	Right lane marking	
Germany				15	15	30
United Kingdom				20	10	20
Belgium				30	20	30
Denmark				30	15	30
Netherlands				15	10	15

Country	Pattern (m)		Width (cm)		
			Left lane marking	Centre line	Right lane marking
Italy			15	15	15
Ireland			15	10	15
Greece			12	12	12
Switzerland			20	15	20
Portugal			20	15	20

Country	Pattern (m)	Width (cm)		
		Left lane marking	Centre line	Right lane marking
Norway		20	15	20
Finland		20	10	20

A.2 China – lane boundary geometry

Lane width should be between 3,0 m to 3,75 m.

Lane boundary width should be 3 100 mm, 150 mm, or 200 mm wide. The interrupted marking lines should be:

- 4 m (segment) + 6 m (void) for the opposite direction;
- for the same direction, 2 m (segment) + 4 m (void) for urban areas;
- 6 m (segment) + 9 m (void) for highways.

NOTE The information about lane boundaries in China is taken from China national standard GB 5768:1999[2].

A.3 Italy – lane boundary geometry

Lane width should be between 2,5 m to 3,75 m for normal lanes and from 2 m to 3,5 m for emergency lanes. However, lanes have been also measured with approximately 4 m.

Lane boundaries should be large from 120 mm (generic), via 150 mm (highway) to 250 mm (borders). Interrupted marking lines should be:

- 3 m (segment) + 3 m (void) for urban areas;
- 3 m (segment) + 4,5 m (void) for extra urban roads;
- 4,5 m (segment) + 7,5 m (void) for highways. In special cases, other markings are possible.

NOTE The data about lane boundary geometry in Italy were taken from the "Manuale della segnaletica stradale permanente"[8].

A.4 Japan – lane boundary geometry

Lane width should be between 2,75 m to 3,5 m for generic lanes and from 3,25 m to 3,75 m for highway lanes.

Lane boundaries should be from 100 mm to 150 mm (borders) to 200 mm (centre) wide.

Lane segments and voids for interrupted marking lines should have the same length (between 3 m to 10 m) for centrelines. For borderlines, painted segments should be within 3 m to 10 m, and 6 m to 20 m for voids.

A.5 United States – lane boundary geometry

Lane width: 2,6 m to 4,2 m.

Lane marker width: 120 mm to 250 mm (250 mm for thick border markers).

Double markers, which indicate "no passing zones" on roads with tow-way traffic have two parallel painted stripes, each 100 mm wide, with approximately 80 mm between them.

Interrupted markers: for dashed markers (with voids between dashes), the mean painted dash length is approximately 4 m (2 m), with a void between dashes of approximately 6 m (2 m).

Other characteristics: pavement marker installation based on California standard plans raised pavement markers can be used in place of painted strips in marking California roads. These markers can be white or yellow, depending on the specific application, following the same logic used to determine whether painted lines are white or yellow.

There are two types of markers: non-reflective circular "dots" and rectangular reflectors.

Dots (D): diameter 100 mm, spherical section with maximum height up to 16 mm above pavement.

Reflectors (R): width 100mm, length (travel direction) 50 mm to 100 mm, height above pavement 10 mm. reflective face shall have an area of at least 1 sq in (6,45 sq cm).

These are used in place of painted lines, which are normally 100 mm wide. Where a double width painted in would be used, two rows of adjacent markers can be used instead.

To represent continuous line (no passing): markers are separated by 1,2 m, arranged in following sequence, repeated continuously: R D D D D D R D D D D D.

Where dashed lines are used, in areas where passing is permitted, or between lanes of multi-lane highways, the painted stripes can be in either of two configurations, each of which has its equivalent in markers:

- painted stripe of length 2,1 m with blank space of 5,2 m repeated continuously, or markers arranged as: R-2,4m-D-1,2m-D-1,2m-D-4,5m-D-1,2m-D-1,2m-D-2,4m-R, also repeated continuously;
- painted stripe of length 3,65 m, separated by space of 11 m, repeated continuously, or markers arranged as: R-5,5m-D-1,2m-D-1,2m-D-1,2m-D-5,5m-R, also repeated continuously.

A.6 Australia – lane boundary geometry

Lane widths 3,5 m desirable, but can range from 2,6 m in turn lanes, 2,8 m on low volume rural roads (with no edge line) and at signalised intersections to 4,5 m on freeway interchange ramps.

Longitudinal lines and their warrants vary between the eight states and territories of Australia. Line widths vary from 80 mm to 200 mm depending on the annual average daily traffic (AADT) and road type and are predominantly white. Yellow lines are used as an edge line in selected locations but are not currently use for dividing/barrier line.

Edge lines (white):

- continuous: 80 mm to 200 mm wide;
- broken: 24 m line, 1 m void with reflector (RRPM) placed in the void.

Two lane pavements between 5,5 m to 6,8 m wide can be treated with edge lines where special circumstances exist, i.e. poor alignment, fog, and similar conditions.

If lane widths are narrow, the kerb can be painted instead of an edge line or outline (adjacent a median).

Edge lines (yellow):

- continuous: 80 mm to 200 mm wide no stopping zones/clearways or in areas subject to snow;
- broken: 9 m line, 1 m gap in areas subject to snow;
- broken: 600 mm stripe and 900 mm gap in yellow for restricted parking;
- broken: 3 m line, 3 m gap for part time clearways.

Broken or interrupted markings:

- continuity lines: 1 m line, 3 m void;
- turn lines: 600 mm stripe, 600 mm void;
- special purpose: 9 m line, 3 m void;
- lane lines: 3 m line, 9 m void;
- dividing lines: 3 m line and 9 m void (most common), 9 m line and 3 m void, 6 m line and 6 m void.

Barrier lines:

- double two-way: two parallel continuous white lines;
- double one-way: one continuous line parallel to a dividing line 3 m line, 9 m void.

Raised reflective pavement markers (RRPMs) are used as part of a simulated lane line (see below) and to augment longitudinal lines. RRPMs can be placed in the void between lines and dividing lines, the void in broken edge lines or either side of a continuous edge line depending on the width of the sealed shoulder.

Simulated lane line-RRPMs and non-reflective raised pavement markers (NRPMN) are used as an alternative to the 3 m painted line and 9 m void in the order RRPM NRPM NRPM NRPM, 9 m void (and repeat).

The data in this subclause are taken from the following sources:

- Australian standard 1742.2:2009[9],
- AUSTROADS Guide to Traffic Management[10],
- AUSTROADS Guide to Road Design Part 3: Geometric Design[11],
- various state published pavement marking standards (e.g. RMS-NSW, VicRoads, Qld Main Roads, SADTI).

A.7 Netherlands – lane boundary geometry

Road markings are:

- length markings;

- cross markings;
- other markings;
- arrow markings;
- expel markings;
- angle markings;
- symbols and traffic markings.

The traffic area (carriageway and traffic lanes) is bounded by length markings which generally trends parallel to the axis of the road. Length markings can occur as an uninterrupted or interrupted (broken) line and can be divided into edge lines and centre or separation lines. Dependent on the position of the marking, the width of the line differs. For interrupted lines, the length of segments and voids depends on the meaning of the marking. For a centreline, a combination of an uninterrupted and/or broken line (spaced out equal to the width of line) is possible.

The requirements for the marking width and the lane width can be spilt up in two: freeways and non-freeways.

Freeways or motor ways:

- 120 km/h-roads;
- lane width (separation lines included, and edge lines excluded): 3,50 m;
- edge line 0,20 m width;
- separation line 0,15 m width.

In special other lane widths are possible.

Rural roads (non-freeways):

- 60 km/h-roads;
 - lane width (markings excluded): 2,75 m;
 - width of edge line and centre of separation line: 0,10 m.
- 80 km/h-roads:
 - lane width (markings excluded): 3,10 m;
 - edge line 0,15 m wide;
 - centre of separation line 0,10 m wide.
- 100 km/h-roads:
 - lane width (markings excluded): 3,25 m;
 - edge line 0,15 m wide;
 - centre of separation line 0,10 m wide.

In special cases other lane widths are possible.

A.8 Canada – lane boundary geometry

The following information on pavement markings was taken from the Manual of Uniform Traffic control devices for Canada^[12]:

- normal width line is 100 mm to 150 mm wide;
- wide line is nearly twice the width of a normal line;
- double line consists of two normal line;
- dashed line is formed by shorter segments and gaps in the ratio of 1:1. These are typically 0,5 m to 3,0 m each.

Lane lines are broken white lines normally with segments and gaps in a 1:2 ratio. A recommended pattern is 3,0 m line segments with 6,0 m gaps. On high speed roads such as freeways, a segment to gap ratio of 1:3 (3,0 m segment, 9,0 m gap) can be used.

On urban streets, the lane width defined by lane lines normally should not be less than 3,1 m, but widths as narrow as 2,8 m have been used. Widths should increase on sharply curved sections of urban streets.

Pavement edge lines are continuous solid lines placed on the pavement of the travelled lane as close as practicable to the travelled lane. A white line is used to the right and a yellow line is used to the left of the travelled land.

The following information on lane width guidelines was taken from the Geometric Design Guide for Canadian Roads^[13]:

- width for two-lane rural roads (≤ 80 km/h) 3,0 m to 3,7 m, and (> 80 km/h) 3,3 m to 3,7 m;
- multilane rural roadways (≤ 100 km/h) 3,5 m to 3,7 m, and (≥ 100 km/h) 3,7 m;
- urban freeways, major arterials, and industrial/ commercial collector roadways 3,7 m;
- minor arterials, residential collectors, and local industrial/commercial roadway 3,5 m to 3,7 m;
- local residential roadways 3,0 m to 3,7 m.

A.9 Republic of Korea – lane boundary geometry

Lane width: 2,75 m to 3,50 m.

Lane marker width should be from 100 mm to 150 mm wide for both borders and centre.

Lane segments and voids interrupted lines should be between 3 m to 10 m. The guidelines include lane width for:

- urban collectors and arterials: 3 m painted, 5 m void;
- rural arterials: 5 m painted, 8 m void and;
- freeways and expressways: 10 m painted and 10 m void.

Annex B (informative)

Test report

B.1 General

This annex provides templates for potential test reports that may be used by parties involved.

B.2 Vehicle

B.2.1 Vehicle characteristics

The following vehicle characteristics may be listed:

- trade name,
- vehicle type,
- VIN N°,
- hand of drive,
- type of gearbox,
- bodywork,
- tires,
- pressures (Fr/Rr).

B.2.2 Technical characteristics of the test equipment

The following technical characteristics of the test equipment may be listed:

- driving robot's software,
- steering robot,
- braking and throttle robot,
- communication,
- post processing software.

B.3 Weather conditions

The following weather information should be noted:

- wind velocity,
- wind direction,
- air temperature,
- luminosity.


B.4 Test result templates

B.4.1 Metric table

The metric table shown in [Table 2](#) should be provided.

B.4.2 Plots

Time histories of variables or trajectory of VUT defined in [4.3](#) shall be plotted with specific time markings, as in [Figure B.1](#) that shows the time history of Y trajectory of VUT and [Figure B.2](#) that shows the time history of yaw rate.




Key

T second

Y lateral trajectory of VUT [m]

Figure B.1 — Time history of Y trajectory of the VUT



Key

T second

Y yaw rate [deg/s]

Figure B.2 — Time history of yaw rate

Bibliography

- [1] [ISO 11270](#), *Intelligent transport systems — Lane keeping assistance systems (LKAS) — Performance requirements and test procedures*
- [2] ISO 22733-1:—¹⁾, *Road vehicles — Test method to evaluate the performance of autonomous emergency braking systems — Part 1: car to car*
- [3] NCAP LSS Test Protocol v2.0.2 (2019)
- [4] ASTM E1136 (2010), *Standard Specification for P195/75R14 Radial Standard Reference Test Tire*
- [5] ASTM E1337-90 (1996), *Standard Test Method of Determining Longitudinal Peak Braking Coefficient of Paved Surface Using a Standard Reference Test Tire*
- [6] No Regulation 13-H of Economic Commission for Europe of the United Nations (UN/ECE) — Uniform provisions concerning the approval of passenger cars with regard to braking
- [7] GB 5768:1999, *Road traffic signs and markings*
- [8] Manuale della segnaletica stradale permanente (1993), [Conferenza del traffico e della circolazione. Ufficio traffico, ACINNOVA](#)
- [9] Australian standard 1742.2 (2009) *Manual of Uniform Traffic control Devices Part 2: Traffic Control devices for general use*
- [10] *Guide to Traffic Management Part 10: Traffic control –Types of Devices* (2020), Austroads
- [11] *Guide to Road Design Part 3: Geometric Design* (2020), Austroads
- [12] *Manual of Uniform Traffic control devices for Canada* (1998), [Transportation Association of Canada](#), [National Committee on Uniform Traffic Control](#)
- [13] *Geometric Design Guide for Canadian Roads* (1999), Transportation Association of Canada

1) Under preparation. Stage at the date of publication: ISO/FDIS 22733-1:2021

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email cservices@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email: cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK