



BSI Standards Publication

## **Determination of salt out (crystallization) temperature of liquid fertilizers**

---

## National foreword

This British Standard is the UK implementation of [ISO 23381:2020](#).

The UK participation in its preparation was entrusted to Technical Committee CII/37, Fertilisers and related chemicals.

A list of organizations represented on this committee can be obtained on request to its committee manager.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2020  
Published by BSI Standards Limited 2020

ISBN 978 0 539 01471 6

ICS 65.080

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2020.

### **Amendments/corrigenda issued since publication**

Date	Text affected
------	---------------

---

**INTERNATIONAL  
STANDARD**

**ISO  
23381**

First edition  
2020-09-17

---

---

**Determination of salt out  
(crystallization) temperature of  
liquid fertilizers**

*Détermination de la température de désolubilisation (cristallisation)  
des engrais liquides*



Reference number  
ISO 23381:2020(E)



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
[copyright@iso.org](mailto:copyright@iso.org)  
[www.iso.org](http://www.iso.org)

# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Principles</b> .....	<b>1</b>
<b>5 Reagents</b> .....	<b>2</b>
<b>6 Equipment</b> .....	<b>3</b>
<b>7 Set Up</b> .....	<b>3</b>
<b>8 Procedure</b> .....	<b>4</b>
<b>Annex A (informative) Examples of the equipment and setup</b> .....	<b>6</b>
<b>Bibliography</b> .....	<b>10</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 134, *Fertilizers, soil conditioners and beneficial substances*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

The global liquid fertilizers market size is estimated to account for a value of USD 2,5 billion in 2019 and is projected to grow at a CAGR of 3,7 % from 2019, to reach a value of USD 3,1 billion by 2025. North America is the leading consumer of the liquid fertilizers with 32 % of the market, followed by Europe (25 %), Asia Pacific (21 %), Latin America (13 %), and the rest of the world at 9 %<sup>[7]</sup>. Liquid fertilizers cover inorganic nitrogen, phosphorus, potash, and micronutrients as well as organic, and synthetic fertilizers applied to soil, as foliar, in fertigation, and as starter solutions and aerial applications and in crops such as cereals, grains, fruits, vegetable, oilseeds, pulses, turf, ornamentals, forage, and plantation crops. Liquid fertilizers are the most efficient way of delivering the required nutrients to the plants at the correct time and in optimal concentration.

Urea ammonium nitrate (UAN 28-32) is an example of a widely used liquid fertilizer. Ammonium polyphosphate (APP, 10-34-0, and 11-37-0), Ammonium thiosulfate (ATS, 12-0-0-26S), potassium thiosulfate (KTS, 0-0-25-17S), magnesium thiosulfate (0-0-0-10S-4Mg), calcium ammonium nitrate (CAN 17), and solutions of water soluble fertilizers such as potassium nitrate (13-0-46), and ammonium chloride solution (6-0-0-16Cl) are few examples of liquid fertilizers.

### Limitations of liquid fertilizers

Liquid fertilizers, although easier to use, and are versatile in application, they have the disadvantage of salting out (crystallize) at cold climate. This phenomenon creates limitation for transportation, storage, and handling during the cold season and proper steps is recommended to avoid crystallization.

Accurate crystallization data and an accurate, easy to use, and a universal method for the determination of salt out temperature (SOT) of liquid fertilizers is a helpful reference for stakeholders to avoid or prevent crystallization of these popular fertilizers during the cold season<sup>[8]</sup>.

Currently, there is no uniform and standard method for the determination of SOTs of liquid (fluid) fertilizers. There are quite a few methods used internally by several manufacturing companies. ASTM D6660 for the freezing point determination of aqueous ethylene glycol base engine coolants by atomic phase transition method, ASTM D1177-17 for the determination of freezing point of aqueous engine coolants, and the ASTM D97 (pour point) have also been cited in the literature for SOT measurements of liquid (fluid) fertilizers. Pour point of a liquid is defined as the temperature below which the liquid loses its flow characteristic. <sup>[4]to[6]</sup>

In addition to these cited methods, there are ISO documents that provide methods to determine the melting/freezing temperature of chemicals. ISO 1392 provides a method for the determination of the crystallization point of chemicals, and [ISO 3016](#) provides a method for petroleum oils for the determination of pour points. <sup>[1],[2]</sup>

Differential scanning calorimetry is a thermoanalytical technique in which the difference in the amount of heat required to increase the temperature of a sample and reference is measured as a function of temperature. Both the sample and reference are maintained at nearly the same temperature throughout the experiment. The temperature increase as a function of time linearly and heat flow curve vs. the temperature increase is the instrument output. These instruments are expensive and the price tag is over \$50,000 (USD).

Moreover, OECD Guidelines refers to the term “melting range” for the transition of solid to liquid.

The proposed method is based on cooling/thawing of the liquid fertilizer. The liquid (fluid) fertilizer is cooled in a dry ice/methanol bath until the liquid is crystallized. It then warms at the ambient temperature. Normally, the SOT is the temperature at which the last crystal dissolves.



# Determination of salt out (crystallization) temperature of liquid fertilizers

## 1 Scope

This document specifies the test procedure for the determination of the salt out temperature (SOT), also known as the crystallization temperature (CT) of liquid (fluid) fertilizers, using an inexpensive and simple technique.

This method might not be applicable to the binary and ternary fertilizers, especially with regards to the last crystal to disappear (LCTD). Some of these exceptions are discussed in the procedure ([Clause 8](#)).

## 2 Normative references

The following referenced documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 3696:1987](#), *Water for analytical laboratory use — Specification and test methods*

## 3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

## 4 Principles

Liquid fertilizers have been defined in [ISO 8157:2015](#).

An aliquot of the original liquid fertilizer sample is placed into a glass test tube and is then immersed into an alcohol-dry ice bath until it crystallizes. The alcohol could be chosen from methanol, ethanol, or isopropanol (IPA). Acetone could also be used instead of alcohols; however, IPA (rubbing alcohol) is preferred due to its higher boiling point. If dry ice is not available, other lowering temperature mixtures such as salt-ice could be used to achieve the proper cooling and crystallization of the fertilizer test sample.

Once the precipitation (formation of salt crystals) is complete, the cooling source is removed and the glass test tube and its contents are allowed to warm up to room temperature. The SOT in most cases is defined when the last crystal to dissolve (LCTD) dissolves (i.e. is no longer visible in the solution). Exceptions to the LCTD rule are covered below and in [8.11](#).

The underlying principal of the technique can be illustrated with the following cooling curve<sup>[9]</sup> shown in [Figure 1](#).

- 5.1 Use only water conforming to grade 3 of [ISO 3696:1987](#).
- 5.2 Dry ice snow maker (cone, clamp, ring, and thermal bag), or supply of dry ice.
- 5.3 CO<sub>2</sub> cylinder with a dip tube for making dry ice (or supply of dry ice).
- 5.4 IPA or other appropriate solvents such as methanol, ethanol, or acetone.
- 5.5 If dry ice is not available, other cooling systems such as an ice-salt bath could be used. However, care must be taken to achieve a proper low temperature.

## 6 Equipment

- 6.1 1 × stir motor apparatus<sup>1)</sup>.
- 6.2 3-Jaw Keyless Chuck with Arbor<sup>2)</sup>.
- 6.3 1 × 2-foot steel rod with attachable base<sup>3)</sup>.
- 6.4 1 × three-prong clamp.
- 6.5 2 × Silver-lined Dewar Vacuum Flask with cap<sup>4)</sup>.
- 6.6 50 cm<sup>3</sup> glass test tubes (several, Pyrex or similar quality).
- 6.7 Thin Stainless steel wire (several inches, such as 40 AWG, 0,079 9 mm, or 30 gauges, 0,010 inch, or 24 gauges, 0,58 mm).
- 6.8 Thin walled latex rubber tubing (several inches).
- 6.9 1 × thermometer (−40 °C to a least +30 °C), red liquor preferred for ease of reading. Alcohol filled thermometers are preferred over mercury-in-glass thermometers due to safety concerns with mercury. It is recommended that several alcohol thermometers with different temperature ranges be available.

## 7 Set Up

- 7.1 Attach a steel rod to its firm base (lab stand).

---

1) Glas-Col Model 099A GT31 or 099D GT 21 from [glas-col.com](#), 800-425-7265, or Stir-Pak Dual Shaft Mixer, Cole-Parmer UX-04555-44, 800-323-4340 are examples of suitable products available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of these products.

2) GLS 099D A210101, fits Glas-Col Stirrer Model 099A GT31 099D GT21, Cole-Palmer Stir-Pak Dual Shaft Mixer has already included the Chuck and is an example of a suitable product available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of this product.

3) Strong Lab Stand and support with a rigid base such as support stand with rod, 1000 mm length, 16 mm diameter, 180 mm base width from VWR, Catalogue # 241-0101 and is an example of a suitable product available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of this product.

4) Such as item # 8600-0099, Pope Scientific, 866-636-2487. It is an example of a suitable product available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of this product.

7.2 Attach the stir motor apparatus to the lab stand.

7.3 Remove the stir blade and associate metal shaft from the stir motor. These shall be replaced by the glass thermometer.

7.4 Take a thermometer that reads at least  $-40\text{ }^{\circ}\text{C}$  and add 1 inch of the thin walled latex rubber tubing to the top (non-bulb) of the thermometer.

7.5 To the bottom 3 inches (bulb end) of the thermometer, coil some stainless steel wire. Ensure that the added wire fits within the glass test tube and does not contact (scratch) sides or bottom of the glass test tube when rotated by stir motor.

7.6 Place the thermometer into where the stir blade rod was before and carefully tighten it around the thermometer.

NOTE If the stir blade rod is tightened too much, the thermometer might break.

7.7 Examples of equipment and set up are shown in [Annex A](#).

## 8 Procedure

8.1 Pour approximately 250 ml of IPA into the silver-lined Dewar vacuum flask (methanol, ethanol, or acetone can be used as well).

8.2 Pour dry ice snow gently (from dry ice supply or the thermal bag) to the Dewar flask. As the dry ice dissipate, add more. Do not add large pieces of dry ice (crush the dry ice, if large pieces exist).

**CAUTION — Dry ice will cause freeze burn. Do not handle with bare hands (use insulated gloves). Dry ice added to IPA (or other aforementioned solvents) creates a bubbly reaction. Add the dry ice slowly.**

8.3 Stir the IPA/dry ice mixture with a spatula. Use a variable transformer (variac) connected to the stirrer. Adjust the variac setting in order to provide adequate stirring of about 50-60 RPM (the setting on variac is about 30-40).

8.4 Add 15 ml of the test sample (liquid fertilizer) to the test tube.

8.5 Affix the test tube containing the test sample with a three-pronged clamp and position such that the thermometer end containing the stainless steel wire is placed inside and centred on the test tube. Make sure the thermometer is almost to the bottom of the test tube, but not touching it; this is done to ensure that almost all the forming crystal will mix and not settle on the test tube bottom.

8.6 Make sure the thermometer can rotate and adequately stir the sample in the test tube without touching the sides and the bottom of the test tube.

8.7 Start stirring.

8.8 As the thermometer stirs the solution in the test tube, take the Dewar flask of alcohol/dry ice and place it around the test tube. Make sure all of the tube containing the test sample is immersed fully into the alcohol/dry ice solution to ensure even cooling.

8.9 Cooling the test sample: cooling for 15 s to 20 s, then take out the Dewar flask for 5 s. Repeat this “into flask/out of flask” sequence until all the liquid contents in the test tube precipitate and the

formation of salt crystals is completed. The resulting slurry may slow the stirring action of the rotating thermometer which is acceptable.

**8.10** Warming the test sample: remove the Dewar flask containing alcohol/dry ice and while stirring, allow the test tube to warm to room temperature.

**8.11** Measurement: record the SOT as the temperature when the last crystal present in the solution is no longer visible.

**8.12** Report the SOT in both °F and °C if specified.

**8.13** If no precipitate or obvious salt crystals form in the liquid sample when the temperature is  $-40\text{ }^{\circ}\text{C}$ , report the SOT at  $< -40\text{ }^{\circ}\text{C}$ .

**8.14** If a few solid crystals remain and do not go into the solution at room temperature, report the SOT at that temperature.

**8.15** If a large amount of solid remains undissolved, repeat the measurement using a fresh test sample and report the SOT when the first crystal appears.

**8.16** In the case of UAN, report the SOT as the first crystal appears upon slow cooling (cooling  $1\text{ }^{\circ}\text{C}$  to  $2\text{ }^{\circ}\text{C}$  per min).

**8.17** Report the SOT as ranges.

## Annex A (informative)

### Examples of the equipment and setup



Figure A.1 — Stir Motor and keyless chuck



Figure A.2 — Stir motor and thermometer assembly



**Figure A.3 — Thermometer with stainless steel wire**




**Figure A.4 — Dewar flask and test tube**



**Figure A.5 — VARIAC**



**Figure A.6 — Set up with liquid fertilizer for SOT testing**



**Figure A.7 — Cooling in dry ice-IPA**



**Figure A.8 — Crystallized liquid fertilizer**

## Bibliography

- [1] ISO 1392, *Determination of crystallizing point — General method*
- [2] [ISO 3016](#), *Produits pétroliers et connexes d'origine naturelle ou synthétique — Détermination du point d'écoulement*
- [3] [ISO 8157:2015](#), *Fertilizers and soil conditioners — Vocabulary*
- [4] ASTM D97, *Test Method for Pour Point of Petroleum Products*
- [5] ASTM D1177-17, *Standard Test Method for Freezing Point of Aqueous Engine Coolants*
- [6] ASTM D6660, *Standard Test Method for Freezing Point of Aqueous Ethylene Glycol Base Engine Coolants by Automatic Phase Transition Method*
- [7] Market and Market. August 2016, Report Code 4538
- [8] LEIKAM D.F. Fluid Fertilizers Foundation Forum, December 8, 2010.
- [9] Engineering Solutions Guide. Tetra Technologies Inc., Second Edition, Chapter 8, 2007



# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

## About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

## Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at [bsigroup.com/standards](http://bsigroup.com/standards) or contacting our Customer Services team or Knowledge Centre.

## Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at [bsigroup.com/shop](http://bsigroup.com/shop), where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

## Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

## Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

## Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to [bsigroup.com/subscriptions](http://bsigroup.com/subscriptions).

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit [bsigroup.com/shop](http://bsigroup.com/shop).

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email [cservices@bsigroup.com](mailto:cservices@bsigroup.com).

## Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

## Useful Contacts

### Customer Services

**Tel:** +44 345 086 9001

**Email:** [cservices@bsigroup.com](mailto:cservices@bsigroup.com)

### Subscriptions

**Tel:** +44 345 086 9001

**Email:** [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com)

### Knowledge Centre

**Tel:** +44 20 8996 7004

**Email:** [knowledgecentre@bsigroup.com](mailto:knowledgecentre@bsigroup.com)

### Copyright & Licensing

**Tel:** +44 20 8996 7070

**Email:** [copyright@bsigroup.com](mailto:copyright@bsigroup.com)

## BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK