



BSI Standards Publication

Aerospace — Lead and runout threads

Part 1: Rolled external threads

National foreword

This British Standard is the UK implementation of [ISO 3353-1:2020](#). Together with [BS ISO 3353-2:2020](#), it supersedes [BS 2A 231:1993](#), which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee ACE/12, Aerospace fasteners and fastening systems.

A list of organizations represented on this committee can be obtained on request to its committee manager.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2020
Published by BSI Standards Limited 2020

ISBN 978 0 539 06941 9

ICS 49.030.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 December 2020.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL STANDARD

ISO
3353-1

Second edition
2020-12-16

Aerospace — Lead and runout threads —

Part 1: Rolled external threads

*Aéronautique et espace — Filets incomplets, débuts et fins de filets —
Partie 1: Filetages extérieurs roulés*



Reference number
ISO 3353-1:2020(E)

© ISO 2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO’s member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols for threads	2
5	Requirements	2
5.1	General requirements	2
5.2	Lead threads	2
5.3	Runout threads	3
5.3.1	Normal shank	3
5.3.2	Pitch diameter shank	4
5.3.3	Stepped shank	4
5.3.4	Screws threaded to the head and bolts threaded to a shoulder	5
5.3.5	Oversized bolts	6
6	Inspection method	7
6.1	General	7
6.2	Use of the charts	7
6.3	Procedure	7
6.3.1	For lead threads	7
6.3.2	For runout threads	7
Annex A (informative) Comments on inspection method		10

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles* Subcommittee SC 4, *Aerospace fastener systems*.

This second edition cancels and replaces the first edition (ISO 3353-1:2002), of which it constitutes a minor revision.

The main changes compared to the previous edition are as follows:

- update of the term “lead threads”;
- editorially revised.

A list of all parts in the [ISO 3353](http://www.iso.org/iso/3353) series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Aerospace — Lead and runout threads —

Part 1: Rolled external threads

1 Scope

This document specifies the lead and runout requirements for rolled external threads for aerospace construction, and the inspection method to be used in case of dispute.

It is applicable whenever it is referenced in a definition document.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

lead thread

portion of the incomplete thread that is fully formed at the root but not at the crest which occurs at the beginning end of either external or internal threads

3.2

runout thread


part of the screw thread in which is located the thread incompletely formed during rolling, between the completely formed threads and the part which has not been rolled

3.3

completely formed thread

thread, the profile of which (ABC) is located, over an axial distance of $1P$, within the limits specified in the definition document for the thread

Note 1 to entry: See [Figure 1](#).



Over the area Z , the thread shall lie within the limits specified in the definition document for the thread.

- a Crest of first completely formed thread.
- b Root of first completely formed thread.
- c Chamfer.


Figure 2 — Lead threads

The possible profile projection comparator inspection shall be carried out using a chart drawn in accordance with [Figure 10](#).

5.3 Runout threads


5.3.1 Normal shank

See [Figure 3](#) and [Figure 4](#).



- a Shank diameter having a nominal value equal to the nominal diameter of the thread = δ .
- b Blank diameter.
- c Root of last completely formed thread.
- d Angle before rolling. The shape is optional within these limits.

Figure 3 — Normal shank




- a Shank diameter having a nominal value equal to the nominal diameter of the thread = δ .
- b Blank diameter.
- c Root of last completely formed thread.

Figure 4 — Normal shank

The possible profile projection comparator inspection shall be carried out using a chart drawn in accordance with [Figure 11](#).

5.3.2 Pitch diameter shank

See [Figure 5](#).




- a Shank diameter having a nominal value equal to the maximum pitch diameter = δ .
- b Root of last completely formed thread.

Figure 5 — Pitch diameter shank

The possible profile projection comparator inspection shall be carried out using a chart drawn in accordance with [Figure 12](#).

5.3.3 Stepped shank

See [Figure 6](#).



- a Diameter of stepped shank, having a nominal value equal to $d_3 \text{ min.} - 0,1 \text{ mm} = \delta$.
- b $\left[1P + \frac{(d \text{ max.} - \delta \text{ nom.})}{2 \tan 35^\circ} \right]$ to $\left[2P + \frac{(d \text{ max.} - \delta \text{ nom.})}{2 \tan 15^\circ} \right]$.
- c Root of last completely formed thread.
- d Angle before rolling. The shape is optional within these limits.


Figure 6 — Stepped shank

The possible profile projection comparator inspection shall be carried out using a chart drawn in accordance with [Figure 13](#).

5.3.4 Screws threaded to the head and bolts threaded to a shoulder

5.3.4.1 Protruding head

See [Figure 7](#).



The beginning of the first thread shall not encroach on the radius R .


- a Blank diameter.
- b Root of last completely formed thread.

Figure 7 — Protruding head

The possible profile projection comparator inspection shall be carried out using a chart drawn in accordance with [Figure 12](#).

5.3.4.2 Flush head

See [Figure 8](#).



The beginning of the first thread shall not encroach on the radius R .

- a Blank diameter.
- b Root of last completely formed thread.


Figure 8 — Flush head

The possible profile projection comparator inspection shall be carried out using a chart drawn in accordance with [Figure 12](#).

5.3.5 Oversized bolts

EXAMPLE Bolts for repairs.

See [Figure 9](#).



- a Diameter of oversized shank = δ .
- b Blank diameter.
- c $\left[1P + \frac{(\delta \text{ nom.} - d \text{ max.})}{2 \tan 35^\circ} \right]$ to $\left[2P + \frac{(\delta \text{ nom.} - d \text{ max.})}{2 \tan 15^\circ} \right]$.
- d Root of last completely formed thread.
- e Angle before rolling. The shape is optional within these limits.

Figure 9 — Oversized bolts

The possible profile projection comparator inspection shall be carried out using a chart drawn in accordance with [Figure 14](#).

6 Inspection method

6.1 General

The method is left to the discretion of the manufacturer, provided that it ensures conformity with the requirements given in [Clause 5](#).

In case of dispute, the method by optical projection, defined hereafter, shall be used. See comments in [Annex A](#).

6.2 Use of the charts

The charts shall be used in conjunction with a profile projection comparator having a magnifying power equal to or greater than $\times 20$.

6.3 Procedure

6.3.1 For lead threads

The inspection shall be carried out using a chart drawn in accordance with [Figure 10](#).




Figure 10 — Lead threads

Rotate the bolt to find the first complete thread (see [Figure 1](#)) nearest to the end of the shank which has the thread crest and root not extending beyond the limits defined by the horizontal lines.

Then move the bolt horizontally until the right flank of the above thread coincides with line DE.

6.3.2 For runout threads

The inspection shall be carried out using a chart drawn in accordance with [Figure 11](#) to [Figure 14](#).




Figure 11 — Runout threads






Figure 12 — Runout threads



a
$$\left[1P + \frac{(d \text{ max.} - \delta \text{ nom.})}{2 \tan 35^\circ} \right]$$

b
$$\left[2P + \frac{(d \text{ max.} - \delta \text{ nom.})}{2 \tan 15^\circ} \right]$$

Figure 13 — Runout threads



$$\begin{aligned} a & \left[1P + \frac{(\delta \text{ nom.} - d \text{ max.})}{2 \tan 35^\circ} \right] \\ b & \left[2P + \frac{(\delta \text{ nom.} - d \text{ max.})}{2 \tan 15^\circ} \right] \end{aligned}$$

Figure 14 — Runout threads

Rotate the bolt to find the last complete thread (see [Figure 1](#)) nearest to the plain shank of the bolt which has the thread crest and root not extending beyond the limits defined by the horizontal lines.

Then move the bolt horizontally until the left flank of the above thread coincides with line FG.

Annex A
(informative)

Comments on inspection method

Assembling the bolt to be checked with a GO screw ring gauge, without entering chamfer, is the preferred method for checking lead and runout threads and produces consistent results.

Alternatively, the profile projection comparator method, while theoretically more accurate, takes considerably longer and depends on the skill of the operator.

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email cservices@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email: cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

