



BSI Standards Publication

**Composition cork — Expansion
joint fillers — Test methods**

INTERNATIONAL STANDARD

ISO
3867

Third edition
2017-07

Composition cork — Expansion joint fillers — Test methods

*Aggloméré composé de liège — Matériau pour le remplissage de
joints de dilatation — Méthodes d'essai*



Reference number
ISO 3867:2017(E)

© ISO 2017



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Apparatus	1
5 Sampling and preparation of test specimens	2
5.1 Sampling.....	2
5.2 Preparation of test specimens.....	2
6 Tests	2
6.1 Determination of dimensions.....	2
6.1.1 Determination of thickness.....	2
6.1.2 Determination of length and width.....	2
6.2 Expansion in water.....	3
6.2.1 Procedure.....	3
6.2.2 Calculation and expression of results.....	3
6.3 Recovery.....	3
6.3.1 Procedure.....	3
6.3.2 Calculation and expression of results.....	3
6.3.3 Retest provision.....	4
6.3.4 Calculation of compression.....	4
6.4 Extrusion.....	4
6.4.1 Procedure.....	4
6.4.2 Calculation and expression of results.....	5
6.5 Water absorption.....	5
6.5.1 Procedure.....	5
6.5.2 Calculation and expression of results.....	5
6.6 Apparent density.....	5
6.6.1 Procedure.....	5
6.6.2 Calculation and expression of results.....	6
7 Test report	6
Bibliography	7

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 87, *Cork*.

This third edition cancels and replaces the second edition (ISO 3867:2001), of which [Clauses 4](#) and [6](#) have been technically revised.

Introduction

Some test methods specified in this document (e.g. compression resistance perpendicular to the faces, extrusion during compression and ability to recover after release of the load) are indicative of the ability of a joint filler to continuously fill a concrete expansion joint and thereby to prevent damage that might otherwise occur during thermal expansion. The resistance to water absorption is a relative measure of durability and life expectancy.

Composition cork — Expansion joint fillers — Test methods

1 Scope

This document specifies test methods to determine the following characteristics of the composition cork intended to be used as a joint filler of expansion joints of concrete or other construction materials:

- apparent density;
- expansion in water;
- compression;
- recovery;
- extrusion;
- water absorption.

These test methods apply to agglomerated cork joint filler with a nominal thickness ranging from 6,3 mm to 25 mm.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 633, *Cork — Vocabulary*

ISO 3869:2017, *Agglomerated cork — Expansion joint fillers — Specifications, packaging and marking*

ISO 7322:2014, *Composition cork — Test methods*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 633 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <http://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Apparatus

4.1 Balance, with resolution of 0,01 g.

4.2 Vernier gauge, with resolution of 0,1 mm.

4.3 Compression testing machine, with one fixed jaw and one mobile jaw which shall move unloaded at a speed of 1,3 mm/min, and having enough capacity to reduce the test specimen to 50 % of its initial thickness.

4.4 Load recorder, to indicate the load with a readability of 1 %.

4.5 Three-sided extrusion mould, to confine the lateral movement of test specimens under compression to one side only. The mould shall have internal dimensions equal to $(100 \pm 0,5)$ mm \times $(100 \pm 0,5)$ mm and sides of such height as to extend at least 13 mm above the test specimens.

4.6 Steel template, measuring 100 mm \times 100 mm, so that it fits the extrusion mould to within 0,13 mm in length and width, equipped with a dial comparator.

4.7 Dial gauge, with a resolution of 0,02 mm.

4.8 Metal plate, measuring $(100 \pm 2,5)$ mm \times $(100 \pm 2,5)$ mm \times 6 mm, with rectified parallel faces.

4.9 Cutting system.

4.10 Climatic chamber.

5 Sampling and preparation of test specimens

5.1 Sampling

5.1.1 The sample taken shall be approximately 0,2 m² from each lot of 100 m² and shall consist of sufficient material to provide at least five test specimens measuring 100 mm \times 100 mm. Each test specimen shall be squarely cut using the cutting system (4.9).

5.1.2 The test specimens from self-expanding agglomerated cork (joint filler) shall be properly banded and wrapped in plastic at the factory immediately after cutting.

Samples shall be packaged for safe transportation to the testing laboratory so that there is no distortion or fissure of the material.

5.2 Preparation of test specimens

5.2.1 If necessary, squarely cut the test specimens immediately before testing so that the test specimens measure 100 mm \times 100 mm. Each test specimen shall be cut using a metal plate (4.8) as cutting system.

5.2.2 The test specimens of self-expanding agglomerated cork shall be dried for 24 h at ambient air after boiling the test specimens (see 6.2.1). Then cut the samples to the dimensions indicated in 5.1.1.

6 Tests

6.1 Determination of dimensions

6.1.1 Determination of thickness

Determine the thickness in accordance with ISO 7322:2014, 6.1.

6.1.2 Determination of length and width

Determine the length and width in accordance with ISO 7322:2014, 6.2.1.

6.2 Expansion in water

6.2.1 Procedure

For self-expanding agglomerated cork, use the five test specimens delivered by the manufacturer, as described in [5.1.2](#).

Determine the thickness (d_1) of one test specimen, as described in [6.1](#). Immerse the test specimen in boiling water for 1 h. Remove the test specimen and allow to cool at room temperature for 15 min. Measure the final thickness to the nearest 0,1 mm.

6.2.2 Calculation and expression of results

Calculate the expansion, E , of composition cork using [Formula \(1\)](#):

$$E = \frac{d_2}{d_1} \times 100 \% \quad (1)$$

where

d_1 is the thickness of each test specimen before immersion, expressed in millimetres, rounded to the nearest 0,1 mm;

d_2 is the thickness of each test specimen after immersion, expressed in millimetres, rounded to the nearest 0,1 mm.

The test result is the average value of individual results expressed as a percentage rounded to the nearest integer.

6.3 Recovery

6.3.1 Procedure

Place on the testing machine one test specimen prepared, as described in [5.2](#). Give the test specimen a single application of a load sufficient to reduce its thickness to 50 % of its initial thickness. Apply the load without shock and at such a rate that the test specimen is compressed approximately at 1,3 mm/min. Record this applied load (F).

Immediately release the load and allow the test specimen to recover for 10 min. Measure the new thickness (d_2), rounded to the nearest 0,1 mm.

6.3.2 Calculation and expression of results

Calculate the recovery, R , using [Formula \(2\)](#):

$$R = \frac{d_1}{d_2} \times 100 \% \quad (2)$$

where

d_1 is the thickness of the test specimen before compression, expressed in millimetres, rounded to the nearest 0,1 mm;

d_2 is the thickness of the test specimen after compression, expressed in millimetres, rounded to the nearest 0,1 mm.

The test result is the average value of the individual results, expressed as a percentage rounded to the nearest integer.

6.3.3 Retest provision

6.3.3.1 The test specimen shall meet the requirements specified in ISO 3869:2017, 4.4. If the test specimen fails to comply with the requirements of the specification, test a new specimen in accordance with the following procedure.

6.3.3.2 Give the test specimen three applications of a load sufficient to reduce its thickness to 50 % of its initial thickness. Apply the load without shock and at such a rate that the test specimen is compressed approximately at 1,3 mm/min.

6.3.3.3 After the first and the second applications, release immediately the load and allow the test specimen to recover for 30 min before the load is applied again.

6.3.3.4 After the third application, release immediately the load and allow the test specimen to recover for 1 h; then measure the thickness again (d_3).

6.3.3.5 Calculate the recovery, R' , using [Formula \(3\)](#):

$$R' = \frac{d_1}{d_2} \times 100 \% \quad (3)$$

where

d_1 is the thickness of the test specimen before compression, expressed in millimetres, rounded to the nearest 0,1 mm;

d_3 is the thickness of the test specimen after the third compression, expressed in millimetres, rounded to the nearest 0,1 mm.

The test result is the average value of the individual results, expressed as a percentage, rounded to the nearest integer.

6.3.4 Calculation of compression

Calculate the pressure, p , to which the test specimen has been submitted during the recovery test, using [Formula \(4\)](#):

$$p = \frac{F}{S} \times 10^{-3} \quad (4)$$

where

F is the maximum force required to reduce the initial thickness of the test specimen to 50 % (see [6.3.1](#)), expressed in newtons, rounded to the nearest 0,1 N;

S is the area of the test specimen (10 000 m²), expressed in square metres, rounded to 0,000 1 m².

The test result is the average value of the individual results, expressed in kilopascals, rounded to the nearest integer.

6.4 Extrusion

6.4.1 Procedure

Place the test specimen in the mould with the steel template ([4.6](#)) mounted on the base of the compression machine.

Give the test specimen one application of a load sufficient to compress it to 50 % of its initial thickness. Apply the load without shock and at such a rate that the test specimen is compressed at approximately 1,3 mm/min.

Measure in the dial gauge the maximum movement of the free edge of the test specimen during its compression.

6.4.2 Calculation and expression of results

The extrusion, X , of the test specimen is given by [Formula \(5\)](#):

$$X = b_1 \quad (5)$$

where b_1 is the maximum distance reached during compression by the free edge of the test specimen, expressed in millimetres, rounded to the nearest 0,1 mm.

The test result is the average value of the individual results, expressed in millimetres, rounded to the nearest 0,1 mm.

6.5 Water absorption

6.5.1 Procedure

Use one of the test specimens prepared as described in [5.2](#) and determine its mass (m_1) to the nearest 0,1 g. Immerse the test specimen in water at a temperature of 18 °C to 25 °C for 24 h. Maintain the test specimen in a horizontal position on the bottom of the container. During the test, the water surface in the container shall be 25 mm above the test specimen.

Remove the test specimen from the water and remove excess surface water from all sides of the test specimen with a paper towel. Immediately determine the mass of the test specimen, to the nearest 0,1 g.

6.5.2 Calculation and expression of results

Calculate the water absorption, A , as a percentage by volume, using [Formula \(6\)](#) (and taking in account the volume in cubic centimetres and the specimen's mass in grams):

$$A = \frac{m_2 - m_1}{d_1 \times S \times 10^{-3}} \times 100 = \frac{m_2 \times m_1}{d_1 \times S \times 10^{-1}} = \frac{m_2 - m_1}{d_1 \times S} \times 10 \quad (6)$$

where

m_1 is the mass of the test specimen before immersion, expressed in grams, rounded to the nearest 0,1 g;

m_2 is the mass of the test specimen after immersion, expressed in grams, rounded to the nearest 0,1 g;

d_1 is the nominal thickness of the test specimen (see [6.1](#)), expressed in millimetres, rounded to the nearest 0,1 mm.

S is the area of the test specimen (10 000 mm²), expressed in square millimetres.

The test result is the average value of the individual results, expressed as percentage by volume, rounded to the nearest integer.

6.6 Apparent density

6.6.1 Procedure

Use one of the test specimens prepared as described in [5.2](#) and determine its mass (m) to the nearest 0,1 g.

Determine its mass (m) to the nearest 0,1 g, after air dry at a temperature of $(20 \pm 3) ^\circ\text{C}$ and a relative humidity $(65 \pm 1) \%$ until it comes to a constant weight.

6.6.2 Calculation and expression of results

The apparent density (ρ) of the test specimen is given by [Formula \(7\)](#):

$$\rho = \frac{m}{l \times b \times d} \times 10^6 \quad (7)$$

where

- m is the mass of the test specimen, expressed in grams, rounded to the nearest 0,1 g;
- l is the nominal length of the test specimen (see [6.1](#)), expressed in millimetres, rounded to the nearest 0,1 mm;
- b is the nominal width of the test specimen (see [6.1](#)), expressed in millimetres, rounded to the nearest 0,1 mm;
- d is the nominal thickness of the test specimen (see [6.1](#)), expressed in millimetres, rounded to the nearest 0,1 mm.

The test result is the average value of the individual results, expressed in kilograms per cubic metre, rounded to the nearest integer.

7 Test report

The test report shall include the following information:

- a) a reference to this document, i.e. ISO 3867;
- b) the complete identification of the product tested, including the type, source and the manufacturer's references;
- c) the sampling report;
- d) the results obtained;
- e) any deviation from this document that may have affected the results.

Bibliography

- [1] ASTM D 545:2014, *Standard Test Methods for Preformed Expansion Joint Fillers for Concrete Construction (Nonextruding and Resilient Types)*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email subscriptions@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK