

BSI Standards Publication

Meat and meat products — Determination of L-(+)-glutamic acid content — Reference method

National foreword

This British Standard is the UK implementation of [ISO 4134:2021](#).

The UK participation in its preparation was entrusted to Technical Committee AW/6, Chemical analysis of meat and meat products.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2021
Published by BSI Standards Limited 2021

ISBN 978 0 539 06212 0

ICS 67.120.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2021.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

**INTERNATIONAL
STANDARD**

**ISO
4134**

Third edition
2021-07-23

**Meat and meat products —
Determination of L-(+)-glutamic acid
content — Reference method**

*Viande et produits à base de viande — Détermination de la teneur en
acide L-(+)-glutamique — Méthode de référence*



Reference number
ISO 4134:2021(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	1
5 Sampling	2
6 Preparation of test sample	2
7 Test method of spectrophotometer	2
7.1 Reagents.....	2
7.1.6 Solution R123, the mixed solution of solution R1, solution R2 and solution R3.....	3
7.2 Apparatus.....	4
7.2.5 Constant temperature drying box.....	4
7.2.6 pH-meter.....	4
7.3 Procedure.....	5
7.3.1 General.....	5
7.3.2 Test portion.....	5
7.3.3 Preparation of extract.....	5
7.3.4 Determination.....	5
7.4 Calculation and results.....	6
7.4.1 Absorbance difference of L-(+)-glutamic acid standard solution.....	6
7.4.2 Absorbance difference of L-(+)-glutamic acid test solution.....	7
7.4.3 Formula of linear regression of L-(+)-glutamic acid standard curve.....	7
7.4.4 L-(+)-glutamic acid concentration of the test solution.....	7
7.4.5 L-(+)-glutamic acid content of test sample.....	7
7.5 Precision.....	8
7.5.1 Interlaboratory test.....	8
7.5.2 Repeatability.....	8
7.5.3 Reproducibility.....	8
7.6 Detection limit.....	8
8 Test method of light absorption microplate reader	8
8.1 Reagents.....	8
8.2 Apparatus.....	8
8.3 Procedure.....	9
8.3.1 General.....	9
8.3.2 Extraction of L-(+)-glutamic acid in the test portion.....	9
8.3.3 Determination.....	9
8.4 Calculation and results.....	10
8.4.1 Absorbance difference for L-(+)-glutamic acid standard solution.....	10
8.4.2 Absorbance difference for L-(+)-glutamic acid test solution.....	10
8.4.3 Formula of linear regression for L-(+)-glutamic acid standard curve.....	11
8.4.4 L-(+)-glutamic acid concentration of the test solution.....	11
8.4.5 L-(+)-glutamic acid content of test sample.....	11
8.5 Precision.....	12
8.5.1 Interlaboratory test.....	12
8.5.2 Repeatability.....	12
8.5.3 Reproducibility.....	12
8.6 Detection limit.....	12
9 Test report	12
Annex A (informative) Safety practices	13
Bibliography	14

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 34, *Food products*, Subcommittee SC 6, *Meat, poultry, fish, eggs and their products*.

This third edition cancels and replaces the second edition (ISO 4134:1999), which has been technically revised. The main changes compared with the previous edition are as follows:

- a new test method, the light absorption microplate reader method, has been added;
- the order of the clauses has been rearranged;
- the Scope ([Clause 1](#)) has been revised to specify free L-(+)-glutamic acid in meat and meat products;
- the Normative references ([Clause 2](#)) have been updated;
- the Terms and definitions ([Clause 3](#)) have been modified by adding the term “free L-(+)-glutamic acid”;
- in [Clause 4](#), the description of “extraction of L-(+)-glutamic acid of test portion” has been modified and the detection wavelength has been changed from “492 nm” to “490 nm”;
- in [7.1](#), the identification of enzyme activity units for diaphorase and glutamate dehydrogenase has been supplemented; the concentration of KOH, NAD has been modified; the NAD and diaphorase have been mixed into a solution; and the buffer, NAD and enzymes have been labelled with R1, R2, and R3;
- the apparatus list ([7.2](#)) has been updated;
- in [7.3](#), the procedure of the test method of spectrophotometer has been modified by halving the sample mass and solution volume;
- in [7.3.4](#), the method of judging the absorbance of the reaction end point has been modified and, as a result, the previous Annex B “Example of plotting and extrapolation of absorbance values” has been deleted;
- in [8.4](#), the formula and symbol description of spectrophotometer has been modified;

- the previous Annex C “Derivation of equation for calculation of L-(+)-glutamic acid content” has been deleted;
- the Bibliography has been updated.

Any feedback or questions on this document should be directed to the user’s national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Meat and meat products — Determination of L-(+)-glutamic acid content — Reference method

1 Scope

This document specifies the spectrophotometer method and the light absorption microplate reader method for the determination of the free L-(+)-glutamic acid content of meat and meat products.

This document is applicable to meat and meat products, including livestock and poultry products.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 648](#), *Laboratory glassware — Single-volume pipettes*

[ISO 1042](#), *Laboratory glassware — One-mark volumetric flasks*

ISO 1442, *Meat and meat products — Determination of moisture content (Reference method)*

[ISO 3696](#), *Water for analytical laboratory use — Specification and test methods*

[ISO 8655-2](#), *Piston-operated volumetric apparatus — Part 2: piston pipettes*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>


3.1

free L-(+)-glutamic acid

L-(+)-glutamic acid and glutamate existing in meat and meat products in the form of free state

4 Principle

The free L-(+)-glutamic acid present in a test portion is extracted with perchloric acid solution. The extract is centrifuged, decanted and filtered, and diluted to appropriate concentration with water, and the pH is adjusted to 10. Nicotinamide adenine dinucleotide (NAD) is reduced by the L-(+)-glutamic acid in the presence of glutamate dehydrogenase, see [Formula \(1\)](#). The resultant reduced nicotinamide adenine dinucleotide (NADH) reacts with idonitrotetrazolium chloride in the presence of diaphorase, see [Formula \(2\)](#). The resulting formazane is measured at a wavelength of 490 nm and the free L-(+)-glutamic acid content of the test sample is calculated.





5 Sampling

Sampling is not part of the method specified in this document. A recommended sampling method is given in CAC/GL 50-2004.

It is important that the sample received by the laboratory is truly representative and has not been damaged or changed during transport or storage.

Start from a representative sample of at least 200 g. Store the sample at a temperature of 4 °C or frozen at -18 °C if not immediately analysed, so that deterioration and change in composition are prevented.

6 Preparation of test sample

Homogenize the laboratory sample with the appropriate equipment (see [7.2.1](#)). Note that the temperature of the sample should not exceed 25 °C. If a mincer is used, process the sample at least twice with the equipment.

Fill a suitable airtight container with the prepared sample. Seal the container and store it at a temperature of 4 °C or frozen at -18 °C if not immediately analysed, so that deterioration and change in composition are prevented. Analyse the sample as soon as practicable, but always within 24 h after homogenization.

7 Test method of spectrophotometer

7.1 Reagents

Only reagents of recognized analytical grade and only water of at least grade 2 purity as defined in [ISO 3696](#) shall be used. Except for the solutions of inorganic compounds ([7.1.1](#) and [7.1.2](#)), store all solutions in stoppered brown glass bottles which have been scrupulously cleaned and steamed or sterilized.

7.1.1 Dilute perchloric acid, $c = 1,0$ mol/l.

WARNING — Contact with oxidizable or combustible materials or with dehydrating or reducing agents can result in fire or explosion. Persons using this acid should be thoroughly familiar with its hazards. See the safety practices listed in [Annex A](#).

Add 8,6 ml of the perchloric acid (70 g/ 100 g, $\rho_{20} = 1,67$ g/ml) to the bulk of water, diluting to 100 ml.

7.1.2 Potassium hydroxide solution, $c = 4$ mol/l, 2 mol/l, 0,5 mol/l and 0,02 mol/l.

Dissolve 22,4 g of potassium hydroxide in water. Dilute the solution to 100 ml, $c = 4$ mol/l, and mix evenly after cooling.

Dissolve 11,2 g of potassium hydroxide in water. Dilute the solution to 100 ml, $c = 2$ mol/l, and mix evenly after cooling.

Transfer 2,5 ml of 2 mol/l potassium hydroxide solution to 10 ml volumetric flask, dilute to the mark with water and mix, $c = 0,5$ mol/l.

Transfer 0,1 ml of 2 mol/l potassium hydroxide solution to 10 ml volumetric flask, dilute to the mark with water and mix, $c = 0,02$ mol/l.

7.1.3 Solution R1, triethanolamine phosphate buffer solution, pH = 8,6.

Dissolve 1,86 g of triethanolamine hydrochloride in approximately 25 ml of water, adjust the pH to 8,6 with 2 mol/l potassium hydroxide solution (7.1.2), detecting with a pH-meter. Add 0,68 g of octylphenol decaethyleneglycol ether (e.g. Triton X-100). Dilute to 100 ml with water and mix (solution A).

Dissolve 0,86 g of dipotassium hydrogen phosphate (K_2HPO_4) and 7 mg of potassium dihydrogen phosphate (KH_2PO_4) in water. Dilute to 100 ml with water and mix evenly (solution B).

Mix 20 ml of solution A with 5 ml of solution B.

The solution is stable for two months when stored at a temperature of between 0 °C and 6 °C.

7.1.4 Solution R2, the mixed solution of NAD and diaphorase (lipoamide dehydrogenase EC ¹⁾ 1.8.1.4), $\rho_{NAD} = 11$ mg/ml, diaphorase, approximately 4 IU/ml.

Weigh 110 mg of NAD, and approximately 8 mg (approximately 40 IU) of diaphorase into a stoppered flask. Add 10,0 ml water and mix evenly.

The solution is stable for one week when stored in the dark at a temperature of between 0 °C and 6 °C.

7.1.5 Solution R3, iodonitrotetrazolium chloride (INT) solution, 2-(4-iodophenyl)-3-(4-nitrophenyl)-5-phenyltetrazolium chloride, $\rho = 0,6$ mg/ml.

Weigh 6 mg of INT into a small, stoppered brown flask. Add 10 ml of water and mix evenly.

The solution is stable for four weeks when stored in the dark at a temperature of between 0 °C and 6 °C.

7.1.6 Solution R123, the mixed solution of solution R1, solution R2 and solution R3.

Pipette 6 ml of solution R1, 2 ml of solution R2 and 2 ml of solution R3 into a stoppered brown glass bottle, and mix evenly before the test.

The mixed solution is stable for 1 h in stoppered brown glass bottles at room temperature.

7.1.7 Glutamate dehydrogenase (GLDH) solution (EC¹ 1.4.1.3), approximately 900 IU/ml.

Weigh 10 mg (approximately 900 IU) of lyophilized glutamate dehydrogenase (GLDH) into a small stoppered flask. Add 1 ml water and mix.

Insulated from ammonium sulfate, ethylene-dinitrilotetraacetic acid (EDTA) and glutaminase, this solution is stable for 12 months when stored at a temperature between 0 °C and 6 °C.

7.1.8 L-(+)-glutamic acid standard stock solution, $\rho = 1\ 000$ mg/l.

Weigh, to the nearest 0,000 1 g, approximately 50,0 mg of L-(+)-glutamic acid ($C_5H_9O_4N$). Dissolve it in approximately 25 ml of water.

Adjust the pH to a value range from 5 to 6 with a few drops of 2 mol/l potassium hydroxide solution (7.1.2). Then adjust the pH to 7,0 slowly with 0,02 mol/l potassium hydroxide solution (7.1.2). Dilute to 50 ml with water and mix evenly.

The solution is stable for six months when stored at a temperature between 0 °C and 6 °C.

1) The EC number refers to the Enzyme Classification number as given in: The International Union of Biochemistry, Enzymenomenclature, Elsevier, Amsterdam, 1965.

7.1.9 L-(+)-glutamic acid standard solution, $\rho = 100$ mg/l.

Pipette accurately 5,0 ml of L-(+)-glutamic acid standard stock solution ([7.1.8](#)) into a 50 ml volumetric flask ([7.2.8](#)), dilute to the mark with water and mix evenly.

The solution is for the current use.

7.1.10 L-(+)-glutamic acid series standard solution, $\rho = 5$ mg/l, 10 mg/l, 15 mg/l, 20 mg/l, 30 mg/l and 40 mg/l.

Pipette accurately 0,50 ml, 1,00 ml, 1,50 ml, 2,00 ml, 3,00 ml and 4,00 ml of L-(+)-glutamic acid standard solution ([7.1.9](#)) into each of six 10 ml volumetric flasks ([7.2.8](#)) separately, dilute to the mark with water and mix evenly.

The solution is for the current use.

7.2 Apparatus

The usual laboratory equipment and, in particular, the following shall be used.

7.2.1 Mechanical or electrical equipment, capable of homogenizing the laboratory sample.

This includes a high-speed rotational cutter, or a mincer fitted with a plate with apertures not exceeding 4,0 mm in diameter.

7.2.2 Laboratory mixer, a stirrer or an oscillator.

7.2.3 Laboratory centrifuge, with 50 ml or 100 ml centrifuge tubes, operating at a radial acceleration of about 2 000g or an equivalent speed (e.g. 3 500 r/min to 4 000 r/min).

7.2.4 Analytical balance, capable of weighing to the nearest 0,001 g, 0,000 1 g.

7.2.5 Constant temperature drying box.

7.2.6 pH-meter.

7.2.7 Filter papers, with a diameter of about 15 cm, high or moderate speed.

7.2.8 One-mark volumetric flasks, capacities of 10 ml, 50 ml and 100 ml, conforming to [ISO 1042](#), class B standard.

7.2.9 Single-volume pipettes, capacities of 50 ml, 25 ml and 1 ml conforming to [ISO 648](#), class B standard.

7.2.10 Single channel or multi-channel transferring pipettes and tips, of 5 ml, 1 000 μ l, 200 μ l and 100 μ l, conforming to [ISO 8655-2](#).

7.2.11 Small plastic spatula or lid, for mixing the content evenly by stirring with the spatula in the cuvette or by shaking the cuvette covered with the lid.

7.2.12 Photoelectric colorimeter, provided with a filter which has a transmittance maximum at a wavelength of 490 nm, or **spectrometer**.

7.2.13 Cuvettes, of 10 mm optical path length.

7.3 Procedure

7.3.1 General

If it is required to check whether the repeatability requirement is achieved, two separate determinations should be performed.

7.3.2 Test portion

Weigh, to the nearest 0,001 g, approximately 25 g, or other appropriate mass (m_1) of the test sample (see [Clause 6](#)).

7.3.3 Preparation of extract

7.3.3.1 Add 50 ml of dilute perchloric acid solution ([7.1.1](#)) to the test sample, homogenize the mixture with the laboratory mixer ([7.2.2](#)).

7.3.3.2 Transfer the homogenized sample to centrifuge tube ([7.2.3](#)). Centrifuge for 10 min at a temperature of 10 °C, at a radial acceleration of about 2 000g or an equivalent speed (e.g. 3 500 r/min to 4 000 r/min). Carefully skim off the fat layer and decant all the supernatant liquid through a filter paper ([7.2.7](#)) into a 100 ml conical flask. Discard the first 10 ml of the filtrate.

7.3.3.3 Pipet 25 ml of the solution (which should be only slightly turbid) with pipette ([7.2.9](#)) into centrifuge tube ([7.2.3](#)). Detecting with the pH-meter ([7.2.6](#)), adjust the pH to a value range from 7 to 8 with 4 mol/l potassium hydroxide solution ([7.1.2](#)), then adjust the pH to 10,0 slowly with 2 mol/l and 0,5 mol/l potassium hydroxide solution ([7.1.2](#)). Centrifuge for 3 min at a radial acceleration of about 2 000g or an equivalent speed (e.g. 3 500 r/min to 4 000 r/min).

NOTE If the pH is slightly above 10,0, it can be adjusted back to the required pH value ([7.1.1](#)) with dilute perchloric acid.

7.3.3.4 Transfer all the supernatant into a 50 ml volumetric flask ([7.2.8](#)). Dilute to the mark with water and mix.

7.3.3.5 Cool the solution in ice for 10 min, and filter through a filter paper ([7.2.7](#)). Discard the first 10 ml of the filtrate.

7.3.3.6 Pipet 5 ml, or some other appropriate volume (V_1) of the filtrate into a 50 ml volumetric flask ([7.2.8](#)). Dilute to the mark with water and mix. The solution obtained will be used to determine the content of free L-(+)-glutamic acid in the test portion.

The volume V_1 should be chosen so that the L-(+)-glutamic acid content of the solution is between 8 mg/l and 40 mg/l.

7.3.4 Determination

7.3.4.1 Preparation of detection instrument

Set up the spectrophotometer ([7.2.12](#)) and preheat the instrument according to the instrument specification until equilibrium conditions are achieved. Set the detection wavelength to 490 nm. Adjust the baseline of the equipment to zero with pure water.

7.3.4.2 Absorbance determination of L-(+)-glutamic acid test solution

7.3.4.2.1 Maintain the temperature of solution R123 (7.1.6), water and the L-(+)-glutamic acid test solution (7.3.3.6) between 20 °C and 25 °C.

Pipette 1,0 ml of solution R123 (7.1.6) into a cuvette (7.2.13) and add 2,0 ml of water. The solution obtained is the blank solution.

Pipette 1,0 ml of solution R123 (7.1.6), 1,8 ml of water and 200 µl of the L-(+)-glutamic acid test solution (7.3.3.6) into another cuvette. The solution obtained is the test solution.

Mix the solutions with the spatula or lid (7.2.11), put it into the spectrophotometer and read the absorbance A_1 of the test solution and A_{b1} of the blank solution at a wavelength of 490 nm against water.

7.3.4.2.2 Pipette 50 µl of the GLDH solution (7.1.7) into each of the cuvettes. Mix the contents of the cuvettes evenly (7.2.11).

Read the absorbance A_1' of the test solution and A_{b1}' of the blank solution at a wavelength of 490 against water after keeping still for 10 min to 15 min, and record the absorbance every 2 min until a constant absorbance is obtained. Take the constant absorbance value as the test result.

The exposure of the reaction solution in light should be avoided as much as possible. The temperature of the solution should be maintained between 20 °C and 25 °C.

7.3.4.3 Absorbance determination of L-(+)-glutamic acid standard solution

Repeat the operations described in 7.3.3.3.1, but replace the L-(+)-glutamic acid test solution (7.3.3.6) with the L-(+)-glutamic acid series standard solution (7.1.10). Read the absorbance A_{s1} of the L-(+)-glutamic acid standard solution and A_{b2} of the blank solution. Then, repeat the operations described in 7.3.3.3.2. Read the absorbance A_{s1}' of the L-(+)-glutamic acid standard solution and A_{b2}' of the blank solution.

NOTE If 7.3.3.3 and 7.3.4.3 are detected at the same batch, the blank solution determination of 7.3.4.3 can be omitted. Take the value of A_{b1} for A_{b2} and A_{b1}' for A_{b2}' directly.

7.3.4.4 Moisture content determination of test sample

Determine the moisture content of the test sample in accordance with ISO 1442.

7.4 Calculation and results

7.4.1 Absorbance difference of L-(+)-glutamic acid standard solution

Calculate the absorbance difference for the L-(+)-glutamic acid standard solution by using [Formula \(3\)](#):

$$\Delta A_{s1} = (A_{s1}' - A_{s1}) - (A_{b2}' - A_{b2}) \quad (3)$$

where

ΔA_{s1} is the absorbance difference for the L-(+)-glutamic acid standard solution;

A_{s1} is the absorbance of the standard solution, measured in [7.3.4.3](#);

A_{s1}' is the absorbance of the standard solution, measured in [7.3.4.3](#);

A_{b2} is the absorbance of the blank solution, measured in [7.3.4.3](#);

A_{b2}' is the absorbance of the blank solution, measured in [7.3.4.3](#).

7.4.2 Absorbance difference of L-(+)-glutamic acid test solution

Calculate the absorbance difference for the L-(+)-glutamic acid test solution by using [Formula \(4\)](#):

$$\Delta A_1 = (A_1' - A_1) - (A_{b1}' - A_{b1}) \quad (4)$$

where

- ΔA_1 is the absorbance difference for L-(+)-glutamic acid test solution;
- A_1 is the absorbance of the test solution, measured in 7.3.3.3.1;
- A_1' is the absorbance of the test solution, measured in 7.3.3.3.2;
- A_{b1} is the absorbance of the blank solution, measured in 7.3.3.3.1;
- A_{b1}' is the absorbance of the blank solution, measured in 7.3.3.3.2.

7.4.3 Formula of linear regression of L-(+)-glutamic acid standard curve

Take the concentration of the L-(+)-glutamic acid series standard solution ([7.1.10](#)) as the x-coordinate axis, and ΔA_{s1} ([7.4.1](#)) as the y-coordinate axis to draw the L-(+)-glutamic acid standard curve. The linear regression formula of the L-(+)-glutamic acid standard curve is shown by [Formula \(5\)](#):

$$y = a \times x + d \quad (5)$$

where

- y is the absorbance difference for the L-(+)-glutamic acid series standard solution;
- x is the concentration of the L-(+)-glutamic acid series standard solution, in milligram per litre;
- a is the coefficient of the equation, round the numerical value to the nearest 0,000 1;
- d is the coefficient of the formula.

7.4.4 L-(+)-glutamic acid concentration of the test solution

Calculate the L-(+)-glutamic acid concentration in the test solution ([7.3.3.6](#)) by using [Formula \(6\)](#):

$$c_1 = \frac{\Delta A_1 - d}{a} \quad (6)$$

where

- c_1 is the numerical value of the concentration of L-(+)-glutamic acid test solution ([7.3.3.6](#)), in milligram per litre;
- ΔA_1 is the absorbance difference for the L-(+)-glutamic acid test solution in [7.4.2](#);
- A is the coefficient of the equation in [7.4.3](#);
- D is the coefficient of the equation in [7.4.3](#).

7.4.5 L-(+)-glutamic acid content of test sample

Calculate the L-(+)-glutamic acid content of the test sample by using [Formula \(7\)](#):

$$W_1 = \frac{c_1}{10\,000 \times m_1} \times \frac{50 + \frac{W_m}{100} \times m_1}{\frac{V_1}{50} \times \frac{25}{50}} \quad (7)$$

where

- W_1 is the numerical value of the L-(+)-glutamic acid content of the test sample, in grams per 100 g;
- c_1 is the numerical value of the concentration of L-(+)-glutamic acid test solution (7.3.3.6), in milligram per litre;
- V_1 is the numerical value of the volume, in millilitres, of filtrate taken in 7.3.3.6;
- m_1 is the numerical value of the mass, in grams, of the test portion (7.3.2);
- W_m is the numerical value of the moisture content (7.3.4.4), in grams per 100 g;
- $\frac{V_1}{50}$ is the dilution factor of filtrate taken in 7.3.3.6;
- $\frac{25}{50}$ "25" is the numerical value of the volume, in millilitres, of the filtrate transferred in 7.3.3.3 for pH adjustment and "50" is the numerical value of the volume, in millilitres, of the solution in 7.3.3.4.

Round the result to the nearest 0,01 g/100 g.

7.5 Precision

7.5.1 Interlaboratory test

The precision of the method was established by an interlaboratory test carried out in accordance with [ISO 5725-1](#) and [ISO 5725-2](#). The results of these tests have been published (see Reference [4]). The values derived from these tests may not be applicable to concentration ranges and matrices types other than those given.

7.5.2 Repeatability

The value less than or equal to which the absolute difference between two test results obtained under repeatability conditions can be expected to be 0,55 % with a probability of 95 % of cases exceeding 0,159 2 g/100 g up to 0,305 0 g/100 g for L-(+)-glutamic acid contents.

7.5.3 Reproducibility

The value less than or equal to which the absolute difference between two test results obtained under reproducibility conditions can be expected to be 0,82 % with a probability of 95 % of cases exceeding 0,159 2 g/100 g up to 0,305 0 g/100 g for L-(+)-glutamic acid contents.

7.6 Detection limit

When W_m (the moisture content of test sample in 7.3.4.4) is 70 and $V_1/50$ (the dilution factor of filtrate taken in 7.3.3.6) is 1/15, the detection limit is 0,02 g/100 g of L-(+)-glutamic acid contents.

8 Test method of light absorption microplate reader

8.1 Reagents

The reagents are the same as those used in [7.1](#).

8.2 Apparatus

In addition to the equipment from [7.2.1](#) to [7.2.9](#), the following apparatus should be also included.

8.2.1 Single channel or multi-channel transferring pipettes and tips, of capacities 1 000 µl, 200 µl, 100 µl and 20 µl conforming to [ISO 8655-2](#).

8.2.2 Light absorption microplate reader, of wavelength 490 nm.

8.2.3 Microplate, of 96 holes (recommended), flat and transparent.

8.2.4 Brown glass vial, with caps, of volume not less than 1,5 ml.

8.3 Procedure

8.3.1 General

If it is required to check whether the repeatability requirement is achieved, two separate determinations should be carried out.

8.3.2 Extraction of L-(+)-glutamic acid in the test portion

The extraction method is the same as [7.3.2](#) and [7.3.3](#).

8.3.3 Determination

8.3.3.1 Preparation of detection instrument

Set up the light absorption microplate reader ([8.2.2](#)), preheat the instrument according to the instrument specification until equilibrium conditions achieved. Set the detection parameters: the detection wavelength of 490 nm, the microplate reading mode by row and by hole, and the reading time interval of approximately 0,5 s per hole.

8.3.3.2 Absorbance determination

8.3.3.2.1 Maintain the temperature of solution R123 ([7.1.6](#)), water, the L-(+)-glutamic acid series standard solution ([7.1.10](#)), the L-(+)-glutamic acid test solution ([8.3.2](#)) between 20 °C and 25 °C.

Pipette 300 µl of solution R123 ([7.1.6](#)) and 600 µl of water into a brown glass vial with caps ([8.2.4](#)). Mix by inverting or shaking the vial slowly. The solution obtained is the blank solution.

Pipette 300 µl of solution R123 ([7.1.6](#)), 540 µl of water and 60 µl of the L-(+)-glutamic acid test solution ([8.3.2](#)) into a brown glass vial ([8.2.4](#)). Mix by inverting or shaking the vial slowly. The solution obtained is the test solution.

Pipette 300 µl of solution R123 ([7.1.6](#)), 540 µl of water and 60 µl of the L-(+)-glutamic acid series standard solution ([7.1.10](#)) into a brown glass vial ([8.2.4](#)). Mix by inverting or shaking the vial slowly. The solution obtained is the standard solution.

8.3.3.2.2 Pipette 200 µl of the blank solution, the standard solution and the test solution ([8.3.3.2.1](#)) into different holes of the same microplate ([8.2.3](#)).

Put the microplate into the light absorption microplate reader and swing for 5 s to 10 s. Read the absorbance A_{b3} of the blank solution, A_{s2} of the L-(+)-glutamic acid series standard solution and A_2 of the L-(+)-glutamic acid test solution at a wavelength of 490 nm.

8.3.3.2.3 Pipette 10 µl of the GLDH solution (7.1.7) into each of the brown glass vials in 8.3.3.2.1. Mix by inverting or shaking the vial slowly.

Take the microplate out and pipette 200 µl of the solution from each brown glass vial into different holes. Each vial is recommended to be determined three times and the numerical average can be used as the test result.

Put the microplate into the light absorption microplate reader and swing for 5 s to 10 s. Read the absorbance A_{b3}' of the blank solution, A_{s2}' of the L-(+)-glutamic acid series standard solution and A_{2}' of the L-(+)-glutamic acid test solution at a wavelength of 490 nm after waiting for 10 min to 15 min, and keep reading the absorbance every 2 min thereafter until a constant absorbance is obtained. Take the constant absorbance value as the test result. If three determinations are performed, take the numerical average of the three constant absorbance as the result.

It should be pipetted or mixed slowly to avoid bubbles. The exposure of the reaction solution in light should be strictly avoided as much as possible. The temperature of the solution should be maintained between 20 °C and 25 °C.

8.3.3.3 Moisture content determination of test sample

The method for determining the moisture content is the same as 7.3.4.4.

8.4 Calculation and results

8.4.1 Absorbance difference for L-(+)-glutamic acid standard solution

Calculate the absorbance difference for the L-(+)-glutamic acid standard solution by using [Formula \(8\)](#):

$$\Delta A_{s2} = (A_{s2}' - A_{s2}) - (A_{b3}' - A_{b3}) \quad (8)$$

where

ΔA_{s2} is the absorbance difference for the L-(+)-glutamic acid series standard solution;

A_{b3} is the absorbance of the blank solution, measured in [8.3.3.2.2](#);

A_{b3}' is the absorbance of the blank solution, measured in [8.3.3.2.3](#);

A_{s2} is the absorbance of the standard solution, measured in [8.3.3.2.2](#);

A_{s2}' is the absorbance of the standard solution, measured in [8.3.3.2.3](#).

8.4.2 Absorbance difference for L-(+)-glutamic acid test solution

Calculate the absorbance difference of the L-(+)-glutamic acid test solution by using [Formula \(9\)](#):

$$\Delta A_2 = (A_2' - A_2) - (A_{b3}' - A_{b3}) \quad (9)$$

where

ΔA_2 is the absorbance difference for the L-(+)-glutamic acid test solution;

A_{b3} is the absorbance of the blank solution, measured in [8.3.3.2.2](#);

A_{b3}' is the absorbance of the blank solution, measured in [8.3.3.2.3](#);

A_2 is the absorbance of the L-(+)-glutamic acid test solution, measured in [8.3.3.2.2](#);

A_2' is the absorbance of the L-(+)-glutamic acid test solution, measured in [8.3.3.2.3](#).

8.4.3 Formula of linear regression for L-(+)-glutamic acid standard curve

Take the concentration of the L-(+)-glutamic acid series standard solution (7.1.10) as the x-coordinate axis, and ΔA_{s2} as the y coordinate axis to draw the L-(+)-glutamic acid standard curve. The linear regression equation of the L-(+)-glutamic acid standard curve is shown by Formula (10):

$$Y = A \times X + D \quad (10)$$

where

- Y is the absorbance difference for the L-(+)-glutamic acid series standard solution;
- X is the concentration of the L-(+)-glutamic acid series standard solution;
- A is the coefficient of the equation, round the numerical value to the nearest 0,000 1;
- D is the coefficient of the formula.

8.4.4 L-(+)-glutamic acid concentration of the test solution

Calculate the L-(+)-glutamic acid concentration in the test solution (8.3.2) by using Formula (11):

$$c_2 = \frac{\Delta A_2 - D}{A} \quad (11)$$

where

- c_2 is the numerical value of the concentration of L-(+)-glutamic acid test solution (8.3.2), in milligrams per litre;
- ΔA_2 is the absorbance difference for the L-(+)-glutamic acid test solution in 8.4.2;
- A is the coefficient of the equation in 8.4.3;
- D is the coefficient of the equation in 8.4.3.

8.4.5 L-(+)-glutamic acid content of test sample

Calculate the L-(+)-glutamic acid content of the test sample by using Formula (12):

$$W_2 = \frac{c_2}{10\,000 \times m_1} \times \frac{50 + \frac{W_m}{100} \times m_1}{\frac{V_1}{50} \times \frac{25}{50}} \quad (12)$$

where

- W_2 is the numerical value of the L-(+)-glutamic acid content of the test sample, in grams per 100 g;
- c_2 is the numerical value of the concentration of L-(+)-glutamic acid test solution (8.4.4), in milligram per litre;
- V_1 is the numerical value of the volume, in millilitres, of filtrate taken in 7.3.3.6;
- m_1 is the numerical value of the mass, in grams, of the test portion (7.3.2);
- W_m is the numerical value of the moisture content (8.3.3.3), in grams per 100 g;
- $\frac{V_1}{50}$ is the dilution factor of filtrate taken in 7.3.3.6;
- $\frac{25}{50}$ "25" is the numerical value of the volume, in millilitres, of the filtrate transferred in 7.3.3.3 for pH adjustment and "50" is the numerical value of the volume, in millilitres, of the solution in 7.3.3.4.

Round the result to the nearest 0,01 g/100 g.

8.5 Precision

8.5.1 Interlaboratory test

The precision of the method was established by interlaboratory tests carried out in accordance with [ISO 5725-1](#) and [ISO 5725-2](#). The results of these tests have been published (see Reference [4]). The values derived from these tests may not be applicable to concentration ranges and matrices other than those given.

8.5.2 Repeatability

The value less than or equal to which the absolute difference between two test results obtained under repeatability conditions can be expected to be 0,43 % with a probability of 95 % of cases exceeding 0,157 7 g/100 g up to 0,298 7 g/100 g for L-(+)-glutamic acid contents.

8.5.3 Reproducibility

The value less than or equal to which the absolute difference between two test results obtained under reproducibility conditions can be expected to be 1,10 % with a probability of 95 % of cases exceeding 0,157 7 g/100 g up to 0,298 7 g/100 g for L-(+)-glutamic acid contents.

8.6 Detection limit

When W_m (the moisture content of test sample in [8.3.3.3](#)) is 70 and $V_1/50$ (the dilution factor of filtrate taken in [7.3.3.6](#)) is 1/15, the detection limit is 0,02 g/100 g of L-(+)-glutamic acid contents.

9 Test report

The test report shall specify:

- the sample;
- the International Standard used (including its year of publication);
- all information necessary for the complete identification of the sample;
- the sampling method used, if known;
- the test method used, with reference to this document;
- all operating details not specified in this document, or regarded as optional, together with details of any incidents which can have influenced the test result(s);
- the test result obtained, or the two test results obtained if the repeatability has been checked;
- any deviations from the procedure;
- any unusual features observed;
- the date of the test.

Annex A (informative)

Safety practices

Safety practices in handling perchloric acid (HClO_4) shall include following.

- a) Remove spilled HClO_4 by immediate and thorough washing with large amounts of water.
- b) Hoods, ducts and other devices for removing HClO_4 vapour shall be made of chemically inert materials and so designed that they can be thoroughly washed with water. Exhaust systems should discharge to a safe location and fans shall be accessible for cleaning.
- c) Avoid the use of organic chemicals in hoods or other fume-removal devices used for HClO_4 digestions.
- d) Use goggles, barrier shields and other devices as necessary for personal protection. Use polyvinyl chloride, not rubber, gloves.
- e) In wet combustion with HClO_4 , treat the sample first with nitric acid to destroy easily oxidizable organics unless otherwise specified. Do not evaporate to dryness.
- f) Contact of HClO_4 with strong dehydrating agents such as phosphorus pentoxide or concentrated sulfuric acid can result in the formation of anhydrous HClO_4 , which reacts explosively with organic matter and with reducing agents. Exercise special care in performing analyses requiring use of HClO_4 with such agents. It is extremely sensitive to shock and heat when the concentration is 72 g/100 g.

NOTE Taken from Reference [5].

Bibliography

- [1] [ISO 5725-1](#), *Accuracy (trueness and precision) of measurement methods and results — Part 1: General principles and definitions*
- [2] [ISO 5725-2](#), *Accuracy (trueness and precision) of measurement methods and results — Part 2: Basic method for the determination of repeatability and reproducibility of a standard measurement method*
- [3] CAC/GL 50-2004, *General guidelines on sampling*
- [4] ISO/TC 34/SC 6/WG 25 report, *Accuracy (trueness and precision) of the ISO/AWI 4134 testing methods*
- [5] AOAC Official Methods of Analysis. *Laboratory Safety, Appendix B*. 1995, p. 3

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email cservices@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email: cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK