

BS ISO 4347:2015



BSI Standards Publication

Leaf chains, clevises and sheaves — Dimensions, measuring forces, tensile strengths and dynamic strengths

bsi.

...making excellence a habit.™

INTERNATIONAL STANDARD

ISO
4347

Fifth edition
2015-09-01

Leaf chains, clevises and sheaves — Dimensions, measuring forces, tensile strengths and dynamic strengths

*Chaînes de levage à mailles jointives, chapes et galets de renvoi —
Dimensions, forces de mesurage, forces de résistances à la traction et
forces de résistances dynamique*



Reference number
ISO 4347:2015(E)

© ISO 2015



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Chains	1
3.1 Nomenclature.....	1
3.2 Chain designation.....	3
3.3 Dimensions.....	4
3.4 Performance Requirements.....	10
3.4.1 General.....	10
3.4.2 Minimum tensile strength.....	10
3.4.3 Application of tensile force.....	10
3.4.4 Dynamic testing.....	10
3.5 Pre-loading.....	10
3.6 Length validation.....	10
3.7 Cranked links.....	11
3.8 Marking.....	11
4 Clevises	11
4.1 Types.....	11
4.2 Dimensions.....	12
4.3 Minimum tensile strength.....	15
4.4 Length adjustment.....	15
5 Sheaves	15
Annex A (informative) Method of calculating chain minimum dynamic strength	17
Annex B (informative) Method of determining maximum test force F_{\max} when conducting dynamic strength conformance test	19
Bibliography	20

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword — Supplementary information](#).

The committee responsible for this document is ISO/TC 100, *Chains and chain sprockets for power transmission and conveyors*.

This fifth edition cancels and replaces the fourth edition (ISO 4347:2004), which has been technically revised. This edition specifies the minimum dynamic strength of the chains.

Introduction

This International Standard includes two series of chains: one derived from the ISO 606 A/ASME B29.8 series, designated by the symbol “LH” or “BL”; the other derived from the ISO 606 B series, designated by the symbol “LL”.

In [Table 1](#) and [Table 2](#), requirements for minimum dynamic strengths are specified. See informative [Annex A](#) for calculation details.

Leaf chains, clevises and sheaves — Dimensions, measuring forces, tensile strengths and dynamic strengths

1 Scope

This International Standard specifies the characteristics of chains used for general lifting purposes, together with the rim profiles of sheaves and the chain attachment ends of clevises. It gives dimensions, limits for interchangeability, length measurement, preloading, minimum tensile strengths and minimum dynamic strengths.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 606, *Short-pitch transmission precision roller and bush chains, attachments and associated chain sprockets*

ISO 15654¹⁾, *Fatigue test methods for transmission precision roller chains and leaf chains*

ASME²⁾ B29.8, *Leaf chains, clevises and sheaves*


3 Chains


3.1 Nomenclature

The nomenclature of chains is shown in [Figure 1](#) (which does not necessarily define the actual form of the chain plates) and as given in [Table 1](#) and [Table 2](#).

1) To be published (Revision of ISO 15654:2004).

2) American Society of Mechanical Engineers.





Key

- 1 inner link
- 2 outer link
- 3 pin
- 4 outer plate
- 5 inner plate

Figure 1 — Symbols related to [Tables 1](#) and [2](#)

3.2 Chain designation

Leaf chain shall be designated by the prefix “LH” [“BL”] for chains derived from the ISO 606 A [ASME B29.8] series, or by the prefix “LL” for chains derived from ISO 606 B series, followed by a number of which the first two digits indicate the pitch expressed in sixteenths of an inch and the last two digits indicate the lacing (number of plates in the outer plate pitch and inner plate pitch).

To obtain the ASME “BL” reference, the same principle is used, except that the pitch is expressed in eighths of an inch using only one or two digits, dependent on pitch.

EXAMPLE 1 A chain with nominal pitch of 12,7 mm derived from chain ISO 08B, consisting of outer plates and inner plates each comprising two plates would be designated by

LL 0822

EXAMPLE 2 A chain with nominal pitch of 19,05 mm derived from ISO 12A [ASME chain No. 60], consisting of outer plates comprising three plates and inner plates comprising four plates would be designated by

LH 1234 [BL 634]

3.3 Dimensions

The dimensions given in [Table 1](#) and [Table 2](#) provide minimum and maximum limits, ensuring interchangeability and connection to standard design clevises.

Manufacturers are responsible for the actual dimensional features of their products.

Chains from different manufacturers shall never be placed together within the same application.

Table 1 — Principal chain dimensions, measuring forces, tensile strengths and dynamic strengths, LH series

ISO chain number	ASME chain number	Pitch		Lacing	Thickness of plates	Hole diameter of inner plates	Pin diameter	Chain path depth	Plate depth	Width over riveted pin	Width between outer plates	Measuring force	Minimum tensile strength	Minimum dynamic strength ^c
		p	p											
		nom.	mm	mm										
				b_0 max.	d_1 min.	d_2 max.	h_1^a min.	h_3 max.	b_1 to b_6 max.	l_1 to l_6 min.	N	F_u kN	F_d kN	
LH 0822 b	BL 422	12,7	2 × 2	2,08	5,11	5,09	12,32	12,07	11,1	4,2	222	22,2	3,10	
LH 0823	BL 423	12,7	2 × 3	2,08	5,11	5,09	12,32	12,07	13,2	6,3	222	22,2	3,74	
LH 0834	BL 434	12,7	3 × 4	2,08	5,11	5,09	12,32	12,07	17,4	10,4	334	33,4	4,13	
LH 0844 d	BL 444	12,7	4 × 4	2,08	5,11	5,09	12,32	12,07	19,6	12,4	445	44,5	4,66	
LH 0846	BL 446	12,7	4 × 6	2,08	5,11	5,09	12,32	12,07	23,8	16,6	445	44,5	4,65	
LH 0866	BL 466	12,7	6 × 6	2,08	5,11	5,09	12,32	12,07	28,0	21,0	667	66,7	6,21	
LH 1022 b	BL 522	15,875	2 × 2	2,48	5,98	5,96	15,34	15,09	12,9	4,9	334	33,4	4,80	
LH 1023	BL 523	15,875	2 × 3	2,48	5,98	5,96	15,34	15,09	15,4	7,4	334	33,4	5,77	
LH 1034	BL 534	15,875	3 × 4	2,48	5,98	5,96	15,34	15,09	20,4	12,3	489	48,9	6,39	
LH 1044 d	BL 544	15,875	4 × 4	2,48	5,98	5,96	15,34	15,09	22,8	14,7	667	66,7	7,20	
LH 1046	BL 546	15,875	4 × 6	2,48	5,98	5,96	15,34	15,09	27,7	19,5	667	66,7	7,19	
LH 1066	BL 566	15,875	6 × 6	2,48	5,98	5,96	15,34	15,09	32,7	24,6	1 000	100,1	9,60	
LH 1222 b	BL 622	19,05	2 × 2	3,3	7,96	7,94	18,34	18,11	17,4	6,6	489	48,9	7,05	
LH 1223	BL 623	19,05	2 × 3	3,3	7,96	7,94	18,34	18,11	20,8	9,9	489	48,9	8,47	
LH 1234	BL 634	19,05	3 × 4	3,3	7,96	7,94	18,34	18,11	27,5	16,5	756	75,6	9,38	
LH 1244 d	BL 644	19,05	4 × 4	3,3	7,96	7,94	18,34	18,11	30,8	19,8	979	97,9	10,6	
LH 1246	BL 646	19,05	4 × 6	3,3	7,96	7,94	18,34	18,11	37,5	26,4	979	97,9	10,6	
LH 1266	BL 666	19,05	6 × 6	3,3	7,96	7,94	18,34	18,11	44,2	33,2	1 468	146,8	14,1	
LH 1622 b	BL 822	25,4	2 × 2	4,09	9,56	9,54	24,38	24,13	21,4	8,2	845	84,5	12,3	
LH 1623	BL 823	25,4	2 × 3	4,09	9,56	9,54	24,38	24,13	25,5	12,3	845	84,5	14,8	
LH 1634	BL 834	25,4	3 × 4	4,09	9,56	9,54	24,38	24,13	33,8	20,5	1 290	129,0	16,3	
LH 1644 d	BL 844	25,4	4 × 4	4,09	9,56	9,54	24,38	24,13	37,9	24,6	1 690	169,0	18,4	
LH 1646	BL 846	25,4	4 × 6	4,09	9,56	9,54	24,38	24,13	46,2	32,7	1 690	169,0	18,4	
LH 1666	BL 866	25,4	6 × 6	4,09	9,56	9,54	24,38	24,13	54,5	41,1	2 536	253,6	24,6	

Table 1 (continued)

ISO chain number	ASME chain number	Pitch		Lacing	Thickness of plates	Hole diameter of inner plates	Pin diameter	Chain path depth	Plate depth	Width over riveted pin	Width between outer plates	Measuring force	Minimum tensile strength	Minimum dynamic strength ^c
		p nom.	mm											
LH 2022 b	BL 1022	31,75		2 × 2	4,9	11,14	11,11	30,48	30,18	25,4	9,8	1 156	115,6	18,8
LH 2023	BL 1023	31,75		2 × 3	4,9	11,14	11,11	30,48	30,18	30,4	14,8	1 156	115,6	22,6
LH 2034	BL 1034	31,75		3 × 4	4,9	11,14	11,11	30,48	30,18	40,3	24,5	1 824	182,4	25,0
LH 2044 d	BL 1044	31,75		4 × 4	4,9	11,14	11,11	30,48	30,18	45,2	29,5	2 313	231,3	28,2
LH 2046	BL 1046	31,75		4 × 6	4,9	11,14	11,11	30,48	30,18	55,1	39,4	2 313	231,3	28,2
LH 2066	BL 1066	31,75		6 × 6	4,9	11,14	11,11	30,48	30,18	65,0	49,2	3 470	347,0	37,6
LH 2422 b	BL 1222	38,1		2 × 2	5,77	12,74	12,71	36,55	36,2	29,7	11,6	1 512	151,2	26,7
LH 2423	BL 1223	38,1		2 × 3	5,77	12,74	12,71	36,55	36,2	35,5	17,4	1 512	151,2	32,0
LH 2434	BL 1234	38,1		3 × 4	5,77	12,74	12,71	36,55	36,2	47,1	28,9	2 446	244,6	35,4
LH 2444 d	BL 1244	38,1		4 × 4	5,77	12,74	12,71	36,55	36,2	52,9	34,4	3 025	302,5	40,0
LH 2446	BL 1246	38,1		4 × 6	5,77	12,74	12,71	36,55	36,2	64,6	46,3	3 025	302,5	39,9
LH 2466	BL 1266	38,1		6 × 6	5,77	12,74	12,71	36,55	36,2	76,2	57,9	4 537	453,7	53,3
LH 2822 b	BL 1422	44,45		2 × 2	6,6	14,32	14,29	42,67	42,24	33,6	13,2	1 913	191,3	35,4
LH 2823	BL 1423	44,45		2 × 3	6,6	14,32	14,29	42,67	42,24	40,2	19,7	1 913	191,3	42,6
LH 2834	BL 1434	44,45		3 × 4	6,6	14,32	14,29	42,67	42,24	53,4	32,7	3 158	315,8	47,1
LH 2844 d	BL 1444	44,45		4 × 4	6,6	14,32	14,29	42,67	42,24	60,0	39,1	3 826	382,6	53,2
LH 2846	BL 1446	44,45		4 × 6	6,6	14,32	14,29	42,67	42,24	73,2	52,3	3 826	382,6	53,0
LH 2866	BL 1466	44,45		6 × 6	6,6	14,32	14,29	42,67	42,24	86,4	65,5	5 783	578,3	70,9
LH 3222 b	BL 1622	50,8		2 × 2	7,52	17,49	17,46	48,74	48,26	40,0	15,0	2 891	289,1	43,4
LH 3223	BL 1623	50,8		2 × 3	7,52	17,49	17,46	48,74	48,26	46,6	22,5	2 891	289,1	52,1
LH 3234	BL 1634	50,8		3 × 4	7,52	17,49	17,46	48,74	48,26	61,8	37,5	4 404	440,4	57,7
LH 3244 d	BL 1644	50,8		4 × 4	7,52	17,49	17,46	48,74	48,26	69,3	44,8	5 783	578,3	65,1
LH 3246	BL 1646	50,8		4 × 6	7,52	17,49	17,46	48,74	48,26	84,5	59,9	5 783	578,3	65,0
LH 3266	BL 1666	50,8		6 × 6	7,52	17,49	17,46	48,74	48,26	100,0	75,0	8 674	867,4	86,8
LH 4022 b	BL 2022	63,5		2 × 2	9,91	23,84	23,81	60,88	60,33	51,8	19,9	4 337	433,7	64,4

Table 1 (continued)

ISO chain number	ASME chain number	Pitch		Lacing	Thickness of plates	Hole diameter of inner plates	Pin diameter	Chain path depth	Plate depth	Width over riveted pin	Width between outer plates	Measuring force	Minimum tensile strength	Minimum dynamic strength ^c
		p nom.	mm											
LH 4023	BL 2023	63,5		2 × 3	9,91	23,84	23,81	60,88	60,33	61,7	29,8	4 337	433,7	77,4
LH 4034	BL 2034	63,5		3 × 4	9,91	23,84	23,81	60,88	60,33	81,7	49,4	6 494	649,4	85,7
LH 4044 ^d	BL 2044	63,5		4 × 4	9,91	23,84	23,81	60,88	60,33	91,6	59,1	8 674	867,4	96,6
LH 4046	BL 2046	63,5		4 × 6	9,91	23,84	23,81	60,88	60,33	111,5	78,9	8 674	867,4	96,4
LH 4066	BL 2066	63,5		6 × 6	9,91	23,84	23,81	60,88	60,33	131,4	99,0	13 011	1 301,1	128,9

^a Chain path depth is the minimum depth of channel through which the assembled chain will pass.

^b These chains have reduced fatigue strength and wear life compared with uneven lacings of the same pitch and same minimum tensile strength. This should be taken into account when selecting a chain for a particular application.

^c Dynamic strength values are based on test specimen each of 5 free pitches for $P \leq 50,8$ mm and each of three free pitches for $P > 50,8$ mm. See Annex A for method of calculation.

^d These chains have reduced wear life compared with uneven lacings of the same pitch and same minimum tensile strength. This should be taken into account when selecting a chain for a particular application.

Table 2 — Principal chain dimensions, measuring forces, tensile strengths and dynamic strengths, LL series

ISO chain number	Pitch		Lacing	Thickness of plates b_0 max.	Hole diameter of inner plates d_1 min.	Pin diameter d_2 max.	Chain path depth h_1^a min.	Plate depth h_3 max.	Width over riveted pin b_1 to b_3 max.	Width between outer plates l_1 to l_3 min.	Measuring force	Minimum tensile strength F_u	Minimum dynamic strength F_d
	p nom.	mm											
LL 0822	12,7		2 × 2	1,55	4,46	4,45	11,18	10,92	8,5	3,1	180	18	2,14
LL 0844	12,7		4 × 4	1,55	4,46	4,45	11,18	10,92	14,6	9,1	360	36	3,21
LL 0866	12,7		6 × 6	1,55	4,46	4,45	11,18	10,92	20,7	15,2	540	54	4,28
LL 1022	15,875		2 × 2	1,65	5,09	5,08	13,98	13,72	9,3	3,4	220	22	3,01
LL 1044	15,875		4 × 4	1,65	5,09	5,08	13,98	13,72	16,1	10,1	440	44	4,52
LL 1066	15,875		6 × 6	1,65	5,09	5,08	13,98	13,72	22,9	16,8	660	66	6,03
LL 1222	19,05		2 × 2	1,9	5,73	5,72	16,39	16,13	10,7	3,9	290	29	4,13
LL 1244	19,05		4 × 4	1,9	5,73	5,72	16,39	16,13	18,5	11,6	580	58	6,20
LL 1266	19,05		6 × 6	1,9	5,73	5,72	16,39	16,13	26,3	19,0	870	87	8,27
LL 1622	25,4		2 × 2	3,2	8,3	8,28	21,34	21,08	17,2	6,2	600	60	8,36
LL 1644	25,4		4 × 4	3,2	8,3	8,28	21,34	21,08	30,2	19,4	1 200	120	12,5
LL 1666	25,4		6 × 6	3,2	8,3	8,28	21,34	21,08	43,2	31,0	1 800	180	16,7
LL 2022	31,75		2 × 2	3,7	10,21	10,19	26,68	26,42	20,1	7,2	950	95	12,0
LL 2044	31,75		4 × 4	3,7	10,21	10,19	26,68	26,42	35,1	22,4	1 900	190	17,9
LL 2066	31,75		6 × 6	3,7	10,21	10,19	26,68	26,42	50,1	36,0	2 850	285	23,9
LL 2422	38,1		2 × 2	5,2	14,65	14,63	33,73	33,4	28,4	10,2	1 700	170	18,9
LL 2444	38,1		4 × 4	5,2	14,65	14,63	33,73	33,4	49,4	30,6	3 400	340	28,4
LL 2466	38,1		6 × 6	5,2	14,65	14,63	33,73	33,4	70,4	51,0	5 100	510	37,9
LL 2822	44,45		2 × 2	6,45	15,92	15,9	37,46	37,08	34,0	12,8	2 000	200	25,8
LL 2844	44,45		4 × 4	6,45	15,92	15,9	37,46	37,08	60,0	38,4	4 000	400	38,7
LL 2866	44,45		6 × 6	6,45	15,92	15,9	37,46	37,08	86,0	64,0	6 000	600	51,6
LL 3222	50,8		2 × 2	6,45	17,83	17,81	42,72	42,29	35,0	12,8	2 600	260	29,0
LL 3244	50,8		4 × 4	6,45	17,83	17,81	42,72	42,29	61,0	38,4	5 200	520	43,5
LL 3266	50,8		6 × 6	6,45	17,83	17,81	42,72	42,29	87,0	64,0	7 800	780	58,0

Table 2 (continued)

ISO chain number	Pitch		Lacing	Thickness of plates	Hole diameter of inner plates	Pin diameter	Chain path depth	Plate depth	Width over riveted pin	Width between outer plates	Measuring force	Minimum tensile strength	Minimum dynamic strength ^c
	p	p											
	nom.	mm											
LL 4022	63,5		2 × 2	8,25	22,91	22,89	53,49	52,96	44,7	16,2	3 600	360	43,1
LL 4044	63,5		4 × 4	8,25	22,91	22,89	53,49	52,96	77,9	48,6	7 200	720	64,6
LL 4066	63,5		6 × 6	8,25	22,91	22,89	53,49	52,96	111,1	81,0	10 800	1 080	86,1
LL 4822	76,2		2 × 2	10,3	29,26	29,24	64,52	63,88	56,1	20,2	5 600	560	58,3
LL 4844	76,2		4 × 4	10,3	29,26	29,24	64,52	63,88	97,4	60,6	11 200	1 120	87,4
LL 4866	76,2		6 × 6	10,3	29,26	29,24	64,52	63,88	138,9	101,0	16 800	1 680	116,6

^a Chain path depth is the minimum depth of channel through which the assembled chain will pass.

^c Dynamic strength values are based on test specimen each of 5 free pitches for $P \leq 50,8$ mm and each of 3 free pitches for $P > 50,8$ mm. See Annex A for method of calculation.

3.4 Performance Requirements

3.4.1 General

WARNING — The test requirements are not to be taken as working loads.

Certain standards, covering one particular type of machine, could contain specific static and dynamic stress limits. Those stress limits were established by the developers of the subject standards based upon long experience in the design and use of the particular type of machinery. The developers of the subject standards are solely responsible for the stress limitation factor.

The test results shall be invalid if the chain has previously been in service or stressed in any way (other than by preloading in accordance with [3.5](#)).

The tensile test shall be considered as a destructive test. Even though a chain may not visibly fail when subjected to a force equivalent to the minimum tensile strength, it will have been stressed beyond the yield point and will be unfit for service.

3.4.2 Minimum tensile strength

The minimum tensile strength shall be that value exceeded when a tensile force is applied to a sample tested to destruction in accordance with [3.4.3](#).

NOTE The minimum tensile strength is not a working force. It is intended primarily as a comparative figure between chains of different construction. For application information, it is necessary to consult the manufacturers or their published data.

3.4.3 Application of tensile force

Slowly apply a tensile force of not less than the minimum tensile strength F_u specified in [Table 1](#) and [Table 2](#) for that particular chain number to the ends of a chain length containing at least five free pitches by means of fixtures permitting free movement on both sides of the chain centreline, in the normal plane of articulation.

Failure shall be considered to have occurred at the first point where increasing extension is no longer accompanied by increasing force, i.e. the summit of the force/extension diagram.

Tests in which failures occur adjacent to the fixtures shall be disregarded.

3.4.4 Dynamic testing

Chains in conformance with this International Standard shall survive a conformance test, following the specifications of ISO 15654, using the dynamic strength values given in [Table 1](#) and [Table 2](#) for the particular chain. These requirements do not apply to connecting links, as their dynamic strength could be reduced. The methods used for calculating the minimum dynamic strength are given in [Annex A](#). The method for determining the maximum test force for the conformance test is given in [Annex B](#).

3.5 Pre-loading

Chain manufactured in accordance with this International Standard shall be preloaded by applying a tensile force equivalent to at least 30 % of the minimum tensile strength given in [Table 1](#) and [Table 2](#).

3.6 Length validation

Finished chains shall be measured after preloading, but before lubricating.

The standard length for measurement shall be a minimum of

- a) 610 mm for ISO chains up to 19,05 mm pitch, or

- b) 1 220 mm for ISO chains above 19,05 mm pitch.

The chain shall be supported throughout its entire length and a measuring force specified in [Table 1](#) and [Table 2](#) for the particular chain number shall be applied.

The measured length shall be nominal pitch times the number of pitches specified by the manufacturer, subject to a tolerance of $\pm 0,25\%$. The number of pitches shall conform to the minimum specified in a) or b) of this subclause.

“LL” series chains can be constructed from plates that are also used for short-pitch transmission roller chains, the actual pitch of the chain not necessarily being equal to its nominal pitch but depending upon the manufacturer.

3.7 Cranked links

Cranked links shall not be used in leaf chains.


3.8 Marking

The chains shall be marked with the manufacturer’s name or trademark. The chain numbers quoted in [Table 1](#) or [Table 2](#), less the digits indicating lacing, should be marked on the chain.

4 Clevises

4.1 Types

There are two basic types of leaf chain clevis: the outside and the inside clevis (see [Figure 2](#)).



Key

- 1 connecting pin
- 2 connecting link^a
- a The connecting link should be used with a press fit outer plate.

Figure 2 — Clevis types

4.2 Dimensions

The dimensions of terminal clevises for use with LH and LL series leaf chains shall be in accordance with [Table 3](#) and [Table 4](#) and [Figure 3](#).

NOTE Limiting dimensions given in those tables are for the purpose of ensuring connection to chains built in accordance with previous editions of this International Standard.




Figure 3 — Symbols related to [Table 3](#) and [Table 4](#)

Table 3 — Clevis dimensions, LH series

ISO chain number	ASME chain number	<i>b</i> ₇	<i>b</i> ₈	<i>b</i> ₉	<i>b</i> ₁₀	<i>b</i> ₁₁	<i>b</i> ₁₂	<i>b</i> ₁₃	<i>b</i> ₁₄	<i>p</i> ₁	<i>d</i> ₁	<i>h</i> ₄	<i>k</i>
		H12 ^a					max.	min.	max.	max.	nom.	min.	min.
mm													
LH 0822	BL 422	—	4,41	—	—	4,03	3,12	—	—	—	5,11	6,35	6,35
LH 0823	BL 423	—	6,53	—	—	6,05	3,12	—	—	—	5,11	6,35	6,35
LH 0834	BL 434	2,21	4,33	10,68	—	4,03	3,12	10,20	—	6,35	5,11	6,35	6,35
LH 0844	BL 444	4,41	4,41	12,89	—	4,03	3,12	12,25	—	8,47	5,11	6,35	6,35
LH 0846	BL 446	4,41	6,53	17,12	—	6,05	3,12	16,32	—	10,59	5,11	6,35	6,35
LH 0866	BL 466	4,41	4,41	12,89	21,36	4,03	3,12	12,25	20,47	8,47	5,11	6,35	6,35
LH 1022	BL 522	—	5,24	—	—	4,80	3,72	—	—	—	5,98	7,92	7,92
LH 1023	BL 523	—	7,76	—	—	7,20	3,72	—	—	—	5,98	7,92	7,92
LH 1034	BL 534	2,62	5,14	12,69	—	4,80	3,72	12,12	—	7,55	5,98	7,92	7,92
LH 1044	BL 544	5,24	5,24	15,31	—	4,80	3,72	14,56	—	10,07	5,98	7,92	7,92
LH 1046	BL 546	5,24	7,76	20,35	—	7,20	3,72	19,40	—	12,59	5,98	7,92	7,92
LH 1066	BL 566	5,24	5,24	15,31	25,38	4,80	3,72	14,56	24,31	10,07	5,98	7,92	7,92
LH 1222	BL 622	—	6,96	—	—	6,41	4,95	—	—	—	7,96	9,53	9,53
LH 1223	BL 623	—	10,31	—	—	9,61	4,95	—	—	—	7,96	9,53	9,53
LH 1234	BL 634	3,48	6,83	16,88	—	6,41	4,95	16,18	—	10,05	7,96	9,53	9,53
LH 1244	BL 644	6,96	6,96	20,36	—	6,41	4,95	19,43	—	13,40	7,96	9,53	9,53
LH 1246	BL 646	6,96	10,31	27,06	—	9,61	4,95	25,89	—	16,75	7,96	9,53	9,53
LH 1266	BL 666	6,96	6,96	20,36	33,76	6,41	4,95	19,43	32,45	13,40	7,96	9,53	9,53
LH 1622	BL 822	—	8,59	—	—	7,93	6,13	—	—	—	9,56	12,70	12,70
LH 1623	BL 823	—	12,73	—	—	11,89	6,13	—	—	—	9,56	12,70	12,70
LH 1634	BL 834	4,29	8,43	20,86	—	7,93	6,13	19,97	—	12,42	9,56	12,70	12,70
LH 1644	BL 844	8,59	8,59	25,15	—	7,93	6,13	23,98	—	16,56	9,56	12,70	12,70
LH 1646	BL 846	8,59	12,73	33,43	—	11,89	6,13	31,96	—	20,70	9,56	12,70	12,70
LH 1666	BL 866	8,59	8,59	25,15	41,71	7,93	6,13	23,98	40,04	16,56	9,56	12,70	12,70
LH 2022	BL 1022	—	10,26	—	—	9,48	7,35	—	—	—	11,14	15,88	15,88
LH 2023	BL 1023	—	15,21	—	—	14,22	7,35	—	—	—	11,14	15,88	15,88
LH 2034	BL 1034	5,13	10,08	24,93	—	9,48	7,35	23,86	—	14,85	11,14	15,88	15,88
LH 2044	BL 1044	10,26	10,26	30,06	—	9,48	7,35	28,65	—	19,80	11,14	15,88	15,88
LH 2046	BL 1046	10,26	15,21	39,96	—	14,22	7,35	38,18	—	24,75	11,14	15,88	15,88
LH 2066	BL 1066	10,26	10,26	30,06	49,86	9,48	7,35	28,65	47,82	19,80	11,14	15,88	15,88
LH 2422	BL 1222	—	12,05	—	—	11,16	8,66	—	—	—	12,74	19,05	19,05
LH 2423	BL 1223	—	17,87	—	—	16,74	8,66	—	—	—	12,74	19,05	19,05
LH 2434	BL 1234	6,02	11,84	29,31	—	11,16	8,66	28,05	—	17,46	12,74	19,05	19,05
LH 2444	BL 1244	12,05	12,05	35,33	—	11,16	8,66	33,68	—	23,28	12,74	19,05	19,05
LH 2446	BL 1246	12,05	17,87	46,97	—	16,74	8,66	44,89	—	29,10	12,74	19,05	19,05
LH 2466	BL 1266	12,05	12,05	35,33	58,61	11,16	8,66	33,68	56,20	23,28	12,74	19,05	19,05
LH 2822	BL 1422	—	13,76	—	—	12,76	9,90	—	—	—	14,31	22,23	22,23
LH 2823	BL 1423	—	20,41	—	—	19,13	9,90	—	—	—	14,31	22,23	22,23
LH 2834	BL 1434	6,88	13,53	33,48	—	12,76	9,90	32,04	—	19,95	14,31	22,23	22,23
LH 2844	BL 1444	13,76	13,76	40,36	—	12,76	9,90	38,47	—	26,60	14,31	22,23	22,23

^a Tolerance H12 is in accordance with ISO 286-2:2010, Clause 6.

Table 3 (continued)

ISO chain number	ASME chain number	b_7	b_8	b_9	b_{10}	b_{11}	b_{12}	b_{13}	b_{14}	p_1	d_1	h_4	k
		H12 ^a				max.	min.	max.	max.	nom.	min.	min.	max.
mm													
LH 2846	BL 1446	13,76	20,41	53,66	—	19,13	9,90	51,28	—	33,25	14,31	22,23	22,23
LH 2866	BL 1466	13,76	13,76	40,36	66,97	12,76	9,90	38,47	64,18	26,60	14,31	22,23	22,23
LH 3222	BL 1622	—	15,65	—	—	14,53	11,28	—	—	—	17,49	25,40	25,40
LH 3223	BL 1623	—	23,22	—	—	21,80	11,28	—	—	—	17,49	25,40	25,40
LH 3234	BL 1634	7,82	15,40	38,11	—	14,53	11,28	36,48	—	22,71	17,49	25,40	25,40
LH 3244	BL 1644	15,65	15,65	45,93	—	14,53	11,28	43,80	—	30,28	17,49	25,40	25,40
LH 3246	BL 1646	15,65	23,22	61,07	—	21,80	11,28	58,38	—	37,85	17,49	25,40	25,40
LH 3266	BL 1666	15,65	15,65	45,93	76,22	14,53	11,28	43,80	73,07	30,28	17,49	25,40	25,40
LH 4022	BL 2022	—	20,53	—	—	19,19	14,86	—	—	—	23,84	31,75	31,75
LH 4023	BL 2023	—	30,49	—	—	28,78	14,86	—	—	—	23,84	31,75	31,75
LH 4034	BL 2034	10,27	20,23	50,11	—	19,19	14,86	48,11	—	29,88	23,84	31,75	31,75
LH 4044	BL 2044	20,53	20,53	60,37	—	19,19	14,86	57,76	—	39,84	23,84	31,75	31,75
LH 4046	BL 2046	20,53	30,49	80,30	—	28,78	14,86	76,99	—	49,80	23,84	31,75	31,75
LH 4066	BL 2066	20,53	20,53	60,37	100,22	19,19	14,86	57,76	96,33	39,84	23,84	31,75	31,75

^a Tolerance H12 is in accordance with ISO 286-2:2010, Clause 6.

Table 4 — Clevis dimensions, LL series

ISO chain number	b_7	b_8	b_9	b_{10}	b_{11}	b_{12}	b_{13}	b_{14}	p_1	d_1	h_4	k
	H12 ^a				max.	min.	max.	max.	nom.	min.	min.	max.
mm												
LL 0822	—	3,35	—	—	2,97	2,33	—	—	—	4,46	6	6,35
LL 0844	3,35	3,35	9,71	—	2,97	2,33	9,07	—	6,35	4,46	6	6,35
LL 0866	3,35	3,35	9,71	16,06	2,97	2,33	9,07	15,17	6,35	4,46	6	6,35
LL 1022	—	3,58	—	—	3,14	2,48	—	—	—	5,09	8	7,92
LL 1044	3,58	3,58	10,33	—	3,14	2,48	9,58	—	6,75	5,09	8	7,92
LL 1066	3,58	3,58	10,33	17,08	3,14	2,48	9,58	16,01	6,75	5,09	8	7,92
LL 1222	—	4,16	—	—	3,61	2,85	—	—	—	5,73	9	9,52
LL 1244	4,16	4,16	11,96	—	3,61	2,85	11,03	—	7,80	5,73	9	9,52
LL 1266	4,16	4,16	11,96	19,76	3,61	2,85	11,03	18,45	7,80	5,73	9	9,52
LL 1622	—	6,81	—	—	6,15	4,8	—	—	—	8,3	12	12,7
LL 1644	6,81	6,81	19,81	—	6,15	4,8	18,64	—	13	8,3	12	12,7
LL 1666	6,81	6,81	19,81	32,81	6,15	4,8	18,64	31,14	13	8,3	12	12,7
LL 2022	—	7,86	—	—	7,08	5,55	—	—	—	10,21	14	15,88
LL 2044	7,86	7,86	22,86	—	7,08	5,55	21,45	—	15	10,21	14	15,88
LL 2066	7,86	7,86	22,86	37,86	7,08	5,55	21,45	35,82	15	10,21	14	15,88
LL 2422	—	10,91	—	—	10,02	7,8	—	—	—	14,65	18	19,05
LL 2444	10,91	10,91	31,91	—	10,02	7,8	30,26	—	21	14,65	18	19,05
LL 2466	10,91	10,91	31,91	52,91	10,02	7,8	30,26	50,50	21	14,65	18	19,05
LL 2822	—	13,46	—	—	12,46	9,68	—	—	—	15,92	20	22,2
LL 2844	13,46	13,46	39,46	—	12,46	9,68	37,57	—	26	15,92	20	22,2
LL 2866	13,46	13,46	39,46	65,47	12,46	9,68	37,57	62,68	26	15,92	20	22,2

^a Tolerance H12 is in accordance with ISO 286-2:2010, Clause 6.

Table 4 (continued)

ISO chain number	b_7	b_8	b_9	b_{10}	b_{11}	b_{12}	b_{13}	b_{14}	p_1	d_1	h_4	k
	H12 ^a				max.	min.	max.	max.	nom.	min.	min.	max.
mm												
LL 3222	—	13,51	—	—	12,39	9,68	—	—	—	17,83	23	25,4
LL 3244	13,51	13,51	39,51	—	12,39	9,68	37,38	—	26	17,83	23	25,4
LL 3266	13,51	13,51	39,51	65,52	12,39	9,68	37,38	62,37	26	17,83	23	25,4
LL 4022	—	17,21	—	—	15,87	12,38	—	—	—	22,91	28	31,75
LL 4044	17,21	17,21	50,41	—	15,87	12,38	47,80	—	33,2	22,91	28	31,75
LL 4066	17,21	17,21	50,41	83,62	15,87	12,38	47,80	79,73	33,2	22,91	28	31,75
LL 4822	—	21,41	—	—	19,84	15,45	—	—	—	29,26	34	38,1
LL 4844	21,41	21,41	62,82	—	19,84	15,45	59,72	—	41,4	29,26	34	38,1
LL 4866	21,41	21,41	62,82	104,2	19,84	15,45	59,72	99,60	41,4	29,26	34	38,1

^a Tolerance H12 is in accordance with ISO 286-2:2010, Clause 6.

4.3 Minimum tensile strength

The clevises and the pins used to anchor chains shall withstand at least the same minimum tensile forces as the chains themselves (see 3.4.2 and 3.4.3).

4.4 Length adjustment

In multi-strand applications, where it becomes necessary within the chain assembly to compensate for small length differences between strands, it is always desirable to provide, within the anchoring device, a length adjustment equal to at least one pitch of the chain.

5 Sheaves

The sheaves shown in Figure 4 shall comply with the following formulae.

- a) Minimum sheave diameter, D_1 :

$$D_1 = 5 \times \text{nominal chain pitch} \quad (1)$$

Smaller diameters may be used if proved by testing.

- b) Minimum width between flanges, b_{15} :

$$b_{15} = 1,05 \times \text{width over riveted bearing pins} \quad (2)$$

- c) Minimum flange diameter, D_2 :

$$D_2 = D_1 + h_3 \quad (3)$$

For dimensions h_3 and the width over riveted bearing pins (dimensions b_1 to b_6), see Figure 1 and Table 1 or Table 2.




Figure 4 — Sheave dimensions

Annex A (informative)

Method of calculating chain minimum dynamic strength

A.1 General

$$F_d = \min(F_{di}; F_{do}) \times f_P \times f_L \text{ for the chain} \quad (\text{A.1})$$

$$F_{di} = n_{iP} \times (h_3 - d_1) \times b_0 \times K_{Si} \text{ for the inner link} \quad (\text{A.2})$$

$$F_{do} = n_{oP} \times (h_3 - d_1) \times b_0 \times K_{Si} + 2 \times (h_3 - d_2) \times b_0 \times K_{So} \text{ for the outer link} \quad (\text{A.3})$$

where

F_d is the minimum dynamic strength of the chain at 3×10^6 cycles in newtons (N);

F_{do} is the dynamic strength of the outer link in newtons (N);

F_{di} is the dynamic strength of the inner link in newtons (N);

n_{iP} is the number of plates with loose fit within the inner chain link;

n_{oP} is the number of plates with loose fit within the outer chain link;

h_3 is the plate depth in mm;

d_1 is the hole diameter of inner plates in mm;

d_2 is the pin diameter in mm;

b_0 is the thickness of plates in mm;

K_{Si} is 110 N/mm² for inner plates (loose fit);

K_{So} is 150 N/mm² for outer plates (press fit);

f_P is the factor for the chain pitch according to [Table A.1](#);

f_L is the factor for the chain lacing according to [Table A.2](#).

Table A.1 — Factor f_P for chain pitch

Chain pitch	f_P , LL series	f_P , LH series
mm	—	—
12,7	0,971	0,975
15,875	0,961	0,965
19,05	0,951	0,956
25,4	0,929	0,936
31,75	0,906	0,916
38,1	0,883	0,895
44,45	0,859	0,874
50,8	0,836	0,852
63,5	0,789	0,810
76,2	0,743	0,768

NOTE Factor f_P for chain pitch according to ISO 606.

Table A.2 — Factor f_L for chain lacing

Lacing	f_L	Derivation of f_L
2 × 2	1,000	= 1/1
2 × 3	0,880	= $f_{L2 \times 2} \cdot 0,88$
3 × 4	0,713	= $f_{L4 \times 4} \cdot f_R$
4 × 4	0,750	= 1,5/2
4 × 6	0,633	= $f_{L6 \times 6} \cdot f_R$
6 × 6	0,667	= 2/3

NOTE Reduction factor $f_R = 0,95$, the factor 0,88 and the definition of factor f_L based on empirical knowledge and is to be understood as a guideline.

A.2 Example for chain LH 1666 [BL 866]

The minimum dynamic strength of the chain LH 1666 [BL 866] can be calculated by

$$F_{di} = 6 \times (24,13 \text{ mm} - 9,56 \text{ mm}) \times 4,09 \text{ mm} \times 110 \text{ N/mm}^2 = 39,3 \text{ kN} \text{ for the inner link} \quad (\text{A.4})$$

$$F_{do} = 4 \times (24,13 \text{ mm} - 9,56 \text{ mm}) \times 4,09 \text{ mm} \times 110 \text{ N/mm}^2 \quad \text{for the outer link} \quad (\text{A.5})$$

$$+ 2 \times (24,13 \text{ mm} - 9,54 \text{ mm}) \times 4,09 \text{ mm} \times 150 \text{ N/mm}^2 = 44,1 \text{ kN}$$

$$F_d = 39,3 \text{ kN} \times 0,936 \times 0,667 = \underline{\underline{24,6 \text{ kN}}} \text{ for the chain LH 1666} \quad (\text{A.6})$$

Annex B (informative)

Method of determining maximum test force F_{\max} when conducting dynamic strength conformance test

B.1 General

The maximum test force F_{\max} is calculated using

$$F_{\max} = \frac{F_d F_u + [F_{\min} (F_u - F_d)]}{F_u} \quad (\text{B.1})$$

where

F_{\max} is the maximum test force, in newtons (N);

F_d is the minimum dynamic strength as given in [Table 1](#) or [Table 2](#), in newtons (N);

F_u is the minimum tensile strength as given in [Table 1](#) or [Table 2](#), in newtons (N);

F_{\min} is the minimum test force (1 % to 5 % of the minimum tensile strength F_u), in newtons (N)

B.2 Example for chain LH 1666 [BL 866]

If the chain manufacturer were to choose a minimum test force (F_{\min}) of 11 412 N (i.e. 4,5 % of the minimum tensile strength according to [Table 1](#)). Then the maximum test force F_{\max} would be determined as follows

$$F_{\max} = \frac{F_d F_u + [F_{\min} (F_u - F_d)]}{F_u} \quad (\text{B.2})$$

and from [Table 1](#)

$$F_d = 24\,600 \text{ N},$$

$$F_u = 253\,600 \text{ N, and}$$

$$F_{\min} = 11\,412 \text{ N},$$

then

$$F_{\max} = \frac{(24\,600 \times 253\,600) + [11\,412 \times (253\,600 - 24\,600)]}{253\,600} = 34\,905 \text{ N} \quad (\text{B.3})$$

Bibliography

- [1] ISO 286-2:2010, *Geometrical product specifications (GPS) — ISO code system for tolerances on linear sizes — Part 2: Tables of standard tolerance classes and limit deviations for holes and shafts*

Licensed copy: University of Manchester Library. The copyright of this document is held by the International Organization for Standardization (ISO). All rights reserved. Version 1.0/04/2016

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com