



BSI Standards Publication

## Hydraulic fluid power — Fluids — Method for coding the level of contamination by solid particles

---

INTERNATIONAL  
STANDARD

**ISO**  
**4406**

Fourth edition  
2021-01

---

---

**Hydraulic fluid power — Fluids  
— Method for coding the level of  
contamination by solid particles**

*Transmissions hydrauliques — Fluides — Méthode de codification du  
niveau de pollution particulaire solide*



Reference number  
ISO 4406:2021(E)



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO’s member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

<b>Contents</b>		Page
<b>Foreword</b> .....		<b>iv</b>
<b>Introduction</b> .....		<b>v</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>1</b>
<b>4</b>	<b>Code definitions</b> .....	<b>1</b>
4.1	General .....	1
4.2	Basis of code .....	2
4.3	Allocation of scale numbers .....	2
4.4	Determination of code using automatic particle counter analysis .....	3
4.5	Determination of code using microscope sizing .....	4
<b>5</b>	<b>Identification statement (reference to this document)</b> .....	<b>4</b>
<b>Annex A (normative) Graphical presentation of the code number</b> .....		<b>5</b>



## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 6, *Contamination control*.

This fourth edition cancels and replaces the third edition (ISO 4406:2017), which has been technically revised.

The main change compared to the previous edition is as follows:

- the use of Particle Contamination Monitors (PCMs) can also be utilized for the determination of the ISO 4406 contamination code (see [subclause 4.4.1](#)) and PCM is referenced throughout this document.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## **Introduction**

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit. Solid particle contaminant is always present in the hydraulic fluid and the amount needs to be determined because the contaminant can cause serious problems.

The ISO 4406 cleanliness code has gained world-wide acceptance as a means of communicating the cleanliness of a hydraulic fluid. Most hydraulic component manufacturers require a certain ISO cleanliness level for warranty purposes, to ensure proper function and for a long, trouble-free life.





# Hydraulic fluid power — Fluids — Method for coding the level of contamination by solid particles

## 1 Scope

This document specifies the code to be used in defining the quantity of solid particles in the fluid used in a given hydraulic fluid power system.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4407, *Hydraulic fluid power — Fluid contamination — Determination of particulate contamination by the counting method using an optical microscope*

ISO 11171, *Hydraulic fluid power — Calibration of automatic particle counters for liquids*

ISO 11500, *Hydraulic fluid power — Determination of the particulate contamination level of a liquid sample by automatic particle counting using the light-extinction principle*

ISO 21018-3, *Hydraulic fluid power — Monitoring the level of particulate contamination of the fluid — Part 3: Use of the filter blockage technique*

ISO 21018-4, *Hydraulic fluid power — Monitoring the level of particulate contamination in the fluid — Part 4: Use of the light extinction technique*

## 3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

## 4 Code definitions

### 4.1 General

The purpose of this code is to simplify the reporting of particle count data by converting the numbers of particles into broad classes or codes, where an increase in one code generally represents a doubling of the contamination level.

The original code, in accordance with the first edition of this document, stated the reporting at two sizes:  $\geq 5 \mu\text{m}$  and  $\geq 15 \mu\text{m}$ . The sizes in this document account for the use of a different calibration standard for optical automatic particle counters (APCs). The reported sizes are  $\geq 4 \mu\text{m(c)}$ ,  $\geq 6 \mu\text{m(c)}$  and



≥ 14 µm(c), as per ISO 11171. The last two of these are equivalent to the 5 µm and 15 µm particle sizes specified in the first edition.

NOTE Throughout this document, the use of µm(c) means that particle size measurements are carried out using an APC that has been calibrated in accordance with ISO 11171 or a particle contamination monitor (PCM) calibrated to ISO 21018-3 or ISO 21018-4.

Measurement of particles using an optical microscope as specified within ISO 4407 establishes the size of a particle as being equal to its longest dimension, whereas an APC derives the size of an equivalent particle from its cross-sectional area, a value different in most cases from that determined using a microscope.

The particle sizes to be reported for measurement by microscope ≥ 5 µm and ≥ 15 µm are unchanged from those specified in the first edition of this document.

**CAUTION — Particle counts are affected by a variety of factors. These factors include procurement of sample, particle counting accuracy and the sample container (where used), and its cleanliness. Proper care should be taken during sample procurement to ensure that the sample obtained is representative of the fluid circulation within the system.**

4.2 Basis of code

The code for contamination levels using APCs or PCMs comprises three scale numbers that permit the differentiation of the dimension and the distribution of the particles as follows:

- the first scale number represents the number of particles equal to or larger than 4 µm(c) per millilitre of fluid;
- the second scale number represents the number of particles equal to or larger than 6 µm(c) per millilitre of fluid; and
- the third scale number represents the number of particles equal to or larger than 14 µm(c) per millilitre of fluid.

The code for microscope counting comprises two scale numbers using 5 µm and 15 µm.

4.3 Allocation of scale numbers

4.3.1 The scale numbers are allocated according to the number of particles counted per millilitre of the fluid sample (see Table 1).

4.3.2 A step ratio of generally two, as given between the upper and lower limits for the number of particles per millilitre in Table 1, has been adopted to keep the number of scale numbers within a reasonable limit and to ensure that each step is meaningful.

Table 1 — Allocation of scale numbers

Number of particles per millilitre		Scale number <sup>a</sup>
More than	Up to and including	
2 500 000	—	> 28
1 300 000	2 500 000	28
640 000	1 300 000	27
320 000	640 000	26
160 000	320 000	25
80 000	160 000	24

<sup>a</sup> Reproducibility below scale number 8 is affected by the actual number of particles counted in the fluid sample. Raw count should be more than 20 particles. If this is not possible, refer to 4.4.7.



Table 1 (continued)

Number of particles per millilitre		Scale number <sup>a</sup>
More than	Up to and including	
40 000	80 000	23
20 000	40 000	22
10 000	20 000	21
5 000	10 000	20
2 500	5 000	19
1 300	2 500	18
640	1 300	17
320	640	16
160	320	15
80	160	14
40	80	13
20	40	12
10	20	11
5	10	10
2,5	5	9
1,3	2,5	8
0,64	1,3	7
0,32	0,64	6
0,16	0,32	5
0,08	0,16	4
0,04	0,08	3
0,02	0,04	2
0,01	0,02	1
0,00	0,01	0

<sup>a</sup> Reproducibility below scale number 8 is affected by the actual number of particles counted in the fluid sample. Raw count should be more than 20 particles. If this is not possible, refer to [4.4.7](#).

4.4 Determination of code using automatic particle counter analysis

- 4.4.1 Counting shall be undertaken in accordance with ISO 11500 or another recognized method, using an APC calibrated to ISO 11171 or a PCM calibrated to ISO 21018-3 or ISO 21018-4.
- 4.4.2 A first scale number shall be allocated to the number of particles equal to or larger than 4 µm(c).
- 4.4.3 A second scale number shall be allocated to the number of particles equal to or larger than 6 µm(c).
- 4.4.4 A third scale number shall be allocated to the number of particles equal to or larger than 14 µm(c).
- 4.4.5 The three numbers shall be written one after the other and separated by oblique strokes (slashes).

EXAMPLE A code of 22/18/13 signifies that there are more than 20 000 and up to and including 40 000 particles equal to or larger than 4 µm(c), more than 1 300 and up to and including 2 500 particles equal to or larger than 6 µm(c), and more than 40 and up to and including 80 particles equal to or larger than 14 µm(c) in 1 mL of a given fluid sample.

Graphical presentation of ISO code results shall be as described in [Annex A](#).

**4.4.6** When applicable, include either “\*” (too numerous to count) or “—” (no requirement to count) notations when reporting the scale number.

EXAMPLE 1    \*/19/14 means that this sample has too many particles equal to or larger than 4 µm(c) to count.

EXAMPLE 2    —/19/14 means that there was no requirement to count particles equal to or larger than 4 µm(c).

**4.4.7** When the raw data in one of the size ranges results in a particle count of fewer than 20 particles, the scale number for that size range shall be labelled with the symbol “≥”.

EXAMPLE    A code of 14/12/≥7 signifies that there are more than 80 and up to and including 160 particles equal to or larger than 4 µm(c) per millilitre and more than 20 and up to and including 40 particles equal to or larger than 6 µm(c) per millilitre. The third part of the code, ≥7, indicates that there are more than 0,64 and up to and including 1,3 particles equal to or larger than 14 µm(c) per millilitre but less than 20 particles were counted, which lowers statistical confidence. Due to this lower confidence, the 14 µm(c) part of the code can be higher than 7, indicating a particle count of more than 1,3 particles per millilitre.

## **4.5 Determination of code using microscope sizing**

**4.5.1** Counting shall be undertaken in accordance with ISO 4407.

**4.5.2** A scale number shall be allocated to the number of particles equal to or larger than 5 µm.

**4.5.3** A second scale number shall be allocated to the number of particles equal to or larger than 15 µm.

**4.5.4** In order to relate to counts obtained with an APC or PCM, the code shall be stated in three-part form with the first part given as “—”.

EXAMPLE    —/18/13.

Graphical presentation of ISO code results shall be as described in [Annex A](#).

## **5 Identification statement (reference to this document)**

The following statement shall be used in test reports, catalogues and sales literature when electing to comply with the requirements of this document:

“Solid contaminant code conforms to ISO 4406, *Hydraulic fluid power — Fluids — Method for coding the level of contamination by solid particles.*”



## Annex A (normative)

### Graphical presentation of the code number

For APC or PCM analysis, the contaminant code is determined by:

- allocating a first scale number to the total number of particles equal to or larger than 4 µm(c);
- allocating a second scale number to the total number of particles equal to or larger than 6 µm(c);
- allocating a third scale number to the total number of particles equal to or larger than 14 µm(c); and
- writing these three numbers one after another separated by oblique strokes (slashes).


EXAMPLE 1 See 22/18/13 in [Figure A.1](#). or if the first scale number is not required or used: —/18/13 determined with an APC or PCM.

For analysis by microscope, use "—" in place of the first scale number and allocate the second, and third numbers based upon the counts at 5 µm and 15 µm, respectively.

EXAMPLE 2 —/18/13 determined with an optical microscope.

Interpolation is acceptable. Extrapolation is not permissible.

Quote scale number at 4 µm(c), 6 µm(c) and 14 µm(c) levels for APCs and PCMs, and at 5 µm and 15 µm for microscope counting.



**Key**

Y<sub>1</sub> number of particles per millilitre larger than indicated size

Y<sub>2</sub> scale number

X<sub>1</sub> particle size, µm(c)

X<sub>2</sub> particle size, µm

Figure A.1 — Example of graphical presentation of ISO code results





# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

## About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

## Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at [bsigroup.com/standards](https://bsigroup.com/standards) or contacting our Customer Services team or Knowledge Centre.

## Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at [bsigroup.com/shop](https://bsigroup.com/shop), where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

## Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

## Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

## Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to [bsigroup.com/subscriptions](https://bsigroup.com/subscriptions).

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit [bsigroup.com/shop](https://bsigroup.com/shop).

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email [cservices@bsigroup.com](mailto:cservices@bsigroup.com).

## Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

## Useful Contacts

### Customer Services

**Tel:** +44 345 086 9001

**Email:** [cservices@bsigroup.com](mailto:cservices@bsigroup.com)

### Subscriptions

**Tel:** +44 345 086 9001

**Email:** [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com)

### Knowledge Centre

**Tel:** +44 20 8996 7004

**Email:** [knowledgecentre@bsigroup.com](mailto:knowledgecentre@bsigroup.com)

### Copyright & Licensing

**Tel:** +44 20 8996 7070

**Email:** [copyright@bsigroup.com](mailto:copyright@bsigroup.com)

## BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

