



BSI Standards Publication

Hydraulic fluid power — Cylinders — Dimensions and tolerances of housings for single-acting piston and rod seals in reciprocating applications

INTERNATIONAL STANDARD

ISO
5597

Third edition
2018-05-01

Hydraulic fluid power — Cylinders — Dimensions and tolerances of housings for single-acting piston and rod seals in reciprocating applications

*Transmissions hydrauliques — Vérins — Dimensions et tolérances
des logements de joints d'étanchéité pour pistons et tiges de piston à
simple effet dans les applications à mouvement alternatif*



Reference number
ISO 5597:2018(E)

© ISO 2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	2
5 Seal housings	2
5.1 General	2
5.2 Axial length	3
5.3 Radial depth	3
6 Dimensions and tolerances	3
6.1 Piston seal housing dimensions	3
6.2 Rod seal housing dimensions	3
6.3 Radial seal space tolerances	3
6.4 Housing length	4
7 Extrusion gap	4
8 Surface roughness	4
8.1 General	4
8.2 Sliding and static sealing surfaces	4
9 Lead-in chamfer	5
10 Identification statement (reference to this document)	6
Bibliography	16

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 7, *Sealing devices*.

This third edition cancels and replaces the second edition (ISO 5597:2010) which has been technically revised to ensure consistency with [ISO 3320](http://www.iso.org/iso/3320).

The main changes compared to the previous edition are:

- Seal housing sizes for a 60 mm diameter cylinder bore added to [Table 3](#);
- 400 mm and 450 mm diameter rods added to [Table 5](#).
- [Table 1](#) has been modified to indicate that, for some seal housings, the axial lengths (seal groove lengths) are too short for the surface roughness to be measured with five sampling lengths.

Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit. Sealing devices are used to contain the pressurized fluid with components having elements with linear motion, i.e. hydraulic cylinders. These sealing devices are used with both cylinder rod and piston seal housings.

This document is one of a series of standards covering dimensions and tolerances of housings.

Hydraulic fluid power — Cylinders — Dimensions and tolerances of housings for single-acting piston and rod seals in reciprocating applications

1 Scope

This document establishes the preferred range of nominal dimensions and associated tolerances for a series of hydraulic cylinder rod and piston seal housings for reciprocating applications in the following range of dimensions:

- for cylinders of 16 mm to 500 mm;
- for rods of 6 mm to 450 mm.

An additional range of seal housings is detailed in this document to meet the reduced envelope requirements of the 160 bar (16 MPa)¹⁾ compact series of [ISO 6020-2](#); these smaller section seals require stricter piston rod and cylinder bore tolerances. The range of dimensions is as follows:

- cylinders of 25 mm to 200 mm;
- rods of 12 mm to 140 mm.

This document does not give details of seal design, since the manner of construction of seals varies with each manufacturer. The design and material of the seal and any incorporated anti-extrusion components are determined by conditions such as temperature and pressure.

This document only applies to the dimensional criteria of products manufactured in conformity with this document; it does not apply to their functional characteristics.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 4287:1997](#), *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters*

[ISO 5598](#), *Fluid power systems and components — Vocabulary*

[ISO 6020-2](#), *Hydraulic fluid power — Mounting dimensions for single rod cylinders, 16 MPa (160 bar) series — Part 2: Compact series*

3 Terms and definitions

For the purposes of this document, the definitions given in [ISO 5598](#) apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

1) 1 bar = 100 kPa = 10⁵ Pa = 0,1 MPa; 1 Pa = 1 N/m².

4 Symbols

Symbols used in this document are as follows:

<i>a</i>	roughness of the side surface of the seal housing
<i>b</i>	roughness of the static pressure mating surface of the seal housing
<i>C</i>	axial length of the lead-in chamfer
<i>C</i> 0	reference material ratio level (see ISO 4287:1997 , 4.5.4)
<i>D</i>	outside diameter (bore diameter) of the seal housing
<i>d</i>	inside diameter (rod diameter) of the seal housing
<i>d</i> ₃	clearance diameter of the piston
<i>d</i> ₄	clearance diameter of the rod seal housing
<i>d</i> ₅	clearance diameter of the rod
<i>e</i>	roughness of dynamic pressure mating surface
<i>f</i>	surface roughness of lead-in chamfer
<i>L</i>	axial length (seal groove length) of the seal housing
<i>r</i>	radius
<i>Rδc</i>	profile section height difference (see ISO 4287:1997 , 4.5.3)
<i>S</i>	$\frac{D-d}{2}$ radial depth (cross-section) of the seal housing
<i>W, X</i>	reference surface
<i>V, Y</i>	maximum run-out tolerance

5 Seal housings

5.1 General

5.1.1 Illustrated examples of typical hydraulic cylinder rod and piston seal housings covered by this document are given in [Figures 1](#) to [4](#).

NOTE These figures are diagrammatic only and do not represent recommendations of a particular housing design.

5.1.2 All sharp edges and burrs shall be removed from corners of supporting surfaces and rounded, although it should be borne in mind that these surfaces are required to provide maximum support against extrusion.

5.1.3 The seal manufacturer shall be consulted for details of housing design that are not specified in this document.

5.2 Axial length

The short axial length, L , as given in [Tables 3](#) and [5](#), shall be adopted only after consultation with the manufacturer.

Consultation with the manufacturer is recommended when making the appropriate selection from the available choices.

NOTE This document includes a choice of axial length for every nominal piston and rod diameter, the exception being cylinders conforming to [ISO 6020-2](#) in which case only one length is provided (see [Clause 1](#) and [Tables 4](#) and [6](#)).

5.3 Radial depth

The larger radial depth (cross-section) of the seal housing, S , shall be chosen where higher stresses or wider tolerances are involved.

Consultation with the manufacturer is recommended when making the appropriate selection from the available choices.

NOTE This document includes an alternative seal housing radial depth (cross-section) for most piston and rod diameters, the exception being at the upper and lower extremities of the diameter range as well as cylinder seal housings conforming to ISO 6020-2, in which case only one radial depth is provided.

6 Dimensions and tolerances

NOTE See [ISO 3320](#).

6.1 Piston seal housing dimensions

6.1.1 Illustrated examples of piston seal housing dimensions are given in [Figures 1](#) and [2](#).

6.1.2 Piston seal housing dimensions (except in the case of cylinders conforming to [ISO 6020-2](#)) shall be selected from [Table 3](#).

6.1.3 Piston seal housing dimensions for use with cylinders conforming to [ISO 6020-2](#) shall be selected from [Table 4](#).

6.2 Rod seal housing dimensions

6.2.1 Illustrated examples of rod seal housing dimensions are given in [Figures 3](#) and [4](#).

6.2.2 Rod seal housing dimensions (except in the case of cylinders conforming to [ISO 6020-2](#)) shall be selected from [Table 5](#).

6.2.3 Rod seal housing dimensions for use with cylinders conforming to [ISO 6020-2](#) shall be selected from [Table 6](#).

6.3 Radial seal space tolerances

6.3.1 Reference shall be made to [Table 7](#) for radial seal space tolerances.

6.3.2 References shall be made to NOTES 1 and 2 of [Table 7](#) for the formulae for calculating tolerances on d (see [Figures 1](#) and [2](#)) and D (see [Figures 3](#) and [4](#)).

NOTE 1 The equations and values shown in [Table 7](#), when used in conjunction with [ISO 286-2](#) limits of D H9 and d_3 f8 (for the piston case) or d f8 and d_5 H9 (for the rod case), in most cases result in tolerances within the span of d h10 and D H10, respectively.

NOTE 2 If alternative limits to those given in NOTE 1 are selected for D and d_3 (for the piston case) or d and d_5 (for the rod case), then the use of the formulae will maintain the necessary radial seal space limits, i.e. any relaxation of tolerance on one housing diameter will be compensated by a tighter tolerance on the other diameter.

6.4 Housing length

A tolerance of $+0,25_0$ mm shall be used on the length of the housing.

7 Extrusion gap

The extrusion gap is determined by the diameter (d_4 or d_3) of the adjacent metal components behind the seal. It is recommended that details concerning d_3 (see [Figures 1](#) and [2](#)) and d_4 (see [Figures 3](#) and [4](#)) be subject to consultations between the housing designer and seal manufacturer.

NOTE 1 Maximum value for the extrusion gap is achieved when the piston or piston rod is in contact with one side of the cylinder or bearing, respectively.

NOTE 2 The extrusion gap for piston seals is further widened by the expansion of the cylinder due to internal pressure.

8 Surface roughness

8.1 General

The surface roughness of the seal housing and any mating part has a significant impact on the life and sealing performance of the seal.

Where surface roughness measurements are taken, it is recommended that instruments complying with [ISO 3274](#), including an electric wave filter, be used.

8.2 Sliding and static sealing surfaces

8.2.1 Unless otherwise agreed the roughness values shall be in accordance with [Table 1](#).

8.2.2 Unless otherwise agreed, the material ratio Rmr of housing surfaces that are in mating contact with the seal should be between 50 % and 80 % at a profile section level ($R\delta c$) of 25 % of Rz , from a reference level, $C0$, of 5 % Rmr (in accordance with [ISO 4287:1997](#), 4.5.4).

8.2.3 For some seal designs, a minimum surface roughness of $0,1 \mu m Ra$ may be required for the sliding sealing surface as the surface otherwise may be too smooth to provide adequate lubrication for the seal.

8.2.4 Exceptional service conditions may necessitate the selection of other grades of surface roughness, in which case they should be subject to agreement between manufacturer and user.

8.2.5 All surfaces against which a seal operates should be free from chatter marks and scores along the operating axis of the seal.

Table 1 — Surface roughness requirements for piston and rod housings^a

Dimensions in micrometres (µm) unless otherwise noted

Radial depth of seal housing <i>S</i> mm	Surface roughness values ^{b, c, d}				Minimum required measuring length mm (5 times single sampling length plus 2 times cut off)	
	Dynamic pressure mating surface ^e <i>e</i>	Static pressure mating surface ^e <i>b</i>		Side surface <i>a</i>		Chamfer <i>f</i>
		Axial length <i>L</i>				
		<i>L</i> ≤ 5,6	<i>L</i> > 5,6			
3,5	<i>Ra</i> 0,4 <i>Rz</i> 1,6	<i>Ra</i> 4 1,6 <i>Rz</i> 4 6,3	—	<i>Ra</i> 2 1,6 <i>Rz</i> 2 6,3	visual inspection or <i>Rz</i> 16 visual inspection	5,6
4		<i>Ra</i> 4 1,6 <i>Rz</i> 4 6,3	<i>Ra</i> 1,6 <i>Rz</i> 6,3			
5		—		<i>Ra</i> 4 1,6 <i>Rz</i> 4 6,3		
≥ 7,5				<i>Ra</i> 1,6 <i>Rz</i> 6,3		

^a Indication of surface roughness according to [ISO 1302](#).

^b See also [Figures 1 to 4](#). See [ISO 13715](#) for design of edges and undefined shapes.

^c The descriptions of *Ra*4 1,6 or *Rz*4 6,3 do not describe a surface roughness of *Ra* 41,6 or *Rz* 46,3. According to [ISO 1302](#) and ISO 4288, they show four sampling lengths and the roughness does not exceed 1,6 µm for *Ra* and 6,3 µm for *Rz*.
A value of *Ra* 1,6 or *Rz* 6,3 can only be measured if the length to be measured is 5,6 mm or longer.

^d Special applications may require different surface roughness values.

^e Visual surface imperfections are not allowed on surfaces *b* and *e* (see [ISO 8785](#)).

9 Lead-in chamfer

9.1 Reference shall be made to [Figures 1 to 4](#) for the location of the lead-in chamfer, *C*.

9.2 The chamfer shall make an angle of between 20° and 30° with the axis.

9.3 The length of the chamfer shall not be less than that given in [Table 2](#).

Table 2 — Lead-in chamfer


Dimensions in millimetres

Radial depth of seal housing, <i>S</i>	3,5	4	5	7,5	10	12,5	15	20
Minimum axial length of lead in chamfer, <i>C</i>	2	2	2,5	4	5	6,5	7,5	10

10 Identification statement (reference to this document)

It is recommended that manufacturers who have chosen to conform to this document use the following statement in test reports, catalogues and sales literature:

“Dimensions and tolerances for hydraulic cylinder rod and piston seal housings are selected in accordance with ISO 5597, *Hydraulic fluid power—Cylinders—Dimensions and tolerances of housings for single-acting piston and rod seals in reciprocating applications.*”



Key

- 1 bore
- 2 piston
- 3 seal-retaining plate
- a rounded and burr-free


NOTE 1 Maximum run-out tolerance $Y = 0,05$.

NOTE 2 See [Table 1](#) for values of a , b , e and f .

NOTE 3 See [Table 2](#) for values of C .

NOTE 4 See [Table 3](#) for values of d , D , S , L and r .

Figure 1 — Example of piston seal housing (except in the case of cylinders conforming to ISO 6020-2 — see [Figure 2](#))



Key

- 1 bore
- 2 piston
- a rounded and burr-free

NOTE 1 Maximum run-out tolerance $Y = 0,05$.

NOTE 2 See [Table 1](#) for values of a , b , e and f .

NOTE 3 See [Table 2](#) for values of C .

NOTE 4 See [Table 4](#) for values of d , D , S , L and r .

Figure 2 — Example of piston seal housing for use with cylinders conforming to ISO 6020-2

Table 3 — Nominal dimensions for piston seal housing (except in the case of cylinders conforming to ISO 6020-2 — see [Table 4](#))

Dimensions in millimetres

Bore diameter ^a <i>D</i>	Radial depth <i>S</i>	Inside diameter <i>d</i>	Axial length ^b <i>L</i>			<i>r</i> maximum
			short	medium	long	
16	4	8	5	6,3	—	0,4
20		12				
25		17				
25	5	15	6,3	8	16	
32	4	24	5	6,3	—	
	5	22	6,3	8	16	
40	4	32	5	6,3	—	
	5	30	6,3	8	16	
50	5	40	6,3	8	16	
	7,5	35	9,5	12,5	25	
60	5	50	6,3	8	16	
	7,5	45	9,5	12,5	25	
63	5	53	6,3	8	16	
	7,5	48	9,5	12,5	25	
80	7,5	65	9,5	12,5	25	
	10	60	12,5	16	32	0,6
90	7,5	75	9,5	12,5	25	0,4
	10	70	12,5	16	32	0,6
100	7,5	85	9,5	12,5	25	0,4
	10	80	12,5	16	32	0,6
110	7,5	95	9,5	12,5	25	0,4
	10	90	12,5	16	32	0,6
125	10	105	12,5	16	32	0,6
	12,5	100	16	20	40	0,8
140	10	120	12,5	16	32	0,6
	12,5	115	16	20	40	0,8
160	10	140	12,5	16	32	0,6
	12,5	135	16	20	40	0,8

^a Bore diameters in accordance with [ISO 3320](#).

^b The application of the axial lengths specified in [Tables 3](#) and [5](#) (short, medium and long) depends upon the respective working conditions.

Bore diameter ^a <i>D</i>	Radial depth <i>S</i>	Inside diameter <i>d</i>	Axial length ^b <i>L</i>			<i>r</i> maximum
			short	medium	long	
180	10	160	12,5	16	32	0,8
	12,5	155	16	20	40	
200	12,5	175	16	20	40	
	15	170	20	25	50	
220	12,5	195	16	20	40	
	15	190	20	25	50	
250	12,5	225	16	20	40	
	15	220	20	25	50	
280		250				
320		290				
360		330				
400	20	360	25	32	63	
450		410				
500		460				

^a Bore diameters in accordance with [ISO 3320](#).

^b The application of the axial lengths specified in [Tables 3](#) and [5](#) (short, medium and long) depends upon the respective working conditions.


Table 4 — Nominal dimensions for piston seal housings for use with cylinders conforming to ISO 6020-2

Dimensions in millimetres

Bore diameter ^a <i>D</i>	Radial depth <i>S</i>	Inside diameter <i>d</i>	Axial length <i>L</i>	<i>r</i> ^b maximum
25	3,5	18	5,6	0,5
32		25		
40	4	32	6,3	
50		42		
63		55		
80	5	70	7,5	
100		90		
125	7,5	110	10,6	
160		145		
200		185		

^a Bore diameters in accordance with [ISO 6020-2](#).

^b This specific dimension permits the use of tools conforming to [ISO 883](#).



Key

- 1 rod
- 2 gland
- 3 seal-retaining plate
- a rounded and burr-free

NOTE 1 Maximum run-out tolerance $Y = 0,05$.


NOTE 2 Maximum run-out tolerance $V = 0,05$.

NOTE 3 See [Table 1](#) for values of a , b , e and f .

NOTE 4 See [Table 2](#) for values of C .

NOTE 5 See [Table 5](#) for values of d , D , S , L and r .

Figure 3 — Example of rod seal housing (except in the case of cylinders conforming to ISO 6020-2 — see [Figure 4](#))



Key

- 1 rod
- 2 gland
- a rounded and burr-free

NOTE 1 Maximum run-out tolerance $Y = 0,05$.

NOTE 2 See [Table 1](#) for values of a , b , e and f .

NOTE 3 See [Table 2](#) for values of C .

NOTE 4 See [Table 6](#) for values of d , D , S , L and r .

Figure 4 — Example of rod seal housing for use with cylinders conforming to ISO 6020-2

Table 5 — Nominal dimensions for rod seal housings (except in the case of cylinders conforming to ISO 6020-2 — see [Table 6](#))

Dimensions in millimetres

Rod diameter ^a <i>d</i>	Radial depth <i>S</i>	Outside diameter <i>D</i>	Axial length ^b <i>L</i>			<i>r</i> maximum
			short	medium	long	
6	4	14	5	6,3	14,5	0,4
8		16				
10		18				
12	5	20	—	8	16	
	4	20	5	6,3	14,5	
14	5	22	—	8	16	
	4	22	5	6,3	14,5	
16	5	24	—	8	16	
	4	24	5	6,3	14,5	
18	5	26	—	8	16	
	4	26	5	6,3	14,5	
20	5	28	—	8	16	
	4	28	5	6,3	14,5	
22	5	30	—	8	16	
	4	30	5	6,3	14,5	
25	5	32	—	8	16	
	4	33	5	6,3	14,5	
28	5	35	—	8	16	
	5	38	6,3	8	16	
32	7,5	43	—	12,5	25	
	5	42	6,3	8	16	
36	7,5	47	—	12,5	25	
	5	46	6,3	8	16	
40	7,5	51	—	12,5	25	
	5	50	6,3	8	16	
45	7,5	55	—	12,5	25	
	5	55	6,3	8	16	
50	7,5	60	—	12,5	25	
	5	60	6,3	8	16	
56	7,5	65	—	12,5	25	
	71	9,5	12,5	25		
63	10	76	—	16	32	0,6
	7,5	78	9,5	12,5	25	0,4
70	10	83	—	16	32	0,6
	7,5	85	9,5	12,5	25	0,4
	10	90	—	16	32	0,6

^a Rod diameters in accordance with [ISO 3320](#).

^b The application of the axial lengths specified in [Tables 3](#) and [5](#) (short, medium and long) depends upon the respective working conditions.

Rod diameter ^a <i>d</i>	Radial depth <i>S</i>	Outside diameter <i>D</i>	Axial length ^b <i>L</i>			<i>r</i> maximum
			short	medium	long	
80	7,5	95	9,5	12,5	25	0,4
	10	100	—	16	32	0,6
90	7,5	105	9,5	12,5	25	0,4
	10	110	—	16	32	0,6
100	10	120	12,5	16	32	0,6
	12,5	125	—	20	40	0,8
110	10	130	12,5	16	32	0,6
	12,5	135	—	20	40	0,8
125	10	145	12,5	16	32	0,6
	12,5	150	—	20	40	0,8
140	10	160	12,5	16	32	0,6
	12,5	165	—	20	40	0,8
160	12,5	185	16	20	40	
	15	190	—	25	50	
180	12,5	205	16	20	40	
	15	210	—	25	50	
200	12,5	225	16	20	40	
	15	230	—	25	50	
220		250	20			
250		280				
280		310				
320	20	360	25	32	63	1
360		400				
400		440				
450		490				

^a Rod diameters in accordance with [ISO 3320](#).

^b The application of the axial lengths specified in [Tables 3](#) and [5](#) (short, medium and long) depends upon the respective working conditions.

Table 6 — Nominal dimensions for rod seal housings for use with cylinders conforming to ISO 6020-2

Dimensions in millimetres

Rod diameter ^a <i>d</i>	Radial depth <i>S</i>	Inside diameter <i>D</i>	Axial length <i>L</i>	<i>r</i> ^b maximum
12	3,5	19	5,6	0,5
14		21		
18		25		
22		29		
28	4	36	6,3	
36		44		
45		53		
56	5	66	7,5	
70		80		
90		100		
110	7,5	125	10,6	
140		155		

^a Rod diameters in accordance with [ISO 6020-2](#).

^b This specific dimension permits the use of tools conforming to [ISO 883](#).

Table 7 — Seal housing radial depth (cross-section) — Tolerances

Dimensions in millimetres

Radial depth <i>S</i>	
Nominal	Tolerance
3,5	+0,15
	−0,05
4	+0,15
	−0,05
5	+0,15
	−0,05
7,5	+0,20
	−0,10
10	+0,25
	−0,10
12,5	+0,30
	−0,15
15	+0,35
	−0,20
20	+0,40
	−0,20

NOTE 1 For pistons:

Calculate the tolerances on the seal housing inside diameter, d (see [Figures 1](#) and [2](#)), in accordance with [Formulae \(1\)](#) and [\(2\)](#):

$$d_{\min} = 2D_{\max} - d_{3,\min} - 2S_{\max} \quad (1)$$

$$d_{\max} = d_{3,\min} - 2S_{\min} \quad (2)$$

NOTE 2 For rods:

Calculate the tolerances on the seal housing outside diameter, D (see [Figures 3](#) and [4](#)), in accordance with [Formulae \(3\)](#) and [\(4\)](#):

$$D_{\min} = d_{5,\max} + 2S_{\min} \quad (3)$$

$$D_{\max} = 2d_{\min} - d_{5,\max} + 2S_{\max} \quad (4)$$

Bibliography

- [1] [ISO 286-2](#), *Geometrical product specifications (GPS) — ISO code system for tolerances on linear sizes — Part 2: Tables of standard tolerance classes and limit deviations for holes and shafts*
- [2] [ISO 883](#), *Indexable hardmetal (carbide) inserts with rounded corners, without fixing hole — Dimensions*
- [3] [ISO 1101](#), *Geometrical product specifications (GPS) — Geometrical tolerancing — Tolerances of form, orientation, location and run-out*
- [4] [ISO 1302](#), *Geometrical Product Specifications (GPS) — Indication of surface texture in technical product documentation*
- [5] [ISO 3274](#), *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Nominal characteristics of contact (stylus) instruments*
- [6] [ISO 3320](#), *Fluid power systems and components — Cylinder bores and piston rod diameters and area ratios — Metric series*
- [7] [ISO 3601-2](#), *Fluid power systems — O-rings — Part 2: Housing dimensions for general applications*
- [8] [ISO 4288](#), *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Rules and procedures for the assessment of surface texture*
- [9] [ISO 8015](#), *Geometrical product specifications (GPS) — Fundamentals — Concepts, principles and rules*
- [10] [ISO 8785](#), *Geometrical Product Specification (GPS) — Surface imperfections — Terms, definitions and parameters*
- [11] [ISO 13715](#), *Technical product documentation — Edges of undefined shape — Indication and dimensioning*

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.
- Standards purchased in hard copy format:
- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email subscriptions@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK