



BSI Standards Publication

## **Fluid power systems and components — Cylinder-rod wiper-ring housings in reciprocating applications — Dimensions and tolerances**

---

## National foreword

This British Standard is the UK implementation of ISO 6195:2021. It supersedes BS ISO 6195:2013, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee MCE/11, Fluid seals and their housings.

A list of organizations represented on this committee can be obtained on request to its committee manager.

### Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2021  
Published by BSI Standards Limited 2021

ISBN 978 0 539 14019 4

ICS 23.100.20

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2021.

### Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

---

INTERNATIONAL  
STANDARD

**ISO**  
**6195**

Fourth edition  
2021-06-30

---

---

**Fluid power systems and  
components — Cylinder-rod wiper-  
ring housings in reciprocating  
applications — Dimensions  
and tolerances**

*Transmissions hydrauliques et pneumatiques — Logements de joints  
racleurs pour tiges de piston à mouvement linéaire de vérins —  
Dimensions et tolérances*



Reference number  
ISO 6195:2021(E)





**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2021, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO’s member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>iv</b>
<b>Introduction</b> .....		<b>v</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>1</b>
<b>4</b>	<b>Symbols</b> .....	<b>1</b>
<b>5</b>	<b>General</b> .....	<b>2</b>
<b>6</b>	<b>Requirements for housings</b> .....	<b>2</b>
6.1	Type A housing .....	2
6.2	Type B housing .....	5
6.3	Type C housing .....	7
6.4	Type D housing .....	9
6.5	Type E housing .....	11
<b>7</b>	<b>Other requirements regarding dimensions</b> .....	<b>14</b>
<b>8</b>	<b>Surface roughness</b> .....	<b>14</b>
<b>9</b>	<b>Identification statement</b> .....	<b>15</b>
<b>Bibliography</b> .....		<b>16</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Sub-committee SC 7, *Sealing devices*.

This fourth edition cancels and replaces the third edition (ISO 6915:2013), which has been technically revised.

The main changes compared to the previous edition are as follows:

- wiper housing sizes for 400 mm and 450 mm rod diameters have been added to [Tables 1, 2, 3, 4 and 5](#).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).



# Introduction

In fluid power systems, power is transmitted and controlled through a fluid (liquid or gas) under pressure within an enclosed circuit. Wiper-rings are used to prevent ingress of contaminants and to thereby protect the seals and bearings within the equipment.

This document is one of a family of standards covering dimensions and tolerances of reciprocating seal housings.

This document is applicable to the following five housing designs:

- Type A: recessed housings with undercut or separate cover to retain elastomeric wipers.
- Type B: open recessed housings for wipers with integral rigid enforcement that are press-fit in the housing.
- Type C: recessed housings with undercut to retain elastomeric wipers (these are the preferred housings for double lip wipers without integral rigid enforcement).
- Type D: recessed housings with undercut to retain elastomer-energized, plastic-faced wipers.
- Type E: recessed housings with undercut or separate cover to retain elastomeric wipers (these are the preferred housings to Type A).

These housing designs are intended for use with the wiper-rings according to [Figure 1](#).




Figure 1 — Types of wiper-rings

This document does not otherwise specify the style, configurations, materials, or performance ratings for the wiper-ring.





# Fluid power systems and components — Cylinder-rod wiper-ring housings in reciprocating applications — Dimensions and tolerances

## 1 Scope

This document specifies dimensions and tolerances of housings for wiper-rings used in reciprocating rod applications for fluid power cylinders. The range of rod diameters is from 4 mm to 450 mm.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 4287:1997](#), *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters*

[ISO 5598](#), *Fluid power systems and components — Vocabulary*

## 3 Terms and definitions

For the purposes of this document, the definitions given in [ISO 5598](#) apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:


- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

## 4 Symbols

The symbols used in this document are as follows:

<i>a</i>	roughness of the side surface of the wiper housing
<i>b</i>	roughness of the surface of the wiper housing bore
<i>C</i>	axial length of the lead-in chamfer
<i>C0</i>	reference material ratio level (see <a href="#">ISO 4287:1997</a> , 4.5.4)
<i>d</i>	rod diameter
<i>D</i> <sub>1</sub>	outside diameter of wiper housing
<i>D</i> <sub>2</sub>	retainer diameter
<i>e</i>	roughness of the rod
<i>f</i>	roughness of the leading chamfer
<i>L</i> <sub>1</sub>	axial length of the wiper housing

Dimensions in millimetres



**Key**

- a May be integral or with separate retaining plate.
- b Rounded and burr free.
- c See [Table 6](#) for dimensions.

**Figure 2 — Type A wiper housing and typical wiper-ring**

Table 1 — Dimensions for Type A wiper housing

Dimensions in millimetres

Rod diameter a, b	Radial depth	Outside diameter	Axial length	Wiper assembly length	Retainer diameter	Retainer radius	Radius
$d$	$S$	$D_1$ H11 <sup>d</sup>	$L_1$	$L_2$ max	$D_2$ H11 <sup>d</sup>	$r_1$ max	$r_2^c$ max
4	4,0	12	5,0 $\begin{smallmatrix} +0,2 \\ 0 \end{smallmatrix}$	8	9,5	0,3	0,5
5		13			10,5		
6		14			11,5		
8		16			13,5		
10		18			15,5		
12		20			17,5		
14		22			19,5		
16		24			21,5		
18		26			23,5		
20		28			25,5		
22		30			27,5		
25		33			30,5		
28		36			33,5		
32		40			37,5		
36		44			41,5		
40	48	45,5					
45	53	50,5					
50	58	55,5					
56	5,0	66	6,3 $\begin{smallmatrix} +0,2 \\ 0 \end{smallmatrix}$	10	63	0,4	
63		73			70		
70		80			77		
80		90			87		
90		100			97		
100	7,5	115	9,5 $\begin{smallmatrix} +0,3 \\ 0 \end{smallmatrix}$	14	110	0,6	
110		125			120		
125		140			135		
140		155			150		
160		175			170		
180		195			190		
200		215			210		

a See [ISO 3320](#) and [ISO 5597](#).  
b One-piece housing can be used with rod diameters greater than 14 mm  
c These specific dimensions permit the use of tools conforming to [ISO 883](#).  
d Tolerances and fits are according to [ISO 286-2](#).



Rod diameter a, b	Radial depth	Outside diameter	Axial length	Wiper assembly length	Retainer diameter	Retainer radius	Radius
$d$	$S$	$D_1$ H11 <sup>d</sup>	$L_1$	$L_2$ max	$D_2$ H11 <sup>d</sup>	$r_1$ max	$r_2^c$ max
220	10,0	240	12,5 <sup>+0,3</sup> <sub>0</sub>	18	233,5	0,8	0,9
250		270			263,5		
280		300			293,5		
320		340			333,5		
360		380			373,5		
400		420			413,5		
450		470			463,5		
<div><div>a</div> See <a href="#">ISO 3320</a> and <a href="#">ISO 5597</a>.</div> <div><div>b</div> One-piece housing can be used with rod diameters greater than 14 mm</div> <div><div>c</div> These specific dimensions permit the use of tools conforming to <a href="#">ISO 883</a>.</div> <div><div>d</div> Tolerances and fits are according to <a href="#">ISO 286-2</a>.</div>							


6.2 Type B housing

6.2.1 Type B housing and a typical wiper-rings are shown in [Figure 3](#).

6.2.2 Type B housing dimensions and tolerances shall conform to [Table 2](#).

6.2.3 Type B wiper-rings are recommended for use with cylinders conforming to [ISO 6020-1](#) and to [ISO 6022](#).

Dimensions in millimetres



Key

- a Rounded and burr free.
- b See [Table 6](#) for dimensions.

Figure 3 — Type B wiper housing and typical wiper-ring

Table 2 — Dimensions for Type B wiper housings


Dimensions in millimetres

Rod diameter <sup>a</sup>	Radial depth	Outside diameter	Axial length	Wiper assembly length
<i>d</i>	<i>S</i>	<i>D</i> <sub>1</sub> H8 <sup>b</sup>	<i>L</i> <sub>1</sub> <sup>+0,5</sup> <sub>0</sub>	<i>L</i> <sub>2</sub> max
4	4,0	12	5	8
5		13		
6		14		
8		16		
10		18		
12	5,0	22	7	11
14		24		
16		26		
18		28		
20		30		
22		32		
25		35		
28		38		
32		42		
36		46		
40		50		
45		55		
50		60		
56		66		
63		73		
70		80		
80		90		
90		100		
100	7,5	115	9	13
110		125		
125		140		
140		155		
160		175		
180		195		
200		215		
220	10,0	240	12	16
250		270		
280		300		
320		340		
360		380		
400		420		
450		470		
<sup>a</sup> See <a href="#">ISO 3320</a> and <a href="#">ISO 5597</a> .				
<sup>b</sup> Tolerances and fits are according to <a href="#">ISO 286-2</a> .				

6.3 Type C housing

6.3.1 Type C housing and a typical wiper-ring are shown in [Figure 4](#).

6.3.2 Type C housing dimensions and tolerances shall conform to [Table 3](#) (the size for use with glands conforming to [ISO 6020-2](#), to [ISO 6020-3](#) and to [ISO 10762](#) are indicated).



Key

- a May be integral or with separate retaining plate.
- b Rounded and burr free.
- c See [Table 6](#) for dimensions.

Figure 4 — Type C wiper housing and typical wiper-ring



Table 3 — Dimensions for Type C wiper housings

Dimensions in millimetres

Rod diameter a, b	Radial depth	Outside diameter	Axial length	Wiper assembly length	Retainer diameter	Radius
<i>d</i>	<i>S</i>	<i>D</i> <sub>1</sub> H11e	<i>L</i> <sub>1</sub>	<i>L</i> <sub>2</sub> max	<i>D</i> <sub>2</sub> H11e	<i>r</i> <sub>1</sub> max
4	3,0	10	4,0 <sup>+0,2</sup> <sub>0</sub>	7,0	6,5	0,3
5		11			7,5	
6		12			8,5	
8		14			10,5	
10		16			12,5	
12 <sup>c</sup>		18			14,5	
14 <sup>c</sup>		20			16,5	
16		22			18,5	
18 <sup>c</sup>		24			20,5	
20		26			22,5	
22 <sup>c</sup>		28			24,5	
25		31			27,5	
28 <sup>c</sup>	4,0	36	5,0 <sup>+0,2</sup> <sub>0</sub>	8,0	31	
32		40			35	
36 <sup>c</sup>		44			39	
40		48			43	
45 <sup>c</sup>		53			48	
50		58			53	
56 <sup>c</sup>	5,0	66	6,0 <sup>+0,2</sup> <sub>0</sub>	9,7	59	
63		73			66	
70 <sup>c</sup>		80			73	
80		90			83	
90 <sup>c</sup>		100			93	
100		110			103	
110 <sup>c</sup>	7,5	125	8,5 <sup>+0,3</sup> <sub>0</sub>	13,0	114	0,4
125		140			129	
140 <sup>c, d</sup>		155			144	
160		175			164	
180 <sup>d</sup>		195			184	
200		215			204	

a See [ISO 3320](#) and [ISO 5597](#).  
b Split housings should be used for rod diameters up to and including 18 mm.  
c These sizes are recommended for use with cylinders conforming to [ISO 6020-2](#) and [ISO 10762](#).  
d These sizes are recommended for use with cylinders conforming to [ISO 6020-3](#).  
e Tolerances and fits are according to [ISO 286-2](#).

Rod diameter a, b	Radial depth	Outside diameter	Axial length	Wiper assembly length	Retainer diameter	Radius
$d$	$S$	$D_1$ H11e	$L_1$	$L_2$ max	$D_2$ H11e	$r_1$ max
220 <sup>d</sup>	10,0	240	12,0 $\begin{smallmatrix} +0,3 \\ 0 \end{smallmatrix}$	18,0	226	0,6
250 <sup>d</sup>		270			256	
280 <sup>d</sup>		300			286	
320		340			326	
360 <sup>d</sup>		380			366	
400		420			406	
450		470			456	


- a See [ISO 3320](#) and [ISO 5597](#).
- b Split housings should be used for rod diameters up to and including 18 mm.
- c These sizes are recommended for use with cylinders conforming to [ISO 6020-2](#) and [ISO 10762](#).
- d These sizes are recommended for use with cylinders conforming to [ISO 6020-3](#).
- e Tolerances and fits are according to [ISO 286-2](#).

## 6.4 Type D housing

**6.4.1** Type D housing and a typical wiper-ring are shown in [Figure 5](#).

**6.4.2** Type D housing dimensions and tolerances shall conform to [Table 4](#).

Dimensions in millimetres



## Key

- a May be integral or with separate retaining plate.
- b Rounded and burr free.
- c See [Table 6](#) for dimensions.

**Figure 5 — Type D wiper housing and typical wiper-ring**

Table 4 — Dimensions for Type D wiper housings

Dimensions in millimetres

Rod diameter a, b, c	Radial depth	Outside diameter	Axial length	Retainer diameter	Retainer width	Radius
<i>d</i>	<i>S</i>	<i>D</i> <sub>1</sub> H9d	<i>L</i> <sub>1</sub> <sup>+0,2</sup> <sub>0</sub>	<i>D</i> <sub>2</sub> H11d	<i>L</i> <sub>3</sub> min	<i>r</i> <sub>1</sub> max
4	2,4	8,8	3,7	5,5	2	0,4
5		9,8		6,5		
6		10,8		7,5		
8		12,8		9,5		
10		14,8		11,5		
12	3,4	18,8	5,0	13,5		0,8
14		20,8		15,5		
16		22,8		17,5		
18		24,8		19,5		
20		26,8		21,5		
22		28,8		23,5		
25		31,8		26,5		
28		34,8		29,5		
32		38,8		33,5		
36		42,8		37,5		
40 <sup>c</sup>	3,4	46,8	5,0	41,5	2	
	4,4	48,8	6,3		3	
45	3,4	51,8	5,0	46,5	2	
	4,4	53,8	6,3		3	
50	3,4	56,8	5,0	51,5	2	
	4,4	58,8	6,3		3	
56	3,4	62,8	5,0	57,5	2	
	4,4	64,8	6,3		3	
63	3,4	69,8	5,0	64,5	2	
	4,4	71,8	6,3		3	
<div><div><sup>a</sup> See <a href="#">ISO 3320</a> and <a href="#">ISO 5597</a>.</div><div><sup>b</sup> Split housings should be used for rod diameters up to and including 28 mm.</div><div><sup>c</sup> From 40 mm rod diameters, the smaller wiper profiles are recommended for light applications. The larger wiper profiles are recommended for heavy duty applications.</div><div><sup>d</sup> Tolerances and fits are according to <a href="#">ISO 286-2</a>.</div></div>						



Rod diameter a, b, c	Radial depth	Outside diameter	Axial length	Retainer diameter	Retainer width	Radius
$d$	$S$	$D_1$ H9d	$L_1 \begin{smallmatrix} +0,2 \\ 0 \end{smallmatrix}$	$D_2$ H11d	$L_3$ min	$r_1$ max
70	4,4	78,8	6,3	71,5	3	1,0
	6,1	82,2	8,1	72,0	4	
80	4,4	88,8	6,3	81,5	3	
	6,1	92,2	8,1	82,0	4	
90	4,4	98,8	6,3	91,5	3	
	6,1	102,2	8,1	92,0	4	
100	4,4	108,8	6,3	101,5	3	
	6,1	112,2	8,1	102,0	4	
110	4,4	118,8	6,3	111,5	3	
	6,1	122,2	8,1	112,0	4	
125	4,4	133,8	6,3	126,5	3	
	6,1	137,2	8,1	127,0	4	
140	6,1	152,2	8,1	142,0	4	
	8,0	156,0	9,5	142,5	5	1,5
160	6,1	172,2	8,1	162,0	4	1,0
	8,0	176,0	9,5	162,5	5	1,5
180	6,1	192,2	8,1	182,0	4	1,0
	8,0	196,0	9,5	182,5	5	1,5
200	6,1	212,2	8,1	202,0	4	1,0
	8,0	216,0	9,5	202,5	5	1,5
220	6,1	232,2	8,1	222,0	4	1,0
	8,0	236,0	9,5	222,5	5	1,5
250	6,1	262,2	8,1	252,0	4	1,0
	8,0	266,0	9,5	252,5	5	1,5
280	6,1	292,2	8,1	282,0	4	
	8,0	296,0	9,5	282,5	5	
320	6,1	332,2	8,1	322,0	4	
	8,0	336,0	9,5	322,5	5	
360	6,1	372,2	8,1	362,0	4	
	8,0	376,0	9,5	362,5	5	
400	12,0	424,0	14,0	402,5	8	
450	12,0	474,0		452,5		

<sup>a</sup> See [ISO 3320](#) and [ISO 5597](#).

<sup>b</sup> Split housings should be used for rod diameters up to and including 28 mm.

<sup>c</sup> From 40 mm rod diameters, the smaller wiper profiles are recommended for light applications. The larger wiper profiles are recommended for heavy duty applications.


<sup>d</sup> Tolerances and fits are according to [ISO 286-2](#).

6.5 Type E housing

6.5.1 Type E housing and a typical wiper-ring are shown in [Figure 6](#).

6.5.2 Type E housing dimensions and tolerances shall conform to [Table 5](#).

6.5.3 Type E wiper-rings are recommended for use with cylinders conforming to [ISO 6020-1](#) and to [ISO 6022](#).



**Key**

- a May be integral or with separate retaining plate.
- b Rounded and burr free.
- c See [Table 6](#) for dimensions.

**Figure 6 — Type E wiper housing and typical wiper-ring**

Table 5 — Dimensions for Type E wiper housings

Dimensions in millimetres

Rod diameter a, b	Radial depth	Outside diameter	Axial length	Wiper assembly length	Retainer width	Retainer diameter	Radius
$d$ f8 <sup>c</sup>	$S$	$D_1$ H11 <sup>c</sup>	$L_1 \begin{smallmatrix} +0,15 \\ 0 \end{smallmatrix}$	$L_2 \text{ max}$	$L_3 \text{ min}$	$D_2$ H11 <sup>c</sup>	$r_1 \text{ max}$
8	4,0	16	4,0	7	1,0	14	0,2
10		18				16	
12		20				18	
14		22				20	
16		24				22	
18		26				24	
20		28				26	
22		30				28	
25		33				31	
28		36				34	
32		40				38	
36		44				42	
40		48				46	
45		53				51	
50		58				56	
56		64				62	
63		71				69	
70		78				76	
80		88				86	
90	6,0	102	5,5	10	1,5	99	0,3
100		112				109	
110		122				119	
125		137				134	
140		152				149	
160		172				169	
180		192				189	
200		212				209	
220	7,5	235	6,5	13	2,0	231	0,5
250		265				261	
280		295				291	
320		335				331	
360		375				371	
400		415				411	
450		465				461	

a See [ISO 3320](#) and [ISO 5597](#).  
b One-piece housings can be used with rod diameters greater than 14 mm.  
c Tolerances and fits are according to [ISO 286-2](#).



7 Other requirements regarding dimensions

- 7.1 Reference shall be made to [Figures 2, 3, 4, 5](#) and [6](#) for the location of the lead-in chamfer, *C*, on the rod end.
- 7.2 The rod-end chamfer shall make an angle of between 20° and 30° with the axis.
- 7.3 The length of the rod-end chamfer shall not be less than specified in [Table 6](#).
- 7.4 The housing lead-in chamfer dimensions for Type B housings shall conform to [Figure 3](#).

Table 6 — Lead-in chamfer

Dimensions in millimetres					
Radial depth of housing, <i>S</i>	$S < 4,0$	$4,0 \leq S < 5,5$	$5,5 \leq S < 7,0$	$7,0 \leq S < 9,0$	$9,0 \leq S < 12,0$
Minimum axial length of lead-in chamfer, <i>C</i>	2,0	2,5	3,0	4,0	5,0

8 Surface roughness

- 8.1 The surface roughness of the wiper housing and any mating part has a significant impact upon the life and sealing performance of the wiper.
- 8.2 Unless otherwise agreed, surface roughness values shall be in accordance with [Table 7](#).
- 8.3 Unless otherwise agreed, the material ratio, *Rmr* of housing surfaces that are in mating contact with the seal should be between 50 % and 80 % at a profile section level (*Rδc*) of 25 % of *Rz*, from a reference level, *C0*, of 5 % *Rmr* (in accordance with [ISO 4287:1997](#) 4.5.4).

Table 7 — Surface roughness requirements for wiper housings <sup>a</sup>

Dimensions in micrometres unless otherwise noted

Radial depth of wiper housing $S$ mm	Surface roughness values $b, c, d$						Minimum required meas- uring length  mm (5 times single sampling length plus 2 times cut off)	
	Dynamic mating surface $e$ $e$	Static mating surface $e$ $b$				Side surface $a$		Chamfer $f$
		Axial length $L$						
		$L < 4$	$4 \leq L < 5$	$5 \leq L < 6$	$L \geq 6$			
$S < 3,4$	$Ra\ 0,4$ $Rz\ 1,6$	$Ra\ 1,6$ visual in- spection $Rz\ 6,3$ visual in- spection	$Ra2\ 1,6$ $Rz2\ 6,3$	$Ra4\ 1,6$ $Rz4\ 6,3$	-	$Ra\ 1,6$ visual inspection $Rz\ 6,3$ visual inspection	$Ra\ 4$ visual in- spection  or $Rz\ 16$  visual in- spection	5,6
$3,4 \leq S < 5$		-	$Ra2\ 1,6$ $Rz2\ 6,3$	$Ra4\ 1,6$ $Rz4\ 6,3$	$Ra\ 1,6$ $Rz\ 6,3$	$Ra\ 2\ 1,6$ $Rz\ 2\ 6,3$		
$5 \leq S < 6$		-	-	-	$Ra\ 1,6$ $Rz\ 6,3$	$Ra\ 4\ 1,6$ $Rz\ 4\ 6,3$		
$S \geq 6$		-	-	$Ra4\ 1,6$ $Rz4\ 6,3$	$Ra\ 1,6$ $Rz\ 6,3$	$Ra\ 1,6$ $Rz\ 6,3$		

<sup>a</sup> Indication of surface roughness to [ISO 1302](#).  
<sup>b</sup> See also [Figures 2, 3, 4, 5](#) and [6](#). See [ISO 13715](#) for design of edges and undefined shapes.  
<sup>c</sup> The descriptions of *Ra*4 1,6 or *Rz*4 6,3 do not describe a surface roughness of *Ra* 41,6 or *Rz* 46,3. According to [ISO 1302](#) and [ISO 4288](#) they show four sampling lengths and that the roughness does not exceed 1,6 µm for *Ra* and 6,3 µm for *Rz*.  
A value of *Ra* 1,6 or *Rz* 6,3 can only be measured if the length to be measured is 5,6 mm or longer.  
<sup>d</sup> Special applications may require different surface roughness values.  
<sup>e</sup> Visual surface imperfections are not allowed on surfaces *b* and *e* (see [ISO 8785](#)).

9 Identification statement

Manufacturers are recommended to use the following statement in test reports, catalogues and sales literature when electing to conform with this standard:

"ISO 6195:2021, Fluid power systems and components — Cylinder-rod wiper-ring housings in reciprocating applications — Dimensions and tolerance."



## Bibliography

- [1] ISO 286 (all parts), *Geometrical product specifications (GPS) — ISO code system for tolerances on linear sizes*
- [2] [ISO 883](#), *Indexable hardmetal (carbide) inserts with rounded corners, without fixing hole — Dimensions*
- [3] [ISO 1302](#), *Geometrical Product Specifications (GPS) — Indication of surface texture in technical product documentation*
- [4] [ISO 3320](#), *Fluid power systems and components — Cylinder bores and piston rod diameters and area ratios — Metric series*
- [5] ISO 4287:1997/Amd 1:2009, *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters — Amendment 1: Peak count number*
- [6] [ISO 4288](#), *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Rules and procedures for the assessment of surface texture*
- [7] [ISO 5597](#), *Hydraulic fluid power — Cylinders — Dimensions and tolerances of housings for single-acting piston and rod seals in reciprocating applications*
- [8] ISO 6020 (all parts), *Hydraulic fluid power — Mounting dimensions for single rod cylinders, 16 MPa (160 bar) series*
- [9] [ISO 6022](#), *Hydraulic fluid power — Mounting dimensions for single rod cylinders, 25 MPa (250 bar) series*
- [10] [ISO 7425-2](#), *Hydraulic fluid power cylinders — Dimensions and tolerances of housings for elastomer-energized, plastic-faces seals — Part 2: Rod seal housings*
- [11] [ISO 8015](#), *Geometrical product specifications (GPS) — Fundamentals — Concepts, principles and rules*
- [12] [ISO 8785](#), *Geometrical Product Specification (GPS) — Surface imperfections — Terms, definitions and parameters*
- [13] [ISO 10762](#), *Hydraulic fluid power — Mounting dimensions for cylinders, 10 MPa (100 bar) series*
- [14] [ISO 13715](#), *Technical product documentation — Edges of undefined shape — Indication and dimensioning*





# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

## About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

## Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at [bsigroup.com/standards](https://bsigroup.com/standards) or contacting our Customer Services team or Knowledge Centre.

## Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at [bsigroup.com/shop](https://bsigroup.com/shop), where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

## Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

## Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

## Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to [bsigroup.com/subscriptions](https://bsigroup.com/subscriptions).

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit [bsigroup.com/shop](https://bsigroup.com/shop).

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email [cservices@bsigroup.com](mailto:cservices@bsigroup.com).

## Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

## Useful Contacts

### Customer Services

**Tel:** +44 345 086 9001

**Email:** [cservices@bsigroup.com](mailto:cservices@bsigroup.com)

### Subscriptions

**Tel:** +44 345 086 9001

**Email:** [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com)

### Knowledge Centre

**Tel:** +44 20 8996 7004

**Email:** [knowledgecentre@bsigroup.com](mailto:knowledgecentre@bsigroup.com)

### Copyright & Licensing

**Tel:** +44 20 8996 7070

**Email:** [copyright@bsigroup.com](mailto:copyright@bsigroup.com)

## BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

