



BSI Standards Publication

Vitreous and porcelain enamels — Determination of the resistance to abrasion

Part 2: Loss in mass after sub-surface abrasion

National foreword

This British Standard is the UK implementation of [ISO 6370-2:2020](#). It supersedes [BS ISO 6370-2:2011](#), which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee STI/36, Vitreous enamel coatings.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2020
Published by BSI Standards Limited 2020

ISBN 978 0 580 99975 8

ICS 25.220.50

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 29 February 2020.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL STANDARD

ISO
6370-2

Third edition
2020-02-10

Vitreous and porcelain enamels — Determination of the resistance to abrasion —

Part 2: Loss in mass after sub- surface abrasion

*Émaux vitrifiés — Détermination de la résistance à l'abrasion —
Partie 2: Perte de masse après abrasion de la couche superficielle*



Reference number
ISO 6370-2:2020(E)

© ISO 2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO’s member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	1
5	Reagents and materials	2
6	Apparatus	2
7	Test specimens	3
8	Procedure	3
9	Expression of results	4
10	Test report	4
Annex A (informative) Identification of the float-bath surface of the reference glass plates		5
Annex B (informative) Calculation of uncertainty of measurement of wear		7
Bibliography		9

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 107, *Metallic and other inorganic coatings*.

This third edition cancels and replaces the second edition ([ISO 6370-2:2011](http://www.iso.org/iso/6370-2:2011)), which has been technically revised. The main changes compared with the previous edition are as follows:

- terms and definitions have been added;
- sanidine (potassium feldspar) has been included as an additional abrasive option for testing;
- the requirements for steel balls have been amended.

A list of all parts in the ISO 6370 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Extensive tests have shown that, with the comparative method described in this document, the uncertainty of measurement of test results is $\pm 5\%$. Furthermore, absolute quantities for the amount of wear give little information, because abrasives used in practice differ considerably in their effect on enamelled surfaces. Each abrasion test with a standardized method can only be carried out with the aim of providing a general classification of various vitreous and porcelain enamels in relation to each other. Absolute quantities for the amount of wear are therefore not required.

Numerous tests have shown that the three required test periods of 30 min were sufficient to obtain comparable results. If the vitreous and porcelain enamel coat to be tested is thicker than 0,2 mm, it is not necessary to determine the loss in mass after each 30 min test period, because the abrasion under the conditions described in this document is directly proportional to the test duration.

Vitreous and porcelain enamels — Determination of the resistance to abrasion —

Part 2: Loss in mass after sub-surface abrasion

WARNING — This document may not be compliant with some countries' health and safety legislations and calls for the use of substances and/or procedures that may be injurious to health if adequate safety measures are not taken. This document does not address any health hazards, safety or environmental matters and legislations associated with its use. It is the responsibility of the user of this document to establish appropriate health, safety and environmentally acceptable practices.

1 Scope

This document specifies a test method for determining the resistance of vitreous and porcelain enamel coatings to abrasion by rubbing, grinding or other mechanical effects.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 648](#), *Laboratory glassware — Single-volume pipettes*

[ISO 3696](#), *Water for analytical laboratory use — Specification and test methods*

[ISO 6344-2](#), *Coated abrasives — Grain size analysis — Part 2: Determination of grain size distribution of macrogrits P12 to P220*

[ISO 6370-1:1991](#), *Vitreous and porcelain enamels — Determination of the resistance to abrasion — Part 1: Abrasion testing apparatus*

[ISO 28764](#), *Vitreous and porcelain enamels — Production of specimens for testing enamels on sheet steel, sheet aluminium and cast iron*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Principle

Mounting of three similarly enamelled test specimens and three reference glass plates in the testing apparatus. Simultaneous exposure of the separated test specimens and reference glass plates to the abrasion attack of a mixture of fused aluminium oxide grains, steel balls and water for three periods of

7 Test specimens

7.1 Prepare the test specimens in accordance with the International Standards for the appropriate basis metal.

Specimens for testing vitreous and porcelain enamels for sheet steel and cast iron shall be prepared in accordance with [ISO 28764](#).

7.2 Rinse each test specimen and reference glass plate with water ([5.2](#)) and wipe it thoroughly with ethanol ([5.1](#)). Dry the test specimens and the reference glass plates in the drying oven ([6.4](#)) for 2 h at $120\text{ }^{\circ}\text{C} \pm 5\text{ }^{\circ}\text{C}$. Remove them from the oven and allow them to stand for at least 2 h in the desiccators ([6.5](#)) and weigh each specimen to the nearest 0,2 mg (initial mass).

8 Procedure

8.1 Carry out one test with each set of at least three test specimens and three reference glass plates.

8.2 Fix the test specimens and the reference glass plates on the oscillating table of the abrasion testing apparatus ([6.1](#)) with the aid of the retaining rings, sealing rings and clamping devices, so that the cover coat sides of the test specimens and the float-bath surface (see [Annex A](#)) of the reference glass plates are facing the interior of the retaining rings (see [ISO 6370-1:1991](#), Figure 1).

8.3 Fill each retaining ring with an abrading charge and close it with the stopper. The abrading charge consists of the following:

- 80 g of steel balls ([5.3](#)) that are 4 mm in diameter;
- 60 g of steel balls ([5.3](#)) that are 3 mm in diameter;
- 35 g of steel balls ([5.3](#)) that are 2 mm in diameter;
- $20\text{ ml} \pm 0,2\text{ ml}$ of water ([5.2](#));
- $3\text{ g} + 0,01\text{ g}$ of abrasives ([5.4](#)).

The limiting deviations in mass for the balls: mass of each single ball.

8.4 Start the oscillating table of the abrasion testing apparatus for a period of $30\text{ min} \pm 1\text{ min}$, corresponding to $9\,000\text{ rotations} \pm 300\text{ rotations}$. Then, remove the specimens and reference glass plates, and thoroughly rinse the test specimens, the reference glass plates, the retaining rings and the sealing rings under running water. Dry the test specimens and reference glass plates in air and replace them on the abrasion testing apparatus with a fresh abrading charge (see [8.3](#)). The steel balls may be used again after thorough cleaning.

If the thickness of the enamel coat to be tested is less than 0,2 mm, it is recommended to weigh the test specimen before the next test period.

Start the oscillating table for a further period of 30 min and then repeat the whole procedure a third time. If the vitreous and porcelain enamel coat being tested has already disappeared, interrupt the test.

8.5 After three test periods of 30 min, remove the test specimens and the reference glass plates from the abrasion testing apparatus. Rinse them thoroughly under running water and then with distilled water ([5.2](#)). Dry the test specimens and the reference glass plates in the drying oven ([6.4](#)) for 2 h at

120 °C ± 5 °C. Then allow them to stand for at least 2 h in the desiccator (6.5) and weigh each to the nearest 0,2 mg (final mass).

A porous surface of the test specimen after abrasion can cause an increase in mass due to the absorption of water. This phenomenon shall be stated in the test report under any unusual features noted during the testing (see Clause 10).

9 Expression of results

9.1 Calculate, for each test specimen and reference glass plate, the loss in mass, Δm , in milligrams (mg).

Calculate the relative amount of wear w_r using Formula (1):

$$w_r = \frac{\Delta m_{S1} + \Delta m_{S2} + \Delta m_{S3}}{\Delta m_{R1} + \Delta m_{R2} + \Delta m_{R3}} \quad (1)$$

where

$\Delta m_{S1}, \Delta m_{S2}, \Delta m_{S3}$ are the respective losses in mass of the three test specimens S1, S2 and S3 tested;

$\Delta m_{R1}, \Delta m_{R2}, \Delta m_{R3}$ are the respective losses in mass of the three reference glass plates tested.

9.2 Calculate the value α for the test specimen tested and the reference glass plates tested using Formula (2):

$$\alpha = \frac{\Delta m_1 + \Delta m_2 + \Delta m_3}{(\Delta m_1^2 + \Delta m_2^2 + \Delta m_3^2 - \Delta m_1 \Delta m_2 - \Delta m_2 \Delta m_3 - \Delta m_1 \Delta m_3)^{1/2}} \quad (2)$$

The abrasion test is considered as reliable if, for each test specimen tested, $\alpha_S > 60$ and, for each reference glass plate tested, $\alpha_R > 60$.

If the values α_S and/or α_R are less than 60, carry out a further test with new test specimens.

For the calculation of uncertainty of measurement of wear, see Annex B.

10 Test report

The test report shall include the following information:

- a reference to this document, i.e. ISO 6370;
- a description of the test specimens;
- the date of the test;
- a reference to which abrasive (5.4) was used;
- the relative amount of wear, w_r ;
- in case of interruption, the duration of the abrasion test;
- any unusual features noted during the testing.

Annex A (informative)

Identification of the float-bath surface of the reference glass plates

A.1 General

The float-bath surface of the glass can be identified by one of methods given in [A.2](#) to [A.4](#).

A.2 Chemical method

A.2.1 Reagents

A.2.1.1 Etching solution, containing the following reagents, which are thoroughly mixed:

- 10 ml of concentrated hydrochloric acid;
- 10 ml of distilled water;
- 8 ml of 40 % (volume fraction) hydrofluoric acid.

A.2.1.2 Cacotheline, 0,1 % (volume fraction) solution in distilled water.

A.2.2 Procedure

Place 2 or 3 drops of the etching solution ([A.2.1.1](#)) on the surface, followed by 1 or 2 drops of the cacotheline solution ([A.2.1.2](#)).

A.2.3 Expression of results

A.2.3.1 Float-bath surface

In 5 s to 10 s, a purple colouration is observed.


A.2.3.2 Top surface

The solution remains yellow.

A.3 Ultraviolet method

Use a lamp with an ultraviolet filter giving a peak output in the range of wavelengths between 254 nm and 365 nm, arranged as shown in [Figure A.1](#).

When viewed from the angle shown in [Figure A.1](#) in a dark room, the float-bath surface exhibits a slight fluorescence.



Key
1 glass

Figure A.1 — Arrangement for the ultraviolet method

WARNING — Ultraviolet radiation in this region of the spectrum will damage the eyes and suitable protective goggles with an ultraviolet-filter shall be used.

A.4 Energy-dispersion-analysis method

Comparison of the two surfaces of the glass by energy dispersion analysis will reveal the tin content of the float-bath surface, which is not present on the other surface.

Annex B (informative)

Calculation of uncertainty of measurement of wear

The values α_S and α_R are closely connected with basic terms of the theory of error calculation.

To calculate the statistical error of the mean arithmetic values

$$\overline{\Delta m_S} = \frac{1}{3}(\Delta m_{S1} + \Delta m_{S2} + \Delta m_{S3})$$

and

$$\overline{\Delta m_R} = \frac{1}{3}(\Delta m_{R1} + \Delta m_{R2} + \Delta m_{R3})$$

according to the general formula

$$S_{\bar{x}}^2 = \frac{1}{n(n-1)} \left[\sum_{i=1}^n (x_i - \bar{x})^2 \right]$$

the following formulae are valid:

$$S_{\Delta m} = \frac{1}{3}(\Delta m_1^2 + \Delta m_2^2 + \Delta m_3^2 - \Delta m_1 \Delta m_2 - \Delta m_2 \Delta m_3 - \Delta m_1 \Delta m_3)^{1/2}$$

$$S_{\overline{\Delta m_S}} = \overline{\Delta m_S} \left(\frac{1}{\alpha_S} \right)$$

$$S_{\overline{\Delta m_R}} = \overline{\Delta m_R} \left(\frac{1}{\alpha_R} \right)$$

For a confidence level of 95 % of three measurements, the fractile of the Student-Fisher distribution is $t_{95} = 4,3$. Consequently, the following formulae are obtained if relative errors of the mean values of less than 7 % are required.

$$\frac{4,3 S_{\overline{\Delta m_S}}}{\overline{\Delta m_S}} \leq 0,07$$

$$\frac{4,3 S_{\overline{\Delta m_R}}}{\overline{\Delta m_R}} \leq 0,07$$

This leads directly to

$$\frac{4,3}{\alpha_S} \leq 0,07$$

$$\frac{4,3}{\alpha_R} \leq 0,07$$

Or, respectively,

$$\alpha_S > 60$$

and

$$\alpha_R > 60$$

According to the law of Gauss for the error propagation and assuming a probability of 90 %, the error for the determination of the relative amount of wear w_r is less than

$$\sqrt{(0,07)^2 + (0,07)^2} \approx 0,1 \text{ or } 10 \%$$

if the stated requirements for α_S and α_R are fulfilled.

Bibliography

- [1] [ISO 683-17](#), *Heat-treated steels, alloy steels and free-cutting steels — Part 17: Ball and roller bearing steels*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email cservices@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email: cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

