



BSI Standards Publication

Hydrodynamic plain journal bearings under steady-state conditions — Circular cylindrical bearings

Part 1: Calculation procedure

National foreword

This British Standard is the UK implementation of [ISO 7902-1:2020](#). It supersedes [BS ISO 7902-1:2013](#), which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee MCE/12, Plain bearings.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2020
Published by BSI Standards Limited 2020

ISBN 978 0 539 05809 3

ICS 21.100.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2020.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL STANDARD

ISO 7902-1

Third edition
2020-06-10

Hydrodynamic plain journal bearings under steady-state conditions — Circular cylindrical bearings —

Part 1: Calculation procedure

*Paliers lisses hydrodynamiques radiaux fonctionnant en régime
stabilisé — Paliers circulaires cylindriques —*

Partie 1: Méthode de calcul



Reference number
ISO 7902-1:2020(E)

© ISO 2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO’s member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and units	1
5 Basis of calculation, assumptions, and preconditions	5
5.1 Reynolds equation	5
5.2 Assumptions and preconditions	5
5.3 Boundary conditions	5
5.4 Basis of calculation	6
5.5 Permissible operational parameters	6
6 Calculation procedure	6
6.1 General	6
6.2 Freedom from wear	6
6.3 The limits of mechanical loading	7
6.4 The limits of thermal loading	7
6.5 Influencing factors	7
6.6 Reynolds number	7
6.7 Calculation factors	7
7 Definition of symbols	9
7.1 Load-carrying capacity	9
7.2 Frictional power loss	9
7.3 Lubricant flow rate	9
7.3.1 General	9
7.3.2 Lubricant feed elements	10
7.3.3 Lubrication grooves	10
7.3.4 Lubrication pockets	10
7.3.5 Lubricant flow rate	11
7.4 Heat balance	11
7.4.1 General	11
7.4.2 Heat dissipation by convection	12
7.4.3 Heat dissipation via the lubricant	12
7.5 Minimum lubricant film thickness and specific bearing load	13
7.6 Operational conditions	13
7.7 Further influencing factors	14
Annex A (informative) Calculation examples	17
Bibliography	32

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 123, *Plain bearings*, Subcommittee SC 8, *Calculation methods for plain bearings and their applications*.

This third edition cancels and replaces the second edition ([ISO 7902-1:2013](http://www.iso.org/iso/7902-1:2013)), which has been technically revised.

The main changes compared to the previous edition are as follows:

- subclause titles have been added;
- symbols have been corrected and added in [Table 1](#);
- calculation values in [Annex A](#) have been corrected;
- adjustments have been made to ISO/IEC Directives, Part 2:2018;
- typographical errors have been corrected.

A list of all parts in the ISO 7902 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Hydrodynamic plain journal bearings under steady-state conditions — Circular cylindrical bearings —

Part 1: Calculation procedure

1 Scope

This document specifies a calculation procedure for oil-lubricated hydrodynamic plain bearings, with complete separation of the shaft and bearing sliding surfaces by a film of lubricant, used for designing plain bearings that are reliable in operation.

It deals with circular cylindrical bearings having angular spans, Ω , of 360°, 180°, 150°, 120°, and 90°, the arc segment being loaded centrally. Their clearance geometry is constant except for negligible deformations resulting from lubricant film pressure and temperature.

The calculation procedure serves to provide dimensions and optimize plain bearings in turbines, generators, electric motors, gear units, rolling mills, pumps, and other machines. It is limited to steady-state operation, i.e. under continuously driven operating conditions, with the magnitude and direction of loading as well as the angular speeds of all rotating parts constant. It can also be applied if a full plain bearing is subjected to a constant force rotating at any speed. Dynamic loadings (i.e. those whose magnitude and direction vary with time), such as those that can result from vibration effects and instabilities of rapid-running rotors, are not taken into account.

NOTE Equivalent calculation procedures exist that enable operating conditions to be estimated and checked against acceptable conditions. The use of them is equally admissible.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 7902-2](#), *Hydrodynamic plain journal bearings under steady-state conditions — Circular cylindrical bearings — Part 2: Functions used in the calculation procedure*

[ISO 7902-3](#), *Hydrodynamic plain journal bearings under steady-state conditions — Circular cylindrical bearings — Part 3: Permissible operational parameters*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Symbols and units

Symbols and units are defined in [Figure 1](#) and [Table 1](#).

Symbol	Designation	Unit
F_f'	Frictional force in both the loaded and the unloaded area of the lubricant film	N
h	Local lubricant film thickness	m
h_{eff}	Effective lubricant film thickness	m
h_G	Depth of lubrication groove	m
h_{lim}	Minimum permissible lubricant film thickness	m
h_{min}	Minimum lubricant film thickness	m
h_P	Depth of lubrication pocket	m
H	Length of the total height of the pedestal bearing	m
k_A	Outer heat transmission coefficient	W/(m ² ·K)
N_B	Rotational frequency of the bearing	s ⁻¹
N_J	Rotational frequency of the shaft	s ⁻¹
p	Local lubricant film pressure	Pa
\bar{p}	Specific bearing load	Pa
p_{en}	Lubricant feed pressure	Pa
p_{lim}	Maximum permissible lubricant film pressure	Pa
\bar{p}_{lim}	Maximum permissible specific bearing load	Pa
P_f	Frictional power	W
P_f'	Frictional power in both the loaded and the unloaded area of the lubricant film	W
P_{th}	Heat flow rate	W
$P_{\text{th,amb}}$	Heat flow rate to the ambient	W
$P_{\text{th,f}}$	Heat flow rate due to frictional power	W
$P_{\text{th,L}}$	Heat flow rate in the lubricant	W
q_L	Coefficient related to lubricant flow rate due to feed pressure	1
q_P	Coefficient related to lubricant flow rate from pocket	1
Q	Lubricant flow rate	m ³ /s
Q_3	Lubricant flow rate due to hydrodynamic pressure	m ³ /s
Q_3^*	Lubricant flow rate parameter due to hydrodynamic pressure	1
Q_p	Lubricant flow rate due to feed pressure	m ³ /s
Q_p^*	Lubricant flow rate parameter due to feed pressure	1
Rz_B	Average peak-to-valley height of bearing sliding surface	m
Rz_J	Average peak-to-valley height of shaft mating surface	m
Re	Reynolds number	1
So	Sommerfeld number	1
So_u	Transition Sommerfeld number	1
T_{amb}	Ambient temperature	°C
T_B	Bearing temperature	°C
$T_{B,0}$	Assumed initial bearing temperature	°C
$T_{B,1}$	Calculated bearing temperature resulting from iteration procedure	°C
T_{eff}	Effective lubricant temperature	°C
T_{en}	Lubricant temperature at bearing entrance	°C
T_{ex}	Lubricant temperature at bearing exit	°C
$T_{\text{ex},0}$	Assumed initial lubricant temperature at bearing exit	°C
$T_{\text{ex},1}$	Calculated lubricant temperature at bearing exit	°C
T_J	Shaft temperature	°C

Symbol	Designation	Unit
T_{lim}	Maximum permissible bearing temperature	°C
\bar{T}_L	Mean lubricant temperature	°C
U_B	Linear velocity (peripheral speed) of bearing	m/s
U_J	Linear velocity (peripheral speed) of shaft	m/s
V_a	Air ventilating velocity	m/s
x	Coordinate parallel to the sliding surface in the circumferential direction	m
y	Coordinate perpendicular to the sliding surface	m
z	Coordinate parallel to the sliding surface in the axial direction	m
$\alpha_{l,B}$	Linear heat expansion coefficient of the bearing	K ⁻¹
$\alpha_{l,J}$	Linear heat expansion coefficient of the shaft	K ⁻¹
β	Attitude angle (angular position of the shaft eccentricity related to the direction of load)	°
ε	Relative eccentricity [$\varepsilon = 2e/(D - D_J)$]	1
ε_u	Transition eccentricity	1
η	Dynamic viscosity of the lubricant	Pa·s
η_{eff}	Effective dynamic viscosity of the lubricant	Pa·s
ν	Kinematic viscosity of the lubricant	m ² /s
ξ	Coefficient of resistance to rotation in the loaded area of the lubricant film	1
ξ'	Coefficient of resistance to rotation in both the loaded and the unloaded area of the lubricant film	1
ξ_G	Coefficient of resistance to rotation in the area of circumferential groove	1
ξ_P	Coefficient of resistance to rotation in the area of the pocket	1
ρ	Density of lubricant	kg/m ³
φ	Angular coordinate in the circumferential direction	rad
φ_1	Angular coordinate of pressure leading edge	rad
φ_2	Angular coordinate of pressure trailing edge	rad
ψ	Relative bearing clearance	1
$\bar{\psi}$	Mean relative bearing clearance	1
ψ_{eff}	Effective relative bearing clearance	1
ψ_{max}	Maximum relative bearing clearance	1
ψ_{min}	Minimum relative bearing clearance	1
ω_B	Angular velocity of bearing	s ⁻¹
ω_F	Angular velocity of rotating force	s ⁻¹
ω_h	Hydrodynamic angular velocity	s ⁻¹
ω_J	Angular velocity of shaft	s ⁻¹
Ω	Angular span of bearing segment	°
Ω_G	Angular span of lubrication groove	°
Ω_P	Angular span of lubrication pocket	°

5 Basis of calculation, assumptions, and preconditions

5.1 Reynolds equation

The basis of calculation is the numerical solution to Reynolds equation for a finite bearing length, taking into account the physically correct boundary conditions for the generation of pressure. Reynolds equation is defined as [Formula \(1\)](#).

$$\frac{\partial}{\partial x} \left(h^3 \frac{\partial p}{\partial x} \right) + \frac{\partial}{\partial z} \left(h^3 \frac{\partial p}{\partial z} \right) = 6\eta (U_J + U_B) \frac{\partial h}{\partial x} \quad (1)$$

See References [3] to [5] and References [13] to [16] for the derivation of Reynolds equation and References [6] to [8], [14] and [15] for its numerical solution.

5.2 Assumptions and preconditions

The following idealizing assumptions and preconditions are made, the permissibility of which has been sufficiently confirmed both experimentally and in practice.

- a) The lubricant corresponds to a Newtonian fluid.
- b) All lubricant flows are laminar.
- c) The lubricant adheres completely to the sliding surfaces.
- d) The lubricant is incompressible.
- e) The lubricant clearance gap in the loaded area is completely filled with lubricant. Filling up of the unloaded area depends on the way the lubricant is supplied to the bearing.
- f) Inertia effects, gravitational and magnetic forces of the lubricant are negligible.
- g) The components forming the lubrication clearance gap are rigid or their deformation is negligible; their surfaces are ideal circular cylinders.
- h) The radii of curvature of the surfaces in relative motion are large in comparison with the lubricant film thicknesses.
- i) The lubricant film thickness in the axial direction (z-coordinate) is constant.
- j) Fluctuations in pressure within the lubricant film normal to the bearing surfaces (y-coordinate) are negligible.
- k) There is no motion normal to the bearing surfaces (y-coordinate).
- l) The lubricant is isoviscous over the entire lubrication clearance gap.
- m) The lubricant is fed in at the start of the bearing liner or where the lubrication clearance gap is widest; the magnitude of the lubricant feed pressure is negligible in comparison with the lubricant film pressures.

5.3 Boundary conditions

The boundary conditions for the generation of lubricant film pressure fulfil the following continuity conditions:

- at the leading edge of the pressure profile: $p(\varphi_1, z) = 0$;
- at the bearing rim: $p(\varphi, z = \pm B/2) = 0$;

- at the trailing edge of the pressure profile: $p[\varphi_2(z), z] = 0$;
- $\partial p / \partial \varphi[\varphi_2(z), z] = 0$.

For some types and sizes of bearing, the boundary conditions may be specified.

In partial bearings, if [Formula \(2\)](#) is satisfied:

$$\varphi_2 - (\pi - \beta) < \frac{\pi}{2} \quad (2)$$

Then the trailing edge of the pressure profile lies at the outlet end of the bearing is:

$$p(\varphi = \varphi_2, z) = 0$$

5.4 Basis of calculation

The numerical integration of the Reynolds equation is carried out (possibly by applying transformation of pressure as suggested in References [5], [13] and [14]) by a transformation to a differential formula which is applied to a grid system of supporting points, and which results in a system of linear formulae. The number of supporting points is significant to the accuracy of the numerical integration; the use of a non-equidistant grid as given in References [8] and [15] is advantageous. After substituting the boundary conditions at the trailing edge of the pressure profile, integration yields the pressure distribution in the circumferential and axial directions.

The application of the similarity principle to hydrodynamic plain bearing theory results in dimensionless magnitudes of similarity for parameters of interest, such as load-carrying capacity, frictional behaviour, lubricant flow rate and relative bearing length. The application of magnitudes of similarity reduces the number of numerical solutions required of Reynolds equation specified in [ISO 7902-2](#). Other solutions may also be applied, provided they fulfil the conditions laid down in [ISO 7902-2](#) and are of a similar numerical accuracy.

5.5 Permissible operational parameters

[ISO 7902-3](#) includes permissible operational parameters towards which the result of the calculation shall be oriented in order to ensure correct functioning of the plain bearings.

In special cases, operational parameters deviating from [ISO 7902-3](#) may be agreed upon for specific applications.

6 Calculation procedure

6.1 General

Calculation is understood to mean determination of correct operation by computation using actual operating parameters (see [Figure 2](#)), which can be compared with operational parameters. The operating parameters determined under varying operating conditions shall therefore lie within the range of permissibility as compared with the operational parameters. To this end, all operating conditions during continuous operation shall be investigated.

6.2 Freedom from wear

Freedom from wear is guaranteed only if complete separation of the mating bearing parts is achieved by the lubricant. Continuous operation in the mixed friction range results in failure. Short-time operation in the mixed friction range, for example, starting up and running down machines with plain bearings is unavoidable and does not generally result in bearing damage. When a bearing is subjected to heavy load, an auxiliary hydrostatic arrangement may be necessary for starting up and running down at a

slow speed. Running-in and adaptive wear to compensate for deviations of the surface geometry from the ideal are permissible as long as they are limited in area and time and occur without overloading effects. In certain cases, a specific running-in procedure may be beneficial, depending on the choice of materials.

6.3 The limits of mechanical loading

The limits of mechanical loading are a function of the strength of the bearing material. Slight permanent deformations are permissible as long as they do not impair correct functioning of the plain bearing.

6.4 The limits of thermal loading

The limits of thermal loading result not only from the thermal stability of the bearing material but also from the viscosity-temperature relationship and by degradation of the lubricant.

6.5 Influencing factors

A correct calculation for plain bearings presupposes that the operating conditions are known for all cases of continuous operation. In practice, however, additional influences frequently occur, which are unknown at the design stage and cannot always be predicted. The application of an appropriate safety margin between the actual operating parameters and permissible operational parameters is recommended. Influences include, for example:

- spurious forces (e.g. out-of-balance, vibrations);
- deviations from the ideal geometry (e.g. machining tolerances, deviations during assembly);
- lubricants contaminated by, for example, dirt, water, air;
- corrosion, electrical erosion.

Data on other influencing factors are given in [7.7](#).

6.6 Reynolds number

The Reynolds number shall be used to verify that [ISO 7902-2](#), for which laminar flow in the lubrication clearance gap is a necessary condition, can be applied:

$$Re = \frac{\rho U_j \frac{C_{R,eff}}{2}}{\eta} = \frac{\pi D N_j \frac{C_{R,eff}}{2}}{\nu} \leq 41,3 \sqrt{\frac{D}{C_{R,eff}}} \quad (3)$$

In the case of plain bearings with $Re > 41,3 \sqrt{D/C_{R,eff}}$ (e.g. as a result of high peripheral speed), higher loss coefficients and bearing temperatures shall be expected. Calculations for bearings with turbulent flow cannot be carried out in accordance with this document.

6.7 Calculation factors

The plain bearing calculation takes into account the following factors (starting with the known bearing dimensions and operational data):

- the relationship between load-carrying capacity and lubricant film thickness;
- the frictional power rate;
- the lubricant flow rate;
- the heat balance.

All these factors are mutually dependent.

The solution is obtained using an iterative method; the sequence is outlined in the flow chart in [Figure 2](#).

For optimization of individual parameters, parameter variation can be applied; modification of the calculation sequence is possible.




Figure 2 — Outline of calculation

7 Definition of symbols

7.1 Load-carrying capacity

A characteristic parameter for the load-carrying capacity is the dimensionless Sommerfeld number, So :

$$So = \frac{F\psi_{\text{eff}}^2}{DB\eta_{\text{eff}}\omega_h} = So\left(\varepsilon, \frac{B}{D}, \Omega\right) \quad (4)$$

Values of So as a function of the relative eccentricity, ε , the relative bearing length, B/D , and the angular span of bearing segment, Ω , are given in [ISO 7902-2](#). The variables ω_h , η_{eff} , and ψ_{eff} take into account the thermal effects and the angular velocities of shaft, bearing, and bearing force (see [7.4](#) and [7.7](#)).

The relative eccentricity, ε , together with the attitude angle, β (see [ISO 7902-2](#)), describes the magnitude and position of the minimum thickness of lubricant film. For a full bearing ($\Omega = 360^\circ$), the oil should be introduced at the greatest lubricant clearance gap or, with respect to the direction of rotation, shortly before it. For this reason, it is useful to know the attitude angle, β .

7.2 Frictional power loss

Friction in a hydrodynamic plain bearing due to viscous shear stress is given by the coefficient of friction $f = F_f/F$ and the derived non-dimensional characteristics of frictional power loss ξ and f/ψ_{eff} :

$$\xi = \frac{F_f\psi_{\text{eff}}}{DB\eta_{\text{eff}}\omega_h} \quad (5)$$

$$\frac{f}{\psi_{\text{eff}}} = \frac{\xi}{So} \quad (6)$$

They are applied if the frictional power loss is encountered only in the loaded area of the lubricant film.

It is still necessary to calculate frictional power loss in both the loaded and unloaded areas. Then the values, f , F_f , ξ , and $\frac{f}{\psi_{\text{eff}}}$, are substituted by f' , F'_f , ξ' , and $\frac{f'}{\psi_{\text{eff}}}$, respectively in [Formulae \(5\)](#) and [\(6\)](#).

This means that the whole of the clearance gap is filled with lubricant.

The values of f/ψ_{eff} and f'/ψ_{eff} for various values of ε , B/D , and Ω are given in [ISO 7902-2](#). It also gives the approximation formulae, based on Reference [17], which are used to determine frictional power loss values in the bearings, taking account of the influence of lubrication pockets and grooves.

The frictional power in a bearing or the amount of heat generated is given by [Formulae \(7\)](#) and [\(8\)](#).

$$P_f = P_{\text{th},f} = fF \frac{D}{2} \omega_h \quad (7)$$

$$P'_f = f'F \frac{D}{2} \omega_h \quad (8)$$

7.3 Lubricant flow rate

7.3.1 General

The lubricant fed to the bearing forms a film of lubricant separating the sliding surfaces. The pressure build-up in this film forces lubricant out of the ends of the bearing. This is the proportion Q_3 of the lubricant flow rate, resulting from the build-up of hydrodynamic pressure.

$$Q_3 = D^3 \psi_{\text{eff}} \omega_h Q_3^* \quad (9)$$

where $Q_3^* = Q_3^*(\varepsilon, B/D, \Omega)$ is given in [ISO 7902-2](#).

There is also a flow of lubricant in the peripheral direction through the narrowest clearance gap into the diverging, pressure-free gap. For increased loading and with a small lubrication gap clearance, however, this proportion of the lubricant flow is negligible.

The lubricant feed pressure, p_{en} , forces additional lubricant out of the ends of the plain bearing. This is the amount Q_p of the lubricant flow rate resulting from feed pressure as defined by [Formula \(10\)](#).

$$Q_p = \frac{D^3 \psi_{\text{eff}}^3 p_{\text{en}}}{\eta_{\text{eff}}} Q_p^* \quad (10)$$

where $Q_p^* = Q_p^*(\varepsilon, B/D, \Omega)$ is given in [ISO 7902-2](#).

7.3.2 Lubricant feed elements


Lubricant feed elements are lubrication holes, lubrication grooves, and lubrication pockets. The lubricant feed pressure, p_{en} , should be markedly less than the specific bearing load, \bar{p} , to avoid additional hydrostatic loads. Usually, p_{en} lies between 0,05 MPa and 0,2 MPa. The depth of the lubrication grooves and lubrication pockets is considerably greater than the bearing clearance.

7.3.3 Lubrication grooves

Lubrication grooves are elements designed to distribute lubricant in the circumferential direction. The recesses machined into the sliding surface run circumferentially and are kept narrow in the axial direction. If lubrication grooves are located in the vicinity of pressure rise, the pressure distribution is split into two independent pressure “hills” and the load-carrying capacity is markedly reduced (see [Figure 3](#)). In this case, the calculation shall be carried out for half the load applied to each half bearing. However, because of the build-up of hydrodynamic pressure, Q_3 , only half of the lubricant flow rate shall be taken into account when balancing heat losses (see [7.4](#)), since the return into the lubrication groove plays no part in dissipating heat. It is more advantageous, for a full bearing, to arrange the lubrication groove in the unloaded part. The entire lubricant flow amount, Q_p , goes into the heat balance.

7.3.4 Lubrication pockets

Lubrication pockets are elements for distributing the lubricant over the length of the bearing. The recesses machined into the sliding surface are oriented in the axial direction and should be as short as possible in the circumferential direction. Relative pocket lengths should be such as $b_p/B < 0,7$. Although larger values increase the lubricant flow rate, the oil emerging over the narrow, restricting webs at the ends plays no part in dissipating heat. This is even more true if the end webs are penetrated axially. For full bearings ($\Omega = 360^\circ$), a lubrication pocket opposite to the direction of load as well as two lubrication pockets normal to the direction of loading are machined in. Since the lubricant flow rate, even in the unloaded part of the bearing, provides for the dissipation of frictional heat arising from shearing, the lubrication pockets shall be fully taken into account in the heat balance. For shell segments ($\Omega < 360^\circ$), the lubricant flow rate due to feed pressure through lubrication pockets at the inlet or outlet of the shell segment makes practically no contribution to heat dissipation, since the lubrication pockets are scarcely restricted at the segment ends and the greater proportion of this lubricant flow emerges directly.



Key

- 1 lubrication hole
- 2 lubrication groove

Figure 3 — Lubricant film pressure in bearings with lubrication groove

7.3.5 Lubricant flow rate

If the lubricant fills the loaded area of the bearing and there is no lubricant in the unloaded part, then the heat dissipation counts as lubricant flow rate in the loaded part only.

The influence of the type and the arrangement of the lubricant feed elements on the lubricant flow rate are dealt with in [ISO 7902-2](#).

The overall lubricant flow rate is given by

- for lubricant filling only in the loaded area of the bearing:

$$Q = Q_3 \quad (11)$$

- for lubricant filling in the whole circular lubrication clearance gap including unloaded part, i.e. 2π :

$$Q = Q_3 + Q_p \quad (12)$$

7.4 Heat balance

7.4.1 General

The thermal condition of the plain bearing can be obtained from the heat balance. The heat flow, $P_{th,f}$, arising from frictional power in the bearing, P_f , is dissipated via the bearing housing to the environment and the lubricant emerging from the bearing. In practice, one or other of the two types of heat dissipation dominates. By neglecting the other, an additional safety margin is obtained during the design stage. The following assumptions can be made:

- a) pressureless-lubricated bearings (e.g. ring lubrication) dissipate heat mainly through convection to the environment: $P_{th,f} = P_{th,amb}$;
- b) pressure-lubricated bearings dissipate heat mainly via the lubricant: $P_{th,f} = P_{th,L}$.

Calculation examples are introduced in [Annex A](#).

7.4.2 Heat dissipation by convection

Heat dissipation by convection takes place by thermal conduction in the bearing housing and radiation and convection from the surface of the housing to the environment. The complex processes during the heat transfer can be summed up by:

$$P_{th,amb} = k_A A (T_B - T_{amb}) \quad (13)$$

where

$$k_A = (15 \text{ to } 20) \text{ W}/(\text{m}^2 \cdot \text{K})$$

or, by ventilating the bearing housing with air at a velocity of $V_a > 1,2 \text{ m/s}$

$$k_A = 7 + 12\sqrt{V_a}$$

See References [5] and [16].

Should the area of the heat-emitting surface, A , of the bearing housing not be known exactly, the following can be used as an approximation

— for cylindrical housings:

$$A = 2\frac{\pi}{4}(D_H^2 - D^2) + \pi D_H B_H$$

— for pedestal bearings:

$$A = \pi H \left(B_H + \frac{H}{2} \right)$$

— for bearings in the machine structure:

$$A = (15 \text{ to } 20) DB$$

7.4.3 Heat dissipation via the lubricant

In the case of force-feed lubrication, heat dissipation is via the lubricant:

$$P_{th,L} = \rho c_p Q (T_{ex} - T_{en}) \quad (14)$$

For mineral lubricants, the volume-specific heat is given by:

$$\rho \times c_p = 1,8 \times 10^6 \text{ J}/(\text{m}^3 \cdot \text{K})$$

From the heat balance, it follows that $P_{th,f} = P_{th,amb}$ for pressureless-lubricated bearings and $P_{th,f} = P_{th,L}$ for pressure-lubricated bearings.

This gives bearing temperature, T_B (see Reference [17]), and lubricant outlet temperature, T_{ex} (see Reference [17]). The effective film lubricant temperature with reference to the lubricant viscosity is

- in the case of pure convection: $T_{eff} = T_B$, and
- in the case of heat dissipation via the lubricant: $T_{eff} = \bar{T}_L = 0,5 (T_{en} + T_{ex})$.

At high peripheral speed, it is possible to select, instead of these mean values, a temperature which lies nearer to the lubricant outlet temperature.

The values calculated for T_B and T_{ex} shall be checked for their permissibility by comparison with the permissible operational parameters, T_{lim} , given in [ISO 7902-3](#).

In the sequence of calculations, at first only the operational data T_{amb} or T_{en} are known, but not the effective temperature, T_{eff} , which is required at the start of the calculation. The solution is obtained by first starting the calculation using an estimated temperature rise, i.e.

a) $T_{B,0} - T_{amb} = 20 \text{ K}$

b) $T_{ex,0} - T_{en} = 20 \text{ K}$

and the corresponding operating temperatures, T_{eff} . From the heat balance, corrected temperatures, $T_{B,1}$ or $T_{ex,1}$, are obtained, which, by averaging with the temperatures previously assumed ($T_{B,0}$ or $T_{ex,0}$), are iteratively improved until the difference between the values with index 0 and 1 becomes negligibly small, for example 2 K. The condition then attained corresponds to the steady condition. During the iterative steps, the influencing factors given in [7.7](#) shall be taken into account. As a rule, the iteration converges rapidly. It can also be replaced by graphical interpolation in which, for calculating $P_{th,f}$ and $P_{th,amb}$ or $P_{th,L}$, several temperature differences are assumed. If the heat flows $P_{th,amb} = f(T_B)$ or $P_{th,L} = f(T_{ex})$ are plotted, then the steady condition is given by the intersection of the two curves (see [Figure A.1](#)).

7.5 Minimum lubricant film thickness and specific bearing load

The clearance gap, h , in a circular cylindrical journal bearing with the shaft offset is a function given by:

$$h = 0,5D\psi_{eff}(1 + \varepsilon \cos \varphi)$$

starting with $\varphi = \varphi_1$, in the widest clearance gap (see [Figure 1](#)).

The minimum lubricant film thickness

$$h_{min} = 0,5D\psi_{eff}(1 - \varepsilon) \quad (15)$$

shall be compared with the permissible operational parameter, h_{lim} , specified in [ISO 7902-3](#).

The specific bearing load:

$$\bar{p} = \frac{F}{DB} \quad (16)$$

shall be compared with the permissible operational parameter, p_{lim} , specified in [ISO 7902-3](#).

In partial bearings, if the follow formula is satisfied:

$$\varphi_2 - (\pi - \beta) < \frac{\pi}{2}$$

then

$$h_{min} = 0,5D\psi(1 + \varepsilon \cos \varphi_2)$$

7.6 Operational conditions

Should the plain bearing be operated under several, varying sets of operating conditions over lengthy periods, then they shall be checked for the most unfavourable \bar{p} , h_{min} , and T_B . First, a decision shall be

reached as to whether or not the bearing can be lubricated without pressure and whether or not the heat dissipation by convection suffices. The most unfavourable thermal case shall be investigated, which, as a rule, corresponds to an operating condition at high rotary frequency together with heavy loading. If, for pure convection, excessive bearing temperatures occur, which even by increasing the dimensions of the bearing or of the surface area of the housing to their greatest possible extent cannot be lowered to permissible values, then force-feed lubrication and oil cooling are necessary.

If an operating condition under high thermal loading (low dynamic lubricant viscosity) is followed directly by one with high specific bearing load and low rotary frequency, this new operating condition should be investigated while keeping the thermal condition from the preceding operating point.

The transition to mixed friction is due to contact of the roughness peaks of the shaft and bearing under the criteria for h_{lim} specified in [ISO 7902-3](#), whereby deformation is also to be taken into account. A transition eccentricity:

$$\varepsilon_u = 1 - \frac{h_{lim}}{\frac{D}{2}\psi_{eff}}$$

and a transition Sommerfeld number:

$$So_u = \frac{F\psi_{eff}^2}{DB\eta_{eff}\omega_h} = f\left(\varepsilon_u, \frac{B}{D}, \Omega\right)$$

(see [ISO 7902-2](#)) can be assigned to this value. Thus, the individual transition conditions (load, viscosity, and rotary speed) can be determined. The transition condition can be described by just three coexistent parameters. In order to be able to determine one of them, the two others shall be substituted in the manner appropriate to this condition. For rapid run-down of the machine, the thermal state corresponds mostly to the previous continuously driven operating condition of high thermal loading. If cooling is shut off immediately when the machine is switched off, this can result in an accumulation of heat in the bearing, so that a yet more unfavourable value shall be selected for h_{eff} . If the machine runs down slowly, lowering of the temperature of the lubricant or bearing is to be expected.

7.7 Further influencing factors

The calculation procedure applies to steady-state operation, in particular for loading that is constant in magnitude and direction and in which it is possible for the shaft and the bearing to rotate with uniform speed. The effective angular velocity is given by:

$$\omega_h = \omega_j + \omega_B \quad (17)$$

The calculation procedure, however, also applies for the case of a constant load which rotates at an angular velocity ω_F . In this case, the angular velocity is given by:

$$\omega_h = \omega_j + \omega_B - 2\omega_F$$

For an out-of-balance force rotating with the shaft ($\omega_F = \omega_j$), then:

$$\omega_h = -\omega_j + \omega_B$$

The absolute value of ω_h shall be used to calculate the Sommerfeld number. It shall be borne in mind that in the case where $\omega_h < 0$, the shaft eccentricity is at the angle $-\beta$ (see [Figure 4](#)).

NOTE All rotary motions and angular directions are positive with respect to the direction of shaft rotation.

The dynamic viscosity is strongly dependent on temperature. It is thus necessary to know the temperature dependence of the lubricant and its specification (see [ISO 3448](#)). The effective dynamic viscosity, η_{eff} , is determined by means of the effective lubricant film temperature, T_{eff} , that is η_{eff}

results from averaging temperatures T_{en} and T_{ex} and not from averaging the dynamic viscosities $\eta(T_{\text{en}})$ and $\eta(T_{\text{ex}})$.

The dynamic viscosity is also pressure-dependent, but to a lesser degree. For bearings in steady-state conditions and under the usual specific bearing loads, \bar{p} , the pressure dependence can, however, be neglected. This neglecting of pressure dependency represents an additional design factor of safety.

For non-Newtonian lubricants (intrinsically viscous oils, multi-range oils), reversible and irreversible fluctuations in viscosity occur as a function of the shear loading within the lubricant clearance gap and of the service life. These effects are investigated only for a few lubricants^[7] and are not taken into account in all parts of [ISO 7902](#).

The operation bearing clearance results from the fit and the thermal expansion behaviour of bearing and shaft. In the installed condition (20 °C), the relative bearing clearance is given by:

$$\psi_{\text{max}} = \frac{D_{\text{max}} - D_{\text{J,min}}}{D} \quad (18)$$

$$\psi_{\text{min}} = \frac{D_{\text{min}} - D_{\text{J,max}}}{D} \quad (19)$$

$$\bar{\psi} = 0,5 (\psi_{\text{max}} + \psi_{\text{min}}) \quad (20)$$

The deciding factor in the calculation is the effective relative bearing clearance, ψ_{eff} , at the effective lubricant film temperature, T_{eff} , which can be regarded (subject to the assumptions in [5.5](#)) as the mean temperature of bearing and shaft. Insofar as the coefficients of linear expansion of the shaft, $\alpha_{\text{I,J}}$, and of the bearing, $\alpha_{\text{I,B}}$, do not differ, the clearance when cold (20 °C) is equal to the clearance when hot (T_{eff}). Should shaft and bearing (bearing liner with housing) show different temperatures (T_{J} , T_{B}) due to external influences, then this shall be taken into account [see [Formula \(22\)](#)]. The linear expansion of the thin bearing layer can be neglected.

For coefficients of linear expansion which differ for shaft and bearing, the thermal change of the relative bearing clearance is given by:

$$\Delta\psi = (\alpha_{\text{I,B}} - \alpha_{\text{I,J}})(T_{\text{eff}} - 20\text{ °C}) \quad (21)$$

$$\Delta\psi = \alpha_{\text{I,B}}(T_{\text{B}} - 20\text{ °C}) - \alpha_{\text{I,J}}(T_{\text{J}} - 20\text{ °C}) \quad (22)$$

$$\psi_{\text{eff}} = \bar{\psi} + \Delta\psi \quad (23)$$

Permissible operational values for the bearing clearance are given in [ISO 7902-3](#).




Figure 4 — Definition of the attitude angle β

Annex A (informative)

Calculation examples

A.1 Example 1

A full bearing ($\Omega = 360^\circ$) with dimensions $D = 120$ mm and $B = 60$ mm, operated under a load $F = 36\,000$ N at a rotational frequency, N_J , $33,33\text{ s}^{-1}$ is to be investigated. It is assumed that this operating condition is the critical one for the heat balance. The bearing housing, of surface area $A = 0,3\text{ m}^2$, and the solid liner are made of aluminium alloy, the shaft being of steel. Oil is supplied via a hole with $d_L = 5$ mm, diametrically opposite the loaded area in the bearing liner, as shown in [Figure 2](#). The lubricant employed is an oil of viscosity grade ISO VG 100 (see [ISO 3448](#)). The lubricant has the temperature dependence shown in [Table A.1](#). First of all, an investigation is to be made as to whether the bearing can perform without force-feed lubrication. In this case, heat dissipation occurs only by convection. The ambient temperature should be $T_{\text{amb}} = 40\text{ }^\circ\text{C}$ and the maximum permissible bearing temperature should be $T_{\text{lim}} = 70\text{ }^\circ\text{C}$.

Should T_{lim} be exceeded, then force-feed lubrication with external oil cooling is to be provided. In such a case, it is assumed that the lubricant is fed to the bearing at an overpressure of $p_{\text{en}} = 5 \times 10^5$ Pa and a lubricant inlet temperature of $T_{\text{en}} = 58\text{ }^\circ\text{C}$.

Dimensions and operational data

Bearing force	$F = 36\,000\text{ N}$
Rotational frequency of shaft	$N_J = 33,33\text{ s}^{-1}$
Rotational frequency of bearing	$N_B = 0\text{ s}^{-1}$
Angular span	$\Omega = 360^\circ$
Maximum bore of bearing	$D_{\text{max}} = 120,070 \times 10^{-3}\text{ m}$
Minimum bore of bearing	$D_{\text{min}} = 120,050 \times 10^{-3}\text{ m}$
Lubrication hole diameter	$d_L = 5 \times 10^{-3}\text{ m}$
Maximum diameter of shaft	$D_{J,\text{max}} = 119,950 \times 10^{-3}\text{ m}$
Minimum diameter of shaft	$D_{J,\text{min}} = 119,930 \times 10^{-3}\text{ m}$
Relative bearing length	$B/D = 0,5$
Mean peak-to-valley height of bearing	$Rz_B = 2 \times 10^{-6}\text{ m}$
Mean peak-to-valley height of shaft	$Rz_J = 1 \times 10^{-6}\text{ m}$
Coefficient of linear expansion of bearing	$\alpha_{l,B} = 23 \times 10^{-6}\text{ K}^{-1}$
Coefficient of linear expansion of shaft	$\alpha_{l,J} = 11 \times 10^{-6}\text{ K}^{-1}$
Lubricant oil	ISO VG 100

Table A.1 — Temperature dependence of ISO VG 100

T_{eff} °C	$\eta_{\text{eff}}(T_{\text{eff}})$ Pa·s
40	0,098
50	0,057
60	0,037
70	0,025

Area of heat-emitting surface of the bearing housing	$A = 0,3 \text{ m}^2$
Heat transfer coefficient	$k_A = 20 \text{ W}/(\text{m}^2\cdot\text{K})$
Ambient temperature	$T_{\text{amb}} = 40 \text{ °C}$
Lubricant inlet temperature for force-feed lubrication	$T_{\text{en}} = 58 \text{ °C}$
Lubrication feed overpressure for force-feed lubrication	$p_{\text{en}} = 5 \times 10^5 \text{ Pa}$
Specific heat by volume of the lubricant	$\rho \times c_p = 1,8 \times 10^6 \text{ J}/(\text{m}^3\cdot\text{K})$

Limiting values

Maximum permissible specific bearing load	$\bar{p}_{\text{lim}} = 10 \times 10^6 \text{ Pa}$
Maximum permissible bearing temperature	$T_{\text{lim}} = 70 \text{ °C}$
Minimum permissible lubricant film thickness	$h_{\text{lim}} = 9 \times 10^{-6} \text{ m}$

Calculation based on the flow chart (see [Figure 2](#))

Check the laminar flow [see [Formula \(3\)](#)] at an assumed bearing temperature $T_{\text{B},0} = 60 \text{ °C}$ and an assumed lubricant density $\rho = 900 \text{ kg}/\text{m}^3$:

$$Re = \frac{\pi \times 120 \times 10^{-3} \times 33,33 \times 1,48 \times 10^{-3} \times 120 \times 10^{-3} \times 900}{2 \times 0,037} = 27,14$$

$$< 41,3 \times \sqrt{\frac{120 \times 10^{-3}}{1,48 \times 10^{-3} \times 120 \times 10^{-3}}} = 1\,073,5$$

$$Re = 27,14 < 1\,073,5$$

Using [Formula \(16\)](#):

$$\bar{p} = \frac{36\,000}{120 \times 10^{-3} \times 60 \times 10^{-3}} = 5 \times 10^6 \text{ Pa}$$

The specific bearing \bar{p} is permissible, since $\bar{p} < \bar{p}_{\text{lim}}$.

Heat dissipation by convection

Assumed initial bearing temperature:

$$T_{\text{B},0} = T_{\text{eff}} = 60 \text{ °C}$$

Effective dynamic viscosity of the lubricant at $T_{\text{eff}} = 60 \text{ °C}$ from the input parameters:

$$\eta_{\text{eff}} = 0,037 \text{ Pa}\cdot\text{s}$$

Relative bearing clearances [see [Formulae \(18\)](#), [\(19\)](#), and [\(20\)](#)]:

$$\psi_{\text{max}} = \frac{(120,070 - 119,930) \times 10^{-3}}{120 \times 10^{-3}} = 1,1667 \times 10^{-3}$$

$$\psi_{\text{min}} = \frac{(120,050 - 119,950) \times 10^{-3}}{120 \times 10^{-3}} = 0,8333 \times 10^{-3}$$

$$\bar{\psi} = 0,5 \times (1,1667 + 0,8333) \times 10^{-3} = 10^{-3}$$

Thermal change of the relative bearing clearance [see [Formula \(21\)](#)]:

$$\Delta\psi = (23 - 11) \times 10^{-6} \times (60 - 20) = 0,48 \times 10^{-3}$$

Effective relative bearing clearance [see [Formula \(23\)](#)]:

$$\psi_{\text{eff}} = (1 + 0,48) \times 10^{-3} = 1,48 \times 10^{-3}$$

Effective angular velocity [see [Formula \(17\)](#)]:

— Angular velocity of the shaft:

$$\omega_{\text{J}} = 2 \times \pi \times N_{\text{J}} = 209,42 \text{ s}^{-1}$$

— Angular velocity of the bearing:

$$\omega_{\text{B}} = 0$$

$$\omega_{\text{h}} = 209,42 + 0 = 209,42 \text{ s}^{-1}$$

Sommerfeld number [see [Formula \(4\)](#)]:

$$So = \frac{36\,000 \times 1,48^2 \times 10^{-6}}{120 \times 10^{-3} \times 60 \times 10^{-3} \times 0,037 \times 209,42} = 1,413$$

Relative eccentricity (see [ISO 7902-2](#)):

$$\varepsilon = f\left(So, \frac{B}{D}, \Omega \right) = 0,773$$

Minimum lubricant film thickness [see [Formula \(15\)](#) and [Figure 2](#)]:

$$h_{\text{min}} = 0,5 \times 120 \times 10^{-3} \times 1,48 \times 10^{-3} \times (1 - 0,773) = 20,2 \times 10^{-6} \text{ m}$$

Specific coefficient of friction [see [Formula \(5\)](#) and [ISO 7902-2](#)]:

$$\frac{f'}{\psi_{\text{eff}}} = f\left(So, \frac{B}{D}, \Omega \right) = 3,68$$

Coefficient of friction:

$$f' = \frac{f'}{\psi_{eff}} \times \psi_{eff} = 3,68 \times 1,48 \times 10^{-3} = 5,45 \times 10^{-3}$$

Heat flow due to frictional power in bearing [see [Formula \(7\)](#)]:

$$P_{th,f} = 5,45 \times 10^{-3} \times 36\,000 \times \frac{120 \times 10^{-3}}{2} \times 209,42 = 2\,465,3 \text{ N}\cdot\text{m/s} = 2\,465,3 \text{ W}$$

Heat flow rate via bearing housing and shaft to the environment [see [Formula \(13\)](#)]

$$P_{th,amb} = 20 \times 0,3 \times (T_{B,1} - 40)$$

From $P_{th,f} = P_{th,amb}$ it follows that

$$T_{B,1} = \frac{2\,465,3}{20 \times 0,3} + 40 = 450,9 \text{ }^{\circ}\text{C}$$

Since $T_{B,1} > T_{B,0}$, the assumption of a bearing temperature of $T_{B,0} = 60 \text{ }^{\circ}\text{C}$ shall be corrected.

Improved assumption of the bearing temperature:

$$T_{B,0}^{i+1} = T_{B,0}^i + 0,2(T_{B,1}^i - T_{B,0}^i) = 60 + 0,2 \times (450,9 - 60) = 138,18$$

NOTE The assumption can be presented in alternative ways.

The further steps of the iteration are given in [Table A.2](#). In the sixth step of the calculation, the difference between the assumed bearing temperature, $T_{B,0}$, and the calculated bearing temperature, $T_{B,1}$, is less than $1 \text{ }^{\circ}\text{C}$. The bearing temperature, T_B , has thus been calculated to a sufficient degree of accuracy.

Since $T_B > T_{lim}$, heat dissipation by convection does not suffice. This bearing has therefore to be cooled by the lubricant (force-feed lubrication).

Table A.2 — Results of iterative calculations for heat dissipation by convection

Variable	Unit	Step of the calculation					
		1	2	3	4	5	6
$T_{B,0} = T_{eff}$	$^{\circ}\text{C}$	60	138,2	135,8	134,7	134	133,8
η_{eff}	$\text{Pa}\cdot\text{s}$	0,037	0,003 6	0,003 8	0,003 9	0,004	0,004 1
ψ_{eff}	1	$1,48 \times 10^{-3}$	$2,418 \times 10^{-3}$	$2,39 \times 10^{-3}$	$2,376 \times 10^{-3}$	$2,368 \times 10^{-3}$	$2,365 \times 10^{-3}$
So	1	1,413	38,78	35,89	34,3	33,47	32,57
ε	1	0,773	0,977	0,974	0,973 8	0,973	0,972
h_{min}	m	$20,2 \times 10^{-6}$	$3,34 \times 10^{-6}$	$3,73 \times 10^{-6}$	$3,74 \times 10^{-6}$	$3,84 \times 10^{-6}$	$3,97 \times 10^{-6}$
f'/ψ_{eff}	1	3,68	0,47	0,501	0,508	0,52	0,528
P_f	W	2 465,3	515,7	542,8	546	556,4	565,4
$T_{B,1}$	$^{\circ}\text{C}$	450,9	126,0	130,5	131	132,7	134,2
$T_{B,0}^{i+1}$	$^{\circ}\text{C}$	138,2	135,8	134,7	134	133,8	

Heat dissipation via the lubricant (force-feed lubrication)

Assumed initial lubricant outlet temperature:

$$T_{ex,0} = T_{en} + 20 \text{ }^{\circ}\text{C} = 78 \text{ }^{\circ}\text{C}$$

Effective lubricant film temperature (see [7.4](#)):

$$T_{\text{eff}} = 0,5 \times (58 + 78) = 68 \text{ }^{\circ}\text{C}$$

Effective dynamic viscosity of the lubricant at $T_{\text{eff}} = 68 \text{ }^{\circ}\text{C}$ from the given parameters:

$$\eta_{\text{eff}} = 0,0271 \text{ Pa}\cdot\text{s}$$

Thermal modification of the relative bearing clearance [see [Formula \(21\)](#)]:

$$\Delta\psi = (23 - 11) \times 10^{-6} \times (68 - 20) = 0,576 \times 10^{-3}$$

Effective relative bearing clearance [see [Formula \(23\)](#)]:

$$\psi_{\text{eff}} = (1 + 0,576) \times 10^{-3} = 1,576 \times 10^{-3}$$

Sommerfeld number [see [Formula \(4\)](#)]:

$$So = \frac{36\,000 \times 1,576^2 \times 10^{-6}}{120 \times 10^{-3} \times 60 \times 10^{-3} \times 0,0271 \times 209,42} = 2,188$$

Relative eccentricity (see [ISO 7902-2](#)):

$$\varepsilon = f\left(So, \frac{B}{D}, \Omega \right) = 0,825$$

Minimum lubricant film thickness [see [Formula \(15\)](#) and [Figure 2](#)]:

$$h_{\text{min}} = 0,5 \times 120 \times 10^{-3} \times 1,576 \times 10^{-3} \times (1 - 0,825) = 16,55 \times 10^{-6} \text{ m}$$

Specific coefficient of friction [see [Formula \(6\)](#) and [ISO 7902-2](#)]:

$$\frac{f'}{\psi_{\text{eff}}} = \frac{f'}{\psi_{\text{eff}}}\left(So, \frac{B}{D}, \Omega \right) = 2,78$$

Coefficient of friction:

$$f' = \frac{f'}{\psi_{\text{eff}}} \times \psi_{\text{eff}} = 2,78 \times 1,576 \times 10^{-3} = 4,381 \times 10^{-3}$$

Heat flow rate due to frictional power in bearing [see [Formula \(7\)](#)]:

$$P_{\text{th},f} = 4,381 \times 10^{-3} \times 36\,000 \times \frac{120 \times 10^{-3}}{2} \times 209,42 = 1\,981,7 \text{ N}\cdot\text{m/s} = 1\,981,7 \text{ W}$$

$$Q_3 = 120^3 \times 10^{-9} \times 1,576 \times 10^{-3} \times 209,42 \times 0,0968 = 55,21 \times 10^{-6} \text{ m}^3/\text{s}$$

Lubricant flow rate due to feed pressure [see [ISO 7902-2:2020](#), Formula (6)]:

$$q_L = 1,204 + 0,368 \times \frac{5}{60} - 1,046 \times \left(\frac{5}{60} \right)^2 + 1,942 \times \left(\frac{5}{60} \right)^3 = 1,229$$

$$Q_p^* = \frac{\pi}{48} \times \frac{(1 + 0,825)^3}{\ln\left(\frac{60}{5} \right) \times 1,229} = 0,1303$$

$$Q_p = \frac{120^3 \times 10^{-9} \times 1,576^3 \times 10^{-9} \times 5 \times 10^5}{0,027\ 1} \times 0,130\ 3 = 16,26 \times 10^{-6}\ \text{m}^3/\text{s}$$

Lubricant flow rate [see [Formula \(12\)](#)]:

$$Q = (55,21 + 16,26) \times 10^{-6} = 71,47 \times 10^{-6}\ \text{m}^3/\text{s}$$

Heat flow rate via the lubricant [see [Formula \(14\)](#)]:

$$P_{th,L} = 1,8 \times 10^6 \times 71,47 \times 10^{-6} \times (T_{ex} - 58)$$

Since $P_{th,f} = P_{th,L}$

$$T_{ex,1} = \frac{1\ 981,7}{1,8 \times 10^6 \times 71,47 \times 10^{-6}} + 58 = 73,4\ ^\circ\text{C}$$

Since $T_{ex,1} < T_{ex,0}$, the assumption of a lubricant outlet temperature of $T_{ex,0} = 78\ ^\circ\text{C}$ shall be corrected.

Improved assumption of the lubricant outlet temperature:

$$T_{ex,0} = 0,5 \times (78 + 73,4) = 75,7\ ^\circ\text{C}$$

The further steps of the iteration are given in [Table A.3](#).

Table A.3 — Results of iterative calculations for heat dissipation via the lubricant in full bearing

Variable	Unit	Step of the calculation		
		1	2	3
T_{en}	$^\circ\text{C}$	58	58	58
$T_{ex,0}$	$^\circ\text{C}$	78	75,7	74,9
T_{eff}	$^\circ\text{C}$	68	66,85	66,45
η_{eff}	$\text{Pa}\cdot\text{s}$	0,027 1	0,028 3	0,028 8
ψ_{eff}	1	$1,576 \times 10^{-3}$	$1,562 \times 10^{-3}$	$1,557 \times 10^{-3}$
So	1	2,196	2,058	2,01
ε	1	0,825 4	0,824 6	0,818
h_{min}	m	$16,55 \times 10^{-6}$	$16,49 \times 10^{-6}$	17×10^{-6}
f'/ψ_{eff}	1	2,78	2,84	2,9
P_f	W	1 981,7	2 006,6	2 042,3
Q_3	m^3/s	$55,21 \times 10^{-6}$	$54,55 \times 10^{-6}$	$54,2 \times 10^{-6}$
Q_p	m^3/s	$16,32 \times 10^{-6}$	$15,14 \times 10^{-6}$	$14,58 \times 10^{-6}$
Q	m^3/s	$71,53 \times 10^{-6}$	$69,69 \times 10^{-6}$	$68,78 \times 10^{-6}$
$T_{ex,1}$	$^\circ\text{C}$	73,4	74	74,5
$T_{ex,0}$	$^\circ\text{C}$	75,7	74,9	

In the third step of the calculation, the difference between the assumed initial lubricant outlet temperature, $T_{ex,0}$, and the calculated lubricant outlet temperature, $T_{ex,1}$, is smaller than 1 °C. The lubricant outlet temperature, T_{ex} , has therefore been calculated to a sufficient degree of accuracy.

Since $T_{ex} < T_{lim}$, the lubricant outlet temperature is permissible.

Since $h_{min} > h_{lim}$, the minimum lubricant film thickness is permissible.

Instead of the iteration calculation, it is possible to use graphical interpolation. This is done by performing the calculation for a series of assumed temperatures, T_B or T_{ex} , expected (which cover the range of the expected solution).

In [Table A.4](#), all intermediate results for the case of heat dissipation via the lubricant (force-feed lubrication) are given. The fourth step of the calculation gives the same values as the graphical solution shown in [Figure A.1](#).

Table A.4 — Second results of iterative calculations for heat dissipation via the lubricant in full bearing

Variable	Unit	Step of the calculation			
		1	2	3	4
T_{en}	°C	58	58	58	58
T_{ex}	°C	62	82	102	74,87
T_{eff}	°C	60	70	80	66,44
η_{eff}	Pa·s	0,037	0,025	0,018	0,028 7
ψ_{eff}	1	$1,48 \times 10^{-3}$	$1,6 \times 10^{-3}$	$1,72 \times 10^{-3}$	$1,557 \times 10^{-3}$
So	1	1,413	2,445	3,920	2,02
ε	1	0,773	0,838 3	0,880 1	0,818
h_{min}	m	$20,2 \times 10^{-6}$	$15,6 \times 10^{-6}$	$12,4 \times 10^{-6}$	17×10^{-6}
f'/ψ_{eff}	1	3,68	2,572	1,89	2,895
P_f	W	2 465,3	1 863,7	1 470,13	2 040,09
Q	m ³ /s	$57,94 \times 10^{-6}$	$76,05 \times 10^{-6}$	$98,91 \times 10^{-6}$	$69,13 \times 10^{-6}$
$P_{th,L}$	W	417,2	3 285,36	7 833,7	2 099,2




Figure A.1 — Graphical solution for heat dissipation via lubricant in full bearing

A.2 Example 2

A partial bearing with dimensions $D = 1\,010\text{ mm}$ and $B = 758\text{ mm}$ ($\Omega = 150^\circ$) lubricated via a lubrication pocket, as shown in [Figure A.2](#), with slight overpressure. According to [7.3](#), the lubricant flow rate Q_p plays no part in the heat balance. Heat dissipation is thus due to the lubricant flow rate, Q_3 , alone, as a result of generation of internal pressure. The lubricant inlet temperature is $T_{\text{en}} = 24\text{ °C}$. There is no difference in the thermal expansion between shaft, bearing liner, and bearing housing. The lubricant has the temperature dependence shown in [Table A.5](#).

Dimensions and operational data

Bearing force	$F = 10^6 \text{ N}$
Rotational frequency of shaft	$N_J = 1,428 \text{ 3 s}^{-1}$
Angular velocity of shaft	$\omega_J = \omega_h = 8,974 \text{ s}^{-1}$
Angular span	$\Omega = 150^\circ$
Bearing bore	$D = 1\,010 \times 10^{-3} \text{ m}$
Mean relative bearing clearance	$\bar{\psi} = 10^{-3}$
Thermal modification of the relative bearing clearance	$\Delta\psi = 0$
Relative bearing length	$B/D = 0,75$
Lubricant oil	ISO VG 46

Table A.5 — Temperature dependence of ISO VG 46

T_{eff} °C	$\eta_{\text{eff}}(T_{\text{eff}})$ Pa·s
20	0,132 4
30	0,072 1
40	0,043

Lubricant inlet temperature for force-feed lubrication	$T_{\text{en}} = 24 \text{ }^\circ\text{C}$
Specific heat by volume of the lubricant	$\rho \times c_p = 1,8 \times 10^6 \text{ J}/(\text{m}^3\cdot\text{K})$

Limiting values

Maximum permissible specific bearing load	$\bar{p}_{\text{lim}} = 10 \times 10^6 \text{ Pa}$
Maximum permissible bearing temperature	$T_{\text{lim}} = 70 \text{ }^\circ\text{C}$
Minimum permissible lubrication film thickness	$h_{\text{lim}} = 9 \times 10^{-6} \text{ m}$




Figure A.2 — Partial bearing lubricated via pocket

Calculation based on the flow chart (see [Figure 2](#))

Check the laminar flow [see [Formula \(3\)](#)] at an assumed effective lubricant film temperature $T_{\text{eff}} = 40\text{ °C}$ and an assumed lubricant density $\rho = 900\text{ kg/m}^3$:

$$Re = \frac{\pi \times 1010 \times 10^{-3} \times 1,4283 \times 10^{-3} \times 1010 \times 10^{-3} \times 900}{2 \times 0,043} = 47,9$$

$$< 41,3 \times \sqrt{\frac{1010 \times 10^3}{10^{-3} \times 1010 \times 10^3}} = 1306$$

$$Re = 47,9 < 1306$$

Flow is laminar. Thus, all parts of [ISO 7902](#) are applicable in this case.

From [Formula \(16\)](#):

$$\bar{p} = \frac{10^6}{758 \times 10^{-3} \times 1010 \times 10^{-3}} = 1,306 \times 10^6\text{ Pa}$$

The specific bearing load \bar{p} is permissible, since $\bar{p} < \bar{p}_{\text{lim}}$

Heat dissipation is via the lubricant.

[Table A.6](#) gives the intermediate results in the individual steps of the calculation. In the fourth step of the calculation, the difference between the assumed initial lubricant outlet temperature, $T_{\text{ex},0}$, and the calculated outlet temperature, $T_{\text{ex},1}$, is less than 1 °C . The lubricant outlet temperature, T_{ex} , has therefore been calculated to a sufficient degree of accuracy.

Since $T_{\text{ex}} < T_{\text{lim}}$, the lubricant outlet temperature is permissible. Since $h_{\text{min}} > h_{\text{lim}}$, the minimum lubricant film thickness is permissible

Table A.6 — Results of iterative calculations for heat dissipation via the lubricant in partial bearing

Variable	Unit	Step of the calculation			
		1	2	3	4
T_{en}	°C	24	24	24	24
$T_{\text{ex},0}$	°C	44	38,5	36,2	35,2
T_{eff}	°C	34	31,3	30,1	29,6

Variable	Unit	Step of the calculation			
		1	2	3	4
η_{eff}	Pa·s	0,058	0,07	0,074	0,077
So	1	2,507	2,079	1,967	1,89
ε	1	0,798	0,767	0,758	0,75
h_{min}	m	$102,01 \times 10^{-6}$	$117,67 \times 10^{-6}$	$122,21 \times 10^{-6}$	$126,25 \times 10^{-6}$
f'/ψ_{eff}	1	1,65	1,822	1,87	1,92
P_f	W	7 477,6	8 248	8 474,6	8 701,2
Q_3	m ³ /s	$46,04 \times 10^{-5}$	$46,60 \times 10^{-5}$	$46,69 \times 10^{-5}$	$46,88 \times 10^{-5}$
$T_{\text{ex},1}$	°C	33	33,8	34,1	34,3
$T_{\text{ex},0}$	°C	38,5	36,2	35,2	

A.3 Example 3

A partial bearing with angular span $\Omega = 150^\circ$ is to be investigated; the lubricant is supplied to the loaded area of the bearing under overpressure via the upper half, as shown in [Figure A.3](#).

The upper half has a circumferential groove. Two lubrication pockets are located at the joint face at $\pm 90^\circ$ to the application of the load; one of the pockets is a feeding one.

Heat is dissipated via the lubricant and, according to 7.4, overall lubricant flow rate is to be calculated from [Formulae \(11\)](#) and [\(12\)](#). There is no difference in expansion between shaft, bearing, and bearing housing.

The lubricant has the temperature dependence shown in [Table A.7](#).




Figure A.3 — Partial bearing with circumferential groove in upper half

Dimensions and operational data

Bearing force	$F = 18\,000\text{ N}$
Rotational frequency of shaft	$N_J = 25\text{ s}^{-1}$
Angular velocity of shaft	$\omega_J = \omega_h = 157\text{ s}^{-1}$
Angular span	$\Omega = 150^\circ$
Bearing bore	$D = 200 \times 10^{-3}\text{ m}$
Mean relative bearing clearance	$\bar{\psi} = 2 \times 10^{-3}$
Thermal modification of the relative bearing clearance	$\Delta\psi = 0$
Relative bearing length	$B/D = 0,5$
Width of a 180° lubrication groove	$b_G = 30 \times 10^{-3}\text{ m}$
Depth of a lubrication groove	$h_G = 2,5 \times 10^{-3}\text{ m}$
Width of the lubrication pocket	$b_P = 60 \times 10^{-3}\text{ m}$
Depth of the lubrication pocket	$h_P = 2,5 \times 10^{-3}\text{ m}$
Lubricant oil	ISO VG 32

Table A.7 — Temperature dependence of ISO VG 32

T_{eff} °C	$\eta_{\text{eff}}(T_{\text{eff}})$ Pa·s
40	0,031
50	0,022
60	0,014
70	0,009 4

Lubricant inlet temperature for force-feed lubrication	$T_{\text{en}} = 40\text{ °C}$
Lubricant feed overpressure for force-feed lubrication	$p_{\text{en}} = 0,5 \times 10^5\text{ Pa}$
Specific heat by volume of the lubricant	$\rho \times c_p = 1,8 \times 10^{-6}\text{ J}/(\text{kg}\cdot\text{K})$

Limiting values

Maximum permissible specific bearing load	$\bar{p}_{\text{lim}} = 10 \times 10^6\text{ Pa}$
Maximum permissible bearing temperature	$T_{\text{lim}} = 80\text{ °C}$
Minimum permissible lubrication film thickness	$h_{\text{lim}} = 20 \times 10^{-6}\text{ m}$

Calculation based on the flow chart (see [Figure 2](#))

Check the laminar flow [see [Formula \(3\)](#)] at an assumed bearing temperature $T_{B,0} = 60\text{ °C}$ and an assumed lubricant density $\rho = 900\text{ kg/m}^3$:

$$Re = \frac{\pi \times 200 \times 10^{-3} \times 25 \times 2 \times 10^{-3} \times 200 \times 10^{-3} \times 900}{2 \times 0,014} = 201,96$$

$$< 41,3 \times \sqrt{\frac{200 \times 10^{-3}}{2 \times 10^{-3} \times 200 \times 10^{-3}}} = 923,5$$

$$Re = 201,96 < 923,5$$

Flow is laminar. Thus, all parts of [ISO 7902](#) are applicable in this case.

Using [Formula \(16\)](#):

$$\bar{p} = \frac{18\,000}{0,5 \times 200 \times 10^{-3} \times 200 \times 10^{-3}} = 0,9 \times 10^6 \text{ Pa}$$

The specific bearing load \bar{p} is permissible, since $\bar{p} < \bar{p}_{\text{lim}}$.

Heat dissipation is via the lubricant. [Table A.8](#) gives the intermediate results in the various steps of the calculation.

The specific feature of this calculation is the determination of frictional power and lubricant flow rate based on the flow in the lubrication pockets and grooves. The first step of the calculation is given as an example.

The angular span of lubrication groove Ω_G equals π and the angular span of lubrication pocket Ω_P equals $\pi/3$.

Frictional power in the lubrication pockets and grooves [see [ISO 7902-2:2020](#), Formulae (4) and (5)]:

$$\xi_P = 2 \times 0,5 \times \frac{\pi}{6} \times \left[4 + 0,0012 \times \left(\frac{900 \times 157 \times 2,5 \times 10^{-3} \times 200 \times 10^{-3}}{2 \times 0,022} \right)^{0,94} \right] = 2,74$$

$$\xi_G = 0,5 \times \pi \times \left[4 + 0,0012 \times \left(\frac{900 \times 157 \times 2,5 \times 10^{-3} \times 200 \times 10^{-3}}{2 \times 0,022} \right)^{0,94} \right] = 8,23$$

Friction force in the whole lubricant film [see [ISO 7902-2:2020](#) Formula (3)]:

$$F'_f = \frac{0,022 \times 157 \times 100 \times 10^{-3} \times 200 \times 10^{-3}}{2 \times 10^{-3}} \times$$

$$\left[1,042 \times 4,6 - \frac{60 \times 10^{-3}}{100 \times 10^{-3}} \times \left(\frac{\pi}{3 \times 2 \sqrt{1-0,734^2}} - \frac{2 \times 10^{-3} \times 200 \times 10^{-3}}{2 \times 2,5 \times 10^{-3}} \times 2,74 \right) \right]$$

$$\left[- \frac{30 \times 10^{-3}}{100 \times 10^{-3}} \times \left(\frac{\pi}{2 \sqrt{1-0,734^2}} - \frac{2 \times 10^{-3} \times 200 \times 10^{-3}}{2 \times 2,5 \times 10^{-3}} \times 8,23 \right) \right] = 136,98$$

Heat flow rate due to frictional power in bearing:

$$P_{\text{th},f} = 136,98 \times \frac{200 \times 10^{-3}}{2} \times 157 = 2\,150,6 \text{ N} \cdot \text{m/s} = 2\,150,6 \text{ W}$$

Lubricant flow rate due to generation of internal pressure [see [Formula \(9\)](#)]:

$$Q_3 = 200^3 \times 10^{-9} \times 2 \times 10^{-3} \times 157 \times 0,0435 = 109,27 \times 10^{-6} \text{ m}^3/\text{s}$$

Lubricant flow rate due to feed pressure [see [ISO 7902-2:2020](#), Formulae (10) and (11)] is the sum of flow rates from lubrication pockets and grooves:

$$q_p = 1,188 + 1,582 \times \left(\frac{60 \times 10^{-3}}{100 \times 10^{-3}} \right) - 2,585 \times \left(\frac{60 \times 10^{-3}}{100 \times 10^{-3}} \right)^2 + 5,563 \times \left(\frac{60 \times 10^{-3}}{100 \times 10^{-3}} \right)^3 = 2,408\,2$$
$$Q_p^* = \frac{\pi}{6} \times \frac{1}{\ln \left(\frac{100 \times 10^{-3}}{60 \times 10^{-3}} \right) \times 2,408\,2} + \frac{1}{48} \times \frac{\pi (1 + 1,5 \times 0,734^2) + 6 \times 0,734 + 1,33 \times 0,734^3}{\frac{100 \times 10^{-3} - 30 \times 10^{-3}}{200 \times 10^{-3}}} = 1,530\,8$$
$$Q_p = \frac{200^3 \times 10^{-9} \times 2^3 \times 10^{-9} \times 0,5 \times 10^5}{0,022} \times 1,530\,9 = 222,68 \times 10^{-6} \text{ m}^3/\text{s}$$

Lubricant flow rate [see [Formulae \(11\)](#) and [\(12\)](#)]:

$$Q = (109,27 + 222,68) \times 10^{-6} = 331,95 \times 10^{-6} \text{ m}^3/\text{s}$$

Heat dissipation via lubricant [see [Formula \(14\)](#)]:

$$P_{th,L} = 1,8 \times 10^6 \times 331,95 \times 10^{-6} \times (T_{ex,1} - 40)$$

$P_{th,f} = P_{th,L}$ yields:

$$T_{ex,1} = \frac{2\,150,6}{1,8 \times 10^6 \times 331,95 \times 10^{-6}} + 40 = 43,6 \text{ }^\circ\text{C}$$

Table A.8 — Results of iterative calculations for heat dissipation via the lubricant in partial bearing with pocket and groove

Variable	Unit	Step of the calculation			
		1	2	3	4
T_{en}	°C	40	40	40	40
$T_{ex,0}$	°C	60	51,8	48,3	47,2
T_{eff}	°C	50	45,9	44,2	43,6
η_{eff}	Pa·s	0,022	0,024	0,027 5	0,028
So	1	1,042	0,955	0,834	0,819
ε	1	0,734	0,725	0,7	0,698
h_{min}	m	$53,2 \times 10^{-6}$	55×10^{-6}	60×10^{-6}	$60,4 \times 10^{-6}$
f'/ψ_{eff}	1	4,6	4,8	5,4	5,45
P_f	W	2599,9	2 713	3 052,1	3 080,3
Q_3	m³/s	$109,27 \times 10^{-6}$	$109,27 \times 10^{-6}$	$108,52 \times 10^{-6}$	$108,02 \times 10^{-6}$
Q_p	m³/s	$222,66 \times 10^{-6}$	$202,24 \times 10^{-6}$	$172,03 \times 10^{-6}$	$168,62 \times 10^{-6}$
Q	m³/s	$331,93 \times 10^{-6}$	$311,51 \times 10^{-6}$	$280,55 \times 10^{-6}$	$276,64 \times 10^{-6}$
$T_{ex,1}$	°C	43,6	44,8	46	46,2
$T_{ex,0}$	°C	51,8	48,3	47,2	

[Table A.9](#) gives the results of the calculation, taking account of the lubricant flow rate via a lubrication pocket. As before, it is assumed that lubricant fills both the loaded and unloaded areas of the lubrication clearance.

In this case, in the first step of the calculation, lubricant flow rate from the pocket is:

$$q_p = 2,408\,2$$

$$Q_p^* = \frac{\pi}{6} \times \frac{1}{\ln\left(\frac{100 \times 10^{-3}}{60 \times 10^{-3}}\right) \times 2,4082} = 0,4256$$
$$Q_p = \frac{200^3 \times 10^{-9} \times 2^3 \times 10^{-9} \times 0,5 \times 10^5}{0,022} \times 0,4256 = 61,88 \times 10^{-6} \text{ m}^3/\text{s}$$

Table A.9 — Results of iterative calculations for heat dissipation via the lubricant in partial bearing with pockets

Variable	Unit	Step of the calculation			
		1	2	3	4
T_{en}	°C	40	40	40	40
$T_{\text{ex},0}$	°C	60	53,5	50,5	49,2
T_{eff}	°C	50	46,75	45,25	44,6
η_{eff}	Pa·s	0,022	0,023 9	0,025 2	0,026 3
So	1	1,042	0,959	0,91	0,872
ε	1	0,734	0,727	0,717	0,71
h_{min}	m	$53,2 \times 10^{-6}$	$54,6 \times 10^{-6}$	$56,6 \times 10^{-6}$	58×10^{-6}
f'/ψ_{eff}	1	4,6	4,75	5	5,18
P_f	W	2 599,9	2 684,7	2 826	2 927,7
Q_3	m ³ /s	$109,27 \times 10^{-6}$	$109,17 \times 10^{-6}$	$108,52 \times 10^{-6}$	$108,02 \times 10^{-6}$
Q_p	m ³ /s	$61,91 \times 10^{-6}$	$56,98 \times 10^{-6}$	$54,04 \times 10^{-6}$	$51,78 \times 10^{-6}$
Q	m ³ /s	$171,18 \times 10^{-6}$	$166,25 \times 10^{-6}$	$162,56 \times 10^{-6}$	$159,8 \times 10^{-6}$
$T_{\text{ex},1}$	°C	47,0	47,4	47,9	48,4
$T_{\text{ex},0}$	°C	53,5	50,5	49,2	

Bibliography

- [1] [ISO 3448](#), *Industrial liquid lubricants — ISO viscosity classification*
- [2] [ISO 4378-5](#), *Plain bearings — Terms, definitions, classification and symbols — Part 5: Application of symbols*
- [3] REYNOLDS O. On the theory of lubrication and its application to Mr. Beauchamp Tower's experiments including an experimental determination of the viscosity of olive oil. *Phil. Trans.* (1866), 177, pp. 157-234. *Ostwalds Klassiker der exakten Wissenschaften*, Leipzig. Nr. 218, Leipzig, 1927
- [4] SOMMERFELD A. Zur hydrodynamischen Theorie der Schmiermittelreibung. *Zeitschrift für Mathematik und Physik*. 1904, **40** pp. 97-155
- [5] VOGELPOHL G. Beiträge zur Gleitlagerberechnung. VDI-Forschungsheft, Nr. 386, Düsseldorf, 1954
- [5] SASSENFELD H., & WALTHER A. Gleitlagerberechnung. VDI-Forschungsheft, Nr. 441, Düsseldorf, 1954
- [6] RAIMONDI A.A., & BOYD J. A solution for the finite journal bearing and its application to analysis and design *Trans. A.S.L.E* (1958), 1, part 1, pp. 159-174; part 2, pp. 175-194; part 3, pp. 194-209
- [7] BUTENSCHON H.-J. Das hydrodynamische zylindrische Gleitlager endlicher Breite unter instationärer Belastung. Dissertation, TU Karlsruhe, 1976
- [8] WISSUSSEK D. Der Einfluß reversibler und irreversibler Viskositätsänderungen auf das Verhalten hydrodynamischer stationär belasteter Gleitlager. Dissertation, TU Hannover, 1975
- [9] LANG O.R., & STEINHILPERS W. *Gleitlager, Konstruktionsbücher, 31*, Springer Verlag Berlin, Heidelberg, New York, 1978
- [10] DILLENKOFER H. Einfluß der Lage der Ölzuführungsstelle auf das Betriebsverhalten stationär belasteter zylindrischer Gleitlager endlicher Breite. Dissertation, Universität Stuttgart, 1975
- [11] HOPPE J. Einfluß der Oberflächenwelligkeit von Lagerzapfen auf das Verhalten hydrodynamisch geschmierter Radialgleitlager. Dissertation, Universität Karlsruhe, 1981
- [12] PINKUS C., & STERNLICHT B. *Theory of hydrodynamic lubrication*. McGraw-Hill Book Company, Inc, New York, Toronto, London, 1961
- [13] KVINITSKY B.I., KIRKATCH N.F., POLTAVSKY Y.D. The solution of Reynolds' equation under natural boundary conditions for hydrodynamic journal bearings, *Wear*, 37, 2, pp. 217-231, Elsevier Sequoia, Lausanne, 1978
- [14] KVINITSKY B.I., & KIRKATCH N.F. *Calculation of plain journal bearings (reference book)*. Mashinostroenic, Moscow, 1979
- [15] KOROVCHINSKY M.V. *Theoretical basis for plain bearings operation*. Mashgiz, Moscow, 1959
- [16] CONSTANTINESCU V. Basic Relationships in Turbulent Lubrication and their Extension to include Thermal Effects. *Transactions of the ASME, Series, F*, No. 2, 95, 1973, pp. 35-43

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than one device provided that it is accessible by the sole named user only and that only one copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than one copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright and Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email cservices@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email: cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

