



BSI Standards Publication

Passenger cars — Power-off reaction of a vehicle in a turn — Open-loop test method

National foreword

This British Standard is the UK implementation of ISO 9816:2018. It supersedes BS ISO 9816:2006, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee AUE/15, Safety related to vehicles.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018
Published by BSI Standards Limited 2018

ISBN 978 0 580 91594 9

ICS 43.100

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 April 2018.

Amendments/corrigenda issued since publication

Date	Text affected
<hr/>	

INTERNATIONAL STANDARD

ISO
9816

Third edition
2018-04-15

Passenger cars — Power-off reaction of a vehicle in a turn — Open- loop test method

*Voitures particulières — Réponse d'un véhicule à un lever de pied en
virage — Méthode d'essai en boucle ouverte*



Reference number
ISO 9816:2018(E)

© ISO 2018

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Variables	2
5.1 Reference system	2
5.2 Variables to be measured	2
6 Measuring equipment	3
6.1 Description	3
6.2 Transducers installations	3
6.3 Data processing	3
7 Test conditions	3
8 Test method	3
8.1 Warm-up	3
8.2 Initial driving condition	4
8.2.1 General	4
8.2.2 Initial driving condition — Constant-radius method	4
8.2.3 Initial driving condition — Constant-speed method	4
8.3 Power-off procedure	5
9 Data evaluation and presentation of results	5
9.1 General	5
9.2 Time histories	5
9.3 Initial point in time t_0	5
9.4 Characteristic values	6
9.4.1 General	6
Annex A (normative) Test report — General data	9
Annex B (normative) Presentation of results	10
Bibliography	23

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#).

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 33, *Vehicle dynamics and chassis components*.

This third edition of ISO 9816 cancels and replaces the second edition ([ISO 9816:2006](#)) which has been technically revised. The main changes compared to the previous edition are as follows:

- an update was made regarding alternative powertrain systems.

Introduction

The main purpose of this document is to provide repeatable and discriminatory test results.

The dynamic behaviour of a road vehicle is a very important aspect of active vehicle safety. Any given vehicle, together with its driver and the prevailing environment, constitutes a closed-loop system that is unique. The task of evaluating the dynamic behaviour is therefore very difficult since the significant interaction of these driver-vehicle-environment elements are each complex in themselves. A complete and accurate description of the behaviour of the road vehicle must necessarily involve information obtained from a number of different tests.

Since this test method quantifies only one small part of the complete vehicle handling characteristics, the results of these tests can only be considered significant for a correspondingly small part of the overall dynamic behaviour.

Moreover, insufficient knowledge is available concerning the relationship between overall vehicle dynamic properties and accident avoidance. A substantial amount of work is necessary to acquire sufficient and reliable data on the correlation between accident avoidance and vehicle dynamic properties in general and the results of these tests in particular. If this test method is used for regulation purposes, the correlation between test results and accident statistics should be checked.

Passenger cars — Power-off reaction of a vehicle in a turn — Open-loop test method

1 Scope

This document specifies open-loop test methods to determine the reactions of a vehicle in a turn to a sudden drop in motive power resulting from release of the accelerator pedal. It applies to passenger cars as defined in ISO 3833.

The open-loop manoeuvre specified in this test method is not representative of real driving conditions, but is useful to obtain measures of a vehicle's power-off behaviour resulting from specific types of control inputs under closely controlled test conditions.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 8855](#), *Road vehicles — Vehicle dynamics and road-holding ability — Vocabulary*

ISO 15037-1:2018¹⁾, *Road vehicles — Vehicle dynamics test methods — Part 1: General conditions for passenger cars*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in [ISO 8855](#), [ISO 15037-1](#) and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

For the purposes of this document, the terms and definitions given in the general conditions given in, and the following terms and definitions shall apply.

3.1

power-off

vehicle operating condition where the vehicle is in gear and the accelerator pedal is fully released, especially when initiated by a sudden release of the accelerator pedal

3.2

instant of power-off initiation

t_0

moment in time when a rapid release of the accelerator pedal is initiated

1) Under preparation. Stage at time of publication: ISO/DIS.

- lateral acceleration; a_Y ;
- sideslip angle, β , or lateral velocity, v_Y .

In addition, the following variables may be determined:

- longitudinal acceleration, a_X .

The variables are defined in [ISO 8855](#), except the instant of accelerator pedal release t_0 , which is the instant at which the accelerator pedal is released (see [8.3](#)). The variables are not intended to comprise a complete list.

6 Measuring equipment

6.1 Description

The variables selected for test purposes shall be measured by means of appropriate transducers. Their time histories shall be recorded by a multi-channel recording system having a time base. Typical operating ranges and recommended maximum errors of the transducer and recording system are as specified in [ISO 15037-1:2006](#) and [Table 1](#). In the context of this document, these values should be considered as provisional until more experience and data are available.

6.2 Transducers installations

The requirements of [ISO 15037-1](#) shall apply.

6.3 Data processing

The requirements and specifications of [ISO 15037-1](#) shall be followed.

7 Test conditions

Limits and specifications for the ambient and the vehicle test conditions established in [ISO 15037-1](#) shall be followed.

In addition, for standard test conditions, the adjustment and condition of the engine and drive train (especially the differentials, clutches, locks, free-wheel shifts, engine idle-calibration) shall correspond to the vehicle manufacturer's specifications.

Table 1 — Typical operating ranges and recommended maximum errors for recorded variables — Additions and exceptions to ISO 15037-1

Variable	Typical operating range	Recommended maximum error of the combined transducer and recorder system
Instant of power-off initiation	—	0,05 s
Yaw angle	-180° to 180°	±2°
NOTE Increased measuring accuracy be desirable for computation of some of the characteristic values given in Clause 9 .		

8 Test method

8.1 Warm-up

The procedure specified in [ISO 15037-1](#) shall be followed to warm up the tyres and other vehicle components prior to the test.

8.2 Initial driving condition

8.2.1 General

For both the constant-radius and the constant-speed test methods, the initial driving condition is a steady-state circular run as defined in [ISO 15037-1](#).

For either test method, the initial runs shall be conducted from a steady-state circular condition in which a lateral acceleration of about 4 m/s^2 is achieved. In successive runs, the steady-state lateral acceleration of the initial turn shall be increased incrementally from run to run in steps of not more than 1 m/s^2 . It is recommended that increments of $0,5 \text{ m/s}^2$ or less be used when the power-off response changes significantly between runs at the larger increment (1 m/s^2).

For vehicles with manual transmission, the test shall be performed in the lowest gear possible, but not in first gear. The engine speed shall not be higher than 80 % of the engine speed at the maximum power point, as specified by the vehicle manufacturer. If the increase in vehicle speed during a constant-radius test requires a gear change, the previous speed shall be run in both gears.

For vehicles with automatic transmission, the standard drive mode shall be used. The position of the transmission lever and the selected driving programme shall be recorded in the test report (see [Annex A](#)).

Cars with adaptive gear selection or CVT may use different gears or ratios at a given speed. For such cars, engine speed shall be recorded for the purpose of determining gear ratio. It shall be recorded in the test report.

For vehicles with regenerative braking capabilities the specific vehicle configuration may alter the dynamic vehicle behaviour while releasing the accelerator pedal and/or while pressing the brake pedal. Also, the different dynamic vehicle behaviour with or without active regenerative braking shall be considered while performing the tests. The selected level of regenerative braking capability and the transmission lever position shall be documented in the test report.

8.2.2 Initial driving condition — Constant-radius method

During the initial driving condition, the vehicle shall be steered in such a manner that the reference point of the vehicle moves on a circular path of the desired radius. As it is known that the significance of the results and the ability to discriminate between different vehicles increase with increasing test speed, the standard radius of this path shall be 100 m. Smaller radii may be used. The minimum permissible radius is 30 m, but the recommended minimum radius is 40 m.

From run to run, the initial driving speeds shall be those which establish the required steady-state lateral accelerations as described in [8.2.1](#).

8.2.3 Initial driving condition — Constant-speed method

The standard speed for the initial driving condition is 100 km/h. If higher or lower test speeds are selected, they shall be in 20 km/h increments.

From run to run, the steady-state lateral accelerations as required in [8.2.1](#) shall be established by either of the following two methods.

- The test runs are performed using a series of discrete turn radii, consisting of a number of marked circles or circular segments with different radii chosen to establish the required initial lateral accelerations at the selected test speed.
- The test runs are performed using a series of discrete, constant steer angles (with no constraint on initial vehicle path) chosen to establish the required initial lateral accelerations at the selected test speed. The use of an adjustable steering stop is recommended for maintaining constant steer angles.

8.3 Power-off procedure

The position of the steering wheel and the accelerator pedal shall be kept as constant as possible during the initial driving condition. The initial condition is considered to be sufficiently constant if the conditions defined in [ISO 15037-1](#) are fulfilled.

For the constant-radius method, the radius in the initial driving condition may not deviate by more than $\pm 2\%$ of the desired value or ± 2 m, whichever is smaller, during the time interval of 1,3 s to 0,3 s before power-off initiation.

For the constant-speed method, the longitudinal velocity in the initial driving condition may not deviate by more than ± 1 km/h of the desired value during the time interval of 1,3 s to 0,3 s before power-off initiation.

When the initial steady-state driving condition has been established, the steering wheel shall be held fixed by a mechanical device or, alternatively, shall be firmly held by the driver.

The accelerator pedal shall be released as quickly as possible. On vehicles with manual transmission, the clutch shall be kept engaged. On vehicles with automatic transmission, the shift lever shall remain in the initial position.

The data signal indicating the instant of power-off initiation, t_0 , shall be generated when the foot force on the acceleration pedal is lower than 10 N (contact switch).

The transducer signals shall be recorded from at least 1,3 s before to at least 2 s after the instant of power-off initiation. This recording period shall be extended by the settling time of all filters used during recording (0,2 s to 1 s, depending on the type of filter used).

During the recording period, the steering-wheel angle shall not deviate more than $\pm 3\%$ from the steady-state value. To improve accuracy, it is recommended that at least three valid test runs be performed for each lateral acceleration level (see [8.2.1](#)).

Tests shall be carried out for both left and right turns.

9 Data evaluation and presentation of results

9.1 General

General data shall be presented in the test report as referred to in [Annex A](#) and [Annex B](#). For every change in equipment of the vehicle (e.g. load), the general data shall be documented again.

At the present level of knowledge, it is not yet known which variables best represent the subjective feeling of the driver and which variables (i.e. which characteristic values) best describe the dynamic reaction of vehicles. The following specified variables therefore represent only examples for the evaluation of results.

9.2 Time histories

For every test run, time histories of the variables listed in [Clause 5](#) shall be presented. Apart from their evaluation purposes, the time histories serve to monitor correct test performance and functioning of the transducers (see [Figure B.1](#)).

9.3 Initial point in time t_0

The initial point in time t_0 for the following characteristic values is the instant of the power-off initiation.

9.4 Characteristic values

9.4.1 General

The characteristic values should be determined and presented as functions of the initial steady-state lateral acceleration (see [Annex B](#)). The characteristic values in the steady-state condition are defined as mean values during the time interval 1,3 s to 0,3 s before power-off initiation t_0 . The other characteristic values are determined during an observation period beginning at t_0 and ending 2 s later. The representative values at t_n shall be calculated by taking the mean values during the time interval from $t_n - 0,1$ s to $t_n + 0,1$ s. For standard evaluation the actual time is $t_n = t_0 + 1$ s, but t_n may also assume additional values.

For each set of initial conditions, calculate and plot the characteristic values listed below. The reference values of yaw velocity and lateral acceleration used in some of the formulas that follow are those values which would have occurred at time t , had the initial turn radius been maintained while the vehicle proceeded at its actual longitudinal velocity $v_{X,t}$, if the initial radius were maintained by the vehicle. They are defined as follows:

Reference yaw velocity:

$$\dot{\psi}_{\text{Ref},t} = \frac{v_{X,t}}{R_0}$$

Reference lateral acceleration:

$$a_{Y,\text{Ref},t} = \frac{v_{X,t}^2}{R_0}$$

NOTE The throttle-off behaviour of passenger cars is normally designed in a way that the vehicle slightly decreases the radius of curvature of the driving path after the initiation of throttle-off. Therefore, the reference course that would be followed, if the vehicle were to maintain the exact same turn radius after throttle-off is not necessarily the ideal course. This should be kept in mind for the assessment of the following evaluation metrics.

9.4.2 The mean longitudinal acceleration during the time interval t_0 to t_n (see [Figure B.2](#)):

$$-\bar{a}_{X,t_n} = \frac{v_{X,0} - v_{X,t_n}}{t_n - t_0} = f_1(a_{Y,0})$$

9.4.3 The ratio of the value of the yaw velocity at time t_n to the value of the reference yaw velocity at time t_n (see [Figure B.3](#)):

$$\frac{\dot{\psi}_{t_n}}{\dot{\psi}_{\text{Ref},t_n}} = f_2(a_{Y,0})$$

9.4.4 The ratio of the maximum value attained by the yaw velocity to the corresponding reference value of the yaw velocity (see [Figure B.4](#)):

$$\frac{\dot{\psi}_{\text{max}}}{\dot{\psi}_{\text{Ref},t_{\text{max}}}} = f_3(a_{Y,0})$$

where t_{max} is the instant when the maximum value of the yaw velocity is reached.

9.4.5 The difference between the values of the instantaneous yaw velocity at time t_n and the reference yaw velocity at time t_n (see [Figure B.5](#)):

$$\Delta \dot{\psi}_{t_n} = \dot{\psi}_{t_n} - \dot{\psi}_{\text{Ref}, t_n} = \dot{\psi}_{t_n} - \frac{v_{X, t_n}}{R_0} = f_4(a_{Y, 0})$$

9.4.6 The maximum value of the difference between the yaw velocity during power-off and the affiliated reference yaw velocity (see [Figure B.6](#)):

$$\Delta \dot{\psi}_{\text{max}} = (\dot{\psi}_t - \dot{\psi}_{\text{Ref}, t})_{\text{max}} = \left(\dot{\psi}_t - \frac{v_{X, t}}{R_0} \right)_{\text{max}} = f_5(a_{Y, 0})$$

9.4.7 The instantaneous value of yaw acceleration evaluated at time t_n . Time t_n would typically be one second after throttle release, expressed as $t_n = t_0 + 1$ s. Yaw acceleration may be computed by differentiating yaw velocity (see [Figure B.7](#)):

$$\ddot{\psi}_{t_n} = \left. \frac{d\dot{\psi}}{dt} \right|_{t_n} = f_6(a_{Y, 0})$$

9.4.8 The ratio of the value of the lateral acceleration at time t_n to the reference value of the lateral acceleration at time t_n (see [Figure B.8](#)):

$$\frac{a_{Y, t_n}}{a_{Y, \text{Ref}, t_n}} = \frac{R_0}{R_{t_n}} = f_7(a_{Y, 0})$$

9.4.9 The maximum value of the sideslip angle during the observation period and the time t_{bm} (Beta-Max) expressing the time passed after t_0 until the maximum was reached (see [Figure B.9](#)):

$$\beta_{\text{max}} = f_{8-1}(a_{Y, 0}) \quad t_{\text{bm}} = f_{8-2}(a_{Y, 0})$$

9.4.10 The difference between the values of the sideslip angle at time t_n and the initial steady-state value of the sideslip angle (see [Figure B.10](#)):

$$\beta_{t_n} - \beta_0 = f_9(a_{Y, 0})$$

9.4.11 The difference between the maximum value of the sideslip angle during the observation period and the initial steady-state value of the sideslip angle (see [Figure B.11](#)):

$$\beta_{\text{max}} - \beta_0 = f_{10}(a_{Y, 0})$$

9.4.12 The difference between the values of the instantaneous yaw velocity at time t_n and the calculated yaw velocity at time t_n (see [Figure B.12](#)):

$$\dot{\beta}'_{t_n} = \dot{\psi}_{t_n} - \frac{a_{Y, t_n}}{v_{X, t_n}} = f_{11}(a_{Y, 0})$$


where $\dot{\beta}'$ is the sideslip-angle velocity uncorrected for the effects of the sideslip angle itself and the deceleration.

This metric provides information on the vehicle's yaw stability.

9.4.13 The path deviation at time t_n defined as the radial distance of the reference point and its initial circular path (see [Figure B.13](#)):

$$\Delta s_{Y,t_n} = f_{12}(a_{Y,0})$$

where $t_n = t_0 + 2 \text{ s}$.



- Key**
- 1 path deviation
 - 2 vehicle reference point
 - 3 initial circuit path
 - 4 path of reference point
 - R_0 initial radius

Figure 1 — Definition of path deviation

The path deviation is calculated by the path of the reference point in the earth fixed axis system (see [Figure 1](#)). The coordinates of the reference point can be determined for example by transforming the vehicle fixed velocity vectors \vec{v}_X and \vec{v}_Y into the earth fixed system and subsequent integration.

Annex A **(normative)**

Test report — General data

The documentation of general data and test conditions shall be in compliance with ISO 15037-1:2018²⁾, Annex A and Annex B.

2) Under preparation. Stage at time of publication: ISO/DIS.

Annex B
(normative)

Presentation of results

Figure B.1 shows the time histories of variables.

The characteristic values of the vehicle dynamic reaction shall be presented as functions of the initial steady-state lateral acceleration or initial radius, as shown in Figures B.2 to B.13.






Figure B.1 — Time histories of variables during the time interval –1,5 s before and 2,0 s after power-off initiation (scaling depends on variables and test conditions)



Key
X initial lateral acceleration $a_{Y,0}$ (m/s²)
Y $-\bar{a}_{X,t_n}$ (m/s²)

Figure B.2 — Mean longitudinal acceleration $-\bar{a}_{X,t_n}$ during the time interval t_0 to t_n as a function of the initial lateral acceleration $a_{Y,0}$




Key

X initial lateral acceleration $a_{Y,0}$ (m/s²)

Y $\frac{\dot{\psi}_{t_n}}{\dot{\psi}_{Ref, t_n}}$ (-)

Figure B.3 — The ratio of the value of the yaw velocity at time t_n to the value of the reference yaw velocity at time t_n as a function of the initial lateral acceleration $a_{Y,0}$




Key

X initial lateral acceleration $a_{Y,0}$ (m/s²)


Y $\frac{\dot{\psi}_{\max}}{\dot{\psi}_{\text{Ref}, t_{\max}}} (-)$

Figure B.4 — The ratio of the maximum value attained by the yaw velocity $\dot{\psi}_{\max}$ to the corresponding reference value of the yaw velocity $\dot{\psi}_{\text{Ref}, t_{\max}}$ as a function of the initial lateral acceleration $a_{Y,0}$




Key
X initial lateral acceleration $a_{Y,0}$ (m/s²)
Y $\dot{\psi}_{t_n} - \dot{\psi}_{Ref, t_n}$ (°/s)

Figure B.5 — Difference between the value of the yaw velocity at time t_n and the value of the reference yaw velocity at time t_n as a function of the initial lateral acceleration $a_{Y,0}$




Key
X initial lateral acceleration $a_{Y,0}$ (m/s²)
Y $\left(\dot{\psi}_t - \dot{\psi}_{\text{Ref},t}\right)_{\text{max}}$ (°/s)

Figure B.6 — The maximum value of the difference between the yaw velocity during power-off $\dot{\psi}_t$ and the affiliated reference yaw velocity $\dot{\psi}_{\text{Ref},t}$ as a function of the initial lateral acceleration $a_{Y,0}$



Key
X initial lateral acceleration $a_{Y,0}$ (m/s²)
Y $\ddot{\psi}_{t_n}$ (°/s²)

Figure B.7 — The instantaneous value of yaw acceleration at time t_n as a function of the initial lateral acceleration $a_{Y,0}$




Key

X initial lateral acceleration $a_{Y,0}$ (m/s²)


Y $\frac{a_{Y,t_n}}{a_{Y,Ref,t_n}}$ (-)

Figure B.8 — The ratio of the value of the lateral acceleration at time t_n to the value of the reference lateral acceleration at time t_n as a function of the initial lateral acceleration $a_{Y,0}$




Key
X initial lateral acceleration $a_{Y,0}$ (m/s²)
Y1 β_{\max} (°)
Y2 t_{bm} (s)

Figure B.9 — Maximum value of the sideslip angle β_{\max} during the observation period from 0 s to 2 s and the affiliated time $t_{\text{bm}}, \beta_{\max}$ as a function of the initial lateral acceleration $a_{Y,0}$




Key
X initial lateral acceleration $a_{Y,0}$ (m/s²)
Y $\beta_{t_n} - \beta_0$ (°)

Figure B.10 — Difference between the value of the sideslip angle at time t_n and the initial value of the sideslip angle β_0 as a function of the initial lateral acceleration $a_{Y,0}$




Key
X initial lateral acceleration $a_{Y,0}$ (m/s²)
Y $\beta_{\max} - \beta_0(^{\circ})$

Figure B.11 — Difference between the maximum value of the sideslip angle during the observation period from t_0 to t_n and the initial value of the sideslip angle β_0 as a function of the initial lateral acceleration $a_{Y,0}$



Key
X initial lateral acceleration $a_{Y,0}$ (m/s²)
Y $\dot{\beta}'_{t_n}$ (°/s)

Figure B.12 — Difference between the values of the instantaneous yaw velocity at time t_n and the calculated yaw velocity at time t_n as a function of the initial lateral acceleration $a_{Y,0}$



Key
X initial lateral acceleration $a_{Y,0}$ (m/s²)
Y $\Delta s_{Y,t_n}$ (m)

Figure B.13 — Path deviation of the reference point $\Delta s_{Y,t_n}$ at time $t_n = t_0 + 2$ s as a function of the initial lateral acceleration $a_{Y,0}$

Bibliography

- [1] ISO 1176:1990, *Road vehicles — Masses — Vocabulary and codes*
- [2] ISO 2416:1992, *Passenger cars — Mass distribution*
- [3] [ISO 4138](#), *Passenger cars — Steady-state circular driving behaviour — Open-loop test methods*
- [4] ISO 3833, *Road vehicles — Types — Terms and definitions*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
 - The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
 - A single paper copy may be printed for personal or internal company use only.
- Standards purchased in hard copy format:
- A British Standard purchased in hard copy format is for personal or internal company use only.
 - It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email subscriptions@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK